



Content Rules

Feature Description

UPDATED: 27 July 2023

Copyright Notices

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

These materials and all Progress® software products are copyrighted and all rights are reserved by Progress Software Corporation. The information in these materials is subject to change without notice, and Progress Software Corporation assumes no responsibility for any errors that may appear therein. The references in these materials to specific platforms supported are subject to change.

#1 Load Balancer in Price/Performance, 360 Central, 360 Vision, Chef, Chef (and design), Chef Habitat, Chef Infra, Code Can (and design), Compliance at Velocity, Corticon, Corticon.js, DataDirect (and design), DataDirect Cloud, DataDirect Connect, DataDirect Connect64, DataDirect XML Converters, DataDirect XQuery, DataRPM, Defrag This, Deliver More Than Expected, DevReach (and design), Driving Network Visibility, Flowmon, Inspec, Ipswitch, iMacros, K (stylized), Kemp, Kemp (and design), Kendo UI, Kinvey, LoadMaster, MessageWay, MOVEit, NativeChat, OpenEdge, Powered by Chef, Powered by Progress, Progress, Progress Software Developers Network, SequeLink, Sitefinity (and Design), Sitefinity, Sitefinity (and design), Sitefinity Insight, SpeedScript, Stylized Design (Arrow/3D Box logo), Stylized Design (C Chef logo), Stylized Design of Samurai, TeamPulse, Telerik, Telerik (and design), Test Studio, WebSpeed, WhatsConfigured, WhatsConnected, WhatsUp, and WS_FTP are registered trademarks of Progress Software Corporation or one of its affiliates or subsidiaries in the U.S. and/or other countries.

Analytics360, AppServer, BusinessEdge, Chef Automate, Chef Compliance, Chef Desktop, Chef Workstation, Corticon Rules, Data Access, DataDirect Autonomous REST Connector, DataDirect Spy, DevCraft, Fiddler, Fiddler Classic, Fiddler Everywhere, Fiddler Jam, FiddlerCap, FiddlerCore, FiddlerScript, Hybrid Data Pipeline, iMail, InstaRelinker, JustAssembly, JustDecompile, JustMock, KendoReact, OpenAccess, PASOE, Pro2, ProDataSet, Progress Results, Progress Software, ProVision, PSE Pro, Push Jobs, SafeSpaceVR, Sitefinity Cloud, Sitefinity CMS, Sitefinity Digital Experience Cloud, Sitefinity Feather, Sitefinity Thunder, SmartBrowser, SmartComponent, SmartDataBrowser, SmartDataObjects, SmartDataView, SmartDialog, SmartFolder, SmartFrame, SmartObjects, SmartPanel, SmartQuery, SmartViewer, SmartWindow, Supermarket, SupportLink, Unite UX, and WebClient are trademarks or service marks of Progress Software Corporation and/or its subsidiaries or affiliates in the U.S. and other countries. Java is a registered trademark of Oracle and/or its affiliates. Any other marks contained herein may be trademarks of their respective owners.

Please refer to the NOTICE.txt or Release Notes – Third-Party Acknowledgements file applicable to a particular Progress product/hosted service offering release for any related required third-party acknowledgements.

Table of Contents

1 Introduction	6
1.1 Document Purpose	6
1.2 Intended Audience	7
2 Advantages of Content Rules	8
3 Configure a Virtual Service to use Content Rules	10
3.1 Setting up Content Rules	10
3.2 Configuring Virtual Services	11
3.3 Content Rules WUI Options	13
3.3.1 Content Matching	14
3.3.1.1 Use of Flags to Create Dependent Rules	17
3.3.2 Add Header	18
3.3.3 Delete Header	19
3.3.4 Replace Header	20
3.3.5 Modify URL	21
3.3.6 Replace String in Response Body	22
3.3.7 Force Complete RS Match	24
3.4 Content Matching Rules	25
3.4.1 Adding Content Matching Rules	25
3.4.2 Associating Content Matching Rules to a Virtual Service	26
3.5 Header Modification	27
3.5.1 Adding Header Modification Rules	28

3.5.2 Associating Header Rules to a Virtual Service	28
3.6 Response Body String Replacement	30
3.6.1 Adding Response Body String Replacement Rules	31
3.6.2 Associating Response Body String Replacement Rules to a Virtual Service	32
4 Perl Compatible Regular Expressions	35
4.1 PCRE Examples	36
5 Shell Regular Expressions	37
5.1 Shell Regular Expression Examples	37
6 Content Rules Cookbook	39
6.1 Alter the Host Header	39
6.2 Naked Domain Redirect	39
6.3 HTTP Redirect	40
6.4 Change a URL	41
6.5 URL Rewrite Based on Source IP	42
6.6 Add the SSL Secure Flag and HTTPOnly Flag to Cookies from the Real Server	43
6.7 Match Host or Domain	43
6.8 Match URL or Directory	44
6.9 Change Domain or Host	45
6.9.0.1 Option 1: 302 Redirects	45
6.9.0.2 Option 2: Rewrite the URL	45
6.10 Change URL or Directory	46
6.10.0.1 Option 1: 302 Redirects	46

6.10.0.2 Option 2: Rewrite the URL	46
6.11 Redirect Clients from “/” to “/testpage”	47
6.12 Redirect Content to a Different URL While Keeping the Directory or Path	48
6.13 Redirecting Clients from HTTP to HTTPS	48
6.14 Match on Source IP	49
6.15 User-Agent String	50
6.16 Changing the User-Agent String	50
6.17 Change the Host Seen by the Real Server	51
6.18 Content Match on a Query	51
6.19 Content Matching Rule Example	52
6.19.1 Content Matching Rules	53
6.19.2 Virtual Services	53
References	58
Last Updated Date	59

1 Introduction

The Kemp LoadMaster supports content switching, which is sometimes referred to as URL switching. This enables the LoadMaster to direct specific requests to specific Real Servers based on the contents of the requested URL.

For example, if there are two groups of servers - one to serve images and the other to serve all other content - you can create rules to separate these two types of request. Any URL that includes **/images** in it, for example **http://example.com/images/demo.jpg**, is directed to the image server(s). Anything else is directed to the other server(s).

Content switching enables the Kemp LoadMaster to break up traffic based on the content of the request. Traffic can be examined by the:

- Request URL
- HTTP Header
- Source IP address
- Body of a request

Content rules only apply to HTTP or HTTPS traffic. If you want to match or edit the traffic, you must offload/re-encrypt SSL traffic.

The maximum number of content rules that a LoadMaster can have is 1024.

In this document, the term content switching does not refer to the process involved with Layer 2 switching. Instead, content switching refers to the switching of traffic between different servers, depending upon what content was requested.


1.1 Document Purpose

This document describes various aspects of the Content Rules feature of the Kemp LoadMaster. It describes in detail how to configure the Content Rules feature using the LoadMaster Web User Interface (WUI).

1.2 Intended Audience

Anyone who wishes to learn about or implement Content Rules with the Kemp LoadMaster.


2 Advantages of Content Rules



Content rules enable you to:

- Strip out server information
- Redirect requests for the root of a server
- Rewrite redirections from HTTP to HTTPS
- Force connections to close
- Secure cookies

Content switching can be very useful if there are dedicated server types that perform different functions. Examples include: image servers, static content servers, mapping servers, specialized content servers, application servers, and media servers that must all be served from the same general hostname, for example, **www.mysite.com**. Content switching also allows for hostname-specific servers and source IP-specific servers.



The above diagram outlines the order in which content rule operations are performed.

3 Configure a Virtual Service to use Content Rules

There are two parts to configuring content switching: the content rules and the Virtual Service configuration. The content rules are configured globally on the LoadMaster and various rules are applied to specific Real Servers operating under a Virtual Service.

The sections below describe the steps required to configure a Virtual Service that makes use of content switching.

3.1 Setting up Content Rules

To set up a content rule, follow the steps below on the LoadMaster WUI:

1. In the main menu, select **Rules & Checking** and then **Content Rules**.

There is a default (catch-all) rule that matches everything and is not editable. If this rule is applied to the Real Server or SubVS, it is always the last one to match if Content Switching is enabled in a Virtual Service.

2. Click **Create New...**

3 Configure a Virtual Service to use Content Rules

Create Rule

Rule Name

Rule Type

Content Matching ▼

Match Type

Regular Expression ▼

Header Field

Match String

Negation

☐

Ignore Case

☐

Include Host in URL

☐

Include Query in URL

☐

Fail On Match

☐

Perform If Flag Set

[Unset] ▼

Set Flag If Matched

[None] ▼

3. Fill out the form as needed. For details on what each of the options mean, refer to the **Content Rules WUI Options** section.

4. Click **Create Rule**.

The rule is added but does not affect any Virtual Service. After the rules have been added, they must be applied to Real Servers within individual Virtual Services.

3.2 Configuring Virtual Services

To configure a Virtual Service to use content switching, follow the steps below:

1. Log in to the relevant LoadMaster WUI.
2. In the main menu, select **Virtual Services** and **View/Modify Services**.

Status	Real Servers	Operation
● Up	10.154.201.9	Modify Delete
● Up	10.154.201.3	Modify Delete

3. Click **Modify** on the relevant Virtual Service.
4. Expand the **Standard Options** section.

3 Configure a Virtual Service to use Content Rules

▼ Standard Options	
Transparency	<input checked="" type="checkbox"/>
Extra Ports	<input type="text"/> Set Extra Ports
Persistence Options	Mode: None ▼
Scheduling Method	round robin ▼
Idle Connection Timeout (Default 660)	<input type="text"/> Set Idle Timeout
Use Address for Server NAT	<input type="checkbox"/>
Quality of Service	Normal-Service ▼

5. Select **None** in the **Persistence Options** drop-down menu.

6. Expand the **Advanced Properties** section.

▼ Advanced Properties	
Content Switching	Disabled Enable
HTTP Selection Rules	Show Selection Rules
HTTP Header Modifications	Show Header Rules
Response Body Modification	Show Body Modification Rules
Enable HTTP/2 Stack	<input type="checkbox"/>
Enable Caching	<input type="checkbox"/>
Enable Compression	<input type="checkbox"/>
Detect Malicious Requests	<input type="checkbox"/>
Add Header to Request	<input type="text"/> : <input type="text"/> Set Header
Copy Header in Request	<input type="text"/> To Header <input type="text"/> Set Headers
Add HTTP Headers	Legacy Operation(X-ClientSide) ▼
"Sorry" Server	<input type="text"/> Port <input type="text"/> Set Server Address
Not Available Redirection Handling	Error Code: <input type="text"/> ▼
	Redirect URL: <input type="text"/> Set Redirect URL
Default Gateway	<input type="text"/> Set Default Gateway
Service Specific Access Control	Access Control

7. Click **Enable** in the **Content Switching** row.

The enable button is only available if there is a Real Server set up on this Virtual Service.

3 Configure a Virtual Service to use Content Rules

If you exit the Virtual Service modify screen without adding a content rule to a Real Server, you will need to re-enable **Content Switching**.

Rules	Status	Operation
None	Enabled	Disable Modify Delete

- Expand the **Real Servers** section.

There is a column called **Rules**. Content switching has just been enabled so no rules are active.

- Click the **None** button.
- Select the relevant rule in the drop-down list and click **Add**.

The maximum number of content rules that a LoadMaster can have is 1024. There is no limit on a per-Real Server basis regarding how many of these rules can be assigned.

The rule is added to the Real Server. Multiple rules can be added to each Real Server.

3.3 Content Rules WUI Options

The various fields associated with Content Rules in the LoadMaster WUI are described below.

Content Matching Rules						Create New ...
Name	Type	Options	Header	Pattern	Operation	
OWA	RegEx	Ignore Case		/^\\owa.*/	Modify	Delete
Test1	RegEx	Only On 1		/images/	Modify	Delete
Test2	RegEx			/shopping/	Modify	Delete

The **Content Rules** screen displays the rules that have been configured and gives the option to **Modify** or **Delete**.

To define a new rule, click **Create New**.

3 Configure a Virtual Service to use Content Rules

Create Rule

Rule Name	Test3
Rule Type	Content Matching ▼
Match Type	Regular Expression ▼
Header Field	
Match String	/multimedia/
Negation	<input type="checkbox"/>
Ignore Case	<input type="checkbox"/>
Include Host in URL	<input type="checkbox"/>
Include Query in URL	<input type="checkbox"/>
Fail On Match	<input type="checkbox"/>
Perform If Flag Set	[Unset] ▼
Set Flag If Matched	[None] ▼

The **Rule Name** must be alphanumeric, unique, start with an alpha character, and cannot contain spaces. Rules are case sensitive, thus two different rules can exist in the form of **Rule1** and **rule1**. It is not possible to name a content rule **default**.

The options that are available depend on the **Rule Type** that is selected. The available rules are as follows:

- **Content Matching:** Matches the content of the URL, header or body of a request. For example, to redirect requests for the root of a server, set the **Content Matching** rule type to match and send to a SubVS that is set to 301/302 (You can also use **Modfiy URL** rules to rewrite requests for the root of a server.)
- **Add Header:** Adds a header according to the rule. For example, to force connections to close, use an **Add Header** named **Connection** with the value set to close.
- **Del Header:** Deletes the header according to the rule and enables you to strip out server information
- **Replace Header:** Replaces the header according to the rule. For example, to rewrite redirects from HTTP to HTTPS, use the **Replace Header** rule type to rewrite the location header. To secure cookies, use the **Replace Header** rule type to replace/modify the contents of cookies that are set by the Real Server in the **set-cookie** header.
- **Modify URL:** Changes the URL according to the rule.
- **Replace String in Response Body:** Replaces text in the body according to the content in the rule.

3.3.1 Content Matching

When the **Rule Type** selected is **Content Matching**, the following options are available.

3 Configure a Virtual Service to use Content Rules

Create Rule

Rule Name	Test3
Rule Type	Content Matching ▼
Match Type	Regular Expression ▼
Header Field	
Match String	/multimedia/
Negation	<input type="checkbox"/>
Ignore Case	<input type="checkbox"/>
Include Host in URL	<input type="checkbox"/>
Include Query in URL	<input type="checkbox"/>
Fail On Match	<input type="checkbox"/>
Perform If Flag Set	[Unset] ▼
Set Flag If Matched	[None] ▼

Rule Name

This is the name of the rule.

Match Type:

- **Regular Expression:** A powerful way of creating complex matching and replacement rules. Regular expressions can also be used to reference parts of the original string.
- **Prefix:** Matches from the beginning of the string only.
- **Postfix:** Matches from the end of the string only.

When **Prefix** or **Postfix** is selected, the **Match String** should be in the form of a pure string, not a regular expression.

Header Field

The header field name must be matched. If no header field name is set, the default is to match the string within the URL.

Rules can be matched based on the Source IP of the client by entering **src-ip** within the **Header Field** input field. The header field is populated by the source IP of the client.

The **Header Field** can be set to **method** to match on the HTTP method field.

The body of a request can also be matched by typing **body** in the **Header Field** text box. When matching on the **body**, up to the first 50K of the input stream is read.

Match String

3 Configure a Virtual Service to use Content Rules

Enter the pattern to match. Both Shell Regular Expressions and Perl Compatible Regular Expressions (PCRE) are supported.

Kemp recommends using PCRE expressions instead of Shell.

Both are the same in terms of performance. Performance is affected if a highly complex expression is used. The maximum number of characters allowed is 250.

To create a rule that sends all URL requests that have **/images/** as the root path to a group of servers, the **Match String** value should be **images/*** (where **images/*** is an example of a regular expression).

It is possible to perform content switching on URL, HTTP Header, Source IP, or the body of a request. The default behavior is to test the URL, however, a **Header Field** may be specified instead. To use Source IP content switching, use the pseudo-header **src-ip** — the source IP of the client is then available as a text field. The HTTP method can be matched upon by filling out the **Header Field** text box and the method. The body can be matched upon by entering **body** in the **Header Field** text box.

Negation

Negation inverts the sense of the match. Without negation, all requests that include **/images/** for example, would match an applicable rule. With negation, all requests except **/images/** would match the rule.

Ignore Case

If enabled, case is ignored when comparing strings.

Include Host in URL

If selected, this option prepends the hostname, for example, **support.kemptechnologies.com**, to the request URL before performing the match.

You may achieve better results by using flagging instead of using the **Include Host in URL** option. For more information, refer to the **Use of Flags to Create Dependent Rules** section.

Include Query in URL

Selecting this option includes everything after the **?** in a URL. This part of the URL is the URL query. For example, in the URL **http://example.com/images/imagid.jsp?item=1**, the query is **item=1**.

Fail on Match

3 Configure a Virtual Service to use Content Rules

If this rule is matched, then always fail to connect. If an error code or error URL is set, the code/URL is sent back to the client.

3.3.1.1 Use of Flags to Create Dependent Rules

By using the **Perform If Flag Set** and **Set Flag If Matched** options it is possible to make rules dependent on each other, therefore, only execute a particular rule(s) if another rule(s) has been successfully matched.

For example, if a rule called **Test2** should execute only if a rule called **Test1** was matched successfully, complete the following steps:

1. Log in to the LoadMaster WUI.
2. In the main menu, select **Rules & Checking** and **Content Rules**.

Content Matching Rules						Create New ...
Name	Type	Options	Header	Pattern	Operation	
OWA	RegEx	Ignore Case		/^Vowa.*/	Modify	Delete
Test1	RegEx	Only On 1		/images/	Modify	Delete
Test2	RegEx			/shopping/	Modify	Delete

3. Click **Modify** on the **Test1** rule.

Modify Rule Test1

Rule Name	Test1
Rule Type	Content Matching ▼
Match Type	Regular Expression ▼
Header Field	
Match String	/images/
Negation	<input type="checkbox"/>
Ignore Case	<input type="checkbox"/>
Include Host in URL	<input type="checkbox"/>
Include Query in URL	<input type="checkbox"/>
Fail On Match	<input type="checkbox"/>
Perform If Flag Set	[Unset] ▼
Set Flag If Matched	Flag 1 ▼

4. Select **Flag 1** from the **Set Flag If Matched** drop-down list.
5. Click **Modify Rule**.
6. Click **Modify** on the **Test2** rule.

3 Configure a Virtual Service to use Content Rules

Modify Rule Test2

Rule Name	Test2
Rule Type	Content Matching ▼
Match Type	Regular Expression ▼
Header Field	
Match String	/shopping/
Negation	<input type="checkbox"/>
Ignore Case	<input type="checkbox"/>
Include Host in URL	<input type="checkbox"/>
Include Query in URL	<input type="checkbox"/>
Fail On Match	<input type="checkbox"/>
Perform If Flag Set	Flag 1 ▼
Set Flag If Matched	[None] ▼

7. Select **Flag 1** from the **Perform If Flag Set** drop-down list.
8. Click **Modify Rule**.

When the **Test1** rule is successfully matched, a flag (**Flag 1**) is set. The **Test2** rule will not execute unless **Flag 1** is set. So, **Test2** cannot run unless **Test1** has been successfully matched.

If a flag is set during the matching of a request, it can be queried when processing response header modifications. Therefore, if the request sets a given flag, when the server responds, any response rules that are dependent on the flag will only execute if it is set.

Up to nine rule dependencies can be set up (as there are nine flags available to set) which can create a chain of dependent rules.

3.3.2 Add Header

The **Add Header** option adds a static header to the request. This can be used on the client header going to the server, or on the server header going to the client.

3 Configure a Virtual Service to use Content Rules

Modify Rule Test3	
Rule Name	Test3
Rule Type	Add Header ▼
Header Field to be Added	<input type="text"/>
Value of Header Field to be Added	<input type="text"/>
Perform If Flag Set	[Unset] ▼

Rule Name

This field is used for identification and should be named to help remember what the rule does in the Virtual Service.

Header Field to be Added

This is the name of the field inserted in the header.

Do not add the trailing colon.

Value of Header Field to be added

This is the value that will be associated with the inserted header.

Perform if Flag is Set

Only execute this rule if the specified flag is set.

The flag will have been set by a different rule.

3.3.3 Delete Header

The **Delete Header** option removes a header from the request. This can be used on the client header going to the server, or on the server header going to the client.

The **Delete Header** option uses a Regex over the whole header and value of the header. The header will only be deleted if it all matches.

For example, if the header is:

MyHeader: This is good


If **/MyHeader.*This/** is matched, the field will be deleted.

If the header is:

MyHeader: bad news

It will not match so it will not be deleted.

3 Configure a Virtual Service to use Content Rules



The 'Create Rule' dialog box shows the following configuration:

Field	Value
Rule Name	KempTest1
Rule Type	Delete Header
Header Field to be Deleted	
Perform If Flag Set	Flag 1

Buttons: Cancel, Create Rule

Rule Name

This field is used for identification and should be named to help remember what the rule does in the Virtual Service.

Header Field to be Deleted

The LoadMaster removes the header field with this name from the request/response.

Do not add the trailing colon.


Perform if Flag is Set

Only execute this rule if the specified flag is set.

The flag will have been set by a different rule.

3.3.4 Replace Header

The **Replace Header** option matches a header based on its value and replaces its value with the one specified. This can be used on the client header going to the server, or on the server header going to the client.



The 'Create Rule' dialog box shows the following configuration:

Field	Value
Rule Name	OWA
Rule Type	Replace Header
Header Field	
Match String	/^Vowa.*/
Value of Header Field to be replaced	
Perform If Flag Set	[Unset]

Buttons: Cancel, Create Rule

Rule Name

This field is used for identification and should be named to help remember what the rule does in the Virtual Service.

Header Field

This is the name of the field that the substitution will be performed on.

Do not add the trailing colon.

Match String

Enter a pattern to match against the content of this header. If the content matches the pattern, the header value will be replaced. This follows regular expression rules.

Value of Header Field to be replaced

When the rule is matched, the value of the header will be replaced with this text. Regular expressions and back references can be used here to reuse part of the existing value.

`\1` and `\2` can be used as back reference marks in PCRE expressions. For example, if the expression is `/Fred (w.*s) here/` is replaced by `/Mike is \1 and \1 as well/` it results in the following:

Input: **Fred wears here**

Output: **Mike is wears and wears as well**

Perform if Flag is Set

Only execute this rule if the specified flag is set.

The flag will have been set by a different rule.

3.3.5 Modify URL

The **Modify URL** option is a specialized header replacement that only matches the URL in the HTTP headers and replaces it with the one specified. This can be used on the client header going to the server.

3 Configure a Virtual Service to use Content Rules

Create Rule

Rule Name	<input type="text" value="OWA"/>
Rule Type	<input type="text" value="Modify URL"/>
Match String	<input type="text" value="/^Vowa.*"/>
Modified URL	<input type="text"/>
Perform If Flag Set	<input type="text" value="[Unset]"/>

Rule Name

This field is used for identification and should be named to help remember what the rule does in the Virtual Service.

Match String

Enter a pattern to match against the URL. If the URL matches the pattern, the URL value will be replaced. This follows regular expression rules.

Modified URL

Enter the new URL to be sent to the server. Regular expressions and back references can be used here to reuse part of the existing value.

Perform if Flag is Set

Only execute this rule if the specified flag is set.

The flag will have been set by a different rule.

3.3.6 Replace String in Response Body

When the **Rule Type** selected is **Replace String in Response Body**, the following options are available.

3 Configure a Virtual Service to use Content Rules

Create Rule

Rule Name	<input type="text" value="ExampleReplaceStringInRe"/>
Rule Type	<input type="text" value="Replace String in Response Body"/>
Match String	<input type="text" value="http://yourdomain.com"/>
Replacement text	<input type="text" value="https://yourdomain.com"/>
Ignore Case	<input checked="" type="checkbox"/>
Perform If Flag Set	<input type="text" value="[Unset]"/>

Rule Name

The name of the rule. The rule name must be unique.

Match String

The string to match.

Replacement text

The replacement string.

Ignore Case

Enable this check box to ignore the case of the strings when comparing.

Perform If Flag Set

Only execute this rule if the specified flag is set.

The flag will have been set by a different rule.

3.3.7 Force Complete RS Match

Allow connection scaling over 64K Connections	<input type="checkbox"/>
Always Check Persist	<input type="text" value="No"/>
Add Port to Active Cookie	<input type="checkbox"/>
Conform to RFC	<input checked="" type="checkbox"/>
Close on Error	<input type="checkbox"/>
Add Via Header In Cache Responses	<input type="checkbox"/>
Real Servers are Local	<input type="checkbox"/>
Drop Connections on RS failure	<input checked="" type="checkbox"/>
Drop at Drain Time End	<input checked="" type="checkbox"/>
L7 Authentication Timeout (secs)	<input type="text" value="30"/> Set Timeout (Valid values:30 - 300)
L7 Client Token Timeout (secs)	<input type="text" value="120"/> Set Timeout (Valid values:60 - 300)
L7 Connection Drain Time (secs)	<input type="text" value="300"/> Set Time (Valid values:0, 60 - 86400)
Additional L7 Header	<input type="text" value="X-ClientSide"/>
100-Continue Handling	<input type="text" value="RFC-2616 Compliant"/>
Allow Empty POSTs	<input type="checkbox"/>
Allow Empty HTTP Headers	<input type="checkbox"/>
Force Complete RS Match	<input checked="" type="checkbox"/>
Least Connection Slow Start	<input type="text" value="0"/> Set Slow Start (Valid values:0 - 600)
Share SubVS Persistence	<input type="checkbox"/>
Log Insight Message Split Interval	<input type="text" value="10"/> Set Log Split Interval (Valid values:1 - 100)
Include User Agent Header in User Logs	<input type="checkbox"/>

By default, when the LoadMaster tries to locate a Real Server for use with content switching, it tries to use the same Real Server as currently selected, even if the port is not the same. Enabling this option forces the port to also be compared. To enable this option, go to **System Configuration > Miscellaneous Options > L7 Configuration** and select the **Force Complete RS Match** check box.

You may need to enable this option in the event that you are trying to content match to the same Real Server but on different ports, for example:

- Virtual Service 1 -> SubVS 1 -> 10.140.22.146:80
- SubVS 2 -> 10.140.22.146:8080

Content Matching is enabled on each SubVS. If the destination for a content rule is checked (the Real Server) but not the port, the LoadMaster tries to reuse the current connection instead of opening a new connection to save on performance. Enabling this option should force the LoadMaster to also check the port.

3.4 Content Matching Rules

Content Matching rules are also known as selection rules. These rules allow you to match all or some of a **Header Field** or URL string and then set flags if there is a match.

3.4.1 Adding Content Matching Rules

To add a content matching rule, follow the steps below:

1. Log in to the relevant LoadMaster WUI.
2. In the menu on the left, select **Rules & Checking** and **Content Rules**.

Content Matching Rules						Create New ...
Name	Type	Options	Header	Pattern	Operation	
OWA	Regex	Ignore Case		/^\\owa.*\$/	Modify	Delete
Test1	Regex	Set Flag 1		/images/	Modify	Delete
Test2	Regex			/shopping/	Modify	Delete

3. Click **Create New....**

Create Rule

Rule Name

ServiceDesk

Rule Type

Content Matching ▼

Match Type

Regular Expression ▼

Header Field

host

Match String

servicedesk

Negation

☐

Ignore Case

☐

Include Host in URL

☐

Include Query in URL

☐

Fail On Match

☐

Perform If Flag Set

[Unset] ▼

Set Flag If Matched

[None] ▼

4. Enter a recognizable **Rule Name**.
5. Ensure **Content Matching** is selected as the **Rule Type**.
6. Select which **Match Type** to use.

3 Configure a Virtual Service to use Content Rules

For more information on the **Match Type** options, or any of the fields on this form, refer to the **Content Matching** section.

7. Enter the relevant **Header Field**, or enter **body** to match on the body of a request.
8. Enter the **Match String**.
9. Enable/disable any of the check boxes as required.
10. Select any flags as needed in the **Perform If Flag Set** and **Set Flag If Matched** lists.
11. Click **Create Rule**.

3.4.2 Associating Content Matching Rules to a Virtual Service

After a rule is created, you can associate it to a Virtual Service. To do this, follow the steps below:

1. In the main menu of the LoadMaster WUI, select **Virtual Services** and **View/Modify Virtual Services**.

Status	Real Servers	Operation
 Up	10.154.201.3	Modify Delete
 Up	10.154.201.3	Modify Delete

2. Click **Modify** on the relevant Virtual Service.
3. Expand the **Advanced Properties** section.

3 Configure a Virtual Service to use Content Rules

Advanced Properties

Content Switching

Disabled

Enable

HTTP Selection Rules

Show Selection Rules (2 Rules)

HTTP Header Modifications

Show Header Rules

Response Body Modification

Show Body Modification Rules

Enable HTTP/2 Stack

Enable Caching

Enable Compression

Detect Malicious Requests

Add Header to Request

:

Set Header

Copy Header in Request

To Header

Set Headers

Add HTTP Headers

Legacy Operation(X-ClientSide)

"Sorry" Server

Port

Set Server Address

Not Available Redirection Handling

Error Code:

Redirect URL:

Set Redirect URL

Default Gateway

Set Default Gateway

Service Specific Access Control

Access Control

4. Click **Show Selection Rules**.

If any content matching rules exist on this LoadMaster, they will be visible here.

5. Select the relevant rule and click **Add** .

Pattern	Replacement	Operation
servicedesk		Delete
/images/		Promote Delete

If there is more than one rule in a section, the priority at which a rule is applied can be adjusted using the **Promote** button.

3.5 Header Modification

Modifying headers gives control over how HTTP functions. The LoadMaster can add, delete, and replace HTTP headers, including URL modification. This is done on a per Virtual Service basis and can be used for request and/or response headers.

3 Configure a Virtual Service to use Content Rules

Header modification can be used to add identifying information to incoming requests. For example, if the LoadMaster is offloading SSL, the traffic back to the server is usually HTTP plain text. Normally, the server does not know that this had come in on SSL originally. To help identify this traffic as SSL originating, a header such as **SSL_Offload: Yes** can be added.

Another reason you may use a header modification rule is to delete/modify sensitive information returning from the server, such as operating system or web server version.

3.5.1 Adding Header Modification Rules

To add a header modification rule, follow the steps below:

1. Log in to the relevant LoadMaster WUI.
2. In the menu on the left, select **Rules & Checking** and **Content Rules**.
3. Click **Create New**.

Create Rule	
Rule Name	<input type="text" value="idedv_replace"/>
Rule Type	<input type="text" value="Replace Header"/>
Header Field	<input type="text" value="Host"/>
Match String	<input type="text" value="/^.\\$/"/>
Value of Header Field to be replaced	<input type="text" value="10.11.0.194:9004"/>
Perform If Flag Set	<input type="text" value="[Unset]"/>

A number of rule types can be added. The **Add Header**, **Delete Header**, **Replace Header**, and **Modify URL Rule Type** options all modify the HTTP stream in some way. For information about what each of the fields mean, refer to the **Content Rules WUI Options** section. For **Replace Header** and **Modify URL** rules, shell syntax or Perl Compatible Regular Expressions (PCRE) style regular expressions can be used. For information on regular expressions, refer to the **Perl Compatible Regular Expressions** section.

3.5.2 Associating Header Rules to a Virtual Service

Once a rule has been created, it can be associated to a Virtual Service. To do this, follow the steps below:

1. Log in to the relevant LoadMaster WUI.
2. In the main menu, select **Virtual Services** and **View/Modify Services**.

3 Configure a Virtual Service to use Content Rules

Status	Real Servers	Operation
● Up	10.154.201.3	Modify Delete
● Up	10.154.201.3	Modify Delete

- Click **Modify** on the relevant Virtual Service.
- Expand the **Advanced Properties** section.

▼

Advanced Properties

Content Switching

Disabled

Enable

HTTP Selection Rules

Show Selection Rules

HTTP Header Modifications

Show Header Rules

Response Body Modification

Show Body Modification Rules

Enable HTTP/2 Stack

☐

Enable Caching

☐

Enable Compression

☐

Detect Malicious Requests

☐

Add Header to Request

:

Set Header

Copy Header in Request

To Header

Set Headers

Add HTTP Headers

Legacy Operation(X-ClientSide) ▼

"Sorry" Server

Port

Set Server Address

Not Available Redirection Handling

Error Code:

▼

Redirect URL:

Set Redirect URL

Default Gateway

Set Default Gateway

Service Specific Access Control

Access Control

- Click **Show Header Rules**.

3 Configure a Virtual Service to use Content Rules

[<-Back](#)

Modification Rules assigned to tcp/10.154.11.71:443 (Id:5)

Request Rules

Add Rule

Rule: [Add](#)

Response Rules

Add Rule

Rule: [Add](#)

If any header modification rules exist for this LoadMaster, they will be visible here.

Here, either **Request Rules** or **Response Rules** can be added.

Request Rules: These are modifications to the client headers going to the server.

Response Rules: These are modifications to the server headers going back to the client.

6. Select the relevant rule in the relevant section and click **Add**.

Pattern	Replacement	Operation
	example	Delete
test2		Promote Delete

If there is more than one rule in a section, the priority at which a rule is applied can be adjusted using the **Promote** button.

3.6 Response Body String Replacement

Response body string replacement rules can be used to reduce cost and time-to-market when in-transit traffic handling requirements change for applications. For example, you may want to rewrite URLs that are in the BODY of the response and change them from HTTP to HTTPS. This may be

3 Configure a Virtual Service to use Content Rules

needed if there is a third-party application that has a number of hyperlinks embedded. It may be easier to mitigate this with a proxy type feature than it is to have the third party rework the application. The LoadMaster may be used to SSL offload a Virtual Service in front of the application. Because of this configuration, responses need to return to the LoadMaster as HTTPS. These response body string replacement rules can be used to modify the URLs embedded in the BODY.

These rules can also be used to switch domain names, for example, replace **test.yourdomain.com** with **yourdomain.com**.

Rules can be assigned to process the response body. These rules are run over the response body before it is sent to the client.

These rules do not work on binary files or compressed files. Something to be aware of is that it is very common for a browser to send the file compressed. Recommended ways to avoid compressing the files is to configure the server to not compress files being sent or use a content rule to remove the headers that request compression. Contact Kemp Support for further assistance with this.

The whole response is read into the LoadMaster before it is processed.

Each file is treated as a set of lines. The rules (multiple rules are allowed) are run over each line, one at a time. If a match is found, the text is replaced.

The file size must be greater than 512 bytes for the rule to be applied. If the file size is equal to or less than 512 bytes, the rule is not applied.

Body rules are case dependent. They can be made case independent by selecting the **Ignore Case** check box when creating the rule.

The system performs a "global replace" on each line. If more than one rule matches at a particular location, the first rule in the list is performed (rule precedence can be managed by using the **Promote** button in the Virtual Service **Body Modification Rules** screen).

Rules starting with a "beginning of line (^)" only match the start of the line.

Responses can only be handled if they fit in the configured cache memory. Input lines/resulting lines can have a maximum length of approximately 64K bytes in length (before or after - depending on how much data is added and taken away in the modifications). If an input line is more than 64K, it is processed as if it was a line of 64K. If the resulting line after the modification is more than 64K, only the first 64K is included in the output, the rest is ignored.


Response body rules are not compatible with Kerberos Constrained Delegation (KCD). If KCD is enabled on a Virtual Service, it is not possible to assign a body rule to it.

3.6.1 Adding Response Body String Replacement Rules

To add a response body string replacement rule, follow the steps below in the LoadMaster WUI:

3 Configure a Virtual Service to use Content Rules

1. In the menu on the left, go to **Rules & Checking > Content Rules**.
2. Click **Create New**.



The 'Create Rule' dialog box contains the following fields and controls:

- Rule Name:** ExampleReplaceStringInRe
- Rule Type:** Replace String in Response Body ▼
- Match String:** test.yourdomain.com
- Replacement text:** yourdomain.com
- Ignore Case:** ☒
- Perform If Flag Set:** [Unset] ▼
- Buttons:** Cancel, Create Rule

3. Enter the **Rule Name**.
4. Select **Replace String in Response Body** as the **Rule Type**.
5. Enter the string to be matched in the **Match String** text box.
6. Enter the replacement string in the **Replacement text** text box.
7. Select the **Ignore Case** check box if you want case to be ignored during the comparison.
8. Select a flag in the **Perform If Flag Set** drop-down list if you only want the rule to be run if a particular flag is set by another rule.

3.6.2 Associating Response Body String Replacement Rules to a Virtual Service

Once a rule has been created, you can associate it with a Virtual Service. To do this, follow the steps below in the LoadMaster WUI:

1. In the main menu, go to **Virtual Services > View/Modify Services**.
2. Click **Modify** on the relevant Virtual Service.
3. Expand the **Advanced Properties** section.

3 Configure a Virtual Service to use Content Rules

▼

Advanced Properties

Content Switching

Disabled

Enable

HTTP Selection Rules

Show Selection Rules

HTTP Header Modifications

Show Header Rules

Response Body Modification

Show Body Modification Rules

Enable Caching

☐

Enable Compression

☐

Detect Malicious Requests

☐

Enable Multiple Connect

☐

Add Header to Request

:

Set Header

Copy Header in Request

To Header

Set Headers

Add HTTP Headers

Legacy Operation(X-ClientSide) ▼

"Sorry" Server

Port

Set Server Address

Not Available Redirection Handling

Error Code:

▼

Redirect URL:

Set Redirect URL

Default Gateway

Set Default Gateway

Service Specific Access Control

Access Control

4. Click **Show Body Modification Rules**.

<-Back

Body Modification Rules assigned to tcp/10.35.47.111:80 (Id:1)

Body Modification Rules

Add Rule

Rule: ExampleReplaceStringInResponseBodyRule ▼

Add

5. Existing body modification rules are shown here. Select the relevant rule and click **Add**.

Pattern	Replacement	Operation
http://yourcomain.com	https://new.yourdomain.com	Delete
Example	Replacement	Promote Delete

3 Configure a Virtual Service to use Content Rules

If there is more than one rule in a section, you can adjust the priority of the rule by using the **Promote** button.

4 Perl Compatible Regular Expressions

Perl Compatible Regular Expressions (PCRE) implements regular expression pattern matching. It uses the same syntax and semantics as Perl 5. For further information regarding PCRE, refer to www.PCRE.org

When using special characters in PCRE, it is best practice to use the character's ASCII or HTML equivalent rather than the actual character. For example, to match the percentage symbol, instead of writing `/%/`, for the HTML version, use `/%/`, and for the ASCII version use `/\x25/`.

To ensure that an expression is treated as a PCRE, the expression must be enclosed by the forward-slash character (`/`) or it will be treated as a Shell Regular Expression. For example, a PCRE expression would look like this: `/^[Tt]est$/`.

Character	Meaning
<code>.</code>	Matches any character but a line-break
<code>\d</code>	Matches any numeric digit
<code>\w</code>	Matches any alpha character
<code>[]</code>	Matches a set of characters
<code>?</code>	Optionally matches the previous expression
<code>*</code>	Matches the previous expression zero or more times
<code>+</code>	Matches the previous expression one or more times
<code>{x}</code>	Matches the previous expression x times
<code>{x, y}</code>	Matches the previous expression x to y times
<code>^</code>	Matches the beginning of the string/line
<code>\$</code>	Matches the end of the string/line
<code>(x)</code>	Allows grouping of expressions
<code>a b</code>	Alternative expressions, matches a OR b

4.1 PCRE Examples

Some PCRE examples are below:

- `^/$` matches `/` and `/` only
- `^.*test.*$` matches the whole line of any line where `test` is mentioned
- `[A-F0-9]{8}` matches a string of eight hex characters
- `Gr[ae]y` matches both spellings of gray/grey
- `(^|www.)example\.com` matches `www.example.com` and `example.com`
- `[www]?\.example\.com` matches `www.example.com` and `example.com`
- `^[^~].*$` matches any line that does not start with `~`
- `\s\s+` matches multiple consecutive line breaks

5 Shell Regular Expressions

Regular expressions can be used to craft complex matching and replacing rules. The **Match String** can be a Shell Regular Expression, which is a type of statement that matches or excludes based on the strings. An asterisk (*) in a Shell Regular Expression means “match all”.

A Shell Regular Expression is a sequence of characters. Any character, which is not a special character, matches itself. The following special characters are defined.

Character	Meaning
^	This can only be placed at the start of the string and means that the string must match at the start of the URL
\$	This can only be placed at the end of the string and means that the string must match at the end of the URL
?	This matches any single character
*	This matches zero or more characters
[This starts the set notation. This matches a single character which is contained within a set. If the set starts with ^ , then this matches a single character which is not within the set

5.1 Shell Regular Expression Examples

Some examples of Shell Regular Expressions are below:

- **[0-9]** matches any single digit
- **[^abf]** matches any character, which is not “a”, “b” or “f”
- **^[^a-z]** matches any first character in the URL which is not a small letter
- **home/*.gif** matches any URL which points to a **.gif** file in the **/home** directory
- **[gG][iI][fF]** matches any URL which contains the string “gif”, “GIF”, “gIF”, “giF”, “GiF”, and so on.

Given an input URL such as **/home/cgi-bin/XXX.cmd?value=hello**, the end of the string used in matching is terminated by the **?** character, therefore, a postfix string of **cmd** matches this URL, while a postfix of **hello** does

not. To include the end of the string, enable the **Include Query in URL** option.

6 Content Rules Cookbook

Some example rules that can be used in real life scenarios are below. For further information on content rules and to see further examples, refer to <http://kemptechnologies.com/load-balancing-support/kemp-support>.

The examples provided here are for guidance purposes only.
They may not work in all configurations.

6.1 Alter the Host Header

It is often advantageous to have users refer to a web resource by a local hostname, rather than by the Fully Qualified Domain Name (FQDN). This can lead to server complexity if the server expects only the FQDN. This can be avoided by rewriting the host header at the LoadMaster.

Solution

Using the **Rewrite_FQDN** rule below, requests automatically have the full FQDN appended to the header so that server resources see the full hostname.

Rule Name: Rewrite_FQDN

Rule Type: Replace Header

Header Field: Host

Match String: /(.*)/

Replacement String: \1.domain.com

Other Uses: This type of rule can be altered to perform full replacements of the hostname or more complex replacement patterns using PCRE style regular expressions.

6.2 Naked Domain Redirect

There may be scenarios where a **www** prefix needs to be added to the original request, for example, if the original request is **mydomain.com**, the redirect is to **www.mydomain.com**

Solution

Using the **Naked_Domain_Redirect** rule below, requests automatically have **www** appended to the original request.

Rule Name: Naked_Domain_Redirect

Rule Type: Content Matching

Match Type: Regular Expression

Header Field: Host

Match string: /^www\..*/

Negation: Selected

Fail On Match: Selected

6.3 HTTP Redirect

There may be a need to redirect URLs, for example, there is a URL called **xyz.example.com** and there is a new site that users should be directed to with the URL **example.com/en/xyz**.

Solution

To do this, two rules are needed. One rule is needed to handle the host header rewrite, and the other to handle the URL rewrite.

Rule Name: Host_Rewrite

Rule Type: Replace Header

Header Field: Host

Match String: xyz.example.com

Value of Header Field to be replaced: example.com

Perform If Flag Set: [Unset]

Rule Name: URL_Rewrite

Rule Type: Modify URL

Match String: /\^\/\$/

Modified URL: /en/xyz

Perform If Flag Set: [Unset]

Conditional content rules only work in LoadMaster version 6.0-44 or later.

6.4 Change a URL

In some cases there may be a need to change a URL, depending what the original URL is, using a header modification rule. For example, changing **mywebsite:81** to **mynewwebsite** but then, if the URL is **mywebsite:81/project** change it to **ourprojects**.

Solution

Several rules are needed to achieve this kind of modification.

Rule Name: mywebsite

Rule Type: Replace Header

Header Field: Host

Match String: mywebsite

Replace String: mynewwebsite

Set Flag if Matched: Flag 1

Rule Name: project

Rule Type: Modify URL

Match String: /^/project\$/

Modified URL: /

Perform If Flag Set: Flag 1

Rule Name: ourprojects

Rule Type: Replace Header

Header Field: Host

Match String: /.*/

Replace String: ourprojects

Perform If Flag Set: Flag 2

6.5 URL Rewrite Based on Source IP

In some cases it may be required to rewrite a rule based on a source IP subnet. For example, if there are two different websites (A and B) on one webserver and, depending on the source subnet, the user should be redirected to either website A or B. The user is using the same external URL, for example **aaa.bbb.com**, but will get a different website based on the source IP.

Solution

This can be done one of two ways, but either will start the same. First, set up a conditional rule using the following parameters:

Rule Name: Subnet_A

Rule Type: Content Matching

Match Type: Regular Expression

Header Field: src-ip

Match String: /^10\.\0\..*/

Set Flag If Matched: Flag 1

The subnet that needs to be rewritten should be entered in the **Match String**. It must be done as a “classful” address as the LoadMaster is using a pseudo-header “src-ip” to do a text match against the source IP of the request. That means that something like 192.168.0/17 cannot be used – instead, use something like /192\.\168\.\10\..*/ to match an entire Class A, B, or C subnet.

Flag 1 is set if the above rule is matched. This can invoke another rule when matched. The rewrite can be done in two ways. Both are below.

Rule Name: Rewrite_Host

Rule Type: Replace Header

Header Field: Host

Match String: /.*/

Replace String: new.host.com

Perform If Flag Set: Flag 1

OR

Rule Name: Rewrite_URL

Rule Type: Modify URL

Match String: /.*/

Replace String: /new\0

Perform If Flag Set: Flag 1

Either of the two rewrite rules above can be used to either change the host header or the URL depending on how it needs to be changed on the server. Kemp recommends using the hostname option because it usually results in fewer issues.

Once the two rules have been created, navigate to the Virtual Service modify screen. In the **Advanced Properties** section, click **Show Selection Rules** and apply the **Subnet_A** rule. Then, click **Show Header Rules** and apply the rewrite rule. Now, the rewrite should be applied only to requests from the designated subnet.

6.6 Add the SSL Secure Flag and HTTPOnly Flag to Cookies from the Real Server

To add flags to a cookie being generated by the Real Server, the content switching engine must be used.

Rule Name: SetSecure

Rule Type: Replace Header

Header Field: set-cookie

Match String: /(.*?);?\$/

Replace String: \1; secure; httponly

Perform If Flag Set: [Unset]

6.7 Match Host or Domain

Use the following rule to match a host or a domain, for example, **https://www.domain.com**

Rule type: Content Matching

Match Type: Regular Expression

Header Field: Host

Match String: `/^www\.domain\.com$/`

Ignore Case: enabled

Match field

Start Regex: `/`

Start Match: `^`

Regular text: www

Literal character: `\.`

Regular text: domain

Literal character: `\.`

Regular text: com

End Match: `$`

End Regex: `/`

6.8 Match URL or Directory

Use the following rule to match a URL or a directory, for example,
`https://www.domain.com/support/newsite/testpage`

Rule type: Content Matching

Match Type: Regular Expression

Header Field: blank

Match String: `/^\/support/`

Ignore Case: enabled

Match field

Start Regex: `/`

Start Match: `^`

Literal character: \

Regular text: support

End Regex: /

6.9 Change Domain or Host

6.9.0.1 Option 1: 302 Redirects

302 Redirect Logic

When the client connects to **www.domain.com**, the LoadMaster sends a 302 redirect to the client and tells the client to connect to the new domain. This is also used for redirecting HTTP to HTTPS. With this option, the client sees the change in the browser.

Syntax

In the Virtual Service modify screen: **Advanced Properties -> Not Available Redirection Handling.**

Error code: 302 found

Redirect URL: <http://www.newdomain.com>

or for HTTP to HTTPS: <https://%h%s>

Replace with Host/Domain: %h

Replace with URL/Directory/Path: %s

Example: %h and %s are replaced with <http://www.newdomain.com/test/index.html>

6.9.0.2 Option 2: Rewrite the URL

Logic

Match on host and replace host with new host details. With this option, the client does not see the change in the browser.

Syntax

Rule: Replace Header

Header: Host

Match String: [/^www\.domain\.com\\$/](#)

Replace with: www.newdomain.com

Match field

Start Regex: /

Start Match: ^

Regular text: www

Literal character: \.

Regular text: domain

Literal character: \.

Regular text: com

End Match \$

End Regex /

6.10 Change URL or Directory

6.10.0.1 Option 1: 302 Redirects

Logic

When the client connects to **www.domain.com/test**, the LoadMaster sends a 302 redirect to the client and tells the client to connect to the new domain. This is also used for redirecting HTTP to HTTPS. With this option, the client sees the change in the browser.

Syntax

In the Virtual Service modify screen: **Advanced Properties -> Not Available Redirection Handling.**

Error code: 302 found

Redirect URL: **http://www.newdomain.com/newtestpage**

or for HTTP to HTTPS: **https://%h/newtestpage**

Replace with Host/Domain: **%h**

Example: **%h** is replaced with **http://www.newdomain.com**

6.10.0.2 Option 2: Rewrite the URL

Logic

Match on the URL and replace it with a new URL. With this option, the client does not see the change in the browser.

For example, redirecting clients from **http://www.newdomain.com/test** to **http://www.newdomain.com/newpage**.

Syntax

Rule : Modify URL

Header: <Blank>

Modified URL: newpage

Match field

Start Regex: /

Start Match: ^

Regular text: test

End Match: \$

End Regex: /

6.11 Redirect Clients from “/” to “/testpage”

Logic

Match on the URL/directory “/” and replace it with “/testpage”.

Example: www.domain.com/ changed to www.domain.com/testpage/

Syntax

Rule type: Modify URL

Match String: [/^\/\\$/](#)

Replace with: /testpage

Start Regex: /

Start Match: ^

**Literal character: **

End Match: \$

End Regex: /

6.12 Redirect Content to a Different URL While Keeping the Directory or Path

Rule type: Modify URL

Match String: /[^]Directory1(.*)/

Modified URL: /Directory2\1/

Match String: /[^]Directory1(.*)/

Start Regex: /

Start Match: [^]

Regular text: Directory1

Wildcard- capture everything in () and save it as capture group 1: (.*)

End Match: \$

End Regex: /

Modify URL String: /Directory2\1/

Start Regex: /

Start Match: [^]

Replace with saved data in capture group 1: \1

End Match: \$

End Regex: /

6.13 Redirecting Clients from HTTP to HTTPS

302 Redirect Logic

When the client connects to `http://www.domain.com`, the LoadMaster sends a 302 redirect to the client and tells the client to connect to the new domain. This is also used for redirecting HTTP to HTTPS.

Syntax

In the Virtual Service modify screen: **Advanced Properties** -> **Not Available Redirection Handling**.

Error code: 302 found

Redirect URL: `https://www.newdomain.com`

Replace with Host/Domain: %h

Replace with URL/Directory/Path: %s

Example: `http://www.newdomain.com/test/index.html` where **%h** is replaced with `www.newdomain.com/` and **%s** is replaced with `test/index.html`.

6.14 Match on Source IP

Use the following rule to match on Source IP. This can be used to whitelist a single IP or a range. If you select the option **Fail On Match** it behaves as a blacklist.

Rule Type: Content Matching

Match Type: Regular Expression

Header Field: src-ip

If single address 192.168.10.10

Match String: `/^192.168.10.10$/`

If address range 192.168.0.0/16

Match String: `/^192.168.\d{1,3}.\d{1,3}$/`

Match field: `/^192.168.(25[0-5]|2[0-4][0-9]|1[0-9]{2}|[0-9][0-9]?).(25[0-4]|2[0-4][0-9]|1[0-9]{2}|[0-9][0-9]?)$/`

Start Regex: `/`

Start Match: `^`

Match: `192.168.`

`192.168.0 – 192.168.255`

192.168.0.1 – 192.168.255.254

End Match: \$

End Regex: /

6.15 User-Agent String

Use the following rule to match on User-Agent String.

User-Agent String: Content Match

Rule type: Content Matching

Match Type: Regular Expression

Header Field: User-Agent

Match String: Mozilla/5.0 (Windows; U; MSIE 9.0; Windows NT 9.0; en-US)

You can view examples of User-Agent Strings at the following link:

<http://www.useragentstring.com/pages/useragentstring.php>

6.16 Changing the User-Agent String

Rule type: Replace Header

Header Field: User-Agent

Match String: /[^].^{*}\$/

Replace with: Mozilla/5.0 (Windows; U; MSIE 9.0; Windows NT 9.0; en-US)

You can view examples of User-Agent strings at the following link:

<http://www.useragentstring.com/pages/useragentstring.php>

Start Regex: /

Start Match: [^]

Wildcard: ^{*}

End Match: \$

End Regex: /

6.17 Change the Host Seen by the Real Server

If the client connects to a URL which has a different hostname to the Real Server, the Real Server may reject the request. This rule changes the host that is seen by the Real Server.

Rule type: Replace Header

Header Field: Host

Match String: `/^.*`

Value to be replaced: domain.com

Start Regex: `/`

Start Match: `^`

Wildcard: `.*`

End Match: `$`

End Regex: `/`

6.18 Content Match on a Query

Use this rule to perform a content match on a query string.

To query a match on `https://www.domain.com/orders/f?p=100`, use the following settings:

Rule type: Content Matching

Match Type: Regular Expression

Header Field: <blank>

Match String: `/^\\orders\\f\\?p=100.*`

Ignore Case: enabled

Include Query in URL: enabled

Start Regex: `/`

Start Match: `^`

Literal Character: `\\`

Regular text: orders

Literal Character: \f


Literal Character: \?

Regular text: p=100

Wildcard: .*

End Regex: /

6.19 Content Matching Rule Example



This diagram shows an example architecture that can be achieved using content matching rules and SubVSs. The details are shown in the section below.

6.19.1 Content Matching Rules

Content Matching rules are also known as selection rules. These rules allow you to match all or some of a **Header Field** or URL string and then set flags if there is a match.

6.19.2 Virtual Services

To add the parent Virtual Service, follow the steps below in the LoadMaster WUI:

1. In the main menu, select **Virtual Services**.
2. Select **Add New**.

Please Specify the Parameters for the Virtual Service.

Virtual Address	<input type="text" value="10.11.0.194"/>
Port	<input type="text" value="80"/>
Service Name (Optional)	<input type="text" value="Test"/>
Use Template	<input type="text" value="Select a Template"/>
Protocol	<input type="text" value="tcp"/>

3. Enter a valid IP address.
4. Enter **80** as the **Port**.
5. Enter a recognizable **Service Name**.
6. Click **Add this Virtual Service**.

▼ Standard Options

Transparency	<input checked="" type="checkbox"/>
Extra Ports	<input type="text"/> Set Extra Ports
Persistence Options	Mode: <input type="text" value="Super HTTP"/> Timeout: <input type="text" value="6 Minutes"/>
Scheduling Method	<input type="text" value="round robin"/>
Idle Connection Timeout (Default 660)	<input type="text"/> Set Idle Timeout
Quality of Service	<input type="text" value="Normal-Service"/>

7. Select **Super HTTP** as the **Persistence Mode**.
8. Expand the **Advanced Properties** section.

▼

Advanced Properties

Content Switching

Disabled

HTTP Selection Rules

Show Selection Rules

HTTP Header Modifications

Show Header Rules

Response Body Modification

Show Body Modification Rules

Enable HTTP/2 Stack

☐

Enable Caching

☐

Enable Compression

☐

Detect Malicious Requests

☐

Add Header to Request

:

Set Header

Copy Header in Request

To Header

Set Headers

Add HTTP Headers

X-Forwarded-For (+ Via) ▼

"Sorry" Server

Port

Set Server Address

Not Available Redirection Handling

Error Code:

▼

Redirect URL:

Set Redirect URL

Default Gateway

Set Default Gateway

Service Specific Access Control

Access Control

9. Select **X-Forwarded-For** in the **Add HTTP Headers** drop-down list.
10. Expand the **Real Servers** section.

▼ Real Servers

Real Server Check Parameters

HTTP Protocol Checked Port [Set Check Port](#)

URL: [Set URL](#)

Status Codes: [Set Status Codes](#)

Use HTTP/1.1: ☐

HTTP Method: [Show Headers](#)

Custom Headers: [Show Headers](#)

Enhanced Options: ☐

11. Click **Add SubVS**.
12. Click **OK**.

Status	Operation
Enabled	Disable Modify Delete

13. Click **Modify**.

Basic Properties	
SubVS Name	<input type="text" value="jdedv_1"/> Set Nickname
SubVS Type	<input type="text" value="HTTP/HTTPS"/>
SubVS Weight	<input type="text" value="1000"/> Set Weight
SubVS Limit	<input type="text" value="0"/> Set Limit

14. Enter **jdedv_1** as the **SubVS Name**.

15. Expand the **Standard Options** section.

Standard Options	
Transparency	<input type="checkbox"/>
Subnet Originating Requests	<input type="checkbox"/>
Persistence Options	Mode: <input type="text" value="None"/>
Scheduling Method	<input type="text" value="round robin"/>
Idle Connection Timeout (Default 660)	<input type="text"/> Set Idle Timeout
Quality of Service	<input type="text" value="Normal-Service"/>

16. Clear the **Transparency** check box.

17. Click **Show Header Rules**.

Add Rule	
Rule:	<input type="text" value="Modify URL: jde_modify_url"/> Add

18. In the **Request Rules** section, select **Modify URL: jde_modify_url** and click **Add**.

Request Rules	
Name	Rule Type
jde_modify_url	Modify URL
Add Rule	
Rule:	<input type="text" value="Modify URL: jdedv_replace"/> Add

19. In the **Request Rules** section, select **Replace Header: jdedv_replace** and click **Add**.

20. Expand the **Real Servers** section.

Real Servers

Real Server Check Parameters

HTTP Protocol

Checked Port

9004

Set Check Port

URL:

Set URL

Status Codes:

Set Status Codes

Use HTTP/1.1:

☐

HTTP Method:

HEAD

Custom Headers:

Show Headers

Enhanced Options:

☐

21. Click **Add New**.

Please Specify the Parameters for the Real Server

Real Server Address

10.11.0.195

Port

9004

Forwarding method

nat

Weight

1000

Connection Limit

22. Enter the relevant address in the **Real Server Address** text box.

23. Enter **9004** as the **Port**.

24. Click **Add This Real Server**.

The steps from 11 to 24 above describe how to add one SubVS. In this example, eight SubVSs are needed. To add the rest of the SubVSs, follow the steps above but use the settings outlined in the table below:

SubVS Name	Transparency	Request Rules	Checked Port	Real Server Port
jdedv_1 (steps above)	Disabled	jde_modify_url jdedv_replace	9004	9004
jdeps_1	Disabled	jdeps_replace jde_modify_url	9001	9001
jdedv_2	Disabled	jde_modify_url jdedv_replace_2	9004	9004

SubVS Name	Transparency	Request Rules	Checked Port	Real Server Port
jdeps_2	Disabled	jde_modify_url jdeps_replace_2	9001	9001
jdeit_1	Disabled	jde_modify_url jdeit_replace	9002	9002
jdest_1	Disabled	jde_modify_url jdest_replace	9003	9003
jdeit_2	Disabled	jde_modify_url jdeit_replace_2	9002	9002
jdest_2	Disabled	jde_modify_url jdest_replace_2	9003	9003

References

Unless otherwise specified, the following documents can be found at <http://kemptechnologies.com/documentation>.

WUI, Configuration Guide

Kemp LoadMaster, Product Overview

Virtual Services and Templates, Feature Description

Last Updated Date

This document was last updated on 27 July 2023.