



RADIUS ESP Authentication

Feature Description

UPDATED: 27 July 2023

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

These materials and all Progress® software products are copyrighted and all rights are reserved by Progress Software Corporation. The information in these materials is subject to change without notice, and Progress Software Corporation assumes no responsibility for any errors that may appear therein. The references in these materials to specific platforms supported are subject to change.

#1 Load Balancer in Price/Performance, 360 Central, 360 Vision, Chef, Chef (and design), Chef Habitat, Chef Infra, Code Can (and design), Compliance at Velocity, Corticon, Corticon.js, DataDirect (and design), DataDirect Cloud, DataDirect Connect, DataDirect Connect64, DataDirect XML Converters, DataDirect XQuery, DataRPM, Defrag This, Deliver More Than Expected, DevReach (and design), Driving Network Visibility, Flowmon, Inspec, Ipswitch, iMacros, K (stylized), Kemp, Kemp (and design), Kendo UI, Kinvey, LoadMaster, MessageWay, MOVEit, NativeChat, OpenEdge, Powered by Chef, Powered by Progress, Progress, Progress Software Developers Network, SequeLink, Sitefinity (and Design), Sitefinity, Sitefinity (and design), Sitefinity Insight, SpeedScript, Stylized Design (Arrow/3D Box logo), Stylized Design (C Chef logo), Stylized Design of Samurai, TeamPulse, Telerik, Telerik (and design), Test Studio, WebSpeed, WhatsConfigured, WhatsConnected, WhatsUp, and WS_FTP are registered trademarks of Progress Software Corporation or one of its affiliates or subsidiaries in the U.S. and/or other countries.

Analytics360, AppServer, BusinessEdge, Chef Automate, Chef Compliance, Chef Desktop, Chef Workstation, Corticon Rules, Data Access, DataDirect Autonomous REST Connector, DataDirect Spy, DevCraft, Fiddler, Fiddler Classic, Fiddler Everywhere, Fiddler Jam, FiddlerCap, FiddlerCore, FiddlerScript, Hybrid Data Pipeline, iMail, InstaRelinker, JustAssembly, JustDecompile, JustMock, KendoReact, OpenAccess, PASOE, Pro2, ProDataSet, Progress Results, Progress Software, ProVision, PSE Pro, Push Jobs, SafeSpaceVR, Sitefinity Cloud, Sitefinity CMS, Sitefinity Digital Experience Cloud, Sitefinity Feather, Sitefinity Thunder, SmartBrowser, SmartComponent, SmartDataBrowser, SmartDataObjects, SmartDataView, SmartDialog, SmartFolder, SmartFrame, SmartObjects, SmartPanel, SmartQuery, SmartViewer, SmartWindow, Supermarket, SupportLink, Unite UX, and WebClient are trademarks or service marks of Progress Software Corporation and/or its subsidiaries or affiliates in the U.S. and other countries. Java is a registered trademark of Oracle and/or its affiliates. Any other marks contained herein may be trademarks of their respective owners.

Please refer to the NOTICE.txt or Release Notes – Third-Party Acknowledgements file applicable to a particular Progress product/hosted service offering release for any related required third-party acknowledgements.

Table of Contents

1 Introduction	4
1.1 Document Purpose	4
1.2 Intended Audience	4
2 Configure RADIUS ESP Authentication	5
2.1 Prerequisites	5
2.2 Create an SSO Domain	5
2.3 Create a Virtual Service	7
2.4 Set the L7 Client Token Timeout Value	9
3 RADIUS Challenge/Response	11
References	12
RADIUS Authentication and Authorization, Technical Note	12
Web User Interface (WUI), Configuration Guide	12
Last Updated Date	13

1 Introduction

As part of the Kemp Edge Security Pack (ESP), the LoadMaster supports a number of authentication protocols, including Remote Authentication Dial-In User Service (RADIUS).

RADIUS is a widely deployed protocol enabling centralized authentication, authorization and accounting for network access. Originally developed for dial-up remote access, RADIUS is now supported by Virtual Private Network (VPN) servers, wireless access points, authenticating Ethernet switches, Digital Subscriber Line (DSL) access, and other network access types.

A RADIUS client (typically an access server such as a dial-up server, VPN server, or wireless access point) sends user credentials and connection parameter information in the form of a RADIUS message to a RADIUS server. The RADIUS server authenticates and authorizes the RADIUS client request, and sends back a RADIUS message response. RADIUS clients also send RADIUS accounting messages to RADIUS servers. Additionally, the RADIUS standards support the use of RADIUS proxies. A RADIUS proxy is a computer that forwards RADIUS messages between RADIUS clients, RADIUS servers and other RADIUS proxies. RADIUS messages are never sent between the access client and the access server.

1.1 Document Purpose

This document provides step-by-step instructions on how to configure authentication and Single Sign On (SSO) using RADIUS in the LoadMaster.

For instructions on how to use RADIUS authentication for LoadMaster Web User Interface (WUI) access, refer to the [RADIUS Authentication and Authorization, Technical Note](#).

1.2 Intended Audience

This document is intended to be used by anyone who is interested in finding out how to configure RADIUS ESP authentication in the Kemp LoadMaster.

2 Configure RADIUS ESP Authentication

Follow the steps in the sections below to configure the LoadMaster to use RADIUS ESP authentication.

2.1 Prerequisites


Before configuring the LoadMaster, please ensure that there is a RADIUS authentication server in place and that it is configured with the client details (the IP address of the LoadMaster and the shared secret which is used for password encryption).

It is not possible to use RADIUS authentication if you are using a FIPS LoadMaster.

2.2 Create an SSO Domain

Follow the steps below to create an SSO domain in the LoadMaster:

1. In the LoadMaster WUI, navigate to **Virtual Services > Manage SSO**.



2. Enter the name of the SSO configuration in the **Add new Client Side Configuration** field and click **Add**.

2 Configure RADIUS ESP Authentication

Domain EXAMPLE.COM

Authentication Protocol
RADIUS

RADIUS Server(s)
Set RADIUS Server(s)

RADIUS Shared Secret
Please Set Password
Set Shared Secret

Send NAS Identifier
☒

RADIUS NAS Identifier
b100
Set NAS Identifier

Domain/Realm
Set Domain/Realm Name

Logon Format (Phase 1 RADIUS)
Principalname

Logon Format (Phase 2 Real Server)
Principalname

Logon Transcode
Disabled

Failed Login Attempts
0
Set Failed Login Attempts

Public - Untrusted Environment
Private - Trusted Environment

Session Timeout
900
Set Idle Time
900
Set Idle Time

1800
Set Max Duration
28800
Set Max Duration

Use for Session Timeout:
idle time

Test User
Set Test User

Test User Password
Set Test User Password

3. Select the relevant **Authentication Protocol**.

RADIUS and **RADIUS and Unencrypted LDAP** (two factor authentication) are the valid options for RADIUS authentication.

4. Select the relevant **LDAP Endpoint**, if using two factor authentication.
5. Enter the address(es) of the **RADIUS Server(s)** to be used to authenticate this domain and click **Set RADIUS Server(s)**.

Multiple addresses can be entered using a space-separated list.

IPv6 is not supported for RADIUS authentication.

6. Enter the **RADIUS Shared Secret** that is to be used between the RADIUS server and the LoadMaster and click **Set Shared Secret**.

The Shared Secret is a text string that serves as a password between the LoadMaster and the RADIUS server.

7. Decide whether or not to enable the **Send NAS Identifier** check box.

If this check box is disabled (default), a Network Access Server (NAS) identifier is not sent to the RADIUS server. If it is enabled, a NAS identifier string is sent to the RADIUS server. By default,

this is the hostname. Alternatively, if a value is specified in the **RADIUS NAS Identifier** text box, this value is used as the NAS identifier. If the NAS identifier cannot be added, the RADIUS access request is still processed.

8. If you enabled the **Send NAS Identifier** check box, decide whether or not to specify the **RADIUS NAS Identifier**.

If the **Send NAS Identifier** check box is selected, the **RADIUS NAS Identifier** field is shown. When specified, this value is used as the NAS identifier. Otherwise, the hostname is used as the NAS identifier. If the NAS identifier cannot be added, the RADIUS access request is still processed.

9. Enter the **Domain/Realm** and click **Set Domain/Realm Name**.

This is also used with the logon format to construct the normalized username, for example:

- **Principalname:** <Username>@<Domain>
 - **Username:** <Domain>\<Username>
-

10. Select the relevant logon string format in the **Logon Format (Phase 1)** drop-down list.
11. Select the relevant logon string format in the **Logon Format (Phase 2)** drop-down list.
12. Fill out the remaining fields as needed.

2.3 Create a Virtual Service

Follow the steps below to create a Virtual Service and configure the ESP Options:

1. In the main menu of the LoadMaster WUI, navigate to **Virtual Services > Add New**.

Please Specify the Parameters for the Virtual Service.

Virtual Address	<input type="text" value="10.154.11.179"/>
Port	<input type="text" value="80"/>
Service Name (Optional)	<input type="text" value="Example Virtual Service"/>
Use Template	<input type="text" value="Select a Template"/>
Protocol	<input type="text" value="tcp"/>

2 Configure RADIUS ESP Authentication

2. Enter a valid IP address in the **Virtual Address** text box.
3. Fill out the other fields as needed.
4. Click **Add this Virtual Service**.

▼
ESP Options

Enable ESP ☐

5. Expand the **ESP Options** section.
6. Tick the **Enable ESP** check box.

▼
ESP Options

Enable ESP ☒

ESP Logging ☒ User Access: ☒ Security: ☒ Connection: ☒

Client Authentication Mode Form Based ▼

SSO Domain EXAMPLE.COM ▼

Available Domain(s)
None Available

Assigned Domain(s)
None Assigned

> <

[Set Alternative SSO Domains](#)

Allowed Virtual Hosts mail.exchange.com mail.ex

Allowed Virtual Directories /owa*

Pre-Authorization Excluded Directories

Permitted Groups

Permitted Group SID(s)

Include Nested Groups ☐

Steering Groups

SSO Image Set Exchange ▼

SSO Greeting Message

Logoff String

Display Public/Private Option ☐

Disable Password Form ☐

Use Session or Permanent Cookies Session Cookies Only ▼

User Password Change URL https://server/link

User Password Change Dialog Message You must change your

Server Authentication Mode None ▼

[Set Allowed Virtual Hosts](#)

[Set Allowed Directories](#)

[Set Excluded Directories](#)

[Set Permitted Groups](#)

[Set Permitted Group SIDs](#)

[Set Steering Groups](#)

[Set SSO Greeting Message](#)

[Set SSO Logoff String](#)

[Set Password Change URL](#)

[Set Dialog Message](#)

7. Select the relevant **Client Authentication Mode**.

The RADIUS **SSO Domain** will not be available if the **Client Authentication Mode** is set to **Delegate to Server** – please select a different mode.

8. Select the RADIUS SSO domain, which was previously configured, from the **SSO Domain** drop-down list.
9. Fill out any other fields, as needed.
10. Add any Real Servers, as needed.

For an explanation of all of the WUI fields, refer to the [Web User Interface \(WUI\), Configuration Guide](#).

2.4 Set the L7 Client Token Timeout Value

The L7 Client Token Timeout is the duration of time (in seconds) to wait for the client token while the process of authentication is ongoing. The default L7 client token timeout is set to 120 seconds. This can be modified as needed in the LoadMaster WUI. The range of valid values is 60 to 300. To configure the timeout value, follow the steps below:

1. In the main menu, go to **System Configuration > Miscellaneous Options > L7 Configuration**.

2 Configure RADIUS ESP Authentication

Allow connection scaling over 64K Connections	<input checked="" type="checkbox"/>	
Always Check Persist	<input type="text" value="No"/>	
Add Port to Active Cookie	<input type="checkbox"/>	
Conform to RFC	<input checked="" type="checkbox"/>	
Close on Error	<input type="checkbox"/>	
Add Via Header In Cache Responses	<input type="checkbox"/>	
Real Servers are Local	<input type="checkbox"/>	
Drop Connections on RS failure	<input checked="" type="checkbox"/>	
Drop at Drain Time End	<input checked="" type="checkbox"/>	
L7 Authentication Timeout (secs)	<input type="text" value="30"/>	Set Timeout (Valid values:30 - 300)
L7 Client Token Timeout (secs)	<input type="text" value="120"/>	Set Timeout (Valid values:60 - 300)
L7 Connection Drain Time (secs)	<input type="text" value="300"/>	Set Time (Valid values:0, 60 - 86400)
Additional L7 Header	<input type="text" value="X-ClientSide"/>	
100-Continue Handling	<input type="text" value="RFC-2616 Compliant"/>	
Allow Empty POSTs	<input type="checkbox"/>	
Allow Empty HTTP Headers	<input type="checkbox"/>	
Force Complete RS Match	<input type="checkbox"/>	
Least Connection Slow Start	<input type="text" value="0"/>	Set Slow Start (Valid values:0 - 600)
Share SubVS Persistence	<input type="checkbox"/>	
Log Insight Message Split Interval	<input type="text" value="10"/>	Set Log Split Interval (Valid values:1 - 100)
Include User Agent Header in User Logs	<input type="checkbox"/>	

2. Enter the new value in the **L7 Client Token Timeout** text box and click **Set Timeout**.

3 RADIUS Challenge/Response

The LoadMaster supports RADIUS challenge/response authentication. RADIUS challenge/response is supported transparently – if the server sends a challenge, an additional form is displayed and the user is asked to enter the additional token/password.

The authentication flow is as follows:

1. The end user is prompted to enter a username and password.
2. If the username and password credentials have authenticated successfully, the One Time Password (OTP) is requested using a server challenge. An additional form is displayed and the end user needs to enter the additional token/password.
3. The username and OTP details are then submitted to the server for authentication.

Regarding the methods used during the authentication flow – an Access Request is sent from the LoadMaster to the server (which includes the username and password), the server responds with an Access Challenge (if the credentials have authenticated successfully) which will result in a subsequent form to collect the OTP. The LoadMaster then sends another Access Request (with the State and OTP included) and the server then responds with either an Access Accept or Access Reject, depending on whether the authentication was successful or not.

References

Unless otherwise specified, the following documents can be found at <http://kemptechnologies.com/documentation>.

RADIUS Authentication and Authorization, Technical Note

Web User Interface (WUI), Configuration Guide

Last Updated Date

This document was last updated on 27 July 2023.