



WUI FIPS LoadMaster

Configuration Guide

UPDATED: 27 July 2023

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

These materials and all Progress® software products are copyrighted and all rights are reserved by Progress Software Corporation. The information in these materials is subject to change without notice, and Progress Software Corporation assumes no responsibility for any errors that may appear therein. The references in these materials to specific platforms supported are subject to change.

#1 Load Balancer in Price/Performance, 360 Central, 360 Vision, Chef, Chef (and design), Chef Habitat, Chef Infra, Code Can (and design), Compliance at Velocity, Corticon, Corticon.js, DataDirect (and design), DataDirect Cloud, DataDirect Connect, DataDirect Connect64, DataDirect XML Converters, DataDirect XQuery, DataRPM, Defrag This, Deliver More Than Expected, DevReach (and design), Driving Network Visibility, Flowmon, Inspec, Ipswitch, iMacros, K (stylized), Kemp, Kemp (and design), Kendo UI, Kinvey, LoadMaster, MessageWay, MOVEit, NativeChat, OpenEdge, Powered by Chef, Powered by Progress, Progress, Progress Software Developers Network, SequeLink, Sitefinity (and Design), Sitefinity, Sitefinity (and design), Sitefinity Insight, SpeedScript, Stylized Design (Arrow/3D Box logo), Stylized Design (C Chef logo), Stylized Design of Samurai, TeamPulse, Telerik, Telerik (and design), Test Studio, WebSpeed, WhatsConfigured, WhatsConnected, WhatsUp, and WS_FTP are registered trademarks of Progress Software Corporation or one of its affiliates or subsidiaries in the U.S. and/or other countries.

Analytics360, AppServer, BusinessEdge, Chef Automate, Chef Compliance, Chef Desktop, Chef Workstation, Corticon Rules, Data Access, DataDirect Autonomous REST Connector, DataDirect Spy, DevCraft, Fiddler, Fiddler Classic, Fiddler Everywhere, Fiddler Jam, FiddlerCap, FiddlerCore, FiddlerScript, Hybrid Data Pipeline, iMail, InstaRelinker, JustAssembly, JustDecompile, JustMock, KendoReact, OpenAccess, PASOE, Pro2, ProDataSet, Progress Results, Progress Software, ProVision, PSE Pro, Push Jobs, SafeSpaceVR, Sitefinity Cloud, Sitefinity CMS, Sitefinity Digital Experience Cloud, Sitefinity Feather, Sitefinity Thunder, SmartBrowser, SmartComponent, SmartDataBrowser, SmartDataObjects, SmartDataView, SmartDialog, SmartFolder, SmartFrame, SmartObjects, SmartPanel, SmartQuery, SmartViewer, SmartWindow, Supermarket, SupportLink, Unite UX, and WebClient are trademarks or service marks of Progress Software Corporation and/or its subsidiaries or affiliates in the U.S. and other countries. Java is a registered trademark of Oracle and/or its affiliates. Any other marks contained herein may be trademarks of their respective owners.

Please refer to the NOTICE.txt or Release Notes – Third-Party Acknowledgements file applicable to a particular Progress product/hosted service offering release for any related required third-party acknowledgements.

Table of Contents

1 Introduction	10
1.1 Document Purpose	10
1.2 Intended Audience	10
2 Home	11
2.1 Login Information	11
2.2 General Information	12
2.3 Virtual Service and Real Server Status	12
2.4 WAF Status	12
2.5 System Metrics	13
2.6 License Information	14
2.7 About LoadMaster	14
3 Virtual Services	16
3.1 Add New	16
3.2 View/Modify (Existing HTTP Service)	16
3.3 Basic Properties	19
3.4 Standard Options	21
3.5 SSL Properties	31
3.6 Advanced Properties	36
3.7 Web Application Firewall (WAF) Options	45
3.8 Edge Security Pack (ESP) Options	48
3.8.1 SMTP Virtual Services and ESP	64

3.9 Sub Virtual Services	65
3.10 View/Modify (Remote Terminal Service)	68
3.11 Real Servers	68
3.11.1 HTTP or HTTPS Protocol Health Checking	71
3.11.2 Binary Data Health Checking	75
3.11.3 Name Server (DNS) Protocol Health Checking	76
3.11.4 Add a Real Server	76
3.11.5 Modify a Real Server	79
3.12 Manage Templates	80
3.13 Manage SSO Domains	81
3.13.1 Single Sign On Domains	82
3.13.1.1 Client Side (Inbound) SSO Domains	83
3.13.1.1.1 Client Side (Inbound) SAML SSO Domains	88
3.13.1.1.2 Sessions	90
3.13.1.2 Server Side (Outbound) SSO Domains	93
3.13.2 Single Sign On Image Sets	94
3.14 WAF Settings	94
4 Global Balancing	97
4.1 Enable/Disable GSLB	97
4.2 Manage FQDNs	97
4.2.1 Add an FQDN	97
4.2.2 Add/Modify an FQDN	98

4.3 Manage Clusters	104
4.3.1 Add a Cluster	104
4.3.2 Modify a Cluster	104
4.3.3 Delete a Cluster	105
4.3.4 Upgrading GEO Clusters	106
4.4 Miscellaneous Params	106
4.4.1 Resource Check Parameters	107
4.4.2 Stickiness	109
4.4.3 Location Data Update	109
4.5 IP Range Selection Criteria	109
4.6 IP Blacklist Settings	111
4.7 Configure DNSSEC	112
4.8 GSLB Statistics	114
5 Statistics	117
5.1 Real Time Statistics	117
5.1.1 Global	117
5.1.2 Real Servers	119
5.1.3 Virtual Services	122
5.1.4 WAF	125
5.2 Historical Graphs	126
5.3 Device Information	129
6 Real Servers	131

7 Rules & Checking	132
7.1 Content Rules	132
7.1.1 Content Matching Rules	132
7.1.2 Content Matching	132
7.1.3 Add Header	134
7.1.4 Delete Header	135
7.1.5 Replace Header	136
7.1.6 Modify URL	137
7.1.7 Replace String in Response Body	138
7.1.8 Header Modification	138
7.2 Check Parameters	139
7.2.1 Service (Health) Check Parameters	139
7.2.2 Adaptive Parameters	140
8 Certificates & Security	142
8.1 SSL Certificates	142
8.2 Intermediate Certificates	143
8.3 Generate CSR (Certificate Signing Request)	143
8.4 Backup/Restore Certs	146
8.5 Cipher Sets	147
8.6 Remote Access	149
8.6.1 Administrator Access	149
8.6.2 GEO Settings	154

8.6.3 GEO Partners Status	155
8.6.4 WUI Authentication and Authorization	156
8.7 Admin WUI Access	159
8.8 OCSP Configuration	162
8.9 LDAP Configuration	163
9 System Configuration	166
9.1 Network Setup	166
9.1.1 Interfaces	166
9.1.2 Host & DNS Configuration	173
9.1.3 Default Gateway	175
9.1.4 Additional Routes	176
9.1.5 Packet Routing Filter	176
9.1.6 VPN Management	178
9.1.6.1 View/Modify VPN Connection	179
9.2 HA and Clustering	181
9.2.1 HA Mode	182
9.2.1.1 Azure HA Parameters	187
9.2.1.2 AWS HA Parameters	189
9.2.2 Cluster Control	191
9.2.2.1 Cluster Parameters	194
9.3 System Administration	195
9.3.1 User Management	195

9.3.1.1 Modify User	198
9.3.2 Update License	200
9.3.2.1 Online Method	201
9.3.2.2 Offline Method	202
9.3.2.3 Debug Checks	202
9.3.3 System Reboot	202
9.3.4 Update Software	203
9.3.5 Backup/Restore	205
9.3.6 Date/Time	208
9.4 Logging Options	209
9.4.1 System Log Files	210
9.4.1.1 Debug Options	211
9.4.2 Extended Log Files	221
9.4.3 Syslog Options	224
9.4.4 SNMP Options	226
9.4.5 Email Options	230
9.5 Miscellaneous Options	233
9.5.1 WUI Settings	233
9.5.2 L7 Configuration	235
9.5.3 Network Options	240
9.5.4 AFE Configuration	245
9.5.5 Kemp 360 Central Activation Settings	248

10 Help	250
References	252
Last Updated Date	253

1 Introduction

Kemp products optimize web and application infrastructure as defined by high-availability, high-performance, flexible scalability, security and ease of management. Kemp products maximize the total cost-of-ownership for web infrastructure, while enabling flexible and comprehensive deployment options.

1.1 Document Purpose

This document describes the Web User Interface (WUI) of the Kemp LoadMaster. It describes in detail how to configure the various features of the Kemp LoadMaster using the WUI.


The available menu options in the LoadMaster may vary from the ones described in this document. The features available in a LoadMaster depend on what license is in place. To upgrade a license, please call a Kemp representative.

1.2 Intended Audience

This document is intended to help anyone who wishes to configure the Kemp LoadMaster using the WUI.

2 Home

Clicking the **Home** menu option displays the home page which presents a list of basic information regarding the LoadMaster.



If any of the panels are not displaying information, try resetting the browser to default settings.

2.1 Login Information

After initially logging in to the LoadMaster, if Session Management is enabled - some login information is displayed:

- The last login time and IP address of the current user
- The number of successful logins by the current user in the last 30 days

- The total number of failed login attempts by any user (including unknown usernames) since the last successful login

For further information on Session Management, refer to the **OCSP Configuration Admin WUI Access** section.

2.2 General Information

IP address: The IP address of the LoadMaster.

LoadMaster Version: The firmware version of the LoadMaster.

Serial Number: The Serial Number of the LoadMaster.

Boot Time: The time of the last server reboot.

2.3 Virtual Service and Real Server Status

VS Status


This section displays some monitoring information for the Virtual Services, such as the percentage of Virtual Services that are up and the number of disabled Virtual Services. Clicking the **Details** link will display the **View/Modify Services** screen.

Syslog messages are generated every hour about the number of Virtual Services, SubVSs and Real Servers that are up/down, and so on. Syslog messages are also generated when a status changes.

RS Status

This section displays some monitoring information for the Real Servers, such as the percentage of Real Servers that are up and the number of disabled Real Servers. Clicking the **Details** link will display the **Real Servers** screen.

2.4 WAF Status



The Web Application Firewall (WAF) Status section is displayed if at least one Virtual Service has WAF enabled. The values shown here are as follows:

- The total number of requests handled by the WAF (shows all requests, whether they were blocked or not). Two requests are recorded for each connection – one incoming and one outgoing request.
- The total number of events handled by the WAF (that is, requests that were blocked)
- The number of events that have happened in the current hour (since xx.00.00)
- The number of events that have happened since midnight (local time)
- The number of times the event counter has gone over the configured warning threshold today. For example, if the threshold is set to 10 and there has been 20 events, this counter is set to 2. The warning threshold is set on a per-Virtual Service basis by filling out the **Hourly Alert Notification Threshold** field in **WAF Options** in the Virtual Service modify screen. For further information, refer to the **Web Application Firewall (WAF) Options** section.

2.5 System Metrics

CPU Load: The percentage of load to the CPU of the LoadMaster appliance.

TPS [conn/s]: The total number of Transactions Per Second and the number of Secure Sockets Layer (SSL) transactions per second.

Net Load: Network load in megabits per second, shown for each configured interface. The **Net Load** will only be displayed for interfaces which have been configured.

CPU Temp.: Displays the temperature of the CPU on supported hardware platforms.

The CPU Load and Net Load data is updated every 5 seconds.

On Dell LoadMasters, you can retrieve hardware statistics using SNMP. These include:

- Temperature
- Fan speed
- Power supply
- Voltage current

These values are only available using SNMP. For further information on **SNMP Options**, refer to the **SNMP Options** section.

2.6 License Information

License Information

UUID

c6c79fc1-16d1-4ce8-9df9-c0a23879d2b9

Activation Date

Mon Feb 27 20:56:11 UTC 2017

Licensed Until

unlimited

License Type

VLM-5000 + Enterprise+

License Status

Single Perm

Appliance Model

VLM-5000

Subscription

Enterprise+

Subscription Expiry

Tue Feb 27 2018

Subscription Features

ESP - Edge Security Pack expires with subscription
GEO Blacklist IP expires with subscription
ModSecurity expires with subscription
WAF Subscription expires with subscription
SDN - Software Defined Networking expires with subscription

Upgrade

⬆

[View License](#)

[Support & FAQ](#)

[Find Online Documentation](#)

[About LoadMaster](#)

Click the **View License** link to display model, subscription expiry, and subscription feature details, such as the activation date and end date of the LoadMaster license.

If the subscription has expired, a message is displayed in the **License Information** section. To renew a subscription, contact Kemp.

From 13 days prior to the license or subscription expiry date, a message is displayed on the **Home** screen that states the expiry date. To relicense the appliance or to renew your subscription, contact Kemp. Failure to relicense may cause the LoadMaster to stop working.

Upgrade: Upgrade the LoadMaster by buying a license from the Kemp purchase portal.

2.7 About LoadMaster

On the **About LoadMaster** page, you can view licenses for third party software that is used in the LoadMaster.

The LoadMaster contains software which is licensed under one or more of the following licenses.	
The GNU GPL Version 2	View
<hr/>	
The GNU GPL Verison 3	View
<hr/>	
The GNU LGPL Version 2.1	View
<hr/>	
The Linux Kernel License	View
<hr/>	
The ISC Bind License	View
<hr/>	
The Apache License Version 2.0	View
<hr/>	
The Curt Library	View
<hr/>	
The DNSSEC Tools 2.2 Library	View
<hr/>	
The Expat Library	View

To view a license, click the **View** button next to the relevant item.

3 Virtual Services

From this point onwards, the headings in this document generally correspond to the options in the main menu on the left of the LoadMaster WUI.

3.1 Add New

Please Specify the Parameters for the Virtual Service.

Virtual Address

10.11.0.194

Port

443

Service Name (Optional)

Exchange 2013 HTTPS

Protocol

tcp ▼

Here the Virtual IP (VIP) address, port, protocol and name are defined. The VIP address, name and port are manually entered into the text boxes and the protocol is selected from the drop-down list.

You cannot use a special character as the first character of the Service Name.

If templates are installed on your machine, a **Use Template** drop-down list is available whereby you can select a template to configure the Virtual Service parameters such as port and protocol.

For further information regarding templates, please refer to the **Virtual Services and Templates Feature Description** document on the [Kemp Documentation Page](#).

3.2 View/Modify (Existing HTTP Service)


Virtual IP Address	Prot	Name	Layer	Certificate Installed	Status	Real Servers	Operation	
10.154.11.77:80	tcp	Example Virtual Service	L7		Up	10.154.15.21	Modify	Delete
10.154.11.91:80	tcp	Splunk - HTTP redirect	L7		FailMsg		Modify	Delete
10.154.11.91:443	tcp	Splunk	L7	Add New	Down	10.154.11.92	Modify	Delete
10.154.11.91:514	udp	Splunk Syslog UDP	L4		Down		Modify	Delete

This screen displays a list of Virtual Services on the LoadMaster, summarizing the main properties of each and giving the options to modify or delete services, or create a new service.

CAUTION

Delete is permanent, there is no UNDO feature. **Use with care.**

Each configured Virtual Service may be changed by clicking the **Modify** button or deleted by clicking the **Delete** button.



If you try to delete a Virtual Service containing SubVSs, a confirmation warning appears. Click **OK** to confirm the deletion.

The status of the Virtual Service is also displayed. Health checking is enabled by default when a Virtual Service is created. For further information on health checking, refer to the **Real Servers** section.


The Virtual Service status may be one of the following:

- **Up** – At least one Real Server is available.
- **Down** – No Real Servers are available.
- **Sorry** – All Real Servers are down and traffic is routed to a separately configured Sorry Server that is not part of the Real Server set, with no health checking.
- **Disabled** – The Virtual Service has been administratively disabled by unticking the **Activate or Deactivate Service** check box in the **Basic Properties** section of the Virtual Service modify screen.
- **Redirect** – A fixed redirect response has been configured. Redirect Virtual Services can be created by using the Add a Port 80 Redirector VS option in the Advanced Properties section. For more information, refer to the **Advanced Properties** section.
- **Fail Message** – A fixed error message has been configured. A fixed error message can be specified using the Not Available Redirection Handling options. Refer to the **Advanced Properties** section for more information.

3 Virtual Services

- **Unchecked** – Health checking of the Real Servers has been disabled. All Real Servers are accessed and presumed UP.
- **Security Down** – The LoadMaster is unable to reach the Authentication Server and will prevent access to any Virtual Service which has Edge Security Pack (ESP).
- **WAF Misconfigured** – If the WAF for a particular Virtual Service is misconfigured, for example if there is an issue with a rule file, the status changes to WAF Misconfigured and turns red. If the Virtual Service is in this state, all traffic is blocked. WAF can be disabled for that Virtual Service to stop the traffic being blocked, if required, while troubleshooting the problem.

The image below shows the Virtual Service properties screen. It is composed of several component sections:



Properties for tcp/10.154.11.9:80 (Id:7) - Operating at Layer 7

<-Back Duplicate VIP Change Address Export Template

Basic Properties

Service Name Set Nickname

Alternate Address Set Alternate Address

Service Type

Activate or Deactivate Service ☒

▶ Standard Options

▶ SSL Properties (Acceleration Enabled)

▶ Advanced Properties

▶ WAF Options (Enabled)

▶ Real Servers

- **Basic Properties** - where the usual and most common attributes are set
- **Standard Options** – the most widely used features of a Virtual Service
- **SSL Properties** – if SSL acceleration is being used, it will show Acceleration Enabled and this section of the screen is used to configure the SSL functions
- **Advanced Properties** – the additional features for a Virtual Service
- **WAF Options** – where the options relating to the Web Application Firewall (WAF) can be set
- **ESP Options** – where the options relating to ESP are set
- **Real Servers/SubVSs** – where Real Servers/SubVSs are assigned to a Virtual Server

Depending upon the service type, and enabled or disabled features, specific fields and options show in the WUI. The screenshots in this document may not represent every possible configuration.

3.3 Basic Properties

There are three buttons adjacent to the **Basic Properties** heading:

Duplicate VIP

This option makes a copy of the Virtual Service, including any related SubVSs. All Virtual Service configuration settings are copied to the duplicate Virtual Service. When this button is clicked, a screen appears where the IP address and port can be specified for the copied Virtual Service.

Change Address

Clicking this button opens a screen where the virtual IP address and port of the Virtual Service can be modified.

Export Template

Export the Virtual Service settings as a template. Templates can be used to create Virtual Services quickly and easily.

When exporting a Virtual Service template in which the Virtual Service uses a custom **Cipher Set**, the LoadMaster on which the template is imported must include the same custom **Cipher Set**.

Virtual Services created from a template will have all of the settings preconfigured based on the settings in the template. The settings in the Virtual Service can then be changed, as needed. For more information on templates, refer to the **Virtual Services and Templates, Feature Description** on the [Kemp Documentation Page](#).

Basic Properties	
Service Name	Exchange 2013 HTTPS Set Nickname
Alternate Address	<input type="text"/> Set Alternate Address
Service Type	HTTP/HTTPS ▼
Activate or Deactivate Service	<input checked="" type="checkbox"/>

Service Name

This text box allows you to assign a nickname to the Virtual Service being created, or change an existing one.

In addition to the usual alphanumeric characters, the following ‘special’ characters can be used as part of the Service Name: .

@ - _

However, you cannot use a special character as the first character of the Service Name.

Alternate Address

This is where, if so desired, you would specify a secondary address in either IPv6 or IPv4 format.

Service Type

Setting the **Service Type** controls the options displayed for the Virtual Service. It’s important to make sure the Service Type is set according to the type of application that you are load balancing.

WebSocket Virtual Services must be get to the **Generic** Service Type.

The **HTTP/2 Pass-through** Service Type allows HTTP/2 traffic. HTTP/2 does not support transparency. Subnet originating, alternate source address functionality, caching, compression and body rewrites all work, as required.

Activate or Deactivate Service

This check box gives you the option to activate or deactivate a Virtual Service. The default (active) is selected.

3.4 Standard Options

Standard Options	
Force L4	<input type="checkbox"/>
Transparency	<input type="checkbox"/>
Subnet Originating Requests	<input checked="" type="checkbox"/>
Extra Ports	<input type="text"/> Set Extra Ports
Persistence Options	Mode: <input type="text" value="None"/>
Scheduling Method	<input type="text" value="round robin"/>
Idle Connection Timeout (Default 660)	<input type="text"/> Set Idle Timeout

Force L4

Select this check box to force the Virtual Service to run at Layer 4 and not at Layer 7. This is only required in some special circumstances. If in doubt, leave this option unchecked.

L7 Transparency

When using L7, a connection can be transparent. This means the connection arriving at the Real Server appears to come directly from the client. Alternatively, if the connection is not transparent – connections at the Real Server appear to come from the LoadMaster. Kemp recommends keeping transparency disabled in most configurations.

Enabling transparency makes the Virtual Service transparent (no Network Address Translation (NAT)). However, if the client resides on the same subnet as the Virtual IP and Real Servers, then the Virtual Services will automatically NAT the source IP (enabling non-transparency).

If the **Real Servers are local** option is enabled, then the Real Servers are NATed (non-transparent), even if **L7 Transparency** is enabled. This only happens if the Real Server is the originator of the request to the Virtual Service (and not just answering requests from other clients). For further information on the **Real Servers are local** option, refer to the **L7 Configuration** section.

Subnet Originating Requests

This option is only available if **Transparency** is disabled.

If **Subnet Originating Requests** is enabled, the source addresses for connections to the Real Servers is the interface address of the LoadMaster. If this option is disabled, the source address is the Virtual Service IP address. If transparency is enabled, the source address is the IP address of the client and the **Subnet Originating Requests** option is ignored.

If the Real Server is on a subnet, and the **Subnet Originating Requests** option is enabled, then the subnet address of the LoadMaster is used as the source IP address.

The Subnet Originating Requests feature was designed for 'local' Real Servers. It works fine for re-encrypt unless the Real Server is non-local and not on the Default Gateway interface. In this case, you can force the local address by setting it in the **Alternate Source Addresses** field. This works for both normal and re-encrypted Virtual Services.

This switch allows control of subnet originating requests on a per-Virtual Service basis. If the global switch (**Subnet Originating Requests** in **System Configuration > Miscellaneous Options > Network Options** in the main menu) is enabled then it is enabled for all Virtual Services.

It is recommended that the **Subnet Originating Requests** option is enabled on a per-Virtual Service basis.

For more information about the global option, refer to the **Network Options** section.

If the global option is not enabled, it can be controlled on a per-Virtual Service basis.

If this option is switched on for a Virtual Service that has SSL re-encryption enabled, all connections currently using the Virtual Service is terminated.

Extra Ports

You may specify a range of ports, sequential or otherwise, starting with the base port already configured for the Virtual Service. The port numbers are inputted to the field and separated with a space, and the maximum range is 510 ports.

You can enter the extra ports either as port ranges or single ports separated by spaces or comma in whatever order you wish, for example, entering the list **8000-8080, 9002, 80, 8050, 9000** will add the ports 80, 8000 to 8080, 9000 and 9002.

Server Initiating Protocols

By default, the LoadMaster will not initiate a connection with a Real Server until it has received some data from a client. This prohibits certain protocols from working as they need to communicate with the Real Server before transmitting data.

If the Virtual Service uses one of these protocols then select the protocol from the drop-down list to enable it to work correctly.

The protocols that can be selected are:

- SMTP

- SSH
- IMAP4
- MySQL
- POP3
- Other Server Initiating Protocols

The **Server Initiating Protocols** option is not visible when the port specified in the Virtual Service is **80**, **8080** or **443**.

Persistence Options

Persistence is setup on a per Virtual Service basis. This section allows you to select whether persistence is enabled for this service, to set the type of persistence and the persistence timeout value.

If persistence is enabled it means that a client connection to a particular Real Server using the LoadMaster is persistent, in other words - the same client will subsequently connect to the same Real Server. The timeout value determines for how long this particular connection is remembered.

The drop-down list gives you the option to select the type of persistence. These are listed and described below.

Source IP Address

The source IP address (of the requesting client) is used as the key for persistency in this case.

Super HTTP

Super HTTP is the recommended method for achieving persistence for HTTP and HTTPS services with the LoadMaster. It creates a unique fingerprint of the client browser and uses that fingerprint to preserve connectivity to the correct Real Server. The fingerprint is based on the values of the **User-Agent** field, if the **User-Agent** value does not contain the **MSRPC** string.

If the **User-Agent** value contains the **MSRPC** string, then the value of the Authorization header is used to achieve persistence.

In the case that the Authorization header is not present, and the **User Agent** value contains the **MSRPC** string, the persist value will simply be blank with a length of zero.

Server Cookie

The LoadMaster checks the value of a specially set cookie in the HTTP header. Connections with the same cookie will go to the same Real Server.

Server Cookie or Source IP

If cookie persistence fails, it reverts to source-based persistence.

Active Cookie

With Active Cookie persistence, the cookies are generated by the LoadMaster, not the server. When a connection comes into a LoadMaster Virtual Service configured with Active Cookie, the LoadMaster looks for a specific cookie. If that cookie is not there, the LoadMaster inserts it into the HTTP stream with a Set-Cookie directive. Existing cookies are not affected. As with the Server Cookie persistence method, the value for the LoadMaster-generated cookie is unique to each user, allowing the LoadMaster to differentiate between users. A benefit of this method is that no cookies need to be managed or generated by the servers, relieving the burden of server configuration. To gain better dispersion per client connection you can enable the Add Port to Active Cookie feature in the L7 configuration. For further information on this option, refer to the **L7 Configuration** section. With Active Cookie persistence, the cookie is valid for the session or until the persistence time expires. For example, if using Active Cookie persistence with the persistence timeout set to 10 minutes and the client connects at 2pm, then disconnects and reconnects at 2.05pm – this would reset the persistence timeout value. If the client tries to connect to a Virtual Service after the persistence timeout has expired, they would present the old cookie. The LoadMaster will check its persistence table and see that it does not have a valid entry. The LoadMaster would then generate a new cookie for the client and would update its persistence table.

Active Cookie or Source IP

If active cookie persistence fails, it reverts to source-based persistence.

Hash All Cookies

The **Hash All Cookies** method creates a hash of the values of all cookies in the HTTP stream. Cookies with the same value are sent to the same server for each request. If the values change, then the connection is treated as a new connection and the client is allocated to a server according to the load balancing algorithm.

Hash All Cookies or Source IP

Hash All Cookies or Source IP is identical to **Hash All Cookies**, with the additional feature that it will fall back to Source IP persistence in the event no cookies are in the HTTP string.

Super HTTP and Source IP Address

This is the same as super HTTP but it also appends the source IP address to the string, thus improving the distribution of the resulting HASH.

URL Hash

With URL Hash persistence, the LoadMaster will send requests with the same URL to the same server.

HTTP Host Header

With HTTP Host Header persistence, the LoadMaster will send all requests that contain the same value in the HTTP Host: header to the same server.

Hash of HTTP Query Item

This method operates in exactly the same manner as Server Persistence, except that the named item being inspected is a Query Item in the Query String of the URL. All queries with the same Query Item value is sent to the same server.

Selected Header

With Selected Header persistence, the LoadMaster will send all requests that contain the same value in the specified header to the same server.

SSL Session ID

Each session over SSL has its own session ID which can be persisted on.

For this option to appear as a persistence method, the Virtual Service needs to have a Service Type of Generic and SSL acceleration must be disabled.

If a Virtual Service is an SSL service and not offloaded, the LoadMaster cannot meaningfully interact with any of the data in the stream at Layer 7. The reason is, the data is encrypted and the LoadMaster has no way of decrypting it.

If, in the above scenario, a persistence mode that is not based off source IP is required, this is the only other option. When an SSL session is started, it generates a session ID for the connection. This session ID can be used to cause the client to persist to the correct server.

There are some downsides to this however, as most modern browsers regenerate the session ID at very short intervals, basically overwriting it, even if there is a longer interval set on the persist timeout.

UDP Session Initiation Protocol (SIP)


3 Virtual Services

This persistence mode is only available in a UDP Virtual Service when **Force L4** is enabled. SIP uses request and response transactions, similar to HTTP. An initial INVITE request is sent, which contains a number of header fields. These header fields can be used for persistence.

Timeout

For each persistence method, there is a configurable timeout value that determines how long the persistence for each user is honored, selectable from one minute to seven days.

This timeout clock is started when the initial connection is established. The persistence timeout value is updated if the client reconnects within the timeout period. For example, if the persistence timeout is set to 1 hour and the client starts a connection at 2pm, if the client disconnects and then reconnects before 3pm they will still persist to the same Real Server. Also, the persistence record is updated to reflect this and the persistence countdown timer is reset back to 1 hour for this client.



If a client made connections to the Virtual Service repeatedly within the timeout period, the persistence would be honored indefinitely. For instance, given the following scenario:

- Persistence Timeout is set to 10 minutes
- A user makes several requests in the course of 20 minutes, but the time between connections is always less than 1 minute

The request should be sent to the correct Real Server, as long as it is available (that is, passing health checks).

If the user goes idle for 20 minutes, then the next connection is counted as a new session, and may be sent to a different server, depending on scheduling. If the connection is opened for more than 10 minutes and the client disconnects and reconnects, the persistence record would have expired, the LoadMaster will create a new persistence entry for that client and possibly send the client to a new Real Server. This is due to the fact that the persistence countdown starts once a connection is established, not at the closing of the connection.

If you are experiencing persistence issues, this may be due to the fact that the persistence timeout is not long enough. If this is not long enough, then the timeout value should be set for a higher amount. In general, matching this value to your server timeout value is recommended.

Header field name

When **UDP Session Initiation Protocol** is selected as the persistence mode is selected in the LoadMaster, a text box called **Header field name** will appear. The header field that is to be used as the basis for the persistence information should be entered here.

Scheduling Methods

This section allows you to select the method by which the LoadMaster will select a Real Server, for this particular service. The scheduling methods are as follows:

- Round Robin:

Round Robin causes the LoadMaster to assign Real Servers to a session in order, for example the first session connects to Real Server 1, the second to Real Server 2 and so on. There is no bias in the way the Real Servers are assigned.

- Weighted Round Robin:

This method uses the weight property of the Real Servers to determine which Real Servers get preference. The higher the weight a Real Server has, the higher the proportion of connections it will receive.

- Least Connection:

With this method, the current Real Server with the fewest open connections is assigned to the session.

- Weighted Least Connection:

As with **Least Connection**, but with a bias relative to the weight.

- Resource Based (Adaptive):

3 Virtual Services

Adaptive scheduling means that the load on the Real Servers is periodically monitored and that packets are distributed such that load is approximately equal for all machines. More details can be found in the section covering scheduling methods.

- Fixed Weighting:

All traffic goes to highest weight Real Server that is available. Real Servers should be weighted at the time they are create and no two Real Servers should have same weight, otherwise unpredictable results may occur.

Virtual IP Address	Prot	Name Layer	Certificate Installed	Status	Real Servers	Operation
172.21.42.11:80	tcp	L7		 Up	 172.21.42.200  172.21.42.201  172.21.42.202  172.21.42.203  172.21.42.204	Modify Delete

When fixed weighting is in use, the Real Server with the higher weight is indicated with a green star icon.

- Weighted Response Time:

Every 15 seconds the LoadMaster measures the time it takes for a response to arrive for a health check probe and uses this time to adjust the weights of the Real Servers accordingly, that is, a faster response time relative to the other Real Servers leads to a higher weight which in turn leads to more traffic sent to that server.

- Source IP Hash:

Instead of using the weights or doing round robin, a hash of the source IP is generated and used to find the correct real server. This means that the real server is always the same from the same host. You do not need any source IP persistence.

Because this method relies solely on the client (source) IP address and ignores current server load, using this method can lead to a particular Real Server becoming overloaded, or a general traffic imbalance across all Real Servers.

- URL Hash:

The **URL Hash** method works by creating a hash value based on the object referenced in the client request's URL and the number of Real Servers or SubVSs in the Virtual Service. All requests for a particular URL are sent to the same Real Server/SubVS, unless a Real Server or SubVS is added or removed – in which case all hash values are re-calculated and subsequent traffic is redistributed

accordingly. A write always succeeds regardless of any outage (unless everything is down). The URL hash method sends write requests to the next available SubVS when a SubVS is down. For example:

- A Virtual Service has three SubVSs. A write request is received for which there is an existing hash that says to send the write to SubVS 2.
- SubVS 2 is down. The request is sent to SubVS 3.
- If SubVS 3 is down, send to SubVS 1 (in a round-robin fashion).
- When SubVS2 comes back online, go back to honoring the hash and send future requests to SubVS 2.

This scheduling method was developed primarily to support Dell EMC Elastic Cloud Storage (ECS) applications and efficient use of ECS-based resources, but could also be used to support other workloads where storage efficiency is the primary goal. For Dell ECS deployments, the load traffic is distributed across the Virtual Data Centers (VDCs) in the deployment, each of which are represented on LoadMaster as a SubVS. Within each VDC, the traffic is distributed across the Real Servers in the SubVS.

Idle Connection Timeout (Default 660)

The seconds before an idle connection is closed. Setting it to **0** ensures that the default L7 connection timeout is used. You can modify the default **Connection Timeout** value by going to **System Configuration > Miscellaneous Options > Network Options**.

Quality of Service

The **Quality of Service** drop-down sets a Type of Service (ToS) in the IP header of packets that leave the Virtual Service. This means that the next device or service that deals with the packets will know how to treat and prioritise this traffic. Higher priority packets are sent from the LoadMaster before lower priority packets.

The different options are described below:

- **Normal-Service:** No special priority given to the traffic
- **Minimize-Cost:** Used when data needs to be transferred over a link that has a lower “cost”
- **Maximize-Reliability:** Used when data needs to travel to the destination over a reliable link and with little or no retransmission
- **Maximize-Throughput:** Used when the volume of data transferred during an interval is important, even if the latency over the link is high

- **Minimize-Delay:** Used when the time required (latency) for the packet to reach the destination must be low. This option has the quickest queue of each of the **Quality of Service** choices.

The ToS values for each option are provided in the following table:

Bits	Decimal	Importance
1000	8th	Minimal delay
0100	4	Maximum throughput
0010	2	Maximum reliability
0001	1	Minimal costs (in the form of money)
0000	0	Normal service

The **Quality of Service** feature only works with Layer 7 traffic.
It does not work with Layer 4 traffic.

Use Address for Server NAT

By default, when the LoadMaster is being used to SNAT Real Servers, the source IP address used on the internet is that of the LoadMaster. The **Use Address for Server NAT** option allows the Real Servers configured on the Virtual Service to use the Virtual Service as the source IP address instead - if the Real Server makes an outbound request using the same port as the Virtual Service. The LoadMaster does not NAT all outbound ports.

The **Use Address for Server NAT** option is most useful for services such as SMTP when the LoadMaster is in a public domain and when the service requires a reverse DNS check to see if the source address sent from the LoadMaster is the same as the Mail Exchanger (MX) record of the sender.

If the Real Servers are configured on more than one Virtual Service that has this option set, the LoadMaster examines the destination port of the server's request and then selects the Virtual Service with a matching port. The LoadMaster then uses this Virtual Service as the source IP address. If no match is found for the port being requested, the IP address of the LoadMaster is used as the source IP address.

The **Use Address for Server NAT** option only works on Virtual Services which are operating on the default gateway. This option is not supported on non-default gateway interfaces.

3.5 SSL Properties

SSL Properties	
SSL Acceleration	Enabled: <input checked="" type="checkbox"/> Reencrypt: <input type="checkbox"/>
Supported Protocols	<input type="checkbox"/> SSLv3 <input type="checkbox"/> TLS1.0 <input checked="" type="checkbox"/> TLS1.1 <input checked="" type="checkbox"/> TLS1.2 <input checked="" type="checkbox"/> TLS1.3
Require SNI hostname	<input type="checkbox"/>
Self Signed Certificate in use.	
Certificates	<div> <div>Available Certificates</div> <div>None Available</div> <div>Manage Certificates</div> </div> <div> <div>Assigned Certificates</div> <div>None Assigned</div> <div>Set Certificates</div> </div>
Cipher Set	Default Modify Cipher Set
Ciphers	<div>Assigned Ciphers</div> <div> ECDHE-ECDSA-AES256-GCM-SHA384 ECDHE-RSA-AES256-GCM-SHA384 DHE-DSS-AES256-GCM-SHA384 DHE-RSA-AES256-GCM-SHA384 ECDHE-ECDSA-CHACHA20-POLY1305 ECDHE-RSA-CHACHA20-POLY1305 </div>
Client Certificates	No Client Certificates required
Strict Transport Security Header	Don't add the Strict Transport Security Header

SSL Acceleration

This check box appears when the criteria for SSL Acceleration have been met. Select this check box to activate **SSL Acceleration**.

Enabled: If the **Enabled** check box is selected and there is no certificate for the Virtual Service, you are prompted to install a certificate. You can add a certificate by clicking **Manage Certificates** and importing or adding a certificate.

Reencrypt: Selecting the **Reencrypt** check box re-encrypts the SSL data stream before sending it to the Real Server.


Reversed: Selecting this check box means that the data from the LoadMaster to the Real Server is re-encrypted. The input stream must not be encrypted. This is only useful in connection with a separate Virtual Service which decrypts SSL traffic then uses this Virtual Service as a Real Service and loops data back to it. In this way, the client to Real Server data path is always encrypted on the wire.

Supported Protocols

3 Virtual Services

The check boxes in the **Supported Protocols** section enable you to specify which protocols are supported by the Virtual Service. By default, TLS1.1, TLS1.2, and TLS1.3 are enabled and SSLv3 and TLS1.0 are disabled.

Starting with version 7.2.37, when re-encryption is enabled, the TLS version that can be negotiated between the LoadMaster and the Real Servers behind it are no longer constrained by the TLS version settings configured on the client side. All TLS versions and ciphers that are supported on the LoadMaster can be negotiated without restriction by Real Servers. In this way, the LoadMaster can, for example, provide strict security for client-side application access and still support server-side connections to legacy servers that only support specific, less secure, TLS versions, and ciphers. This is illustrated in the example below.



Require SNI hostname

If require Server Name Indication (SNI) is selected, the hostname is always required to be sent in the TLS client hello message.

When **Require SNI hostname** is disabled, the first certificate is used if a host header match is not found.

When **Require SNI hostname** is enabled, a certificate with a matching common name must be found, otherwise an SSL error is yielded. Wildcard certificates are also supported with SNI.

When using a Subject Alternative Name (SAN) certificate, alternate source names are not matched against the host header.

Wildcard certificates are supported but note that the root domain name is not matched, as per RFC 2459. Only anything to the left of the dot is matched. Additional certificates must be added to match the root domain names. For example, www.kemptechnologies.com is matched until a wildcard of *.kemptechnologies.com. Kemptechnologies.com is not matched.

To send SNI host information in HTTPS health checks, enable **Use HTTP/1.1** in the **Real Servers** section of the relevant Virtual Service(s) and specify a host header. If this is not set, the IP address of the Real Server is used.

Certificates

Available certificates are listed in the **Available Certificates** select list on the left. To assign or unassign a certificate, select it and click the right or left arrow button. Then click **Set Certificates**. Multiple certificates can be selected by holding **Ctrl** on your keyboard and clicking each required certificate.

There is a limit of 8171 characters when assigning certificates to a Virtual Service using the WUI.

A Virtual Service can be configured using both RSA and ECC certificates. However, if an RSA and an ECC certificate have the same common name, for example, kemp.com, the first certificate is preferred. If the ECC certificate is first in the list, and a client does not have an ECC cipher, the connection fails. Conversely, if the RSA certificate is first in the list, and a client does not have an RSA cipher, the connection fails.

The total number of certificates that you can add to a Virtual Service is 256, but this number may be further limited by the

size of the certificate file names used. In LMOS Version 7.2.47 and later releases, the number of characters in each certificate file name and extension (not counting the period between them), plus all spaces used to separate multiple file names, must add up to 8176 characters or less (in earlier releases, the limitation is 1023 characters.)

Clicking **Manage Certificates** brings you to the SSL Certificates screen.

Reencryption Client Certificate

With SSL connections, the LoadMaster gets a certificate from the client and also gets a certificate from the server. The LoadMaster transcribes the client certificate in a header and sends the data to the server. The server still expects a certificate. This is why it is preferable to install a pre-authenticated certificate in the LoadMaster.

Reencryption SNI Hostname

Specify the Server Name Indication (SNI) hostname to use when connecting to the Real Servers.

This field is only visible when SSL re-encryption is enabled.

Cipher Set

A cipher is an algorithm for performing encryption or decryption.

Each Virtual Service (which has **SSL Acceleration** enabled) has a cipher set assigned to it. This can either be the system-defined cipher set or a user-customized cipher set. You can select a system-defined cipher set to quickly and easily select and apply the relevant ciphers.

In the FIPS LoadMaster, there are three system-defined cipher sets; **WUI**, **Default** and **BestPractices**. Each of these cipher sets only contain ciphers that are supported by FIPS.

Refer to the **SSL Accelerated Services for the FIPS, Feature Description** on the [Kemp Documentation Page](#) for a full list of the ciphers supported by the FIPS LoadMaster.

You can edit the list of ciphers which are assigned to a Virtual Service by clicking **Modify Cipher Set**. If changes are made to a preconfigured cipher set, a new custom cipher set is created. You can create custom cipher sets and use them across different Virtual Services.

By default, the name for the custom cipher set is **Custom_<VirtualServiceID>**. Kemp recommends changing the name of custom cipher sets because if another system-defined cipher set is modified,

the name again defaults to **Custom_<VirtualServiceID>** and overwrites any existing cipher sets with that name.

It is not possible to modify the list of ciphers in a system-defined cipher set. Instead, a new custom cipher is created when changes are made to the ciphers list.

Ciphers

The **Ciphers** list is read only and displays a list of the currently assigned ciphers. Clicking **Modify Cipher Set** brings you to the **Cipher Set Management** screen. This screen allows you to create new, and modify existing custom cipher sets.

Client Certificates

- **No Client Certificates required:** enables the LoadMaster to accept HTTPS requests from any client. This is the recommended option.

By default the LoadMaster accepts HTTPS requests from any client. Selecting any of the other values below requires all clients to present a valid client certificate. In addition, the LoadMaster also passes information about the certificate to the application.

You should not change this option from the default of **No Client Certificates required**. Only change from the default option if you are sure that all clients that access this service have valid client certificates.

- **Client Certificates required:** requires that all clients forwarding a HTTPS request must present a valid client certificate.
- **Client Certificates and add Headers:** requires that all clients forwarding a HTTPS request must present a valid client certificate. The LoadMaster also passes information about the certificate to the application by adding headers.
- The below options send the certificate in its original raw form. The different options let you specify the format that you want to send the certificate in:
 - Client Certificates and pass DER through as SSL-CLIENT-CERT
 - Client Certificates and pass DER through as X-CLIENT-CERT
 - Client Certificates and pass PEM through as SSL-CLIENT-CERT
 - Client Certificates and pass PEM through as X-CLIENT-CERT

Verify Client using OCSP

Verify (using Online Certificate Status Protocol (OCSP)) that the client certificate is valid.


This option is only visible when ESP is enabled.

Strict Transport Security Header

Enable this option to add the Strict-Transport-Security header to all LoadMaster-generated messages (ESP and error messages). The options in this drop-down list are as follows:

- **Don't add the Strict Transport Security Header**
- **Add the Strict Transport Security Header - no subdomains**
- **Add the Strict Transport Security Header - include subdomains**

3.6 Advanced Properties



Advanced Properties

Content Switching Disabled

HTTP Selection Rules [Show Selection Rules](#)

HTTP Header Modifications [Show Header Rules](#)

Response Body Modification [Show Body Modification Rules](#)

Enable Caching ☐

Enable Compression ☐

Detect Malicious Requests ☐

Add Header to Request : [Set Header](#)

Copy Header in Request To Header [Set Headers](#)

Add HTTP Headers [Legacy Operation\(X-Forwarded-For\)](#)

'Sorry' Server Port [Set Server Address](#)

Not Available Redirection Handling Error Code: [Set Redirect URL](#)

Redirect URL: [Set Redirect URL](#)

Default Gateway [Set Default Gateway](#)

Alternate Default Gateway [Set Alternate Default Gateway](#)

Service Specific Access Control [Access Control](#)

Content Switching

Clicking the **Enable** button, enables rule-based Content Switching on this Virtual Service. Once enabled, rules must be assigned to the various Real Servers. Rules can be attached to Real Server by clicking the **None** button located next the Real Server. Once rules are attached to a Real Server the **None** button will display the count of rules attached.

Rules Precedence

3 Virtual Services

Clicking the **Rules Precedence** button displays the order in which Content Switching rules are applied. This option only appears when Content Switching and rules are assigned to the Real Server (s).

<-Back						
Request Match Rules assigned to tcp/10.35.47.61:443 (Id:1)						
Name	Rule Type	Options	Header	Pattern	Replacement	Operation
KempTest1	Match Content		Test	Test		Delete
KempTest2	Match Content		Testing	Testing		Promote Delete

This screen shows the Content Switching rules that are assigned to the Real Servers of the Virtual Services and the order in which they apply. A rule may be promoted in the order of precedence by clicking its corresponding **Promote** button.

HTTP Selection Rules

Show the selection rules that are associated with the Virtual Service.

HTTP Header Modifications

Clicking **Show Header Rules** displays the order in which Header Modification rules are implemented. The number of rules (of both request and response type) is displayed on the actual button.

<-Back

Modification Rules assigned to tcp/10.35.47.61:443 (Id:1)

Request Rules

Name	Rule Type	Options	Header	Pattern	Replacement	Operation
KempHeader1	Add Header		Test		Test	<div>Delete</div>
KempHeader3	Replace Header		Testing	Testing	Tested	<div>Promote</div> <div>Delete</div>

Response Rules

Name	Rule Type	Options	Header	Pattern	Replacement	Operation
KempHeader1	Add Header		Test		Test	<div>Delete</div>

Add Rule

Rule:

Replace Header: KempHeader3 ▾

Add

From within the screen you can **Add** and **Delete** Header Modification rules. The order in which the rules are applied can be changed by clicking the **Promote** buttons.

Response Body Modification

Clicking the **Show Body Modification Rules** button displays the response body modification rules assigned to the Virtual Service. The number of assigned rules is displayed in the button label.

[<-Back](#)

Body Modification Rules assigned to tcp/10.35.47.111:80 (Id:1)

Body Modification Rules

Name	OptionsPattern	Replacement	Operation
ExampleReplaceStringInResponseBodyRule	http://yourcomain.com	https://new.yourdomain.com	Delete
ExampleRule2	Example	Replacement	Promote Delete

Add Rule

Rule: [Add](#)

From this screen, you can **Add** and **Delete** response body modification rules to/from the Virtual Service. You can change the order that the rules are applied in by clicking the **Promote** button.

Response body rules are not compatible with Kerberos Constrained Delegation (KCD). If KCD is enabled on a Virtual Service, it is not possible to assign a body rule to it.

Enable HTTP/2 Stack

Enable HTTP/2 client requests to be served by the LoadMaster directly. HTTP/2 requests are made using a secure connection. Please ensure the **SSL Properties** are configured and the **BestPractices Cipher Set** is selected if enabling this option. The **Enable Caching** check box should also be selected to optimize end user experience.

Enable Caching

This option enables caching of static content. This saves valuable Real Server processing power and bandwidth. Caching can be enabled per HTTP and offloaded HTTPS Virtual Services.

Types of file that can be cached may be defined in AFE configuration under the **Systems Configuration > Miscellaneous Options** menu.

Maximum Cache Usage

This option limits the size of the cache memory per Virtual Service. For example, two Virtual Services, each running with a limit of 50% will use 100% of the cache store. The default is **No Limit**. It is recommended to limit the cache size to prevent unequal use of the cache store. Ensure that the cache maximum usage is adjusted so that each Virtual Service has a percentage of cache to use. If there is not remaining space to be allocated for a cache enabled Virtual Service, that service will not cache content.

Enable Compression

Files sent from LoadMaster are compressed with Gzip.

If compression is enabled without caching, LoadMaster performance may suffer. When compression and caching are both enabled on a Virtual Service, compression will only be applied to the cached entry (if the entry would be cached). The first request is not compressed; it is used to fill the cache. The system can either fill the cache or compress the request – it cannot do both at the same time.

The types of file that can be compressed may be defined in AFE configuration in the **Systems Configuration > Miscellaneous** section of the LoadMaster WUI.

Compression is not recommended for files 100MB or greater in size.

More RAM may need to be added to Virtual LoadMasters using the hypervisor to compress large files.

Detect Malicious Requests

The Intrusion Prevention System (IPS) service will provide in-line protection of Real Server(s) by providing real-time mitigation of attacks and isolation of Real Server(s). Intrusion prevention is based on the industry standard SNORT database and provides real-time intrusion alerting.

To get updated or customized rules, please refer to the SNORT website: <https://www.snort.org/>.

The detection code only handles HTTP-classed rules.

Selecting the **Detect Malicious Requests** check box enables the IPS per HTTP and offloaded HTTPS Virtual Services. There are two options for handling of requests that match a SNORT rule. **Drop Connection**, where a rule match will generate no HTTP response, or **Send Reject**, where a rule match will generate a response to the client of HTTP 400 “Invalid Request”. Both options prevent the request from reaching the Real Server(s).

Enable Multiple Connect

Enabling this option permits the LoadMaster to manage connection handling between the LoadMaster and the Real Servers. Requests from multiple clients are sent over the same TCP connection.

Multiplexing only works for simple HTTP GET operations. The **Enable Multiple Connect** check box will not be available in certain situations, for example if WAF, ESP or SSL Acceleration is enabled.

Port Following

Port following enables a switch from an HTTP connection to an HTTPS (SSL) connection to be persistent on the same Real Server. Port following is possible between UDP and TCP connections.

To switch on port following, the following must be true:

- The Virtual Service where port following is being switched on must be an HTTPS service
- There must be a HTTP service
- Both of these Virtual Services must the same Layer 7 persistence mode selected, that is, **Super HTTP** or **Source IP Address** persistence

Port following is not available on SubVSs.

For further information, refer to the **Port Following, Feature Description** on the [Kemp Documentation Page](#).

Add Header to Request

Input the key and the value for the extra header that is to be inserted into every request sent to the Real Servers.

Click the **Set Header** button to implement the functionality.

Copy Header in Request

This is the name of the source header field to copy into the new header field before the request is sent to the Real Servers. Enter the name of the header field into which the source header is to be copied in the **To Header** text box.

Add HTTP Headers

This option allows you to select which headers are to be added to the HTTP stream. The options available include:

- Legacy Operation(X-ClientSide)
- None
- X-Forwarded-For (+ Via)
- X-Forwarded-For (No Via)
- X-ClientSide (+ Via)
- X-ClientSide (No Via)
- Via Only

In the Legacy operation, if the system is in HTTP kernel mode, then a header is added. Otherwise nothing is done. For the other operation methods, then the system is forced into HTTP kernel mode and the specified operation is performed.

Sorry Server

Enter the IP Address and Port number in the applicable fields. If no Real Servers are available, the LoadMaster will redirect to a specified location, with no checking. The IP address of a Sorry Server must be on a network or subnet that is defined on the LoadMaster.

When using a Layer 4 Virtual Service, the Sorry Server should be on the same subnet as the Real Server.

When using a Layer 7 Virtual Service, the Sorry Server can be on any local network. It is also possible to add a non-local sorry server. For this, **Transparency** must be disabled, there must be a route to the Sorry Server and the **Enable Non-Local Real Servers** option must be enabled (**System Configuration > Miscellaneous Options > Network Options**).

Sorry Server functionality does not work with SSL reencryption.

Not Available Redirection Handling

When no Real Servers are available to handle the request you can define the error code and URL that the client should receive.

- **Error Code:** If no Real Servers are available, the LoadMaster can terminate the connection with a HTTP error code. Select the appropriate error code.
- **Redirect URL:** When there are no Real Servers available and an error response is to be sent back to the client, a redirect URL can also be specified. If the string entered in this text box does not include **http://** or **https://** the string is treated as being relative to the current location, so the hostname is added to the string in the redirect. This field also supports the use of wildcards such as **%h** and **%s** which represent the requested hostname and Uniform Resource Identifier (URI) respectively.
- **Error Message:** When no Real Servers are available and an error response is to be sent back to the client, the specified error message is added to the response.

For security reasons, the returned HTML page only returns the text **Document has moved**. No request-supplied information is returned.

- **Error File:** When no Real Servers are available and an error response is to be sent back to the client, the specified file is added to the response. This enables simple error HTML pages to be sent in response to the specified error.

The maximum size of this error page is 16KB.

Not Available Server/Port

▼ Advanced Properties			
Not Available Server	<input type="text"/>	Port	<input type="text"/>
Service Specific Access Control	<input type="button" value="Access Control"/>	<input type="button" value="Set Server Address"/>	

In a UDP Virtual Service there is an option to specify a **Not Available Server** and **Port**. When there are no Real Servers available to handle the request this option defines the URL that the client will receive.

The value of the **Not Available Server** can only be changed for UDP if the service is not currently using the **Not Available Server**.

Add a Port 80 Redirector VS

If no port 80 Virtual Service is configured, one can be created. It will then redirect the client to the URL specified in the **Redirection URL:** field.

Click the **Add HTTP Redirector** button to implement the redirector.

When the **Add HTTP Redirector** button is clicked, a redirect Virtual Service is created and this WUI option disappears from the relevant Virtual Service.

Default Gateway

Specify the Virtual Service-specific gateway to be used to send responses back to the clients. If this is not set, the global default gateway is used.

Click the **Set Default Gateway** button to implement the default gateway. The **Default Gateway** for a Virtual Service is only used for that Virtual Service.

If the global **Use Default Route Only** option is set in **System Configuration > Miscellaneous Options > Network Options**, traffic from Virtual Services that have the **Default Gateway** set is only routed to the interface where the Virtual Service's default route is located. This can allow the LoadMaster to be directly connected to client networks without returning traffic directly using the adjacent interface.

Alternate Default Gateway

This field is only visible if an **Alternate Address** is set for the Virtual Service. You should only use the **Alternate Default Gateway** field if all of the following conditions are met:

- The **Alternate Address** has a different address family to the main Virtual Service address, for example, the Virtual Service address is IPv4 and the **Alternate Address** is IPv6 or the other way around.

- The Virtual Service **Default Gateway** is set.
- A second Virtual Service **Default Gateway** is set for the other address family.

Alternate Source Addresses

If no list is specified, the LoadMaster will use the IP address of the Virtual Service as its local address. Specifying a list of addresses ensures the LoadMaster will use these addresses instead.

Click the **Set Alternate Source Addresses** button to implement the Alternate Source Addresses.

This option is only available if the **Allow connection scaling over 64K Connections** option is enabled in the **L7 Configuration** screen.

Service Specific Access Control

Allows you to change the Virtual Service-specific **Access Control** lists.

If you implement the Access Control Lists option, the **Extra Ports** option will not work correctly.

When using Access Control Lists on a Virtual Service that has the same IP address as an interface (which Kemp does not recommend) the following ports are never blocked:

- 443 (WUI)
- 22 (SSH)
- 161 (SNMP)
- 53 (DNS)

3.7 Web Application Firewall (WAF) Options

▼ WAF Options

Web Application Firewall

Enabled: ☒ 3 from 4 WAF VSs already configured

Default Operation:

Audit Only ▼

Audit mode:

Audit Relevant ▼

Options

Inspect HTML POST Request Content ☒

Process Responses ☐

Hourly Alert Notification Threshold

0

Set Alert Threshold

Available Rulesets

Generic Rules

☒ ip_reputation
☐ known_vulns
☐ malware_detection
☒ botnet_attacks
☐ creditcard_known
☐ creditcard_track_pan

Application Specific

☐ cpanel_attacks
☐ drupal_attacks
☐ Joomla_attacks
☐ modx_attacks
☐ netcat_attacks

List of rules

Clear All

Set All

Rule Filter:

☒ 2200924:SLR/MALICIOUS_SOFTWARE/BOTNET:SLR: Common IRC Botnet Attack Command String Identified
☒ 2250117:SLR/WEB_ATTACK/RFI:Remote File Inclusion Attack
☒ 2250118:SLR/WEB_ATTACK/RFI:Remote File Inclusion Attack
☒ 2250119:SLR/WEB_ATTACK/RFI:Remote File Inclusion Attack
☒ 2250120:SLR/WEB_ATTACK/LFI:Local File Inclusion (LFI) Attack
☒ 2250121:SLR/WEB_ATTACK/LFI:Local File Inclusion (LFI) ENV Attack in User-Agent
☒ 2250122:SLR/WEB_ATTACK/PHP_INJECTION:e107 PHP

Apply

Reset

The Web Application Firewall (WAF) feature must be enabled before you can configure these options.

▼ WAF Options

Web Application Firewall

Enabled: ☒ 2 from 4 WAF VSs already configured

To enable WAF, select the **Enabled** check box. A message is displayed next to the **Enabled** check box displaying how many WAF-enabled Virtual Services exist and it also displays the maximum number of WAF-enabled Virtual Services that can exist.

▼ WAF Options

Web Application Firewall

Enabled: ☐ WAF not allowed If ESP KCD Server Authentication Mode configured. Insufficient memory available to enable WAF. At least 512MB of free memory is recommended.

If the maximum number of WAF-enabled Virtual Services have been reached, the **Enabled** check box is grayed out.

45

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

A message displays if there is insufficient memory available to enable WAF.

Utilizing WAF can have a significant performance impact on your LoadMaster deployment. Please ensure that the appropriate resources are allocated.

For virtual and bare metal LoadMaster instances, a minimum of 2GB of allocated RAM is required for operation of WAF. The default memory allocation for Virtual LoadMasters and LoadMaster Bare Metal instances prior to LoadMaster Operating System version 7.1-22 is 1GB of RAM. If this default allocation has not been changed please modify the memory settings before attempting to proceed with WAF configuration.

Default Operation

Select the default operation of the WAF:

- **Audit Only:** This is an audit-only mode – logs are created but requests and responses are not blocked.
- **Block Mode:** Either requests or responses are blocked.

Audit mode

Select what logs to record:

- **No Audit:** No data is logged.
- **Audit Relevant:** Logs data which is of a warning level and higher. This is the default option for this setting.
- **Audit All:** Logs all data through the Virtual Service.

Selecting the **Audit All** option produces a large amount of log data. Kemp does not recommend selecting the **Audit All** option for normal operation. However, the **Audit All** option can be useful when troubleshooting a specific problem.

Inspect HTML POST Request Content

Enable this option to also process the data supplied in POST requests.

Three additional options (**Enable JSON Parser**, **Enable XML Parser**, and **Enable Other Content Types**) only become available if **Inspect HTML Post Request Content** is enabled.

Enable JSON Parser

Enable verification of JavaScript Object Notation (JSON) POST requests.

Enable XML Parser

Enable verification of XML POST requests.

Enable Other Content Types

Enable verification of POST content types (other than XML/JSON).

Enabling the inspection of any other content types may increase system resource utilization (CPU and memory). A specific list of content types should be considered.

When this option is enabled, a text box is provided to enter a comma-separated list of POST content types allowed for WAF analysis. By default, all types (other than XML/JSON) are enabled.

Process Responses

Enable this option to verify responses sent from the Real Servers.

This can be CPU and memory intensive.

If a Real Server is gzip encoding, WAF will not check that traffic, even if **Process Responses** is enabled.

Hourly Alert Notification Threshold

This is the threshold of incidents per hour before sending an alert. Setting this to **0** disables alerting. This threshold also relates to the **Events over Limit Today** number which is displayed on the WUI home page. For example, if the threshold is set to 10 and there has been 20 events, the counter is set to 2.

Rules

This is where you can assign/un-assign generic, application-specific, application-generic and custom rules to/from the Virtual Service.

You cannot assign application-specific and application-generic rules to the same Virtual Service.

Individual rules within each ruleset can be enabled/disabled as required. To enable a ruleset, tick the relevant check box. If you have not enabled/disabled rules in that ruleset previously, all rules are enabled by default in the right box. If you have previously enabled/disabled rules in that ruleset, within that Virtual Service – the rules will retain their previous settings.

You can enable/disable individual rules as needed by ticking the relevant ruleset on the left and ticking/unticking the rules on the right.

Some rules or rule sets may have dependencies on other rules. There is no dependency check in the LoadMaster when rules are disabled - before disabling any rule, please be aware of any rule chains or dependencies.

When finished making changes, click the **Apply** button.

Clicking the **Clear All** button will disable all rules for the selected ruleset.


Clicking the **Set All** button will enable all rules for the selected ruleset.

Text can be entered in the **Rule Filter** text box to filter the rules to only show rules which contain the filter text.

Clicking **Reset** will disable all rulesets and rules.

3.8 Edge Security Pack (ESP) Options

The ESP feature must be enabled before you can configure these options. To enable the ESP function, please select the **Enable ESP** check box.

A screenshot of a user interface element for the Edge Security Pack (ESP). It consists of a rectangular box with a thin border. Inside the box, on the left, is a downward-pointing triangle icon followed by the text "ESP Options". On the right side of the box, there is the text "Enable ESP" followed by an unchecked checkbox.

The full **ESP Options** screen will appear.

The ESP feature can only be enabled if the Virtual Service is a HTTP, HTTPS, or SMTP Virtual Service.

ESP Options

Enable ESP ☒

ESP Logging

User Access: ☒ Security: ☒ Connection: ☒

Client Authentication Mode

Form Based

SSO Domain

EXAMPLE.COM

Available Domain(s)

SECOND.COM

THIRD.COM

Assigned Domain(s)

None Assigned

Set Alternative SSO Domains

Allowed Virtual Hosts

Set Allowed Virtual Hosts

Allowed Virtual Directories

/

Set Allowed Directories

Pre-Authorization Excluded Directories

/owa/auth /owa/auth*

Set Excluded Directories

Permitted Groups

Set Permitted Groups

Permitted Group SID(s)

Set Permitted Group SIDs

Include Nested Groups

☐

Steering Groups

Set Steering Groups

Verify Bearer Header

☐

SSO Image Set

Exchange

SSO Greeting Message

Set SSO Greeting Message

Logoff String

/owa/logoff.owa

Set SSO Logoff String

Display Public/Private Option

☒

Disable Password Form

☐

Enable Captcha

☒ Warning: All Captcha parameters must be set before it can be used

Captcha Public Key

Set Captcha Public Key

Captcha Private Key

Set Captcha Private Key

Captcha Access URL

www.google.com/recaptcha/api.js

Set Captcha Access URL

Captcha Verification URL

www.google.com/recaptcha/api/siteverify

Set Captcha Verify URL

Use Session or Permanent Cookies

Session Cookies Only

User Password Change URL

/owa/auth/expiredpassword.

Set Password Change URL

User Password Change Dialog Message

Set Dialog Message

User Password Expiry Warning

☒ 15 days

Server Authentication Mode

None

Enable ESP

Enable or disable the ESP feature set by selecting or removing the checkmark from the **Enable ESP** checkbox.

ESP Logging

There are three types of logs stored in relation to the ESP feature. Each of these logs can be enabled or disabled by selecting or deselecting the relevant checkbox. The types of log include:

- **User Access:** logs recording all user logins
- **Security:** logs recording all security alerts
- **Connection:** logs recording each connection

Logs are persistent and can be accessed after a reboot of the LoadMaster. For further information on logs please refer to the **Extended Log Files** section.

Client Authentication Mode

Specifies how clients attempting to connect to the LoadMaster are authenticated. The following types of methods are available:

- **Delegate to Server:** the authentication is delegated to the server
- **Basic Authentication:** standard Basic Authentication is used
- **Form Based:** clients must enter their user details within a form to be authenticated on the LoadMaster
- **Client Certificate:** clients must present the certificate which is verified against the issuing authority
- **NTLM:** NTLM credentials are based on data obtained during the interactive logon process and consist of a domain name and a user name
- **SAML:** The LoadMaster supports SAML, playing the role of a SAML service provider. The service provider provides secure, gated access to a resource.

The remaining fields in the **ESP Options** section will change based on the **Client Authentication Mode** selected.

SSO Domain

Select the Single Sign-On (SSO) Domain within which the Virtual Service is included.

Please refer to the **Manage SSO Domains** section for further information on configuring SSO Domains. An SSO Domain must be configured to correctly configure the ESP feature.

Only SSO domains with the **Configuration type** of **Inbound Configuration** are shown as options in this **SSO Domain** field.

Alternative SSO Domains

Many organizations use extranets to share information with customers and partners. It is likely that extranet portals will have users from two or more Active Directory domains. Rather than authenticating users from individual domains one at a time, assigning **Alternative SSO Domains** gives the ability to simultaneously authenticate users from two or more domains using one Virtual Service.

This option appears only when more than one domain has been configured and when the **Authentication Protocol** for the SSO domains are set to **LDAP**.

Please refer to the **Manage SSO Domains** section for further information on configuring **SSO Domains**.

SSL Properties

SSL Acceleration

Enabled: ☒

Reencrypt: ☒

Supported Protocols

☐ SSLv3
 ☒ TLS1.0
 ☒ TLS1.1
 ☒ TLS1.2

Require SNI hostname

☐

Before configuring the **ESP Options** to use **Alternative SSO Domains** ensure that, in the **SSL Properties** section, the **Enabled** and **Reencrypt** tick boxes are selected.

ESP Options

Enable ESP

☒

ESP Logging

User Access: ☒

Security: ☒

Connection: ☒

Client Authentication Mode

Form Based

SSO Domain

DOMAIN

Available Domain(s)

SECOND

THIRD

TEST2

Assigned Domain(s)

None Assigned

Alternative SSO Domains

>

<

Set Alternative SSO Domains

The domain name which appears in the **SSO Domain** drop-down list is the default domain. This is also the domain which is used if only one is configured.

Previously configured alternative domains appear in the **Available Domain(s)** list.

SSO Domain

DOMAIN

Available Domain(s)

TEST2

Assigned Domain(s)

SECOND

THIRD

Alternative SSO Domains

>

<

Set Alternative SSO Domains

To assign alternative SSO Domains:

1. Highlight each of the domains you wish to assign and click the > button.

An assigned domain is a domain which can be authenticated using a particular Virtual Service.

All domains which appear as available may be assigned to a Virtual Service.

2. Click the **Set Alternative SSO Domains** button to confirm the updated list of Assigned Domain(s).

3. Choose **Basic Authentication** from the **Server Authentication Mode** drop-down list.

When logging in to a domain using the ESP form, users should enter the name of the SSO Domain if an alternative domain needs to be accessed. If no domain name is entered in the username, users are, by default, logged on the domain entered in the default SSO Domain drop-down list.

To view the status of the Virtual Services, click **Virtual Services** and **View/Modify Services** in the main menu.

A list of the **Virtual Services** displays showing the current status of each service.

If alternative domains are assigned and there is an issue with a particular domain, the affected domain name is indicated in the **Status** column.

Allowed Virtual Hosts

The Virtual Service will only be allowed access to specified virtual hosts. Any virtual hosts that are not specified are blocked.

Enter the virtual host name(s) in the **Allowed Virtual Hosts** field and click the **Set Allowed Virtual Hosts** button to specify the allowed virtual hosts.

Multiple domains may be specified within the field allowing many domains to be associated with the Single Sign On Domain.

The use of regular expressions is allowed within this field.

If this field is left blank, the Virtual Service is blocked.

When using the **Permitted Groups** field in **ESP Options**, you need to ensure that the SSO domain set here is the directory for

the permitted groups. For example, if the **SSO Domain** is set to webmail.example and webmail is not the directory for the permitted groups within example.com, it will not work. Instead, the **SSO Domain** needs to be set to .example.com.

Allowed Virtual Directories

The Virtual Service will only be allowed access to the specified virtual directories, within the allowed virtual hosts. Any virtual directories that are not specified are blocked.

Enter the virtual directory name(s) in the **Allowed Virtual Directories** field and click the **Set Allowed Virtual Directories** button to specify the allowed virtual directories.

The use of regular expressions is allowed within this field.

Pre-Authorization Excluded Directories

Any virtual directories specified within this field will not be pre-authorized on this Virtual Service and are passed directly to the relevant Real Servers.

Permitted Groups

Specify the groups that are allowed to access this Virtual Service. When set, if a user logs in to a service published by this Virtual Service, the user must be a member of at least one of the groups specified. Performance may be impacted if a large number of groups are entered. Groups entered in this field are validated using an LDAP query.

Some guidelines about this field are as follows:

- The group(s) specified must be valid groups on the Active Directory in the SSO domain associated with the Virtual Service. The SSO domain in the LoadMaster must be set to the directory for the groups. For example, if the SSO domain in the LoadMaster is set to webmail.example and webmail is not the directory for the groups, it will not work. Instead, the SSO domain may need to be set to .example.com.
- The group(s) listed must be separated by a semi-colon

A space-separated list does not work because most groups contain a space in the name, for example **IT Users**.

- Do not use the **Domain Users** group because it is a default primary group for new users.
- The following characters are not allowed in permitted group names:
/ : + *

- The authentication protocol of the SSO domain must be LDAP
- The groups should be specified by name, not by full distinguished name
- Do not enter the same group name in both the **Permitted Groups** and **Steering Groups** fields. This causes a conflict. When you specify a steering group, it is assumed to behave like a permitted group, so you do not need to enter the same group in both the **Permitted Groups** and **Steering Groups** fields.

Permitted Group SID(s)

This field is the equivalent of the **Permitted Groups** field. If specifying permitted groups, you can complete either the **Permitted Groups** field or the **Permitted Groups SID(s)** field (security identifiers).

In the **Permitted Group SID(s)** field you can specify the group SIDs that are allowed to access this Virtual Service. After you type the groups, click **Set Permitted Group SIDs**.

This field allows a list of group SIDs of up to 64 bytes in length (192 characters in the format *NN NN NN*).

Each group is separated by a semi-colon. Spaces are used to separate bytes in certain group SIDs. Here is an example:

S-1-5-21-3763804817-1170992687-1336323834-1151

SIDs can be found by using the **get-adgroup-Identity GroupName** command.

Include Nested Groups

This field relates to the **Permitted Groups** setting. Enable this option to include nested groups in the authentication attempt. If this option is disabled, only users in the top-level group are granted access. If this option is enabled, users in both the top-level and first sub-level group are granted access.

Steering Groups

Steering groups can be used to steer client traffic to individual Real Servers in a Virtual Service based on the Active Directory (AD) group membership of users initiating client traffic. An example scenario would be a Virtual Service which has four Real Servers. Two Real Servers could be configured to have a primary association with Active Directory Group 1 and two Real Servers could be configured to have a primary association with AD Group 2. When a user attempts to access the Virtual Service, their group membership will be verified and the information used to steer their request to the

appropriate Real Servers. If the Real Servers selected based on group membership are not available, the default behavior is to fall back to the assigned scheduling method for the Virtual Service.

For further information, refer to the [ESP Steering Groups Technical Note](#) on the [Kemp Documentation Page](#).

Steering groups are not available if using **Basic Authentication** or **SAML** authentication.

Do not enter the same group name in both the **Permitted Groups** and **Steering Groups** fields. This causes a conflict. When you specify a steering group, it is assumed to behave like a permitted group, so you do not need to enter the same group in both the **Permitted Groups** and **Steering Groups** fields.

SSO Image Set

This option is only available if **Form Based** is selected as the **Client Authentication Mode**. You can choose which form to use to gather the Username and Password. There are three form options, **Exchange**, **Blank** and **Dual Factor Authentication**. There are also options to display the form and error messages in other languages.

- Exchange Form




The screenshot shows a web-based login form for Kemp LoadMaster. At the top left is the Kemp logo, consisting of a yellow cube icon and the word "kemp" in lowercase. Below the logo, the text reads "Welcome to AKTEST.COM" and "Password expires in 4 days. To change password [Click Here](#)". There are two yellow input fields: the first is labeled "Username:" and the second is labeled "Password:". To the right of the password field is a "Log On" button. At the bottom left, it says "Secured by Kemp LoadMaster" and "© 2002-2019 Kemp Technologies Inc. All rights reserved.". At the bottom right, there is a blue footer bar with the Kemp logo.

3 Virtual Services

The **Exchange Form** contains the Kemp Logo


- Blank Form



A screenshot of the Exchange Form login interface. It features a blue header bar with the Kemp logo. Below the header, there are two yellow input fields labeled 'Username:' and 'Password:'. To the right of the password field is a 'Log On' button. At the bottom, there is a footer with the text 'Secured by Kemp LoadMaster © 2002-2019 Kemp Technologies Inc. All rights reserved.' and the Kemp logo.

The **Blank Form** does not contain the large Kemp logo.

- Dual Factor Authentication



A screenshot of the Dual Factor Authentication form. It features a large Kemp logo at the top left. Below the logo, there are two radio buttons for 'Test' with labels 'This is a public or shared computer' and 'This is a private computer'. Underneath, there are two sections: 'Remote Credentials' with 'Username:' and 'Passcode:' fields, and 'Internal Credentials' with 'Internal Username:' and 'Internal Password:' fields. A 'Log On' button is located at the bottom right. The footer contains the text 'Secured by Kemp LoadMaster © 2002-2019 Kemp Technologies Inc. All rights reserved.' and the Kemp logo.


The **Dual Factor Authentication** form contains four fields - two for the remote credentials and two for the internal credentials.

Remote Credentials are credentials that are used to authenticate against remote authentication servers before allowing the user to authenticate against Domain Servers such as Active Directory servers.

Internal Credentials are credentials that are used to authenticate against the internal domain servers such as Active Directory Servers.

SSO Greeting Message

This option is only available if **Form Based** is selected as the **Client Authentication Mode**. The login forms can be further customized by adding text. Enter the text that you would like to appear on the form within the **SSO Greeting Message** field and click **Set SSO Greeting Message**. The message can have up to 255 characters.

The image shows a login form for Kemp LoadMaster. At the top is the Kemp logo. Below it is a circular icon with a yellow fingerprint. The text "Authorized Access Only!" is centered. There are two radio buttons: the first is selected and labeled "This is a public or shared computer", and the second is labeled "This is a private computer". Under "Remote Credentials", there are fields for "Username:" and "Passcode:". Under "Internal Credentials", there are fields for "Internal Username:" and "Internal Password:". A "Log On" button is at the bottom right. At the bottom left, it says "Secured by Kemp LoadMaster" and "© 2002-2019 Kemp Technologies Inc. All rights reserved.". The Kemp logo is also in the bottom right corner of the form area.

The SSO Greeting Message field accepts HTML code, so you can insert an image if required.

There are several characters that are not supported. These are the grave accent character (`) and the single quote ('). If a grave accent character is used in the SSO Greeting Message, the character will not display in the output, for example a ` b ` c

becomes abc. If a single quote is used, users will not be able to log in.

Logoff String

This option is only available if **Form Based** or **SAML** is selected as the **Client Authentication Mode**. Normally this field should be left blank. For OWA Virtual Services, the **Logoff String** should be set to **/owa/logoff.owa** or in customized environments, the modified **Logoff String** needs to be specified in this text box. Multiple logoff strings can be entered by using a space-separated list. You can enter up to 255 characters in this field.

If the URL to be matched contains sub-directories before the specified string, the logoff string will not be matched. Therefore, the LoadMaster will not log the user off.

Additional Authentication Header

This option is only available if **SAML** is selected as the **Client Authentication Mode**. Specify the name of the HTTP header. This header is added to the HTTP request from the LoadMaster to the Real Server and its value is set to the user ID for the authenticated session. You can enter up to 255 characters in this field.

Display Public/Private Option



The image shows a login form for Kemp LoadMaster. At the top left is the Kemp logo. Below it are two radio buttons: "This is a public or shared computer" (selected) and "This is a private computer". Below these are two text input fields labeled "Username:" and "Password:". To the right of the password field is a "Log On" button. At the bottom left, it says "Secured by Kemp LoadMaster" and "© 2002-2019 Kemp Technologies Inc. All rights reserved." At the bottom right is the Kemp logo again.

Enabling this check box will display a public/private option on the ESP log in page. Based on the option the user selected on the login form, the **Session timeout** value is set to the value specified for either public or private in the **Manage SSO Domain** screen. If the user selects the private option

their username is stored for that session. Refer to the **Manage SSO Domains** section for more information about these fields.

Disable Password Form

Enabling this option removes the password field from the login page. This may be needed when password validation is not required, for example if using RSA SecurID authentication in a singular fashion. By default, this option is disabled.

Enable Captcha

Select this check box to allow CAPTCHA verification on the login page.

The LoadMaster only supports CAPTCHA v2.

The **Client Authentication Mode** must be set to **Form Based** for the **Enable Captcha** check box to be visible.

All CAPTCHA parameters must be set before it can be used.

Both the LoadMaster and the client machine must be able to access Google for this to work.

Before the CAPTCHA has been correctly answered, the submit button on the login form is disabled. If the user does not submit the form within two minutes of answering the CAPTCHA, the CAPTCHA times out (Google-specified timeout), and the user must verify a new CAPTCHA (the submit button is disabled until the new CAPTCHA has been verified).

Captcha Public Key

The key that was provided as the public key when you signed up for the CAPTCHA service.

Captcha Private Key

The key that was provided as the private key when you signed up for the CAPTCHA service.

Captcha Access URL

The URL of the service that provides the CAPTCHA challenge. Usually:
www.google.com/recaptcha/api.js

Do not start this URL with https.

Only CAPTCHA V2 is currently supported.

CAPTCHA Verification URL

The URL of the service that verifies the response to the CAPTCHA challenge. Usually:
www.google.com/recaptcha/api/siteverify

Do not start this URL with https.

Only CAPTCHA V2 is currently supported.

Use Session or Permanent Cookies

Three options are available to select for this field:

- **Session Cookies Only:** This is the default and most secure option
- **Permanent Cookies only on Private Computers:** Sends permanent cookies only on private computers
- **Permanent Cookies Always:** Sends permanent cookies in all situations

Permanent cookies only work with Internet Explorer (IE) and IE must be set to accept **Third Party Cookies** and the site must be added to the **Trusted Sites**.

The expiry time of a permanent cookie can be set by configuring the **Session Timeout** fields in the modify SSO screen. The maximum value is 7 days (**604800** seconds).

Specify if the LoadMaster should send session or permanent cookies to the users' browser when logging in.

Permanent cookies should only be used when using single sign on with services that have sessions spanning multiple applications, such as SharePoint.

User Password Change URL

This is relevant when using client-side forms-based authentication and LDAP. Specify the URL that users can use to change their password, for example
https://mail.kempqakcd.net/owa/auth/expiredpassword.aspx?url=/owa/auth.owa

If a user's password has expired, or if they must reset their password, this URL and the **User Password Change Dialog Message** is displayed on the login form.

This URL must be entered in the ESP **Pre-Authorization Excluded Directories** field - this is required to bypass pre-authentication.

If using this expired password functionality in an Exchange 2010 environment:

- The **Pre-Authorization Excluded Directories** must be set to **/owa/auth.owa /owa/auth*/owa/14.3.123.3****. 14.3.123.3 is the sub-path of the Exchange server that must be added to the excluded directories.
- When changing passwords, users cannot use a User Principal Name (UPN) (for example, joebloggs@example.com) in the **Domain\user name** field in the Change Password window, unless Exchange 2010 SP1 RU3 or later is deployed on the Client Access servers.

For further information, refer to the following Microsoft TechNet article:

[https://technet.microsoft.com/en-us/library/bb684904\(v=exchg.141\).aspx](https://technet.microsoft.com/en-us/library/bb684904(v=exchg.141).aspx)

User Password Change Dialog Message

This text box is only visible if something is set for the **User Password Change URL** text box. Specify the text to be displayed on the login form when the user must reset their password. Special characters are not permitted in this field.

User Password Expiry Warning

By default, SSO users are notified about the number of days before they must change their password. If you disable this option, the password expiry notification will not appear on the login forms.

You can specify the number of days to show the warning before the password is expired. The default value for this field is **15 days**. This field is only visible if the **Client Authentication Mode** is set to **Form Based** and the **User Password Change URL** is set.

The language of the warning text is based on the **SSO Image Set** that is selected (English, French, or Portuguese).

Verify Bearer Header

Select this check box to verify if the authentication header contains a bearer record. This is used when doing JSON web token validation.

The **Verify Bearer** Header field (and the two fields detailed below) are only available if the **Client Authentication Mode** is

set to **Delegate to Server, Basic Authentication, Form Based, or NTLM**.

Bearer Header Validation Certificate

This option is only visible if the **Verify Bearer Header** check box is selected.

Select the relevant certificate/key used to decrypt the bearer header token from the **Bearer Header Validation Certificate** drop-down list (this must first be uploaded to the LoadMaster by going to **Certificates & Security > SSL Certificates > Import Certificate**). This is used when doing JSON web token validation.

Bearer Header Validation Text

This option is only visible if the **Verify Bearer Header** check box is selected.

You can enter up to five bearer header validation strings (comma-separated list) in the **Bearer Header Validation Text** field. This is used when doing JSON web token validation.

Server Authentication Mode

Specifies how the LoadMaster is authenticated by the Real Servers. The following types of methods are available:

- **None:** no client authentication is required
- **Basic Authentication:** standard Basic Authentication is used
- **KCD:** KCD authentication is used
- **Server Token:** On reception and verification of the SAML response, the LoadMaster requests a long-lived token. The LoadMaster then builds a redirection URL with the token specified.

You can only select **Server Token** as the **Server Authentication Mode** if **SAML** is selected as the **Client Authentication Mode**.

- **Form Based:** can only be selected if the **Client Authentication Mode** is set to **Form Based**.
 - When **Form Based** authentication is selected, the **Form Authentication Path** field appears.
 - When the **Form Authentication Path** field is populated, the **Form POST Format** and **POST Format Username Only** fields appear. The username and password from the client-side, form-based authentication is injected into the form POST format to build the POST body.

•

This feature is predominantly used in Microsoft Exchange deployments and has only been tested with Exchange 2013 and 2016. Therefore, the following strings do not need to be explicitly configured for Exchange 2013/2016. They are used by default in the implementation:

- **Form Authentication Path:** /owa/auth.owa

- **Form POST Format:**

destination=%s#authRedirect=true&flags=4&forcedownlevel=0&username=%s&password=%s&passwordText=&isUtf8=1

The **Form POST Format** field only becomes visible when the **Form Authentication Path** is set.

If the deployment is not Exchange, Kemp recommends that the settings are evaluated based on the required interaction with the Real Server and subsequently set appropriately.

POST Format Username Only

Enable this option to send the username only (without the domain part) in the server-side form based authentication POST request.

If **Delegate to Server** is selected as the **Client Authentication Mode**, then **None** is automatically selected as the **Server Authentication mode**. Similarly, if **Basic Authentication** is selected as the **Client Authentication Mode**, then **Basic Authentication** is automatically selected as the **Server Authentication mode**.

When choosing a specific **Client Authentication Mode** protocol, it is important to understand what **Server Authentication Mode** protocols are compatible:

Client Authentication Mode	Default Compatible Server Authentication Mode
Delegate to Server	None
Basic Authentication	Basic Authentication

Client Authentication Mode	Default Compatible Server Authentication Mode
Form Based	Basic Authentication
	KCD
	Form Based
	None
NTLM	KCD
	None
Client Certificate	KCD
SAML	KCD
SAML	None
SAML	Server Token

Server Side configuration

This option is only visible when the **Server Authentication mode** value is set to **KCD**.

Select the SSO domain for the server side configuration. Only SSO domains which have the **Configuration type** set to **Outbound Configuration** are shown here.

Token Server FQDN

This option is only visible when the **Server Authentication mode** value is set to **Server Token**.

Set the FQDN for the token server. When set, LoadMaster contacts the token server at the given FQDN during sign-on and obtains a permanent access token from that token server. If this parameter is unset, then LoadMaster obtains the token from the Real Server (as in previous releases).

3.8.1 SMTP Virtual Services and ESP

If you create an SMTP Virtual Service (with **25** as the port), the ESP feature is available when you select the **Enable ESP** checkbox but with a reduced set of options.

▼ ESP Options	
Enable ESP	<input checked="" type="checkbox"/>
Connection Logging	<input checked="" type="checkbox"/>
Permitted Domains	<input type="text"/> Set Permitted Domains

Enable ESP

Enable or disable the ESP feature set by selecting or deselecting the **Enable ESP** checkbox.

Connection Logging

Logging of connections can be enabled or disabled by selecting or deselecting the **Connection Logging** checkbox.

Permitted Domains

All the permitted domains that are allowed to be received by this Virtual Service must be specified here. For example, if you wish the Virtual Service to receive SMTP traffic from john@kemp.com, then the **kemp.com** domain must be specified in this field.

3.9 Sub Virtual Services


From within a Virtual Service you can create one or more 'Sub Virtual Services' (SubVS). A SubVS is linked to, and uses the IP address of, the 'parent' Virtual Service. The SubVSs may have different settings (such as health check methods and content rules) to the parent Virtual Service and to each other. This allows the grouping of related Virtual Services, all using the same IP address. This could be useful for certain configurations such as Exchange or Lync which typically are comprised of a number of Virtual Services.

Users with the Virtual Services permission can add a SubVS.

Users with the Real Server permission cannot add a SubVS.

▼ Real Servers		Add New ... Add SubVS ...
Real Server Check Parameters	<input type="text" value="TCP Connection Only"/>	Checked Port <input type="text"/> Set Check Port
Enhanced Options: <input checked="" type="checkbox"/>		

To create a SubVS, within a Virtual Service configuration screen, expand the **Real Servers** section and click the **Add SubVS** button.



A message appears stating that the SubVS has been created.

You cannot have Real Servers and SubVSs associated with the same Virtual Service. You can however, associate a Real Server with a SubVS.

SubVSs						Add New ...		
Id	Name	Weight	Limit	Critical	Status	Operation		
1		1	1	<input type="checkbox"/>	Enabled	Disable	Modify	Delete
2		1000	0	<input type="checkbox"/>	Enabled	Disable	Modify	Delete

When the SubVS is created, the **Real Servers** section of the Virtual Services configuration screen is replaced with a **SubVSs** section.

All the SubVSs for the Virtual Service are listed here. The **Critical** check box can be enabled to indicate that the SubVS is required for the Virtual Service to be considered available. If a non-critical SubVS is down, the Virtual Service is reported as up and a warning is logged. If a critical SubVS is down, a critical log is generated and the Virtual Service is marked as down. If the email options are configured, an email is sent to the relevant recipients. For further information on the email options, refer to the **Email Options** section. In all cases, if the Virtual Service is considered to be down and the Virtual Service has a sorry server or an error message configured, these are used.

To modify the SubVS, click the relevant **Modify** button. A configuration screen for the SubVS appears. This contains a subset of the configuration options available for a normal Virtual Service.

3 Virtual Services

Basic Properties	
SubVS Name	<input type="text"/> Set Nickname
SubVS Type	<input type="text" value="HTTP/HTTPS"/>
SubVS Weight	<input type="text" value="1000"/> Set Weight
SubVS Limit	<input type="text" value="0"/> Set Limit
▼ Standard Options	
Transparency	<input checked="" type="checkbox"/>
Persistence Options	Mode: <input type="text" value="None"/>
Scheduling Method	<input type="text" value="round robin"/>
Idle Connection Timeout (Default 660)	<input type="text"/> Set Idle Timeout
Quality of Service	<input type="text" value="Normal-Service"/>
▼ Advanced Properties	
Content Switching	Disabled
HTTP Selection Rules	Show Selection Rules
HTTP Header Modifications	Show Header Rules
Enable Multiple Connect	<input type="checkbox"/>
Add Header to Request	<input type="text"/> Set Header
Add HTTP Headers	<input type="text" value="Legacy Operation(X-ClientSide)"/>
"Sorry" Server	<input type="text"/> Port <input type="text"/> Set Server Address
Not Available Redirection Handling	Error Code: <input type="text"/> Set Redirect URL
	Redirect URL: <input type="text"/>
▼ WAF Options	
Web Application Firewall	Enabled: <input type="checkbox"/>
▼ ESP Options	
Enable ESP	<input type="checkbox"/>
▼ Real Servers	
Real Server Check Parameters	<input type="text" value="HTTP Protocol"/> <input type="text"/> Set Check Port
URL:	<input type="text"/> Set URL
Use HTTP/1.1:	<input type="checkbox"/>
HTTP Method:	<input type="text" value="HEAD"/>
Custom Headers:	Show Headers

The SubVSs can also be modified by clicking the relevant **Modify** button from within the main Virtual Services view. A Virtual Service with SubVSs is colored differently within the Virtual IP address section and the SubVSs are listed in the Real Server section. The SubVS details can be viewed by clicking the 'parent' Virtual Service to expand the view to include the SubVSs.

If you would like to remove a Virtual Service which contains SubVSs, you must remove the SubVSs first before you are able to delete the main service.

SubVSs may have different ESP configurations than their parent Virtual Service, however care must be taken to ensure that the parent Virtual Service and SubVS ESP options do not conflict.

3.10 View/Modify (Remote Terminal Service)

Properties of the Virtual Service include the Generic Type and also provide Remote Terminal specific options.

Persistence

If the terminal servers support a Session Directory, the LoadMaster will use the "routing " supplied by the Session Directory to determine the correct host to connect to. The LoadMaster persistency timeout value is irrelevant here - it is a feature of the Session Directory.

The switch "IP address redirection" in the Session Directory configuration must not be selected for this to work.

Using Session Directory with LoadMaster is optional, in terms of persistence. If the client pre-populates the username and password fields in the initial request, then this value is stored on the LoadMaster. As long as these fields are still populated upon reconnect, the LoadMaster will look up the name and reconnect to the same server as the original connection. The persistence timeout is used to limit the time the information is kept on the LoadMaster.

If using **Terminal-Service or Source IP** mode, then if neither of these two modes succeeds, then the source IP address is used for persistency.

Service Check for the Virtual Service

Only three options are available; **ICMP**, **TCP** and **RDP**. Remote Terminal Protocol (RDP) opens a TCP connection to the Real Server on the Service port (port 3389). The LoadMaster sends an a1110 Code (Connection Request) to the server. If the server sends an a1101 Code (Connection Confirm) then LoadMaster closes the connection and marks the server as active. If the server fails to respond within the configured response time for the configured number of times, or if it responds with a different status code, it is assumed dead.

3.11 Real Servers

This section allows you to create a Real Server and lists the Real Servers that are assigned to the Virtual Service. The properties of the Real Servers are summarized and there is also the opportunity to add or delete a Real Server, or modify the properties of a Real Server. When Content Switching is

3 Virtual Services

enabled, there is also the opportunity to add rules to, or remove rules from, the Real Server (see Add Rule).

Real Server Check Method

This provides a list of health checks for well-known services, as well as lower level checks for TCP/UDP or ICMP. With the service health checks, the Real Servers are checked for the availability of the selected service. With TCP/UDP the check is simply a connect attempt.

Real Servers

Add New ...

Real Server Check Method

TCP Connection Only

Checked Port

Set Check Port

Enhanced Options

☒ Minimum number of RS required for VS to be considered up

2

Id	IP Address	Port	Forwarding method	Weight	Limit	Critical	Healthcheck On	Status	Operation
3	10.154.11.65	80	nat	1000	0	<input type="checkbox"/>	10.154.11.92/443	Enabled	Disable Modify Delete
2	10.154.15.21	80	nat	1000	0	<input type="checkbox"/>	Self	Enabled	Disable Modify Delete

The tables below describe the options that may be used to verify Real Server health. You may also specify a health check port on the Real Server. If none are specified here, it will default to the Real Server port.

When the **HTTP/HTTPS**, **Generic** and **STARTTLS protocols** Service Types are selected, the following health check options are available.

Method	Action
ICMP Ping	An ICMP ping is sent to the Real Server
HTTP	HTTP checking is enabled
HTTPS	HTTPS (SSL) checking is enabled
TCP	A basic TCP connection is checked
Mail	The SMTP (Simple Mail Transfer Protocol) is used
NNTP	The NNTP (Network News Transfer Protocol) is used
FTP	The FTP (File Transfer Protocol) is used
Telnet	The Telnet protocol is used
POP3	The POP3 (Post Office Protocol – mail client protocol) is used
IMAP	The IMAP (Internet Message Access Protocol – mail client protocol) is used
Name Service (DNS) Protocol	The Name Service Protocol is used

3 Virtual Services

Binary Data	Specify a hexadecimal string to send and specify a hexadecimal string to check for in the response
LDAP	Select an LDAP endpoint to use for the health checks. If LDAP is selected as the health check protocol, the server IP address (or addresses) and ports from the LDAP endpoint configuration is used instead of the Real Server IP address and port. For further information on LDAP endpoints, refer to the LDAP Configuration section.
None	No checking performed

When the **Remote Terminal** Service Type is selected the following health check options are available.

Method	Action
ICMP Ping	An ICMP ping is sent to the Real Server
TCP	A basic TCP connection is checked
Remote Terminal Protocol	An RDP Routing Token is passed to the Real Server. This health check supports Network-Level Authentication.
None	No checking performed

For a UDP virtual service, only the **ICMP Ping** and **Name Service (DNS) Protocol** options are available for use

Enhanced Options

Enabling the **Enhanced Options** check box provides an additional health check option – **Minimum number of RS required for VS to be considered up**. If the **Enhanced Options** check box is disabled (the default), the Virtual Service is considered available if at least one Real Server is available. If the **Enhanced Options** check box is enabled, you can specify the minimum number of Real Servers that must be available to consider the Virtual Service to be available.

Minimum number of RS required for VS to be considered up

This option will only appear if the **Enhanced Options** check box is enabled and if there is more than one Real Server.

Select the minimum number of Real Servers required to be available for the Virtual Service to be considered up.

If less than the minimum number of Real Servers is available, a critical log is generated. If some Real Servers are down but it has not reached the minimum amount specified, a warning is logged. If the email options are configured, an email is sent to the relevant recipients. For further information on the email options, refer to the **Email Options** section.

Note that the system marks a Virtual Service as down whenever a Real Server that is marked as **Critical** becomes unavailable – even if **Enhanced Options** are enabled and there are more than the specified minimum number of Real Servers still available.

In all cases, if the Virtual Service is considered to be down and the Virtual Service has a sorry server or an error message configured, these are used.


If the minimum number is set to the total number of Real Servers and one of the Real Servers is deleted, the minimum will automatically reduce by one.

When using content rules in a SubVS, the minimum number of Real Servers required has a slightly different meaning. A rule is said to be available and can be matched if and only if the number of available Real Servers with that rule assigned to them is greater than the limit. If the number of available Real Servers is below this limit, the rule can never be matched - the SubVS is marked as down and this is logged appropriately.

If a Real Server on a SubVS is marked as critical – the SubVS is marked as down if that Real Server is down. However, the parent Virtual Service will not be marked down unless that SubVS is marked as critical.

3.11.1 HTTP or HTTPS Protocol Health Checking

When either the **HTTP Protocol** or **HTTPS Protocol** options are selected a number of extra options are available as described below.



The screenshot shows the 'Real Servers' configuration window. Under the 'Real Server Check Parameters' section, the following options are visible:

- Protocol:** HTTP Protocol (dropdown menu)
- Checked Port:** 25 (text input)
- Set Check Port:** (button)
- URL:** (text input)
- Set URL:** (button)
- Status Codes:** (text input)
- Set Status Codes:** (button)
- Use HTTP/1.1:** (checkbox, unchecked)
- HTTP Method:** GET (dropdown menu)
- Reply 200 Pattern:** (text input)
- Set Pattern:** (button)
- Custom Headers:** (button labeled 'Show Headers')
- Enhanced Options:** (checkbox, unchecked)

The **post data** option only appears if the **POST HTTP Method** is selected.

The **Reply 200 Pattern** option only appears if either the **POST** or **GET HTTP Method** is selected

URL

By default, the health checker tries to access the URL to determine if the machine is available. A different URL can be specified here.

Status Codes

Health check status codes can be set to override default functionality. Without any **Status Codes** set, the following HTTP status codes are considered to be Up:

- 200-299
- 301
- 302
- 401

Additionally, 2xx status codes are subject to pattern matching the response data, if this is configured. Other codes are considered up without pattern matching, even if it is set.

If custom health check codes are set:

- Check codes may be set to a list of numbers, each from 300-599
- Check codes may be up to 127 characters long, which means 32 valid codes
- Any code in the list is considered to have a health check status of Up
- Configured codes override the default set
 - 2xx codes are always considered up in all cases and are subject to pattern matching, if configured
 - Check codes may be official HTTP status codes, unofficial codes or custom-defined user codes – as long as they fall in the range of 300-599
 - For a list of official HTTP status codes, refer to:
https://en.wikipedia.org/wiki/List_of_HTTP_status_codes

- For a list of unofficial codes, refer to:
https://en.wikipedia.org/wiki/List_of_HTTP_status_codes#Unofficial_codes
- Microsoft sub-codes using decimals can be supported, but only by the top-level status code
- For a list of Microsoft sub-codes using decimals, refer to:
<https://support.microsoft.com/en-us/kb/943891>
- Sub-codes may not be configured in the Status Codes field – please use the three digit code
- Sub-codes are grouped by the top-level code

Use HTTP/1.1

By default, the LoadMaster uses HTTP/1.0. However you may opt to use **HTTP/1.1** which will operate more efficiently. When using HTTP/1.1, the health checks are multiplexed to a single connection. This means that more health checks are sent to the server in a single connection which is more efficient from a connection point of view, that is, there is only one connection rather than multiple connections.

Optimization only works on HTTP (not HTTPS) connections.

HTTP/1.1 Host

This field will only be visible if '**Use HTTP/1.1**' is selected.

When using **HTTP/1.1** checking, the Real Servers require a hostname to be supplied in each request. If no value is set, then this value is the IP address of the Virtual Service.

To send SNI host information in HTTPS health checks, please enable **Use HTTP/1.1** in the **Real Servers** section of the relevant Virtual Service(s) and specify a host header. If this is not set, the IP address of the Real Server is used.

HTTP Method

When accessing the health check URL, the system can use either the **HEAD**, **GET** or **POST** method.

Post Data

This field will only be available if the **HTTP Method** is set to **POST**. When using the **POST** method, up to 2047 characters of POST data can be passed to the server.

Reply 200 Pattern

When using the **GET** or the **POST** method, the contents of the returned response message can be checked. If the response contains the string specified by this Regular Expression, then the machine is determined to be up. The response will have all HTML formatting information removed before the match is performed. Only the first 4K of response data can be matched.

The LoadMaster will only check for this phrase if the reply from the server is a 200 code. If the reply is something else, the page is marked as down without checking for the phrase. However, if the reply is a redirect (code 302), the page is not marked as down. This is because the LoadMaster assumes that the phrase will not be present and also it cannot take the service down, as the redirect would then become useless.

An exclamation mark (!) at the start of a search pattern negates the outcome of the search. For example, a pattern of 'fail' returns true if the string 'fail' appears in the response; while a pattern of '!fail' returns false if 'fail' appears in the response.

Both Regular Expressions and Perl Compatible Regular Expressions (PCRE) can be used to specify strings. For further information on Regular Expressions and PCRE, please refer to the **Content Rules, Feature Description** document on the [Kemp Documentation Page](#).

Custom Headers

Here you can specify up to 4 additional headers/fields which are sent with each health check request. Clicking the **Show Headers** button will show the entry fields. The first field is where you define the key for the custom header that is to be part of the health check request. The second field is the value of the custom header that is to be sent as part of the health check request. Once the information is input, click the **Set Header** button. Each of the headers can be up to a maximum of 20 characters long and the fields can be up to a maximum of 100 characters long. However, the maximum allowed number of characters in total for the 4 header/fields is 256.

The following special characters are allowed in the **Custom Headers** fields:

; . () / + = - _

If a user has specified **HTTP/1.1**, the Host field is sent as before to the Real Server. This can be overridden by specifying a Host entry in the additional headers section. The User-Agent can also be overridden in the same manner. If a Real Server is using adaptive scheduling, the additional headers which are specified in the health check are also sent when getting the adaptive information.

It is possible to perform a health check using an authenticated user: enable **Use HTTP/1.1**, select **HEAD** as the **HTTP Method** and enter the Authorization header with the correctly constructed value. The Authorization field is constructed as follows:

1. The username and password are combined into a string “username:password”.

3 Virtual Services

2. The resulting string is then encoded using the RFC2045-MIME variant of Base64, except not limited to 76 char/line.
3. The authorization method and a space, for example, "Basic " is then put before the encoded string.

For example, if the user agent uses 'Aladdin' as the username and 'open sesame' as the password then the field is formed as follows:

Authorization: Basic QWxhZGRpbjpvcGVuIHNlc2FtZQ==

To send SNI host information in HTTPS health checks, please enable **Use HTTP/1.1** in the **Real Servers** section of the relevant Virtual Service(s) and specify a host header. If this is not set, the IP address of the Real Server is used.

Rules

If any of the Real Servers have Content Switching rules assigned to them the **Rules** column appears in the Real Servers section. A button with the number of rules assigned to each of the Real Server (or with **None** if there are no rules assigned) is displayed in the **Rules** column.

Clicking the button within the **Rules** column opens the **Rules Management** screen.

OperationName	Match Type	Options	Header	Pattern
Delete ExampleRule	Regex			Example
Delete ExampleMatchRule	Regex			Example2
Add Rule Rule: <input type="text" value="default"/> Add				

From within this screen you can **Add** or **Delete** the rules assigned to a Real Server.

3.11.2 Binary Data Health Checking

When **Binary Data** is selected as the health check method, some other fields are available, as described below.

▼ Real Servers

Real Server Check Parameters

Binary Data ▼

Checked Port

[Set Check Port](#)

Data to Send:

[Set Transmitted Data](#)

Reply Pattern:

[Set Pattern](#)

Find Match Within: Bytes

[Set Match Length](#)

Data to Send

Specify a hexadecimal string to send to the Real Server.

This hexadecimal string must contain an even number of characters.

Reply Pattern

Specify the hexadecimal string which is searched for in the response sent back from the Real Server. If the LoadMaster finds this pattern in the response, the Real Server is considered up. If the string is not found, the Real Server is marked as down.

This hexadecimal string must contain an even number of characters.

Find Match Within

When a response is returned, the LoadMaster will search for the **Reply Pattern** in the response. The LoadMaster will search up to the number of bytes specified in this field for a match.

Setting this to **0** means that the search is not limited. Data is read from the Real Server until a match is found. A maximum of 8 KB is read from the Real Server.

Setting the value to less than the length of the reply string means that the check will act as if the value has been set to **0**, that is, all packets (up to 8 KB) are searched.

3.11.3 Name Server (DNS) Protocol Health Checking

Name Server (DNS) Protocol health checking is only available when using a UDP Virtual Service.

▼ Real Servers		Add New ...
Real Server Check Method	Name Service (DNS) Protocol ▼	Checked Port <input type="text"/>
		Set Check Port
DNS query	<input type="text"/>	
	Set Query	

Checked Port

The port to be checked. If there is no port specified, the Real Server port is used.

DNS query

Specify the query string to be requested from the name server. This field has a maximum length of 126 characters.

3.11.4 Add a Real Server

Clicking the **Add New** button brings you to the following screen where the properties of the Real Server are set.

Please Specify the Parameters for the Real Server

Allow Remote Addresses

☒

Real Server Address

Port

Forwarding method

Weight

Connection Limit

<-Back

Add This Real Server

Allow Remote Addresses: By default only Real Servers on local networks can be assigned to a Virtual Service. Enabling this option will allow a non-local Real Server to be assigned to the Virtual Service. This option is enabled by default.

To make the **Allow Remote Addresses** option visible, **Enable Non-Local Real Servers** must be selected (in **System Configuration > Miscellaneous Options > Network Options**). Also, **Transparency** must be disabled in the Virtual Service.

When alternative gateways/non-local Real Servers are set up, health checks are routed through the default gateway.

Real Server Address: The Real Server address. This can either be an IP address or a Fully Qualified Domain Name (FQDN). This is not editable when modifying a Real Server. An FQDN can only be used if a **Nameserver** is configured. The resolved name is listed next to the IP address in parenthesis. For further information, refer to the **Host & DNS Configuration** section. If an FQDN is used when adding a Real Server – the name is resolved at the time of adding. If it fails to resolve, the Real Server is not created and an error is generated.

You can either type the address of a new Real Server, or select an existing Real Server from the drop-down list provided. The entries before the line in the drop-down list are existing Real Servers. The entries below the line are auto-complete form options. Real Servers already added to this SubVS are not listed in the drop-down list.

This drop-down list does not appear on Safari browsers due to a browser limitation.

Add to all SubVSs

When adding a Real Server to a SubVS, a check box is available that, when selected, adds the Real Server to all SubVSs in that Virtual Service.

Port: The forwarding port of the Real Server. This field is editable, so the port may be altered later if required.

Forwarding Method: Either NAT (Network Address Translation) or Route (Direct) forwarding. The available options are dependent on the other modes selected for the service.

Weight: The Real Server's weight. This is weight of the Real Server, as used by the Weighted Round Robin, Weighted Least Connection and Adaptive scheduling methods. The default initial value for the weight is **1000**, the maximum is **65535**, and the minimum is **1**. It is a good benchmark to give a Real Server a weight relative to its processor speed, for example, if server1 seems to bring four times the power of server2, assign a weight of **4000** to server1 and weight of **1000** to server2.

Connection Limit: The maximum number of open connections that a Real Server will accept before it is taken out of the rotation. This is only available for Layer 7 traffic. The limit stops new connections from being created, but it will allow requests that already have persistent connections to the server. Persistent connections include connections to a Virtual Service using Session Broker Persistence which include a Session Broker cookie as set by the Connection Broker.

A maximum number of 1024 Real Servers is allowed. This is the global limit and is divided among the existing Virtual Services. For example, if one Virtual Service had 1000 Real Servers, then the remaining Virtual Services can only have 24 further Real Servers in total.

Click the **Add This Real Server** button and it gets added to the pool.

Critical

This option will only appear if the **Enhanced Options** check box is enabled. For further information on the **Enhanced Options** check box, refer to the **Real Servers** section.

In the Real Servers section of the Virtual Service modify screen, there is a **Critical** check box for each of the Real Servers. Enabling this option indicates that the Real Server is required for the Virtual Service to be considered available. The Virtual Service is marked as down if the Real Server has failed or is disabled.

If a Real Server on a SubVS is marked as critical – the SubVS is marked as down if that Real Server is down. However, the parent Virtual Service will not be marked down unless that SubVS is marked as critical.

This option overrides the **Minimum number of RS required for VS to be considered up** field. For example, if the minimum is set to two and only one Real Server is down but that Real Server is set to critical – the Virtual Service is marked as down.

In all cases, if the Virtual Service is considered to be down and the Virtual Service has a sorry server or an error message configured, these are used.

Healthcheck On

This option will only appear if the **Enhanced Options** check box is enabled. For further information on the **Enhanced Options** check box, refer to the **Real Servers** section.

In the Real Servers section of the Virtual Service modify screen, there is a **Healthcheck On** drop-down list for each of the Real Servers. This allows you to specify what Real Server the health check is based on. This can either be set to **Self** to perform the health check based on that particular Real Server status, or another Real Server can be selected. For example – if Real Server 1 is down, any Real Servers which have their health check based on Real Server 1 will also be marked as down, regardless of their actual Real Server status.

Some points to be aware of are listed below:

- A Real Server can only follow a Real Server and not a SubVS.
- A Real Server can follow a Real Server that is also following a third Real Server. The status of the first two Real Servers will reflect the status of the third Real Server.
- Chains of Real Servers are allowed – but loops are not allowed and cannot be created.
- If a Real Server is deleted (either singly or as part of a Virtual Service), all Real Servers that are following the Real Server are reset to normal behaviour (that is, they will start using the Virtual Service health check options).
- If all Real Servers in a Virtual Service are following Real Servers on a different Virtual Service, the health check parameters for the Virtual Service are not shown on the WUI (because the settings do not affect any Real Servers).
- Disabling the **Enhanced Options** check box will disable all Real Server health check following for that Virtual Service.

3.11.5 Modify a Real Server

When you click the **Modify** button of a Real Server, the following options are available:

Please Specify the Parameters for the Real Server on tcp/10.154.11.61:443 (Id:1)	
Real Server Address	10.154.11.92
Port	<input type="text" value="80"/>
Forwarding method	<input type="text" value="nat"/>
Weight	<input type="text" value="1000"/>
Connection Limit	<input type="text" value="0"/>

Real Server Address

This field shows the address of the Real Server. This is not an editable field.

Port

This is a field detailing the port on the Real Server that is to be used.

Forwarding Method

This is a field detailing the type of forwarding method to be used. The default is NAT; Direct Server Return can only be used with L4 services.

Weight

When using Weighted Round Robin Scheduling, the weight of a Real Server is used to indicate what relative proportion of traffic should be sent to the server. Servers with higher values will receive more traffic.

Connection Limit

This is the maximum amount of open connections that can be sent to the real server before it is taken out of rotation. The maximum limit is 100,000.

3.12 Manage Templates

Templates make the setting up of Virtual Services easier by automatically creating and configuring the parameters for a Virtual Service. Before a template can be used to configure a Virtual Service, it must be imported and installed on the LoadMaster.

Name	Comment	Kemp Certified	Operation
SharePoint 2013 Central Administration Site HTTP	Handles SharePoint 2013 Central Administration Site via HTTP. (Version 1.1)	Yes	Delete
SharePoint 2013 Central Administration Site HTTPS	Handles SharePoint 2013 Central Administration Site via HTTPS. (Version 1.1)	Yes	Delete
SharePoint 2013 Central Administration Site HTTPS Offloaded	Handles SharePoint 2013 Central Administration Site via HTTPS with SSL offloading. (Version 1.1)	Yes	Delete
SharePoint 2013 Central Administration Site HTTPS Re-encrypted	Handles SharePoint 2013 Central Administration Site via HTTPS with SSL offloading and re-encryption. (Version 1.1)	Yes	Delete

Import Templates

Template file: [Choose File](#) No file chosen [Add New Template](#)

Click the **Choose File** button, select the template you wish to install and click the **Add New Template** button to install the selected template. This template is now available for use when you are adding a new Virtual Service.

Click **Delete** to remove the template.

The **Kemp Certified** column will indicate whether the template was supplied by Kemp or not. If a template is certified, it has been provided by Kemp. If a template is not certified, it might be a template created by you (by exporting a Virtual Service).

For further details on templates, such as how to use a template to create and configure a new Virtual Service and where to obtain Kemp templates, please refer to the Virtual Services and Templates Feature Description document on the [Kemp documentation page](#).

3.13 Manage SSO Domains

Before using the Edge Security Pack (ESP) the user must first set up a Single Sign-On (SSO) Domain on the LoadMaster. The SSO Domain is a logical grouping of Virtual Services which are authenticated by an LDAP server.

The maximum number of SSO domains that are allowed is 128.

Client Side Single Sign On Configurations

Add new Client Side Configuration

Add

Server Side Single Sign On Configurations

Add new Server Side Configuration

Add

Single Sign On Image Sets

Add new Custom Image Set

Image File:

Choose File

 No file chosen

Add Custom Image Set

Click the **Manage SSO Domains** menu option to open the **Manage Single Sign On Options** screen.

3.13.1 Single Sign On Domains

Two types of SSO domains can be created – client side and server side.

Client Side configurations allow you to set the **Authentication Protocol** to **LDAP**, **RSA-SecurID**, **Certificates** or **RSA-SecurID and LDAP**.

Server Side configurations allow you to set the **Authentication Protocol** to **Kerberos Constrained Delegation** (KCD).

To add a new SSO Domain enter the name of the domain in the **Name** field and click **Add**. You can enter up to 64 characters in this field. The name entered here does not need to relate to the allowed hosts within the Single Sign On Domain.

When using the **Permitted Groups** field in **ESP Options**, you need to ensure that the SSO domain set here is the directory for the permitted groups. For example, if the **SSO Domain** is set to

webmail.example and webmail is not the directory for the permitted groups within example.com, it will not work. Instead, the **SSO Domain** needs to be set to .example.com.

If the **Domain/Realm** field is not set, the domain **Name** set when initially adding an SSO domain is used as the **Domain/Realm** name.

3.13.1.1 Client Side (Inbound) SSO Domains

Domain EXAMPLE.COM

Authentication Protocol	LDAP ▼	
LDAP Endpoint	LDAP_EXAMPLE ▼	Manage LDAP Configuration
Domain/Realm	10.154.60.61	Set Domain/Realm Name
Logon Format	Username ▼	
Logon Transcode	Disabled ▼	
Failed Login Attempts	3	Set Failed Login Attempts
Reset Failed Login Attempt counter after	60	Set Reset-Failed Timeout
Unblock Timeout	1800	Set Unblock Timeout
	Public - Untrusted Environment	Private - Trusted Environment
	900	900
	Set Idle Time	Set Idle Time
Session Timeout	1800	28800
	Set Max Duration	Set Max Duration
	Use for Session Timeout: idle time ▼	
Use LDAP Endpoint for Healthcheck	<input type="checkbox"/>	
Test User	test1@example.com	Set Test User
Test User Password	•••••	Set Test User Password

Authentication Protocol

This dropdown allows you to select the transport protocol used to communicate with the authentication server. The options are:

- LDAP
- RSA-SecurID
- Certificates

If you create an SSO domain with the **Authentication Protocol** set to **Certificates**, ensure to set the **LDAP Protocol** to **LDAPS** in the LDAP endpoint.

- RSA-SecurID and LDAP
- SAML

The fields displayed on this screen will change depending on the **Authentication protocol** selected.

LDAP Endpoint

Select the LDAP endpoint to use. Click the **Manage LDAP Configuration** button to go to the **LDAP Configuration** screen. For further information on LDAP endpoints, refer to the **LDAP Configuration** section.

This option is only available if the **Authentication Protocol** is set to **LDAP** or **RSA-SecurID and LDAP**.

RSA-SecurID Server(s)

Type the IP addresses of the server or servers which are used to authenticate the domain into the server(s) field and click the set server(s) button.

Multiple server addresses can be entered within this text box. Each entry must be separated by a space.

Check Certificate to User Mapping

This option is only available when the **Authentication Protocol** is set to **Certificates**. When this option is enabled - in addition to checking the validity of the client certificate, the client certificate will also be checked against the altSecurityIdentities (ASI) attribute of the user on the Active Directory.

If this option is enabled and the check fails, the login attempt will fail. If this option is not enabled, only a valid client certificate (with the username in the SubjectAltName (SAN)) is required to log in, even if the altSecurityIdentities attribute for the user is not present or not matching.

For more information, refer to the **Kerberos Constrained Delegation, Feature Description** on the [Kemp Documentation Page](#).

Allow fallback to check Common Name

Enabling this option allows a fallback to check the Common Name (CN) in the certificate when the SAN is not available.

This field only appears when the **Authentication Protocol** is set to **Certificates**.

Domain/Realm

The login domain to be used. This is also used with the logon format to construct the normalized username, for example;

- **Principalname:** <username>@<domain>
- **Username:** <domain>\<username>

If the **Domain/Realm** field is not set, the **Domain** name set when initially adding an SSO domain is used as the **Domain/Realm** name.

RSA Authentication Manager Config File

This option is only available when the **Authentication Protocol** is set to **RSA-SecurID**.

This file needs to be exported from the RSA Authentication Manager.

For more information on the RSA authentication method, including how to configure it, refer to the **RSA Two Factor Authentication, Feature Description** on the [Kemp Documentation Page](#).

RSA Node Secret File

This option is only available when the **Authentication Protocol** is set to **RSA-SecurID**.

A node secret must be generated and exported in the RSA Authentication Manager.

It is not possible to upload the RSA node secret file until the RSA Authentication Manager configuration file is uploaded. The node secret file is dependent on the configuration file.

Logon Format

This drop-down list allows you to specify the format of the login information that the client has to enter.

The options available vary depending upon which **Authentication Protocol** is selected.

Not Specified: The username will have no normalization applied to it - it is taken as it is typed.

Principalname: Selecting this as the **Logon format** means that the client does not need to enter the domain when logging in, for example **username@domain**. The SSO domain added in the corresponding text box is used as the domain in this case.

Username: Selecting this as the **Logon format** means that the client needs to enter the domain and username, for example **domain\username**.

Username Only: Selecting this as the **Logon Format** means that the text entered is normalized to the username only (the domain is removed).

The **Username Only** option is only available for the **RSA-SecurID** protocols.

- **Logon Format (Phase 2 Real Server)**

Specify the logon string format used to authenticate to the Real Server.

The **Logon Format (Phase 2 Real Server)** field only appears if the **Authentication Protocol** is set to **RSA-SecurID**.

Logon Format (Phase 2 LDAP)

Specify the logon string format used to authenticate to LDAP.

The **Logon Format (Phase 2 LDAP)** field only appears if the **Authentication Protocol** is set to **RSA-SecurID and LDAP**.

Logon Transcode

Enable or disable the transcode of logon credentials, from ISO-8859-1 to UTF-8, when required.

If this option is disabled, log in using the format that the client dictates. If this option is enabled, check if the client uses UTF-8. If the client does not use UTF-8, use ISO-8859-1.

Failed Login Attempts

The maximum number of consecutive failed login attempts before the user is locked out. Valid values range from **0** to **99**. Setting this to **0** means that users will never be locked out.

When a user is locked out, all existing logins for that user are terminated, along with future logins.

Reset Failed Login Attempt Counter after

When this time (in seconds) has elapsed after a failed authentication attempt (without any new attempts) the failed login attempts counter is reset to **0**. Valid values for this text box range from **60** to **86400**. This value must be less than the **Unblock timeout** value.

Unblock timeout

The time (in seconds) before a blocked account is automatically unblocked, that is, unblocked without administrator intervention. Valid values for this text box range from **60** to **86400**. This value must be greater than the **Reset Failed Login Attempt Counter after** value.

Session timeout

The **idle time** and **max duration** values can be set here for trusted (private) and untrusted (public) environments. The value that is used is dependent on whether the user selects public or private on their login form. Also, either **max duration** or **idle time** can be specified as the value to use.

Idle time: The maximum idle time of the session in seconds, that is, idle timeout.

Max duration: The max duration of the session in seconds, that is, session timeout.

Valid values for these fields range from **60** to **604800** (seconds).

Use for Session Timeout: A switch to select the session timeout behaviour (**max duration** or **idle time**).

The underlying network traffic may keep the session active, even if there is no obvious user interaction.

Use LDAP Endpoint for Healthcheck

Select this check box to use the LDAP endpoint administrator username and password for health checking. If this is enabled, the **Test User** and **Test User Password** textboxes will not be available.

For more information on LDAP endpoints, refer to the **LDAP Configuration** section.

This option is only available for the following protocols; **LDAP**, **Certificates** and **RSA-SecurID and LDAP**.

Test User and Test User Password

In these two fields, enter credentials of a user account for your SSO Domain. The LoadMaster will use this information in a health check of the Authentication Server. This health check is performed every 20 seconds.

3.13.1.1.1 Client Side (Inbound) SAML SSO Domains

The fields vary when the **Authentication Protocol** is set to **SAML**. The SAML-specific fields are described below.

Domain EXAMPLE.COM

Authentication Protocol	SAML ▼	
IdP Provisioning	MetaData File ▼	
IdP MetaData File	<input type="button" value="Choose File"/> <input type="text" value="No file chosen"/> <input type="button" value="Import IdP MetaData File"/>	
IdP Entity ID	<input type="text" value="http://fs.espworld.com/adfs/services/trust"/>	<input type="button" value="Set IdP Entity ID"/>
IdP SSO URL	<input type="text" value="https://fs.espworld.com/adfs/ls"/>	<input type="button" value="Set IdP SSO URL"/>
IdP Logoff URL	<input type="text" value="https://fs.espworld.com/adfs/ls"/>	<input type="button" value="Set IdP Logoff URL"/>
IdP Certificate	No certificate available ▼	
SP Entity ID	<input type="text" value="http://espesp"/>	<input type="button" value="Set SP Entity ID"/>
SP Signing Certificate	Use Self Signed ▼	
Download SP Signing Certificate	<input type="button" value="Download"/>	
Session Control	SP Session Idle Duration ▼	
SP Session Idle Duration (secs)	<input type="text" value="900"/>	<input type="button" value="Set SP Idle Duration"/>

IdP Provisioning

The **Manual** option enables you to manually input details into the IdP fields.

The **MetaData File** option allows you to upload an **IdP MetaData File**. This simplifies the configuration of the IdP attributes, including the **IdP Entity ID**, **IdP SSO URL** and **IdP Logoff URL**. The metadata file can be downloaded from the IdP.

IdP Metadata File

This field is only visible if the **IdP Provisioning** field is set to **MetaData File**. To upload the file - click **Browse**, navigate to and select the relevant file and click **Import IdP MetaData File**.

IdP Entity ID

Specify the IdP entity identifier.

IdP SSO URL

Specify the IdP SSO URL.

IdP Logoff URL

Specify the IdP logoff URL.

IdP Certificate

The **IdP Certificate** is very important in terms of verification of the assertions that must be contained in the SAML response that is received from the IdP. Without the certificate, verification cannot proceed.

IdP Certificate Match

If this option is enabled, the IdP certificate assigned must match the certificate in the IdP SAML response.

SP Entity ID

This is an identifier that is shared to enable the IdP to understand, accept and have knowledge of the entity when request messages are sent from the LoadMaster. This must correlate to the identifier of the relying party on the AD FS server.

SP Signing Certificate

It is optional to sign requests that are sent in the context of logon. Currently, the LoadMaster does not sign those requests.

In the context of log off requests – it is mandatory and these requests must be signed. This is to avoid any spoofing and to provide extra security in relation to log off functionality. This ensures that users are not being hacked and not being logged off unnecessarily.

In the **SP Signing Certificate** drop-down list, you can choose to use a self-signed certificate or third party certificate to perform the signing.

Download SP Signing Certificate

If using a self-signed certificate, click **Download** to download the certificate. This certificate must be installed on the IdP server (for example AD FS) to be added to the relying party signature.

The AD FS server requires this certificate for use of the public key to verify the signatures that the LoadMaster generates.

Session Control

Select the relevant session control option. The available options are:

- **SP Session Idle Duration**
- **SP Session Max Duration**
- **IdP Session Max Duration**

The IdP maximum duration value cannot be set in the LoadMaster. The value is taken from the IdP protocol. If the value is not already set in the IdP authentication response, the default value of 30 minutes is assigned as the IdP maximum duration.

SP Session Idle Duration

Specify the session idle duration (in seconds). This field is only visible if **SP Session Idle Duration** is set as the **Session Control** option.

SP Session Max Duration

Specify the maximum duration of the session (in seconds). This field is only visible if **SP Session Max Duration** is set as the **Session Control** option.

3.13.1.1.2 Sessions

Client Side Single Sign On Configurations

Name	Operation
AKTEST.COM	<button>Modify</button> <button>Delete</button> <button>Sessions</button>

Add new Client Side Configuration

Add

Clicking the **Sessions** button, for a client-side SSO domain, opens a screen listing the current open sessions on that domain.

3 Virtual Services

Domain AKTEST.COM Users Management

[<-Back](#) [Refresh](#)

Open Sessions 4

Filter users:

Users	Source	Dest IP	Created	Expires	Cookie
<input type="checkbox"/> test1@aktest.com	-	172.16.2.252	2016-11-01 17:16:16	2016-11-01 17:26:16	-
<input type="checkbox"/> ldap@aktest.com	-	172.16.2.252	2016-11-01 17:16:27	2016-11-01 17:26:27	-
<input type="checkbox"/> ewrgui@aktest.com	-	172.16.2.252	2016-11-01 17:16:19	2016-11-01 17:26:19	-
<input type="checkbox"/> ldaptest@aktest.com	10.35.0.108:53538	172.16.2.252	2016-11-01 17:16:34	2016-11-01 19:46:34	6541dc3524c76ac1b256306fe501db03

[Kill All](#)

Currently Blocked Users

Blocked User	When	Operation
test1@aktest.com	Tue Nov 1 17:16:16 UTC 2016	unlock

[Unlock All](#)

You can filter the list by entering a search term in the **Filter users** text box.

The following information is provided about each session:

- **Users:** The username/domain of the client.
- **Source:** The client (host) IP address and source port.
- **Dest IP:** The destination IP address of the connection.
- **Created:** The date and time the connection was created.
- **Expires:** The date and time that the connection expires.
- **Cookie:** The cookie used in the connection.

Clicking the **Kill All** button kills all open sessions (flushes the SSO cache).

3 Virtual Services

Domain AKTEST.COM Users Management

[<-Back](#) [Refresh](#)

Open Sessions

Filter users:

Users	Source	Dest IP	Created	Expires	Cookie
<input checked="" type="checkbox"/> ldaptest10@aktest.com	-	172.16.2.252	2016-10-17 12:04:52	2016-10-17 13:44:52	-
<input checked="" type="checkbox"/> ldaptest3@aktest.com	-	172.16.2.252	2016-10-17 11:57:42	2016-10-17 13:37:42	-
<input checked="" type="checkbox"/> ldaptest11@aktest.com	10.35.0.108:38164	172.16.2.252	2016-10-17 12:00:31	2016-10-17 14:30:31	f86acf092e1af639c6923766428e23e4

[Kill All](#) [Kill Selected](#) [Block Selected](#) [Show All](#)

Currently Blocked Users

Blocked User	When	Operation
test1@aktest.com	Mon Oct 17 10:57:58 UTC 2016	unlock
ldaptest4@aktest.com	Mon Oct 17 10:57:52 UTC 2016	unlock

Selecting one or more sessions provides some further options:

- **Kill Selected**
- **Block Selected**
- **Show All**

Logs are added to the audit log for every kill session operation. For example:

- Kill 'non-cookie' session log:
Nov 9 16:47:31 LM ssomgr: Deleted a session tester@aktest.com:- for domain AKTEST.COM
- Kill 'cookie' session log:
Nov 9 16:47:31 LM ssomgr: Deleted a session
ldaptest@aktest.com:420cf78373643b3c0171d95c757e7bf3 for domain AKTEST.COM
- Kill all domain sessions log:
Nov 9 16:48:46 LM ssomgr: Deleted all domain AKTEST.COM user sessions

Currently Blocked Users

This section displays a list of users who are currently blocked and it also shows the date and time that the block occurred. It is possible to remove the block by clicking the **unlock** button in the **Operation** drop-down list.

Different formats of the same username are treated as the same username, for example, **administrator@kemptech.net**,

kemptech\administrator and **kemptech.net\administrator** are all treated as one username.

3.13.1.2 Server Side (Outbound) SSO Domains

Authentication Protocol

This dropdown allows you to select the transport protocol used to communicate with the authentication server. The only option available for outbound (server side) configurations is **Kerberos Constrained Delegation** (KCD).

For further information on KCD, please refer to the **KCD Feature Description** on the [Kemp Documentation Page](#).

Kerberos Realm

The address of the Kerberos Realm.

Colons, slashes and double quotes are not allowed in this field.

This field only supports one address.

Kerberos Key Distribution Center (KDC)

The host name or IP address of the Kerberos Key Distribution Center. The KDC is a network service that supplies session tickets and temporary session keys to users and computers within an Active Directory domain.

This field only accepts one host name or IP address. Double and single quotes are not allowed in this field.

Kerberos Trusted User Name


Before configuring the LoadMaster, a user must be created and trusted in the Windows domain (Active Directory). This user should also be set to use delegation. This trusted administrator user account is used to get tickets on behalf of users and services when a password is not provided. The user name of this trusted user should be entered in this text box.

Double and single quotes are not allowed in this field.

Kerberos Trusted User Password

The password of the Kerberos trusted user.

3.13.2 Single Sign On Image Sets




The screenshot shows a web interface titled "Single Sign On Image Sets". Below the title is a link "Add new Custom Image Set". Underneath, there is a label "Image File:" followed by a "Choose File" button and the text "No file chosen". To the right of this is a blue button labeled "Add Custom Image Set".

To upload a new image set, click **Choose File**, browse to and select the file and click **Add Custom Image Set**. After adding the file, the supplied image set(s) are listed on this page. It will also be available to select in the **SSO Image Set** drop-down list in the **ESP Options** section of the Virtual Service modify screen.

For more information on SSO image sets, including information on how the .tar file should be structured, refer to the **Custom Authentication Form, Technical Note** on the [Kemp Documentation Page](#).

3.14 WAF Settings

You can get to this screen by selecting **Virtual Services > WAF Settings** in the main menu of the LoadMaster WUI.



The screenshot shows the "Logging" section of the WAF Settings. It includes a "Logging Format" dropdown menu set to "Native", a checked "Enable Remote Logging" checkbox, and input fields for "Remote URI", "Username", and "Password". A blue button labeled "Set Remote Parameters" is located at the bottom right of the form.

Logging Format

Select either Native or JSON depending on what format you want the audit logs to appear in.

Enable Remote Logging

This check box enables you to enable or disable remote logging for WAF.

Remote URI

Specify the Uniform Resource Identifier (URI) for the remote logging server.

Username

Specify the username for the remote logging server.

Password

Specify the password for the remote logging server.

Automated WAF Rule Updates

Enable Automated Rule Updates ☒

Last Updated: Tue 01 Dec 15 [Download Now](#) [Show Changes](#)

Enable Automated Installs ☒ When to Install

Manually Install rules [Install Now](#) Last Installed: Tue 01 Dec 15

The automatic and manual download options are greyed out if the WAF subscription has expired.

Enable Automated Rule Updates

Select this check box to enable the automatic download of the latest WAF rule files. This is done on a daily basis, if enabled.

Last Updated

This section displays the date when the last rules were downloaded. It gives you the option to attempt to download the rules now. It will also display a warning if rules have not been downloaded in the last 7 days. The **Show Changes** button is displayed if the rules have been downloaded. This button can be clicked to retrieve a log of changes which have been made to the Kemp WAF rule set.

Enable Automated Installs

Select this check box to enable the automatic daily install of updated rules at the specified time.

When to Install

Select the hour at which to install the updates every day.

Manually Install rules

This button allows you to manually install rule updates, rather than automatically installing them. This section also displays when the rules were last installed.

Custom Rules

Installed Rules	Installed Date	Operation
modsecurity_crs_55_marketing	Tue, 01 Dec 2015 13:43:23	Delete Download
modsecurity_crs_55_response_profiling	Tue, 01 Dec 2015 13:43:23	Delete Download
modsecurity_crs_56_pvi_checks	Tue, 01 Dec 2015 13:43:23	Delete Download

Ruleset File: [Choose File](#) No file chosen [Add Ruleset](#)

Custom Rule Data

Installed Data Files	Installed Date	Operation
modsecurity_50_outbound_malware	Tue, 01 Dec 2015 13:43:23	Delete Download

Data File: [Choose File](#) No file chosen [Add Data File](#)

Custom Rules

This section allows you to upload custom rules and associated data files. Individual rules can be loaded as files with a .conf extension, or you can load a package of rules in a Tarball (.tar.gz) file. A Tarball of rule files usually includes a number of individual .conf and .data files.

The .conf files should be in standard ModSecurity rule file format.

Custom Rule Data

This section allows you to upload data files which are associated to the custom rules.

4 Global Balancing

This menu option may not be available in your configuration. These features are part of the GSLB Feature Pack and are enabled based on the license that has been applied to the LoadMaster. If you would like to have these options available, contact Kemp to upgrade your license.

4.1 Enable/Disable GSLB

Click this menu option to either enable or disable GEO features. When GEO is enabled, the **Packet Routing Filter** is enabled by default and cannot be changed. When GEO is disabled, it is possible to either enable or disable the **Packet Routing Filter** in **System Configuration > Access Control > Packet Filter**.

4.2 Manage FQDNs

A Fully Qualified Domain Name (FQDN), sometimes also referred to as an absolute domain name, is a domain name that specifies its exact location in the tree hierarchy of the Domain Name System (DNS). It specifies all domain levels, including the top-level domain and the root zone. A fully qualified domain name is distinguished by its lack of ambiguity: it can only be interpreted in one way. The DNS root domain is unnamed, which is expressed by the empty label, resulting in an FQDN ending with the dot character.

Configured Fully Qualified Names								
Fully Qualified Domain Name	Type	IP Address	Cluster	Checker	Availability	Requests/s	Parameters	Operation
Example.com.	Proximity	1.1.1.1	Example Cluster	ICMP Ping	✓ Up	0	0°0'0"N 0°0'0"W	Modify Delete

From this screen, you can **Add** or **Modify** an FQDN.

4.2.1 Add an FQDN

Add a FQDN

New Fully Qualified Domain Name [Add FQDN](#)

New Fully Qualified Domain Name

The FQDN name, for example `www.example.com`. Wildcards are supported, for example `*.example1.com` matches anything that ends in `.example1.com`.

4.2.2 Add/Modify an FQDN

Configure example.com.

Selection Criteria Location Based ▾
 Fail Over ☐
 Public Requests Public Sites Only ▾
 Private Requests Private Sites Only ▾
 Site Failure Handling Failure Delay (minutes) Set Failure Delay
 Enable Local Settings ☒
 TTL Set TTL value
 Stickiness Set Sticky timeout
 Unanimous Cluster Health Checks ☐

IP Address	Cluster	Checker	Availability Parameters	Operation
10.154.11.50	Select Cluster ▾	Icmp Ping ▾	<input type="text"/> Set Addr Up Show Locations	Disable Delete

Available Locations

- Everywhere
- Continents**
- Africa
- Asia
- Europe
- North America

Assigned Locations

- Continents**
- Countries**
- Custom Locations**

Save Changes

Selection Criteria

The selection criterion used to distribute the resolution requests can be selected from this drop-down list. The Selection Criteria available are:

- **Round Robin** - traffic distributed sequentially across the server farm (cluster), that is, the available servers.
- **Weighted Round Robin** – Incoming requests are distributed across the cluster in a sequential manner, while taking account of a static “weighting” that can be pre-assigned per server.
- **Fixed Weighting** - the highest weight Real Server is used only when other Real Server(s) are given lower weight values.
- **Real Server Load** - LoadMaster contains logic which checks the state of the servers at regular intervals and independently of the configured weighting.
- **Proximity** – traffic is distributed to the closest site to the client. When using **Proximity** scheduling, new public sites are automatically mapped to geographic coordinates based on the GEO database. New private sites are mapped to 0°0'0" and function as expected. This coordinate

- should be overridden with accurate values to ensure correct balancing. The position of the client is determined by their IP address.
- **Location Based** - traffic is distributed to the closest site to the client. The positioning of the sites is set by inputting the location of the site (country or continent) during setup. The position of the client is determined by their IP address. If there is more than one site with the same country code, requests are distributed in a round robin fashion to each of the sites.
- **All Available** – returns all possible healthy targets for an A, AAAA or ANY query request. The contents of the returned list is also controlled by the **Public Requests** and **Private Requests** settings:
 - For **Public Sites Only** the list can only contain public addresses. Likewise, for **Private Sites Only** the list can only contain private addresses.
 - For **Prefer Public** the list only contains public addresses, unless no public addresses are available – in which case the list contains private addresses (if any are available). Likewise, for **Prefer Private** the list only contains private addresses, unless no private addresses are available – in which case the list contains public addresses (if any are available).
 - For **All Sites** the list contains all available addresses

The purpose of this is to provide a list of preferred addresses, if they are available. Otherwise, provide a list of non-preferred addresses as a failback measure for improved availability.

Fail Over

The **Fail Over** option is only available when the **Selection Criteria** is set to **Location Based**. When the **Fail Over** option is enabled, if a request comes from a specific region and the target is down, the connection will fail over and be answered with the next level in the hierarchy. If this is not available, the connection is answered by the nearest (by proximity) target. If this is not possible, the target with the lowest requests are picked. For example, if a request from Ireland is received, but the site assigned to **Ireland** is unavailable, a site assigned to **Europe** is selected. If the site assigned to Europe is also unavailable, a site assigned to **Everywhere** is selected. If this too is unavailable, the site with the lowest requests of the available sites in the same continent is selected using the round robin method. The **Fail Over** setting affects all targets.

Public Requests & Private Requests

The **Isolate Public/Private Sites** setting has been enhanced in version 7.1-30. The checkbox has been migrated to two separate dropdown menus to allow more granular control of DNS responses. Existing behavior has been preserved and is migrated from your current setting, ensuring that no change in DNS responses is experienced.

These new settings allow administrators finer control of DNS responses to configured FQDNs. Administrators may selectively respond with public or private sites based on whether the client is from a public or private IP. For example, administrators may wish to allow only private clients to be sent to private sites.

The following table outlines settings and their configurable values:

Setting	Value	Client Type	Site Types Allowed
Public Requests	Public Only	Public	Public
	Prefer Public	Public	Public, Private if no public
	Prefer Private	Public	Private, Public if no private
	All Sites	Public	Private and Public
Private Requests	Private Only	Private	Private
	Prefer Private	Private	Private, Public if no private
	Prefer Public	Private	Public, Private if no public
	All Sites	Private	Private and Public

Note that exposing private IP address information to public queries in this way may result in exposed network details. Select this setting at your own risk.

Site Failure Handling

The default is for failover to occur automatically. However, in certain circumstances, for example in a multi-site Exchange 2010 configuration, this may not be optimal and different behaviour may be required. **Failure Delay** is set in minutes. If a **Failure Delay** is set, a new option called **Site Recovery Mode** becomes available.

Site Recovery Mode

This option is only available if a **Failure Delay** has been set. There are two options:

- **Automatic:** The site is brought back into operation immediately upon site recovery
- **Manual:** Once the site has failed, disable the site. Manual intervention is required to restore normal operation.

Enable Local Settings

Selecting this option will display two additional fields – **TTL** and **Stickiness**. These can be set on a per-FQDN basis or globally. To set them for an FQDN – enable local settings and configure them as needed. The per-FQDN settings will default to the value of the global settings when the FQDN is created.

TTL

The Time To Live (TTL) value dictates how long the reply from the GEO LoadMaster can be cached by other DNS servers or client devices. The time interval is defined in seconds. This value should be as practically low as possible. The default value for this field is 10. Valid values range from 1 to 86400.

Stickiness

‘Stickiness’, also known as persistence, is the property that enables all name resolution requests from an individual client to be sent to the same resources until a specified period of time has elapsed. For further information on Stickiness, refer to the **GEO Sticky DNS, Feature Description** on the [Kemp Documentation Page](#).

Unanimous Cluster Health Checks

If this option is enabled, if any IP addresses fail health checking - other FQDN IP addresses which belong to the same cluster are marked as down. When **Unanimous Cluster Health Checks** is enabled, the IP addresses which belong to the same cluster within a specific FQDN are either all up or all down. For example, **example.com** has addresses 172.21.58.101, 172.21.58.102 and 172.21.58.103 which all belong to cluster **cl58**:

- If 172.21.58.101 fails, the unanimous policy forces 172.21.58.102 and 172.21.58.103 down as well.
- When 172.21.58.101 comes back, the unanimous policy brings back 172.21.58.102 and 172.21.58.103 along with it.

So, at any given time – either all three addresses are available or all three addresses are down.

The same approach applies for site failure mode with manual recovery. Manual recovery causes a failed address to be disabled, so the administrator can re-enable it after fixing the problem. When **Unanimous Cluster Health Checks** is enabled, all three addresses are disabled.

The unanimous policy ignores disabled addresses. So, if you know that an address is down, and for whatever reason you want to continue using the other addresses that belong to the same cluster, you can disable the failed address and the unanimous policy will not force down the other addresses with it.

When **Unanimous Cluster Health Checks** are enabled, some configuration changes may cause FQDN addresses to be forced down or brought back up. For example, if an address is forced down and you remove it from the cluster while the unanimous policy is in effect, the address should come

back up. Similarly, if you add an address to a cluster where the unanimous policy is in effect and one of the addresses is down, the new address should be forced down. This change may not occur immediately, but it should happen the next time health checking occurs.

If there are addresses with the **Checker** set to **None** combined with addresses that have health checking configured – addresses with no health checking will not be forced down, but they can be forcibly disabled if the **Site Recovery Mode** is set to **Manual**. For example, say there are three addresses:

- 172.21.58.101 with a **Checker** of **Cluster Checks**
- 172.21.58.102 with a **Checker** of **Cluster Checks**
- 172.21.58.103 with a **Checker** of **None**

If site failure handling is off or automatic, the failure of 172.21.58.101 causes 172.21.58.102 to be forced down, but 172.21.58.103 remains up. The rationale is that if you do not want health checking on 172.21.58.103 then it should remain up.

However, if the **Site Recovery Mode** is set to **Manual**, failure of 172.21.58.101 causes both 172.21.58.102 and 172.21.58.103 to be disabled, along with 172.21.58.101. For site recovery – all addresses are disabled, even the ones with no health checking configured. This is to keep traffic away from the problem data center until the system administrators fix it. This does not conflict with having addresses with no health checking because you can have an address that is up but disabled.

Cluster

If needed, the cluster containing the IP address can be selected.

Checker

This defines the type of health checking that is performed. The options include:

- **None:** This implies that no health check is performed to check the health status of the machine (IP address) associated to the current FQDN
- **ICMP Ping:** This tests the health status by pinging the IP address
- **TCP Connect:** This will test the health by trying to connect to the IP address on a specified port
- **Cluster Checks:** When this is selected, the health status check is performed using the method associated with the selected cluster

- When using **Real Server Load** as the **Selection Criteria**, and the cluster **Type** is set to **Local LM** or **Remote LM**, a drop-down list appears called **Mapping Menu**. The **Mapping Menu** drop-down list displays a list of Virtual Service names (where

available) and Virtual Service IP addresses from that LoadMaster. It lists each Virtual Service IP address with no port, as well as all of the Virtual IP address and port combinations. Select the Virtual IP address that is associated with this mapping.

If a Virtual Service with no port is selected, the health check checks all Virtual Services with the same IP address as the one selected. If one of them is in an “Up” status, the FQDN shows as “Up”. The port does not come into consideration.

If a Virtual Service with a port is selected, the health check only checks against the health of that Virtual Service when updating the health of the FQDN.

For further information regarding health checks, refer to the **GEO, Feature Description** on the [Kemp Documentation Page](#).

Parameters

The parameters for the Selection Criteria are described and can be changed within this section. The parameters differ depending on the **Selection Criteria** in use, as described below:

- **Round Robin** – no parameters available
- **Weighted Round Robin** – the weight of the IP address can be set by changing the value in the **Weight** text box and clicking the **Set Weight** button
- **Fixed Weighting** – the weight of the IP address can be set in the **Weight** text box
- **Real Server Load** – the weight of the IP address can be set in the **Weight** text box and the Virtual Service which is measured can be chosen from the **Mapping** field
- **Proximity** – the physical location of the IP address can be set by clicking the **Show Coordinates** button
- **Location Based** – the locations associated with the IP address can be set by clicking the **Show Locations** button

Delete IP address

An IP address can be deleted by clicking the **Delete** button in the **Operation** column of the relevant IP address.

Delete FQDN

An FQDN can be deleted by clicking the **Delete** button at the bottom of the **Modify (Configure) FQDN** screen.

4.3 Manage Clusters

GEO clusters is a feature mainly used inside data centers. Health checks are performed on a machine (IP address) associated to a specific FQDN, using the containing cluster server, rather than the machine itself.

Configured Clusters

IP Address	Name	Coordinates	Type	Checker	Availability	Operation
10.154.11.190	Example	0°0'5"N 0°0'5"E	Default	None	✓ Up	Modify Delete
172.20.0.29	Example2	0°0'0"N 0°0'0"W	Default	None	✓ Up	Modify Delete

Add a Cluster

IP address Name [Add Cluster](#)

In the **Manage Clusters** screen there are options to **Add**, **Modify** and **Delete** clusters.

4.3.1 Add a Cluster

Add a Cluster

IP address Name [Add Cluster](#)

When adding a cluster, there are 2 text boxes to fill out:

- **IP address** – the IP address of the cluster
- **Name** – the name of the cluster. This name can be used to identify the cluster while in other screens.

4.3.2 Modify a Cluster

Modify Cluster ExampleCluster

IP Address	Name	Location	Type	Checkers	Operation
10.154.11.158	<input type="text" value="ExampleCluster"/> Set Name	Location: 0°0'0"N 0°0'0"W Show Locations	<input type="text" value="Default"/>	<input type="text" value="None"/>	Disable
		Manually set location: 0°0'0"N 0°0'0"E Resolved location: 0°0'0"N 0°0'0"W <div> <input type="text" value="0"/>°<input type="text" value="0"/>'<input type="text" value="0"/>N <input type="text" value="0"/>°<input type="text" value="0"/>'<input type="text" value="0"/>E Set Location </div>			

Name

The name of the cluster.

Location

If needed, the **Show Locations** button can be clicked to enter the latitude and longitude of the location of the IP address.

Type

The cluster type can be **Default**, **Remote LM** or **Local LM**:

- **Default:** When the type of cluster is set to **Default**, the check is performed against the cluster using one of the following three available health checks:
 - **None:** No health check is performed. Therefore, the machine always appears to be up.
 - **ICMP Ping:** The health check is performed by pinging against the cluster IP address.
 - **TCP Connect:** The health check is performed by connecting to the cluster IP address on the port specified.
- **Local LM:** When **Local LM** is selected as the **Type**, the **Checkers** field is automatically set to **Not Needed**. This is because the health check is not necessary because the cluster is the local machine.
- **Remote LM:** The health check for this type of cluster is **Implicit** (it is performed using SSH).

The only difference between **Remote LM** and **Local LM** is that it saves a TCP connection because it gets the information locally and not over TCP. Otherwise, the functionality is the same.

Checkers

The health check method used to check the status of the cluster.

If the **Type** is set to **Default** the health check methods available are **ICMP Ping** and **TCP Connect**.

If **Remote LM** or **Local LM** is selected as the **Type**, the **Checkers** dropdown list is unavailable.

Disable

If needed, a cluster can be disabled by clicking the **Disable** button in the **Operation** column.

4.3.3 Delete a Cluster

To delete a cluster, click the **Delete** button in the **Operation** column of the relevant cluster.

Use the **Delete** function with caution. There is no way to undo this deletion.

4.3.4 Upgrading GEO Clusters

When upgrading GEO clusters, it is strongly recommended that all nodes are upgraded at the same time. Since GEO clusters operate in active-active mode, upgrading at the same time ensures that consistent behavior is experienced across all nodes.

If you must operate a GEO cluster with mixed versions, be sure to make all changes from the most recent version. This prevents configuration loss due to incompatible configurations. Additionally, changing configuration options not present in older versions will result in disparate behavior.

4.4 Miscellaneous Params

A description of the sections and fields in the **Miscellaneous Params** menu option are below.

Source of Authority		
Zone Name	<input type="text" value="ZoneNameExample.com."/>	<button>Set Zone Name</button>
Source of Authority	<input type="text" value="example.com."/>	<button>Set SOA</button>
Name Server	<input type="text" value="example.com."/>	<button>Set Nameserver</button>
SOA Email	<input type="text" value="example@kemptechnologies.com."/>	<button>Set SOA Email</button>
TTL	<input type="text" value="10"/>	<button>Set TTL value</button>

Zone Name

Enter the zone name to use. A zone name is necessary for DNSSEC configurations. All FQDNs within the zone are signed using the provided key. All FQDNs outside the zone continue to work but the responses are unsigned.

Source of Authority

This is defined in RFC 1035. The SOA defines global parameters for the zone (domain). There is only one SOA record allowed in a zone file.

Name Server

The Name Server is defined as the forward DNS entry configured in the Top Level DNS, written as a Fully-Qualified Domain Name (FQDN and ends with a dot), for example **lm1.example.com.**

If there is more than one Name Server, for example in a HA configuration, then you would add the second Name Server in the field also, separated by a blank space, for example **lm1.example.com lm2.example.com**.

SOA Email

This textbox is used to publish a mail address of a person or role account dealing with this zone with the “@” converted to a “.”. The best practice is to define (and maintain) a dedicated mail alias, for example “hostmaster” [RFC 2142] for DNS operations, for example **hostmaster@example.com**.

TTL

The Time To Live (TTL) value dictates how long the reply from the GEO LoadMaster can be cached by other DNS servers or client devices. This value should be as practically low as possible. The default value for this field is 10. The time interval is defined in seconds.

4.4.1 Resource Check Parameters

Resource Check Parameters		
Check Interval	<input type="text" value="120"/>	<button>Set Check Interval</button>
Connection Timeout	<input type="text" value="20"/>	<button>Set Timeout value</button>
Retry attempts	<input type="text" value="2"/>	<button>Set Retry Attempts</button>

Check Interval

Defined in seconds, this is the delay between health checks. This includes clusters and FQDNs. The valid range for this field is between 9 and 3600. The default value is 120.

The interval value must be greater than the timeout value multiplied by the retry value ($\text{Interval} > \text{Timeout} * \text{Retry} + 1$). This is to ensure that the next health check does not start before the previous one completes.

If the timeout or retry values are increased to a value that breaks this rule, the interval value is automatically increased.

Connection Timeout

Defined in seconds, this is the allowed maximum wait time for a reply to a health check. The valid range for this field is between 4 and 60. The default value is 20.


Retry Attempts

This is the consecutive number of times in which a health check must fail before it is marked down and removed from the list of healthy Real Servers. The default retry attempts is 2.

The maximum detection window for failed clusters of FQDNs is the **Check Interval** + (**Connection Timeout** * (**Retry attempts** + 1)). On average, the maximum time is half that.

The timeline diagram below illustrates what happens from the time a resource IP is added or enabled, to when it goes down and then comes back up again:

1. When a resource IP is enabled/created, an ICMP request is sent by the LoadMaster to the resource IP. Assuming it responds, the resource is marked UP.
2. After 120 seconds has elapsed (the default **Check Interval**), an ICMP request is sent to the resource IP. If 20 seconds (the default **Connection Timeout**) elapses and the IP fails to respond, the LoadMaster will send up to two additional requests (the default **Retry Attempts**) and wait for 20 seconds between each. If all three of these requests receive no response, then the resource is marked down, and the **Check Interval** timer is reset.
3. After 120 seconds elapses, the LoadMaster attempts to send an ICMP request to the resource IP. If the resource has now come back up and responds before the **Connection Timeout** elapses, the LoadMaster marks it UP and resets the **Check Interval** timer.



4.4.2 Stickiness

Stickiness

Stickiness

60

Set Sticky Timeout

‘Stickiness’, also known as Global Persistence, is the property that enables all name resolution requests from an individual client to be sent to the same resources until a specified period of time has elapsed. For further information on **Stickiness**, refer to the **GEO Sticky DNS, Feature Description** on the [Kemp Documentation Page](#).

4.4.3 Location Data Update

Location Data Update

GeoIP:20180327 Build 1 Copyright (c) 2018 MaxMind Inc All Rights Reserved
GeoCity:20180327 Build 1 Copyright (c) 2018 MaxMind Inc All Rights Reserved
GeoIPv6:20180828 Build 1 Copyright (c) 2018 MaxMind Inc All Rights Reserved
GeoCityv6:20180828 Build 1 Copyright (c) 2018 MaxMind Inc All Rights Reserved

Geodata.patch

Choose File

 No file chosen

Install Update

The location patch contains the geographically-encoded IP to location data. Data files can be obtained directly from Kemp using normal support channels. These files are a repackaged distribution of MaxMind; the GeoIP database.

The legacy MaxMind GeoLite database is only supported on LoadMaster version 7.2.44 and below. The new MaxMind GeoLite2 database is only supported on LoadMaster version 7.2.45 and above.

To obtain the latest release, contact support: <https://kemptechnologies.com/support>.

4.5 IP Range Selection Criteria

Add a new IP address

IP Address

Add Address

This section allows a new IP address range to be defined.

IP Address Ranges configured			
IP/IPv6 Address Range	Coordinates	Location	Operation
10.154.11.190/32		Ireland	<button>Modify</button> <button>Delete</button>

After adding an address, clicking **Modify** will open the modify settings screen. It is also possible to delete a range after it has been added.

IP Address	Coordinates	Location
10.154.11.190/32	<div><div></div><div></div><div></div><div>N</div><div></div><div></div><div></div><div>E</div></div> <div><button>Save</button> <button>Delete</button></div>	<div>Ireland</div>

This section allows the definition of up to 64 IP ranges per data center.

IP Address

Specify an IP address or network. Valid entries here are either a single IP, for example **192.168.0.1**, or a network in Classless Inter-Domain Routing (CIDR) format, for example **192.168.0.0/24**.

Coordinates

Specify the latitude and longitude of the location.

Location

Specify the location to be assigned to the address.

Add a new custom location

Add location

Add Custom Location

This section allows you to add a custom location.


Custom Locations configured	
Custom Location Name	Operation
New York	<button>Modify</button> <button>Delete</button>

Existing custom locations can also be modified and deleted in this section.

4.6 IP Blacklist Settings

It is possible to download blacklist rules from Kemp to block access from IP addresses that are on the blacklist. A whitelist can be manually specified that will override the blacklist.

This is a licensable feature. If you cannot see these options, or if any fields are grayed out, please contact Kemp to upgrade your license.



The screenshot shows the 'Automated IP Blacklist Data Update settings' section. It includes a checkbox for 'Enable Automated GEO IP Blacklist data Updates' which is currently disabled. Below this, it shows 'Last Updated: 01 Jun 2016 08:15:28' with 'Download Now' and 'Show Changes' buttons. There is also a checkbox for 'Enable Automated Installs' which is disabled, with a 'When to Install' dropdown set to '04:00'. Below that, it says 'Manually Install GEO IP Blacklist data' with an 'Install Now' button and 'Last Installed: 01 Jun 2016 08:15:32'. At the bottom of this section is a 'View GEO IP Blacklist data file' link with a 'View' button. The next section is 'IP Whitelist Data settings', which states 'GEO ACL white list is empty'. Below this is an 'Add New Address/Network' section with an input field for 'Address/Network' and an 'Add' button.

Enable Automated GEO IP Blacklist data Updates

If this option is enabled, updates to the GEO IP blacklist are downloaded daily. By default, this option is disabled.

Last Updated

The date when the last updates were downloaded is displayed. If the GEO blacklist data is more than 7 days old, a message appears to inform you.

Download Now

Click this button to download the updates now.

Enable Automated Installs

Select this check box to enable the automatic daily install of updated rules at the specified time.

When to Install

Select the hour at which to install the updates every day.

Manually Install GEO IP Blacklist data

This button enables you to manually install the updates. This section also displays when the updates were last installed. If the GEO blacklist data is not updated for more than 7 days, a message appears to inform you.

View GEO IP Blacklist data file

Clicking the **View** button displays the current GEO IP Blacklist data file.

IP Whitelist Data Settings

This section displays the IP addresses that are currently on the whitelist.

Add New Address/Network

In this section, new addresses and networks can be added to the whitelist. The whitelist overrides the blacklist.

4.7 Configure DNSSEC

Before you can configure DNSSEC, a zone must be defined. To define a zone, go to **Global Balancing > Miscellaneous Params** and specify a **Zone Name**.

Key Signing Key (KSK)

Generate KSK Files

Generate

Import KSK Files

Import

Public Key

DS (SHA-1)

DS (SHA-2)

DNS Security Setting

Enable DNSSEC ☐

After the zone name is defined, the Key Signing Keys (KSKs) must be configured. You have two choices - you can either:

- Import the KSK files by clicking **Import** and browsing to the file locations.
- Generate the KSK files by clicking **Generate**

Generate Key Signing Key Files

Algorithm RSASHA256 ▼

Key Size 2048 ▼

Cancel
Generate

On the generate screen, select the cryptographic **Algorithm** and **Key Size**.

The following algorithms are supported:

- NSEC3RSASHA1
- RSASHA256
- RSASHA512

The default is RSASHA256.

The supported key sizes are 1024, 2048 and 4096 bits. The default is 2048.

Key Signing Key (KSK)

Generate KSK Files

Generate

Import KSK Files

Import

Delete KSK Files

Delete

Public Key

ZoneNameExample.com. IN DNSKEY 257 3 8
 AwEAAC4mmubohFp6sxKxbCrBbMPBzd/+AbPkrFYqDc9OzOfngIJ0Pvca
 fhI6ELbvIQ0d6uDGXC2pHvJHfoHXBjWdt/ITpJG06QVJJ+SF14WU8UCL
 uSSYPH25AffI0kyFbaIwbP0RSPpLHY5o1K1UgiY4BR4YDpnf6BGSY6/
 Usiq0AzEDZ/R1o/iOLsIOJGIm8bYuSBnRaIKVka2OQt5stIjaWS79ytE
 SrmWD7DouCDP7euPXkNyg05crl9p/a9i6LIM1Ps65P1DY9W/SQjU07mv
 KG9EjzLHL4nZKBhB7DogwMKdElqXx1d/xc3d9uUtm4EdjVa5rskBlv+
 LgPoHjkdX4k=

DS (SHA-1)

ZoneNameExample.com. IN DS 21802 8 1
 99DC4F92338AEB32AF8238A82A8409110309F727

DS (SHA-2)

ZoneNameExample.com. IN DS 21802 8 2
 4352D4C5684741DBBC5AD7D919308A187618344015B28C0EC3804B17885EF71E

After the KSK files have been generated/imported, the DNSSEC screen shows the KSK details and gives you an option to delete the KSK files.

The final step is to enable DNSSEC by selecting the check box.

4.8 GSLB Statistics

The **GSLB Statistics** screen (accessible from under the **Global Balancing** section in the main menu) is a centralized snapshot of the GSLB components that enable site resiliency and hybrid traffic distribution.

GSLB Service Status

Boot time	Tue, 12 Mar 2019 10:23:13 GMT
Last configuration	Tue, 12 Mar 2019 08:27:38 GMT

FQDN Statistics

Fully Qualified Domain Name	IP Address	Requests/s	Total
www.abhijeettest.com.	1.2.3.4	0	17

Queries

Type	Requests
A	11
AAAA	10
ANY	6

DNS Request Information

Type	Description	Requests
Requestv4	IPv4 Requests Received.	17
Requestv6	IPv6 Requests Received.	10
ReqEdns0	Requests with DNS Extension Mechanisms Received.	7
ReqTCP	TCP requests received.	6
Response	DNS Responses Sent.	27
RespEDNS0	DNS Responses with DNS Extension Mechanisms Sent.	7
QrySuccess	DNS Queries resulted in a successful answer.	17
QryAuthAns	DNS Queries resulted in authoritative answer.	27
QryNxrrset	DNS Queries resulted in NOERROR responses with no data.	10
QryUDP	UDP queries received.	21

The following sections display on the **GSLB Statistics** screen:

- **GSLB Service Status:** Displays the **Boot time** (the start time of the bind device) and the **Last configuration** (the date and time when the configuration was last modified).

- **FQDN statistics:** Displays the FQDN configuration with IP address information.
- **Queries:** Displays the different DNS query types received.
- **DNS Request Information:** Displays the type of DNS requests with a description and request count.


If you disable and re-enable GSLB, the GSLB statistics reset to zero.

5 Statistics

5.1 Real Time Statistics

Shows the activity for the LoadMasters within the system (**Global**), the **Real Servers**, the **Virtual Services** and the WAF.

5.1.1 Global



Total CPU Activity

This table displays the following CPU utilization information for a given LoadMaster:

Statistic	Description
User	The percentage of the CPU spent processing in user mode
System	The percentage of the CPU spent processing in system mode
Idle	The percentage of CPU which is idle
I/O Waiting	The percentage of the CPU spent waiting for I/O to complete

The sum of these four percentages equals 100%.


Core Temperatures: The temperature for each CPU core is displayed for LoadMaster hardware appliances. Temperature will not show on a Virtual LoadMaster statistics screen.

On Dell LoadMasters, you can retrieve hardware statistics using SNMP. These include:

- Temperature
- Fan speed
- Power supply
- Voltage current

These values are only available using SNMP. For further information on **SNMP Options**, refer to the **SNMP Options** section.

CPU Details: To get statistics for an individual CPU, click the relevant number button in **CPU Details**.



The CPU details screen has two additional statistics displayed - **HW Interrupts** and **SW Interrupts**.

Memory usage

This bar graph shows the percentage (MB) amount of memory in use and the amount of memory free.

Network activity

These bar graphs show the current network throughput on each interface.

For Elastic Network Adapter (ENA) driver interfaces, the speed displayed behaves similar to bonded interfaces in that the speed of the overall interface is the aggregate of the number of separate logical interfaces that have been defined on that interface.

Disk Usage

This section provides an indication of the percentage (GB) used/free of the log partitions. Color-coding is used to highlight different usage levels:

- 0% to 50%: green
- 50% to 90%: orange
- 90% to 100%: red

5.1.2 Real Servers

Global	Real Servers	Virtual Services	WAF									Connections	Bytes	Bits	Packets
Name	IP Address	Status	Total Conns	Last 60 Sec	5 Mins	30 Mins	1 Hour	Active Conns	Current Rate Conns/sec	[%]	Conns/sec				
1⇒	10.154.15.21	✓ Up	0	0	0	0	0	0	0	0	0				
2⇒	10.154.201.2	✓ Up	0	0	0	0	0	0	0	0	0				
3⇒	10.154.201.3	✓ Up	0	0	0	0	0	0	0	0	0				
3	System Total Conns		0	0	0	0	0	0	0 /sec						

These graphs display the connections, bytes, bits or packets, depending on choice. The buttons in the top right of the page toggle which values are displayed. The values displayed for the Real Server comprise of the values for all the Virtual Services accessing the Real Server.

If the Real Server has been assigned to more than one Virtual Service, you can view the statistics for each Real Server by Virtual Service by clicking the arrow (⇒) to the right of the number in the first column. This expands the view to show the statistics for each Virtual Service on the Real Server.

Because of the way that encrypted services are implemented, it is not possible to view the packet statistics on an encrypted Virtual Service.

Name: The **Name** column is automatically populated based on a DNS lookup.

IP Address: This column displays the IP address of the Real Servers, and the Virtual Service (if expanded).

RS 172.22.4.20		Request/Response (ms)		Round Trip Times (ms)	
Real Server	172.22.4.20	Current Average	0 / 341	Current Average	0
Active Conns	4	Current Max	2 / 3329	Current Max	0
Total Conns	1899	Current Min	0 / 107	Current Min	0
Total Bytes	995223622	Long Term Avg	1 / 324	Long Term Avg	0
Total Services	1	Long Term Max	2452 / 7609	Long Term Max	0
Active Services	1	Long Term Min	0 / 62	Long Term Min	0
Functioning Services	1				
Persist Entries	0				

Clicking the links in the **IP Address** column will display another screen containing a number of statistics specific to that Real Server.

Round trip times between the LoadMaster and Real Server are displayed. The performance of the Real Servers is monitored with the following two measurements:

- How long the Real Server takes to respond to the request (first byte).
- How long the Real Server takes to send all the data (last byte) - response time.

In the above graphic the **Request/Response Current Max** figures are **2 / 3329**. This means that it took the Real Server a maximum of 2ms to respond to the request (first byte) and a max of 3329ms to send all the data and this is the measurement of the response time.

Round Trip Time (RTT) to the server cannot be measured if using re-encrypt.

Request/Response times are not applicable if the service being used is a HTTP-like service.

Clicking **Reset Statistics** in the **Debug Options** screen (**System Configuration > System Administration > System Log Files > Debug Options**) clears all the values.

For each RTT or request/response time, the following values are measured:

- **Current Average:** The average time (in milliseconds (ms)) over the last 5 seconds (or since the last statistics reset).
- **Current Max:** The current maximum time (in ms) - in the last 5 seconds (or since the last statistics reset).
- **Current Min:** The current minimum time (in ms) - in the last 5 seconds (or since the last statistics reset).
- **Long Term Avg:** The average time over the whole period since the Virtual Service started handling traffic (or since the last statistics reset).
- **Long Term Max:** The all-time maximum value (in ms) since the Virtual Service started handling traffic (or since the last statistics reset).
- **Long Term Min:** The all-time minimum value (in ms) (or since the last statistics reset).

Values are only present if values have been recorded. For example, no **Current Max** displays if no traffic has passed through the Virtual Service in the last five seconds or if the Virtual Service cannot monitor the specific values.

The **Current Average**, **Current Max**, **Current Min**, **Long Term Avg**, **Long Term Max**, and **Long Term Min** for Virtual Services and Real Servers are also available over SNMP.

Status: This shows the status of the Real Server.

Adaptive: This will only be displayed if an adaptive scheduling method has been selected for a Virtual Service. This column will display the adaptive value.

Total Conns: The total number of connections made.

For Layer 4 UDP connections - the connection count always shows as 0.

Last 60 Sec: The total number of connections in the last 60 seconds.

5 Mins: The total number of connections in the last 5 minutes.

30 Mins: The total number of connections in the last 30 minutes.

1 Hour: The total number of connections in the last hour.

Active Conns: The total number of connections that are currently active.

When using ESP, all connections going through the login process are counted as active connections for the Virtual Service. They are not counted as active connections for the Real Server because they are not actual connections to the Real Server. The WUI page displays the number of active connections associated with the Real Servers, while SNMP displays the number of active connections for the Virtual Service. The API returns the same value as displayed in the WUI. Without ESP, these values are identical. When using ESP, the Virtual Service counts can be much higher than the final counts going to the Real Servers, due to the above reason.

Current Rate Conns/sec: The current rate of connections per second.

[%]: The percentage of connections per second.

Conns/sec: A graphical representations of the connections per second.

System Total Conns: This row displays totals for each of the columns.

5.1.3 Virtual Services

Global Real Servers Virtual Services											Connections Bytes Bits		
Name	Virtual IP Address	Protocol	Status	Total Conns	Last 60 Sec	5 Mins	30 Mins	1 Hour	Active Conns	Current Rate Conns/s	Real Servers RS-IP	[%] Conns/s	
1 Splunk	10.154.11.91:443	tcp	Up	0	0	0	0	0	0	0	10.154.11.90	0	
1	System Total Conns			0	0	0	0	0	0	0 /sec			

These graphs display the connections, bytes, bits or packets, depending on choice. The buttons in the top right of the page toggle which values are displayed. The percentage of distribution across the Virtual Service's Real Servers are displayed.

Name: The name of the Virtual Service.

Virtual IP Address: The IP address and port of the Virtual Service.

VIP 172.21.4.11:80		Request/Response (ms)	Round Trip Times (ms)
Address	172.21.4.11	Current Average 1 / 331	Current Average 0
Port	80	Current Max 1026 / 5484	Current Max 10
Protocol	tcp	Current Min 0 / 102	Current Min 0
Active Conns	75	Long Term Avg 2 / 315	Long Term Avg 0
Total Conns	45095	Long Term Max 2555 / 9881	Long Term Max 28
Total Bytes	23634841712	Long Term Min 0 / 61	Long Term Min 0
Real Servers	16		
Persist Entries	0		

Clicking the links in the **Virtual IP Address** column will display another screen containing a number of statistics specific to that Virtual Service.

Round trip times between the client and LoadMaster are displayed. The performance of the Virtual Service is monitored with the following two measurements:

- How long the Virtual Service takes to respond to the request (first byte).
- How long the Virtual Service takes to send all the data (last byte) - response time.

In the above graphic the **Request/Response Current Max** figures are **1026 / 5484**. This means that it took the Real Server a maximum of 1026ms to respond to the request (first byte) and a max of 5484ms to send all the data and this is the measurement of the response time.

Clicking **Reset Statistics** in the **Debug Options** screen (**System Configuration > System Administration > System Log Files > Debug Options**) clears all the values.

For each RTT or request/response time, the following values are measured:

- **Current Average:** The average time (in milliseconds (ms)) over the last 5 seconds (or since the last statistics reset).
- **Current Max:** The current maximum time (in ms) - in the last 5 seconds (or since the last statistics reset).
- **Current Min:** The current minimum time (in ms) - in the last 5 seconds (or since the last statistics reset).

- **Long Term Avg:** The average time over the whole period since the Virtual Service started handling traffic (or since the last statistics reset).
- **Long Term Max:** The all-time maximum value (in ms) since the Virtual Service started handling traffic (or since the last statistics reset).
- **Long Term Min:** The all-time minimum value (in ms) (or since the last statistics reset).

Values are only present if values have been recorded. For example, no **Current Max** displays if no traffic has passed through the Virtual Service in the last five seconds or if the Virtual Service cannot monitor the specific values.

The **Current Average**, **Current Max**, **Current Min**, **Long Term Avg**, **Long Term Max**, and **Long Term Min** for Virtual Services and Real Servers are also available over SNMP.

Address: The IP address of the Virtual Service.

Protocol: The protocol of the Virtual Service. This will either be **tcp** or **udp**.

Active Conns: The total number of connections that are currently active.

When using ESP, all connections going through the login process are counted as active connections for the Virtual Service. They are not counted as active connections for the Real Server because they are not actual connections to the Real Server. The WUI page displays the number of active connections associated with the Real Servers, while SNMP displays the number of active connections for the Virtual Service. The API returns the same value as displayed in the WUI. Without ESP, these values are identical. When using ESP, the Virtual Service counts can be much higher than the final counts going to the Real Servers, due to the above reason.

Total Conns: The total number of connections made.

Total Bytes: The total number of bytes transmitted.

Real Servers: The total number of Real Servers in this Virtual Service.

Persist Entries: The total number of persistence entries made.

WAF: The status, along with the other WAF statistics below, are displayed if WAF is enabled on the Virtual Service.

Requests: The total number of requests handled by the WAF (shows all requests, whether they were blocked or not). Two requests are recorded for each connection – one incoming and one outgoing request.

Incidents: The total number of events handled by the WAF (that is, requests that were blocked).

Incidents/Hour: The number of events that have happened in the current hour (since xx.00.00).

Incidents/Day: The number of events that have happened since midnight (local time).

Incidents/Dayover: The number of times the event counter has gone over the configured warning threshold today. For example, if the threshold is set to 10 and there has been 20 events, this counter is set to 2. The warning threshold is set on a per-Virtual Service basis by filling out the **Hourly Alert Notification Threshold** field in **WAF Options** in the Virtual Service modify screen. For further information, refer to the **Web Application Firewall (WAF) Options** section.

System Total Conns: This row displays totals for each of the columns.

5.1.4 WAF

Global Real Servers Virtual Services WAF								
WAF Enabled VS Statistics								
Name	Virtual IP Address	Protocol	Status	Total Requests	Total Events	Events this hour	Events Today	Events over Limit Today
1 Example Virtual Service	172.20.0.207:80	tcp	Down	0	0	0	0	0
1	WAF enabled VS Total			0	0	0	0	0

These statistics refresh every 5 to 6 seconds. The following items are displayed on this screen:

Count: The left-most column displays the total number of WAF-enabled Virtual Services.

Name: The name of the WAF-enabled Virtual Service.

Virtual IP Address: The IP address and port of the Virtual Service.

Protocol: The protocol of the Virtual Service (tcp or udp).

Status: The status of the Virtual Service. For information on each of the possible statuses, refer to the **View/Modify (Existing HTTP Service)** section.

Total Requests: The total number of requests handled by the WAF (shows all requests, whether they were blocked or not). Two requests are recorded for each connection – one incoming and one outgoing request.

Total Events: The total number of events handled by the WAF (requests that were blocked).

Events this hour: The number of events that have happened in the current hour (since xx.00.00).

Events Today: The number of events that have happened since midnight (local time).

Events over Limit Today: The number of times the event counter has gone over the configured warning threshold today. For example, if the threshold is set to 10 and there has been 20 events, this counter is set to 2. The warning threshold is set on a per-Virtual Service basis by filling out the **Hourly Alert Notification Threshold** field in **WAF Options** in the Virtual Service modify screen. For further information, refer to the **Web Application Firewall (WAF) Options** section.

5.2 Historical Graphs

The **Historical Graphs** screen provides a graphical representation of the LoadMaster statistics. These configurable graphs provide a visual indication of the traffic that is being processed by the LoadMaster.


In some cases, after upgrading the LoadMaster firmware from version 7.1.35 to a newer firmware version, historical graphs may not display. To fix this, reset the statistic counters (**System Configuration > Extended Log Files > System Log Files > Debug Options > Reset Statistics**).


There are graphs for the network activity on each interface. There is also an option to view graphs for the overall and individual Virtual Services and the overall and individual Real Servers.

The time granularity can be specified by selecting one of the **hour, day, month, quarter** or **year** options.

In the case of the network activity on the interface graphs, you can choose which type of measurement unit you wish to use by selecting one of the **Packet, Bits** or **Bytes** options.

For the Virtual Services and Real Servers graphs you can choose which type of measurement unit you wish to use by selecting one of the **Connections, Bits** or **Bytes** options.


You can configure which Virtual Service statistics are being displayed by clicking the configuration icon:  in the **Virtual Services panel**. This opens the Virtual Services configuration window.




From here, Virtual Services can be added or removed from the statistics display.

You can disable these graphs by disabling the **Enable Historical Graphs** check box in the **WUI Settings** screen.

A maximum of five Virtual Services can be displayed at the same time.

To close the dialog and apply any changes, please ensure to click the  button within the window itself.




You can configure which Real Server statistics are being displayed by clicking the configuration icon,



in the **Real Servers** panel. This opens the Real Servers configuration dialog in a separate window.

From here, Real Servers can be added or removed from the statistics display.

A maximum of five Real Servers can be displayed at the same time.

To close the dialog and apply any changes, please ensure you click the  button within the window itself.

By default, only the statistics for the Virtual Services and Real Servers displayed on the Statistics page are gathered and stored. To view statistics for all Virtual Services and Real Servers, enable the **Collect All Statistics** option in **System Configuration > Miscellaneous Options > WUI Settings**.

This option is disabled by default because collecting statistics for a large number of Virtual Services and Real Servers can cause CPU utilization to become very high.

The graphs in the LoadMaster WUI are auto-scaling and are shown using SI magnitude units. The graph will show the prefix of the scaling factor used so the absolute value can be calculated if needed.

The possible scaling factors and their prefixes are listed in the table below.

Symbol	Prefix	Factor
P	peta	10 ¹⁵
T	tera	10 ¹²
G	giga	10 ⁹
M	mega	10 ⁶
k	kilo	10 ³
m	milli	10 ⁽⁻³⁾
μ	micro	10 ⁽⁻⁶⁾

To calculate the absolute “real” value, take the value shown in the graph and multiply it by the scaling value.

Example

A value of 200 is shown in the connections per second graph with a scaling factor of “m”. As listed in the table above, “m” stands for “milli”. Therefore, to find the absolute value of connections per second for that time – the value of 200 needs to be multiplied by a factor of 10⁽⁻³⁾:

- 10⁽⁻³⁾ = 0.001

- $200 \times 0.001 = 0.2$ connections per second

This calculation shows that there is less than one connection per second and, due to the fact that the connection rate is so low, if the graph shows the absolute number of connections it will just be a straight line at zero and offers no useful information.

5.3 Device Information

UID	Name	Type
▶ 00:00:54:9f:35:1c:c5:30	ovsbr0	Default OpenFlow Switch
▶ 00:00:66:52:10:5f:fb:45	ovsbr1	Default OpenFlow Switch

Information about switches on a controller which has OpenFlow enabled can be viewed by clicking the **device info** button.

5 Statistics

UID	Name	Type	Vendor	Product
▼ 00:00:54:9f:35:1c:c5:30	ovsbr0	Default OpenFlow Switch	Nicira, Inc.	Open vSwitch
Interface Info	ID	Name	State	Mac
	id=0x1	Name:eno1	State:[UP]	Mac:54:9f:35:1c:c5:30
	id=0x4	Name:vnet2	State:[UP]	Mac:fe:54:00:bc:1b:c3
	id=0x7	Name:vnet1	State:[UP]	Mac:fe:54:00:8d:73:9b
	id=0x8	Name:vnet7	State:[UP]	Mac:fe:54:00:b1:4b:3b
	id=0xa	Name:patch-ovsbr0	State:[UP]	Mac:7e:6d:ac:6b:9f:11
	id=0xb	Name:patch-ovsbr3	State:[UP]	Mac:2a:32:8c:e7:4c:5b
	id=0xfffffffffe	Name:ovsbr0	State:[UP]	Mac:54:9f:35:1c:c5:30
Node Info	ID	VID	Port	Mac
	10.154.50.25	0	1	00:0c:29:b1:96:46
	10.154.120.62	0	1	00:50:56:b8:13:45
	10.154.190.197	0	1	00:50:56:b8:4d:7d
	10.154.30.80	0	1	00:0c:29:64:83:1b
	10.154.190.104	0	1	00:50:56:b8:e7:31
	10.154.190.172	0	1	00:0c:29:91:e6:9d
	10.154.190.137	0	1	00:0c:29:d7:aa:5e
	10.154.25.30	0	1	00:50:56:b8:b4:5d
	10.154.190.145	0	1	00:50:56:b8:54:d5
	10.154.120.115	0	1	00:50:56:b8:19:67
	10.154.190.111	0	1	00:50:56:b8:e8:08
	10.154.190.120	0	1	00:50:56:b8:ee:39
	10.154.190.157	0	1	00:50:56:b8:97:f6
	10.154.190.126	0	1	80:3f:5d:08:92:d6
	10.154.0.3	0	1	20:0c:c8:49:f6:4c
	10.154.190.152	0	1	00:0c:29:54:e8:2b
	10.154.190.174	0	1	00:50:56:b8:b7:2e
	10.154.190.115	0	1	00:50:56:b8:7e:6b
	10.154.50.61	0	1	00:50:56:b8:a5:00
	10.154.190.151	0	1	00:50:56:b8:1b:67
	10.154.190.118	0	1	00:50:56:b8:b7:5c
	10.154.190.128	0	1	00:50:56:b8:d4:84
	10.154.75.25	0	1	00:50:56:b8:0c:3f
	10.154.25.102	0	1	00:50:56:b8:70:8c
	10.154.190.190	0	1	00:10:f3:38:4a:e4
	10.89.0.44	0	1	00:0c:29:56:ad:2f
	10.154.190.150	0	1	00:0c:29:2b:d7:ac
	10.154.50.167	0	1	00:0c:29:24:2e:49
	10.154.30.81	0	1	00:0c:29:a1:6a:3b

Further information can be seen by clicking the plus (+) button to expand each of the devices.

6 Real Servers

Real Server	Status	Operation
<input type="checkbox"/> 10.154.11.183	✓ Enabled	<button>Enable</button> <button>Disable</button>
<input type="checkbox"/> 10.154.11.184	✓ Enabled	<button>Enable</button> <button>Disable</button>
<button>Enable</button> <button>Disable</button>		

This screen shows the current status of the Real Servers and gives the option to **Disable** or **Enable** each Real Server. Each Real Server has corresponding buttons to disable (take an online server offline) and enable the Real Server. You can also enable or disable multiple Real Servers at the same time by selecting the relevant Real Servers, and clicking the relevant button at the bottom. The status can be **Enabled** (Green), **Disabled** (Red) or **Partial** (Yellow) – meaning the Real Server is enabled in one Virtual Service.

Caution

Disabling a Real Server will disable it for all Virtual Services configured to use it. If it is the only Real Server available (that is, the last one) the Virtual Service is effectively down and will not pass any traffic.

Real Servers that have DNS names assigned to them appear above/below Real Servers without DNS names. You can sort the list of Real Servers by clicking the **Real Server** or **Status** column headings.

7 Rules & Checking

7.1 Content Rules

7.1.1 Content Matching Rules

Content Matching Rules						Create New ...
Name	Type	Options	Header	Pattern	Operation	
vmworkspace	RegEx	Must Fail Ignore Case		*/admin*		Modify Delete

This screen shows rules that have been configured and gives the option to **Modify** or **Delete**.

To define a new rule, click the **Create New** button. You must give the rule a name.

The **Rule Name** must be alphanumeric, unique, and cannot contain spaces. Rules are case sensitive, thus two different rules can exist in the form of **Rule1** and **rule1**. It is not possible to name a content rule **default**.

The options that are available depend on the **Rule Type** that you select. The available rules are as follows:


Rule Types:

- **Content Matching:** matches the content of the header or body
- **Add Header:** adds a header according to the rule
- **Delete Header:** deletes the header according to the rule
- **Replace Header:** replaces the header according to the rule
- **Modify URL:** changes the URL according to the rule
- **Replace String in Response Body:** replaces text in the body according to the rule

For further information on configuring rules, please refer to the document.

7.1.2 Content Matching

When the **Rule Type** selected is **Content Matching** the following describes the options available.



The 'Create Rule' dialog box contains the following fields and options:

- Rule Name:
- Rule Type:
- Match Type:
- Header Field:
- Match String:
- Negation: ☐
- Ignore Case: ☒
- Include Host in URL: ☐
- Include Query in URL: ☐
- Fail On Match: ☐
- Perform If Flag Set:
- Perform If Flag is NOT Set:
- Set Flag If Matched:

Buttons:

Rule Name

The name of the rule.

Match Type:

- **Regular Expression:** compares the header to the rule
- **Prefix:** compares the prefix of the header according to the rule
- **Postfix:** compares the postfix of the header according to the rule

Header Field

The header field name must be matched. If no header field name is set, the default is to match the string within the URL.

Rules can be matched based on the Source IP of the client by entering **src-ip** within the **Header Field** text box. The header field is populated by the source IP of the client.

Similarly, rules can also be matched based on the HTTP Method used, for example GET, POST or HEAD. The methods that are to be matched should be written in uppercase.

The body of a request can also be matched by typing **body** in the **Header Field** text box.

Match String

Input the pattern that is to be matched. Both Regular Expressions and PCRE are supported. The maximum number of characters allowed is 250.

For further information on Regular Expressions and PCRE, please refer to the **Content Rules, Feature Description** document on the [Kemp Documentation Page](#).

Negation

Invert the sense of the match.

Ignore Case

Ignore case when comparing strings.

Include Host in URL

Prepend the hostname to request URL before performing the match.

Include Query in URL

Append the query string to the URL before performing a match.

Fail On Match

If this rule is matched, then always fail to connect.

Perform If Flag Set

Only try to execute this rule if the specified flag is set.

Perform If Flag is NOT Set

Only try to execute this rule if the specified flag is not set.


Set Flag If Matched

If the rule is successfully matched, set the specified flag.

Using the **Perform If Flag Set** and **Set Flag If Matched** options, it is possible to make rules dependent on each other, that is, only execute a particular rule if another rule has been successfully matched. For more detailed instructions on ‘chaining’ rules, please refer to the **Content Rules, Feature Description** document on the [Kemp Documentation Page](#).

7.1.3 Add Header

When the **Rule Type** selected is **Add Header** the following describes the options available.



The 'Create Rule' dialog box contains the following fields and options:

- Rule Name:** ExampleHeaderRule
- Rule Type:** Add Header (dropdown menu)
- Header Field to be Added:** (empty text box)
- Value of Header Field to be Added:** (empty text box)
- Perform If Flag Set:** Flag 1 (dropdown menu)
- Perform If Flag is NOT Set:** [Unset] (dropdown menu)
- Buttons:** Cancel, Create Rule

Rule Name

This is a text box to enter the name of the rule.

Header Field to be Added

This is a text box to enter the name of the header field to be added.

Value of Header Field to be Added

Enter the value of the header field to be added. You can enter a maximum of 255 characters in this field.

Perform If Flag Set

Only execute this rule if the specified flag is set.


The flag is set by a different rule. For further information on flags please refer to the **Content Matching** section.

Perform If Flag is NOT Set

Only try to execute this rule if the specified flag is not set.

7.1.4 Delete Header

When the **Rule Type** selected is **Delete Header** the following describes the options available.



The 'Create Rule' dialog box contains the following fields and options:

- Rule Name:** ExampleDeleteHeader
- Rule Type:** Delete Header (dropdown menu)
- Header Field to be Deleted:** (empty text box)
- Perform If Flag Set:** Flag 1 (dropdown menu)
- Perform If Flag is NOT Set:** [Unset] (dropdown menu)
- Buttons:** Cancel, Create Rule

Rule Name

This is a textbox to enter the name of the rule.

Header Field to be Deleted

This is for a text box to enter the name of the header field to be deleted.

Perform If Flag Set

Only execute this rule if the specified flag is set.


The flag will have been set by a different rule. For a more detailed explanation of flags please refer to the **Content Matching** section.

Perform If Flag is NOT Set

Only try to execute this rule if the specified flag is not set.

7.1.5 Replace Header

When the **Rule Type** selected is **Replace Header** the following describes the options available.



The screenshot shows a 'Create Rule' dialog box with the following fields and options:

- Rule Name:** ExampleReplaceHeader
- Rule Type:** Replace Header (dropdown menu)
- Header Field:** Example
- Match String:** Example
- Value of Header Field to be replaced:** (empty text box)
- Perform If Flag Set:** Flag 1 (dropdown menu)
- Perform If Flag is NOT Set:** [Unset] (dropdown menu)

At the bottom right, there are two buttons: 'Cancel' and 'Create Rule'.

Rule Name

This is for a textbox to enter the name of the rule.

Header Field

This is for a textbox to enter the header name field where the substitution should take place.

Match String

The pattern that is to be matched.

Value of Header Field to be replaced

This is for a textbox to enter the value of the header field to be replaced.

Perform If Flag Set

Only execute this rule if the specified flag is set.


The flag is set by a different rule. For a more detailed explanation of flags please refer to the **Content Matching** section.

Perform If Flag is NOT Set

Only try to execute this rule if the specified flag is not set.

7.1.6 Modify URL

When the **Rule Type** selected is **Modify URL** the following describes the options available.



The screenshot shows a 'Create Rule' dialog box with the following fields and options:

- Rule Name:** ExampleModifyURLHeader
- Rule Type:** Modify URL (dropdown menu)
- Match String:** Example
- Modified URL:** (empty text box)
- Perform If Flag Set:** Flag 1 (dropdown menu)
- Perform If Flag is NOT Set:** [Unset] (dropdown menu)

At the bottom right, there are two buttons: 'Cancel' and 'Create Rule'.

Rule Name

This is for a textbox to enter the name of the rule.

Match String

This is a textbox to enter the pattern that is to be matched.

Modified URL

This is a textbox to enter the URL that is to be modified.

Perform If Flag Set

Only execute this rule if the specified flag is set.


The flag is set by a different rule. For a more detailed explanation of flags please refer to the **Content Matching** section.

Perform If Flag is NOT Set

Only try to execute this rule if the specified flag is not set.

7.1.7 Replace String in Response Body

When the **Rule Type** selected is **Replace String in Response Body**, the following options are available.



The 'Create Rule' dialog box contains the following fields and controls:

- Rule Name:** ExampleReplaceStringInRes
- Rule Type:** Replace String in Response Body (dropdown menu)
- Match String:** http://yourdomain.com
- Replacement text:** https://yourdomain.com
- Ignore Case:** ☒
- Perform If Flag Set:** [Unset] (dropdown menu)
- Perform If Flag is NOT Set:** [Unset] (dropdown menu)
- Buttons:** Cancel, Create Rule

Rule Name

The name of the rule. The rule name must be unique.

Match String

The string to match.

Replacement text

The replacement string.

Ignore Case

Enable this check box to ignore the case of the strings when comparing.

Perform If Flag Set

Only execute this rule if the specified flag is set.

The flag will have been set by a different rule.

Perform If Flag is NOT Set

Only try to execute this rule if the specified flag is not set.

7.1.8 Header Modification

For separate, detailed documentation on Header Modification, please refer to the **Header Modification Guide, Technical Note** on the [Kemp Documentation Page](#).


7.2 Check Parameters

To access the **Check Parameters** screen, go to **Rules & Checking > Check Parameters** in the main menu of the LoadMaster WUI. The **Check Parameters** screen has two sections - **Service Check Parameters** and **Adaptive Parameters**, depending on the **Scheduling Method** selected in the Virtual Services.

Refer to the relevant section below to find out more information.

7.2.1 Service (Health) Check Parameters

The LoadMaster utilizes Layer 3, Layer 4 and Layer 7 health checks to monitor the availability of the Real Servers and the Virtual Services.



Service Check Parameters	
Check Interval(sec)	9 ▼
Connect Timeout(sec)	4 ▼
Retry Count	2 ▼
Reset values to Default	

Check Interval(sec)

With this field you can specify the number of seconds that will pass between consecutive checks.

Recommended and default value: 9 seconds

Valid values range from the *<mininterval>* (9) to the *<maxinterval>* (901).

The *<mininterval>* is **Retry Count * Connect Timeout (sec) + 1**, that is, a maximum value of 9 by default.

The *<maxinterval>* is 901 [because that is what 60 (maximum **Connect Timeout (sec)**) * 15 (maximum **Retry Count**) + 1 is].

In the WUI, if the value of **Check Interval** is over 120 (because it is forced to this value by setting the **Connect Timeout (sec)** and **Retry Count**), it cannot be changed by modifying the **Check Interval (sec)** drop-down list. To change it, configure the other two options. Otherwise, the maximum value that the interval can be set to is 120.

Connect Timeout (sec)

The HTTP request has two steps: contact the server, and then retrieve the file. A timeout can be specified for each step; how long to wait for a connection, how long to wait for a response.

Default value:4 seconds

Valid values range from **4** to **60**.


Retry Count

This specifies the number of retry attempts the check will make before it determines that the server is not functioning.

Default value: 2

Valid values range from **2** to **15**.

7.2.2 Adaptive Parameters



Adaptive Parameters	
Adaptive Interval (sec)	10 ▼
Adaptive URL	/load Set URL
Port	80 Set Port
Min. Control Variable Value (%)	5 ▼
Reset values to Default	

Adaptive Interval (sec)

This is the interval, in seconds, at which the LoadMaster checks the load on the servers. A low value means the LoadMaster is very sensitive to load, but this comes at a cost of extra load on the LoadMaster itself. **7** seconds is a good starting value. This value must not be less than the HTTP checking interval.

Adaptive URL

The Adaptive method retrieves load information from the servers using HTTP inquiry. This URL specifies the resource where the load information of the servers is stored. This resource can be either a file or program (for example Adaptive Agent) that delivers this information. The standard location is **/load**. It is the servers' job to provide the current load data in this file in ASCII format. In doing so, the following must be considered:

An ASCII file containing a value in the range of 0 to 100 in the first line where: 0=idle and 100=overloaded. As the number increases, that is, the server becomes more heavily loaded, the LoadMaster will pass less traffic to that server. Hence, it 'adapts' to the server loading.

If the server becomes 101% or 102% loaded, a message is added to the logs.

The file is set to **"/load"** by default.

The file must be accessible using HTTP.

The URL must be the same for all servers that are to be supported by the adaptive method.

This feature is not only of interest for HTTP-based Virtual Services, but for all Services. HTTP is merely used as the transport method for extracting the application-specific load information from the Real Server.

Port

This value specifies the port number of the HTTP daemon on the servers. The default value is **80**.

Min. Control Variable Value (%)

This value specifies a threshold below which the balancer will switch to static weight-based scheduling, that is, normal Weighted Round Robin. The value is a percentage of the maximum load (0-50). The default is **5**.

8 Certificates & Security

The sections below describe the various screens in the **Certificates & Security** section of the LoadMaster WUI.

8.1 SSL Certificates



Shown above is the **Manage Certificates** screen. The options on this screen are described below.

Private Key Identifier - to generate a new private key which will be stored on the LoadMaster, enter a name for the private key and click **Generate CSR**.

Add Intermediate – adds an intermediate certificate.

Private Key – is the private key identifier given to the certificate at the time it was created.

Common Name(s) – is the FQDN (Fully Qualified Domain Name) for the site.

Assignment – the **Available VSs** box lists all of the SSL Virtual Services which are configured on the LoadMaster. The **Assigned VSs** box lists the Virtual Services which the certificate has been assigned to. The Virtual Services can be assigned/unassigned by selecting them and clicking the right/left arrow buttons and clicking **Save Changes**.

Operations –

- **Import Certificate** – imports the signed certificate.

When using FIPS in HA mode, ensure to only import certificates when both nodes are up.


- **Delete Key** - deletes the relevant private key and/or certificate
- **Show Reencrypt Certs** - display the re-encrypt certificates

Administrative Certificates

This section contains two drop-down lists:

- **Administrative Certificate** - select the certificate to be used for the administrative interface. Click Use Certificate to apply the changes.
- **Local Machine Certificate** - select the certificate to be used on the local machine interface. Click Use Certificate to apply the changes.

8.2 Intermediate Certificates




Name	Operation
VeriSignCert.pem	Delete

Add a new Intermediate Certificate

Intermediate Certificate Choose File No file chosen

Certificate Name Add Certificate

This screen shows a list of the installed intermediate certificates and the name assigned to them.



Add a new Intermediate Certificate

Intermediate Certificate Choose File No file chosen

Certificate Name ExampleIntermediateCertific Add Certificate

If you already have a certificate, or you have received one from a CSR, you can install the certificate by clicking the **Choose File** button. Navigate to and select the certificate and then enter the desired **Certificate Name**. The name can only contain alpha characters with a maximum of 32 characters.

Uploading several consecutive intermediate certificates within a single piece of text, as practiced by some certificate vendors such as GoDaddy, is allowed. The uploaded file is split into the individual certificates.

8.3 Generate CSR (Certificate Signing Request)

To create a CSR please complete the following steps:

1. In the main menu, go to **Certificates > SSL Certificates**.

The Manage Certificates screen will appear.




The interface shows a 'Certificate Configuration' window. At the top, there is a 'Private Key Identifier' field with the value 'Example' and a 'Generate CSR' button. Below this is a table with columns: 'Private Key', 'Common Name(s)', 'Virtual Services', 'Assignment', and 'Operation'. The table contains one row with the following data: 'ExampleCert Example.com' (with a subtext '[Expires: Sep 1 12:20:38 2020 GMT]'), '172.21.11.11:443', 'None Assigned', and an empty 'Operation' column. To the right of the table is a 'Save Changes' button. On the far right, there is a vertical stack of buttons: 'Add Intermediate', 'Import Certificate', 'Delete Key', and 'Show Reencrypt Certs'.

2. Enter a unique name in the **Private Key Identifier** field for the RSA 2048 key you intend to store on the HSM.

The Private Key Identifier is the password. Make a note of it because you will need it.

3. Click **Generate CSR**.



The form is titled 'All Fields are optional except "Common Name"'. It contains several input fields: '2 Letter Country Code (ex. US)', 'State/Province (Full Name - New York, not NY)', 'City', 'Company', 'Organization (e.g., Marketing,Finance,Sales)', 'Common Name (The FQDN of your web server)', 'Email Address', and 'SAN/UCC Names'. There is also a checkbox for 'Generate Elliptic Curve Request'. At the bottom, there are three buttons: 'Cancel', 'Reset', and 'Create CSR'.

4. Fill in the details in the resulting screen. The **Common Name** field is mandatory, all other fields are optional.

5. Click **Create CSR**.

The resulting key size will be 2048 bits.

The following is your 2048 bit *unsigned* certificate request. Copy the following, in its entirety, and send it to your trusted certificate authority

```
-----BEGIN CERTIFICATE REQUEST-----
MIIC9zCCAd8CAQAwgbEXCZA3BgNVBAYTA1VTMREwDwYDVQQIEwhOZXcgW9yazER
MA8GA1UEBxMlTmV3IFlvcmsxGjAYBgNVBAoTEUtFTVAgVGVjaG5vbG9naWVzMREw
GwYDVQQLEXRlbm93bGVkZ2UgTWFuYXd1bWVudDEUMBIGA1UEAxMLRXhhbXBsZS5j
b20xKzApBgkqhkiG9w0BCQEWHGpibG9nZ3NAa2VtcHRlY2hub2xvZ211cy5jb20w
ggEiMA0GCSqGSIb3DQEBQUAA4IBDwAwggEKaoIBAQC+fCQ6Dx6VAHofGbqH0lEw
7j+DIpYXYt62I4NakrMzkFhkHEI6ond29p4s5Ntw0b2burBjUhw7HGV8kAkdmEx
VTZCSTvtF0k2m0w6hk6+koF1KBkFcJomYcz5ZU0LiCY2oGK8C34RBfes5DAYV7uv
Ks5SvWPHyC/10LZp/+g1sRtf7Nj0KvzIkIGdzSuFumCj1z+BvdSxf+gV2tqw8lNh
eMsuXbrhCyVhaohmz+Df03aubLOpFulyXpHopfOTCbC8mGn3y/xA0gKbdRAMjdZ
VMe6fzt6D1jKYr5W/PZa8UBr9RipVhR6TabluB9xsFVP5MrM5SvbHYDxAXWv9rw7
AgMBAAGgADANBgkqhkiG9w0BAQsFAAOCAQEAZpDqjy+nt6rjuxI10JXUCJ1qJwY
sikrVVSr4dU31gWI8CJIU+YASECvtzSpU0yZKumdHeDSJH3CmYI81vn79xzbt6b
3fDn007oNI+Tj07KWLfgSZTIIo6/yvUOgcIvLaiHHbrXGJ1TLRLYGZMwMtoFE8+3
S1a5ZBZxJZFp8Jho5iWjE5z0eRXa6Ah3wya/O3nM0i6W71/m1zfesQFkTy19+I5g
T7bm9z+pUrIhmQQkcoeJ4Y2FaZz8fl8pRuLLldivV8tCsa/qdX8mCiAnikQMDrN
a4e348uEH9j28WHS140EPNfM3KoAig5iBI6IbKAF3WmUkrBekQNg4MPeA==
-----END CERTIFICATE REQUEST-----
```

[<-Back](#)

6. The CSR is displayed.

7. Copy the CSR into a file and send it to your Certificate Authority for signing. The Certificate Authority will provide you with the certificate which will be put on the server.

Unlike a non-FIPS certificate operation, the private key is never displayed or available during this process. It is stored inside the HSM, and is completely inaccessible to the user.

8.4 Backup/Restore Certs

Certificate Backup

Backup Intermediate Certificates

Passphrase

Retype Passphrase

Create Backup File

Restore Intermediate Certificates

Intermediate Certificate Backup File No file selected.

Passphrase

Restore Intermediate Certificates

Backup Intermediate Certificates: Create a backup of all intermediate certificates. The backup will be encrypted with the given passphrase.

Caution

When backing up certificates, a mandatory passphrase (password) needs to be entered twice. The parameters of the passphrase are that it must be alpha-numeric and it is case sensitive with a maximum of 64 characters. This passphrase is a mandatory requirement to restore a certificate. A certificate cannot be restored without the passphrase. If it is forgotten, there is no way to restore the certificate.

Intermediate Certificate Backup File: browse to and select the intermediate certificate backup file

Passphrase: enter the passphrase associated with the certificate backup file

8.5 Cipher Sets

Cipher Set Management

Cipher Set

Default

Available Ciphers

Filter:

Name	Strength
ECDHE-RSA-AES256-GCM-SHA384	High
ECDHE-ECDSA-AES256-GCM-SHA384	High
ECDHE-RSA-AES256-SHA384	High
ECDHE-ECDSA-AES256-SHA384	High
ECDHE-RSA-AES256-SHA	High
ECDHE-ECDSA-AES256-SHA	High
DH-DSS-AES256-GCM-SHA384	High
DHE-DSS-AES256-GCM-SHA384	High
DH-RSA-AES256-GCM-SHA384	High
DHE-RSA-AES256-GCM-SHA384	High
DHE-RSA-AES256-SHA256	High
DHE-DSS-AES256-SHA256	High
DH-RSA-AES256-SHA256	High
DH-DSS-AES256-SHA256	High

Assigned Ciphers

Filter:

Name	Strength
ECDHE-RSA-AES256-GCM-SHA384	High
ECDHE-ECDSA-AES256-GCM-SHA384	High
ECDHE-RSA-AES256-SHA384	High
ECDHE-ECDSA-AES256-SHA384	High
ECDHE-RSA-AES256-SHA	High
ECDHE-ECDSA-AES256-SHA	High
DH-DSS-AES256-GCM-SHA384	High
DHE-DSS-AES256-GCM-SHA384	High
DH-RSA-AES256-GCM-SHA384	High
DHE-RSA-AES256-GCM-SHA384	High
DHE-RSA-AES256-SHA256	High
DHE-DSS-AES256-SHA256	High
DH-RSA-AES256-SHA256	High
DH-DSS-AES256-SHA256	High

Save as:

Default

Save

Cipher Set

Select the cipher set to view/modify.

The system-defined cipher sets are as follows:

- **Default:** The current default set of ciphers in the LoadMaster.
- **Default_NoRc4:** The Default_NoRc4 cipher set contains the same ciphers as the default cipher set, except without the RC4 ciphers (which are considered to be insecure).

- **BestPractices:** This is the recommended cipher set to use. This cipher set is for services that do not need backward compatibility - the ciphers provide a higher level of security. The configuration is compatible with Firefox 27, Chrome 22, IE 11, Opera 14 and Safari 7.
- **Intermediate_compatibility:** For services that do not need compatibility with legacy clients (mostly Windows XP), but still need to support a wide range of clients, this configuration is recommended. It is compatible with Firefox 1, Chrome 1, IE 7, Opera 5 and Safari 1.
- **Backward_compatibility:** This is the old cipher suite that works with clients back to Windows XP/IE6. This should be used as a last resort only.
- **WUI:** This is the cipher set recommended to be used as the WUI cipher set. The WUI cipher set can be selected in the **Admin WUI Access** screen. For further information, refer to the **Admin WUI Access** section.
- **FIPS:** Ciphers which conform to FIPS (Federal Information Processing Standards).
- **Legacy:** This is the set of ciphers that were available on the old LoadMaster firmware (v7.0-10) before OpenSSL was updated.
- **Null_Ciphers:** Direct Access uses IP-HTTPS which applies its own layer of encryption.

Refer to **Appendix A - Cipher List** for a full list of the ciphers supported by the LoadMaster, and a breakdown of what ciphers are in each of the system-defined cipher sets.

Kemp can change the contents of these cipher sets as required based on the best available information.

Two lists are displayed – **Available Ciphers** and **Assigned Ciphers**. These lists can be filtered by typing some text into the **Filter** text boxes provided. The **Filter** text boxes will only allow you to enter valid text which is contained in the cipher names, for example **ECDHE**. If invalid text is entered, the text box will turn red and the invalid text is deleted.

Ciphers can be dragged and dropped to/from the **Available** and **Assigned** lists as needed. Ciphers which are already assigned will appear greyed out in the **Available Ciphers** list.


Changes cannot be made to a preconfigured cipher set. However, you can start with a preconfigured cipher set – make any changes as needed and then save the cipher set with a new custom name. Enter the new name in the **Save as** text box and click the **Save** button. Custom cipher sets can be used across different Virtual Services and can be assigned as the WUI cipher set.

It is not possible to delete preconfigured cipher sets. However, custom cipher sets can be deleted by selecting the relevant custom cipher set and clicking the **Delete Cipher set** button.

8.6 Remote Access

The sections below describe the different areas within the **Remote Access** screen in the LoadMaster WUI.

8.6.1 Administrator Access



Administrator Access

Allow Remote SSH Access ☒ Using: All Networks Port: 22 Set Port

SSH Pre-Auth Banner Set Pre-Auth Message

Allow Web Administrative Access ☒ Using: eth0: 10.35.48.11 Port: 443

Admin Default Gateway Set Administrative Access

Allow Multi Interface Access ☐

Enable API Interface ☒ Port: via 443 Set Port

Self-Signed Certificate Handling RSA self-signed certs

Outbound Connection Cipher Set None - Outbound Default

Admin Login Method Password Only Access (default) Only Password mode is available if no Pre-Auth Banner is specified

Enable Software FIPS 140-2 Level 1 Mode Enable Software FIPS mode

Enable Kemp Analytics ☒

Allow Remote SSH Access

You can limit the network from which clients can connect to the SSH administrative interface on LoadMaster.

Using

Specify which addresses that remote administrative SSH access to the LoadMaster is allowed.

Only the 'bal' user has rights to access the LoadMaster using SSH.

Port

Specify the port used to access the LoadMaster using the SSH protocol.

SSH Pre-Auth Banner

Set the SSH pre-authentication banner, which is displayed before the login prompt when logging in using SSH. This field accepts up to 5,000 characters.

Allow Web Administrative Access

Selecting this check box allows administrative web access to the LoadMaster. Disabling this option will stop access upon the next reboot. Click **Set Administrative Access** to apply any changes to this field.

Disabling web access is not recommended.

Using

Specify the addresses that administrative web access is to be permitted. Click **Set Administrative Access** to apply any changes to this field. You need to reconnect to the WUI using the new address after the change is applied.

Port

Specify the port used to access the administrative web interface. Click **Set Administrative Access** to apply any changes to this field. You need to reconnect to the WUI using the new port after the change is applied.

Admin Default Gateway

When administering the LoadMaster from a non-default interface, this option allows the User to specify a different default gateway for administrative traffic only. Click **Set Administrative Access** to apply any changes to this field.

Allow Multi Interface Access

Enabling this option allows the WUI to be accessed from multiple interfaces. When this option is enabled, a new option appears in each of the interface screens (**System Configuration > eth<n>**) called **Allow Administrative WUI Access**. When both of these options are enabled, the WUI can be accessed from the IP address of the relevant interface(s) and any **Additional addresses** configured for that interface. Click **Set Administrative Access** to apply any changes to this field.

The certificate used by default to secure WUI connections specifies the initial WUI IP address, and so will not work for WUI connections on other interfaces. If you enable the WUI on multiple interfaces, you will need to install a wildcard certificate for the WUI. For more information on certificates, refer to the **SSL Accelerated Services, Feature Description** on the [Kemp Documentation Page](#).

Enabling the WUI on multiple interfaces can have a performance impact on the system. There is a maximum of 64 network interfaces that can be tracked. There are a maximum of 1024 total addresses where the system will listen on.

real
vs
rules
backup
certs
cert3
certbackup
users
geo

Enable API Interface


Enables/disables the RESTful Application Program Interface (API). You can also specify the port used to access the API interface. If the port is unset, you can access the API over the web interface port.

Self-Signed Certificate Handling

Select the type of self-signed certificates that the system will use. The options are described below:

- **RSA self-signed certs:** By default, these are RSA certificates that are signed with the Kemp RSA root certificate.
- **EC certs with a RSA signature:** The LoadMaster can generate an EC certificate also signed by the original RSA Kemp root certificate.
- **EC certs with an EC signature:** The LoadMaster can generate an EC certificate signed by the Kemp EC root certificate. In this mode, any CSRs generated will also be EC.

You should not switch from **RSA self-signed certs** to **EC certs with an EC signature** directly. If you do this, connections will fail because there is no EC Kemp Certificate Authority (CA) certificate. To work around this, you must first switch from **RSA self-signed certs** to **EC certs with a RSA signature**.



Then, download the new EC Kemp CA certificate by clicking **Download ECC Root Cert** in the bottom-right of the WUI under the main menu after refreshing the page. After you have downloaded the certificate, you can switch to **EC certs with an EC signature** with no loss of connection.

Outbound Connection Cipher Set

Select the cipher set to use on outbound connections (OCSP, email, LDAP, and so on). This is global for all outbound connections. For information on each of the cipher sets available, refer to the **Cipher Sets** section.

Re-encrypt connections are not affected by the outbound cipher set.

Admin Login Method

This option will only appear if Session Management is enabled. For further information on Session Management, refer to the **Admin WUI Access** section or the **User Management, Feature Description** on the [Kemp Documentation Page](#).

Specify the login option for access to the LoadMaster WUI. The following options are available:

The **Pre-Auth Click Through Banner** in the **Admin WUI Access** screen must be set for all **Admin Login Method** options to be made available.

- **Password Only Access (default):** This option provides access using the username and password only – there is no access using client certificates.
- **Password or Client certificate:** The user can log in using either the username/password or using a valid client certificate. If a valid client certificate is in place, the username and password is not required.
The client will be asked for a certificate. If a client certificate is supplied, the LoadMaster will check for a match. The LoadMaster checks if the certificate is a match with one of the local certificates, or checks if the Subject Alternative Name (SAN) or Common Name (CN) of the certificate is a match. The SAN is used in preference to the CN when performing a match. If there is a match, the user is allowed access to the LoadMaster. This works both using the API and user interface.
An invalid certificate will not allow access.
If no client certificate is supplied, the LoadMaster will expect that a username and password is supplied (for the API) or will ask the user to enter a password using the standard WUI login page.
- **Client certificate required:** Access is only allowed with the use of a client certificate. It is not possible to log in using the username and password. SSH access is not affected by this (only the **bal** user can log in using SSH).

- **Client certificate required (Verify via OCSP):** This is the same as the **Client certificate required** option, but the client certificate is verified using an OCSP service. The OCSP Server Settings must be configured for this to work. For further information on the OCSP Server Settings, refer to the **Cipher Sets** section.

Certificate-based authentication will be deprecated at some point in the future.

Some points to note regarding the client certificate methods are below:

- The **bal** user does not have a client certificate. Therefore, it is not possible to log into the LoadMaster as **bal** using the **Client certificate required** methods. However, a non-**bal** user can be created and granted **All Permissions**. This will allow the same functionality as the **bal** user.
- There is no log out option for users that are logged in to the WUI using client certificates, as it is not possible to log out (if the user did log out the next access would automatically log them back in again). The session is terminated when the page is closed, or when the browser is restarted.

For further information on client certificate WUI authentication, including step-by-step instructions on how to configure it, please refer to the **User Management, Feature Description** on the [Kemp Documentation Page](#).

Enable Kemp Analytics

Enables statistical and usage data to be sent to Kemp for analysis. This data is strictly about product usage, enabled capabilities, and statistics. No sensitive user data, or traffic of any kind is either collected or communicated. For more information, visit <https://kemp.ax/KempAnalytics>.

8.6.2 GEO Settings

GEO Settings	
Remote GEO LoadMaster Access	<input type="text"/> Set GEO LoadMaster access
GEO LoadMaster Partners	<input type="text" value="10.154.11.10 172.20.0.184"/> Set GEO LoadMaster Partners
GEO LoadMaster Port	<input type="text" value="22"/> Set GEO LoadMaster Port
GEO Update Interface	<input type="text" value="eth0: 10.154.11.60"/> ▼

Remote GEO LoadMaster Access

Set the addresses of the GEO LoadMasters that can retrieve service status information from this LoadMaster. The addresses are space separated. When in HA mode, only the shared address needs to be entered.

GEO LoadMaster Partners

GEO functionality comes as part of the GSLB Feature Pack and is enabled based on the license that has been applied to the LoadMaster. If you would like to get the GSLB Feature pack, contact Kemp to upgrade your license.

Set the addresses of the partner GEO LoadMasters. The addresses are space separated. These GEO LoadMasters will keep their DNS configurations in sync.

Before partnering GEO LoadMasters, a backup should be taken of the relevant GEO LoadMaster which has the correct/preferred configuration. This backup should then be restored to the other LoadMasters that will be partnered with the original LoadMaster. For more information and step-by-step instructions, refer to the **GEO, Feature Description** on the [Kemp Documentation Page](#).

Up to 64 GEO HA partner addresses can be added.

GEO LoadMaster Port



The port over which GEO LoadMasters will use to communicate with this LoadMaster unit.

GEO update interface

Specify the GEO interface in which the SSH partner tunnel is created. This is the interface that the GEO partners will communicate through.

8.6.3 GEO Partners Status

This section is only visible when GEO partners have been set.

GEO Partners Status	
10.154.11.10	
172.20.0.184	

A GEO partner status of **Green** indicates the two partners can see each other.


A GEO partner status of **Red** indicates the LoadMasters cannot communicate. The reasons for this include (among other possibilities); one of the partners is powered down, there may be a power outage or a cable may be disconnected.

If there is a failure to update the GEO partner, the logs display an error message saying the GEO update to the partner failed. The message displays the IP address of the partner.

8.6.4 WUI Authentication and Authorization

WUI Authorization Options

Click the **WUI Authorization Options** button on the **Remote Access** screen to display the **WUI Authentication and Authorization** screen. This option is only available when Session Management is enabled.



WUI AAA Service	Authentication	Authorization	Options
LDAP	<input checked="" type="checkbox"/>		LDAP Endpoint: <input type="text" value="LDAP_TEST.COM"/> Manage LDAP Configuration Remote User Groups: <input type="text" value="ldaptestgroup;nestedgroup"/> Select groups <input type="checkbox"/> Nested groups Domain: <input type="text" value="aktest.com"/> Set Domain
Local Users	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Use ONLY if other AAA services fail <input checked="" type="checkbox"/>
Test AAA for User			
Username: <input type="text"/> Password: <input type="password"/> Test User			

The **WUI Authentication and Authorization** screen enables the administration of the available authentication (login) and authorization (allowed permissions) options.

Authentication

Users must be authenticated before logging on to the LoadMaster. The LoadMaster allows authentication of users to be performed using the LDAP authentication method as well as Local User authentication.

When all authentication methods are selected, the LoadMaster attempts to authenticate users using the authentication methods in the following order:

1. LDAP
2. Local Users

If the LDAP server is also not available, then Local User authentication methods are used.

If the LDAP authentication method is not selected, then the Local User authentication method is selected by default.

Authorization

The preceding example is of a RADIUS user configuration on a RADIUS server deployed on a Linux system. The LoadMaster determines the user's permissions from the "Reply-Message" (the permissions are similar to the ones for a local WUI user on the LoadMaster).

LoadMaster allows the users to be authorized using Local User authorization. The user's authorization decides what level of permissions the user has and what functions on the LoadMaster they are allowed to perform.

Authorization using LDAP is not supported.

LDAP Endpoint

Select the relevant **LDAP Endpoint** to use. Click the **Manage LDAP Configuration** button to go to the **LDAP Configuration** screen. For further information on LDAP endpoints, refer to the **LDAP Configuration** section.

If client users are being authenticated with client certificates, the Common Name (CN) is normalized to lowercase. Therefore, the associated local user entries (with no password), which may be required for permissions, should be in lowercase also.

Remote User Groups

Any remote user groups that are selected are displayed here. To select, clear, or order the groups, click **Select groups**.

It is important to select and apply the group, or groups. If there are no groups selected, no group checking is performed and remote users can log in without a group check.

Select Remote User Groups		
Groups	Permissions	Order
<input checked="" type="checkbox"/> ExampleGroup2	Certificate Creation, Intermediate Certificates, Certificate Backup	▼
<input checked="" type="checkbox"/> ExampleRemoteUserGroup	Real Servers, Virtual Services, Certificate Creation, Intermediate Certificates, Certificate Backup	▲
Apply Selected Groups		

The groups displayed on this screen are taken from the remote user groups set up in **System Configuration > System Administration > User Management**. For more information, refer to the **User Management** section.

When a user logs in, a check of the user groups on the Active Directory is performed if all the following conditions are met:

- If LDAP WUI Authentication is enabled
- A list of groups is defined
- The user logging in is not locally defined or the **Local Users** option is disabled

You can change the order of the groups on this screen. The first group is checked first. On the first group match, access is enabled and no further groups are checked. If no groups are matched, user access fails and an appropriate log is reported in the syslog. If the user logs in using the group check, the matched group permissions are granted.

Nested Groups

You can enable or disable user nested groups on the WUI Authentication and Authorization screen by using the **Nested groups** check box.

Domain

Specify the domain to use if no domain is provided in the username when group WUI authentication is in use. It is always used as the domain for group search if the Windows login is used in the format *prefix\username*.

The **Domain** field only appears if a group, or groups, are assigned.

Local Users Configuration

Use **ONLY** if other AAA services fail

When selected, the Local Users authentication and authorization methods are used only if the LDAP authentication and authorization services fail to respond/time out.

Test AAA for User

To test a user's credentials, enter their username and password in the **Username** and **Password** fields and click the **Test User** button.

A message appears to inform you whether the user is validated or not. This is a useful utility to check a user's credentials without having to log in or out.

8.7 Admin WUI Access

WUI Access Options	
Supported TLS Protocols	<input type="checkbox"/> SSLv3 <input type="checkbox"/> TLS1.0 <input checked="" type="checkbox"/> TLS1.1 <input checked="" type="checkbox"/> TLS1.2 <input checked="" type="checkbox"/> TLS1.3
WUI Cipher set	<input type="text" value="WUI"/>
WUI Session Management	
Enable Session Management	<input checked="" type="checkbox"/>

WUI Access Options	
Supported TLS Protocols	<input checked="" type="checkbox"/> TLS1.1 <input checked="" type="checkbox"/> TLS1.2
WUI Cipher set	<input type="text" value="WUI"/>
WUI Session Management	
Enable Session Management	<input checked="" type="checkbox"/>
Require Basic Authentication	<input type="checkbox"/>
Basic Authentication Password	<input type="text"/> <input type="button" value="Set Basic Password"/>
Failed Login Attempts	<input type="text" value="3"/> <input type="button" value="Set Fail Limit"/> (Valid values:1-999)
Idle Session Timeout	<input type="text" value="600"/> <input type="button" value="Set Idle Timeout"/> (Valid values: 60-86400)
Limit Concurrent Logins	<input type="text" value="0 (No limit)"/>
Pre-Auth Click Through Banner	<input type="text"/> <input type="button" value="Set Pre-Auth Message"/>

Supported TLS Protocols


Checkboxes are provided here which can be used to specify whether or not it is possible to connect to the LoadMaster WUI using the following protocols; TLS1.1 and TLS1.2. TLS1.1 and TLS1.2 are enabled by default. When connecting to the WUI using a web browser, the highest security protocol which is mutually supported by both the browser and the WUI will be used.

WUI Cipher set

Select the relevant cipher set to use for WUI access. For information on each of the cipher sets available, refer to the **Cipher Sets** section.

Direct Access uses IP-HTTPS which applies its own layer of encryption.

WUI Session Management



When using a FIPS LoadMaster, Session Management is enabled and cannot be disabled.

Users with the 'All Permissions' permission set can view the **Enable Session Management**, **Require Basic Authentication** and the **Basic Authentication Password** fields. However, users with the 'All Permissions' permission set can configure the **Failed Login Attempts** and **Idle Session Timeout** values.

Users with the 'User Administration' permissions set can view the screen but all buttons and input fields are greyed out.

All other users cannot view the **WUI Session Management**, **Currently Active Users** or **Currently Blocked Users** sections of the **WUI Configuration** screen.

It is possible to use one or two steps of authentication.

If **Require Basic Authentication** is disabled, the user only needs to log in using their local username and password. Users are not prompted to log in using the **bal** or **user** logins.

If the **Require Basic Authentication** check box is enabled, there are two levels of authentication enforced in order to access the LoadMaster WUI. The initial level is Basic Authentication where users log in using the **bal** or **user** logins, which are default usernames defined by the system.

Once logged in via Basic Authentication, the user then must log in using their local username and password to begin the session.

Enable Session Management

Session Management is enabled by default and cannot be disabled when using a FIPS LoadMaster. This will force all users to login to the session using their normal credentials.

The user is required to log in in order to continue to use the LoadMaster.


LDAP users need to login using the full domain name. For example, an LDAP username should be **test@kemp.com** and not just test.

Please Specify Your User Credentials

User

Login

Password

After a user has logged in, they may log out by clicking the Logout button, , in the top right-hand corner of the screen.

Require Basic Authentication

If Basic Authentication is enabled, there are two levels of authentication enforced in order to access the LoadMaster WUI. The initial level is Basic Authentication where users log in using the **bal** or **user** logins, which are default usernames defined by the system.

Once logged in via Basic Authentication, the user then must log in using their local username and password to begin the session.

Basic Authentication Password

The Basic Authentication password for the **user** login can be set by typing the password into the **Basic Authentication Password** text box and clicking the **Set Basic Password** button.

The password needs to be at least 8 characters long and should be a mix of alpha and numeric characters. If the password is considered to be too weak, a message appears asking you to enter a new password.

Only the **bal** user is permitted to set the Basic Authentication password.

Failed Login Attempts

The number of times that a user can fail to login correctly before they are blocked can be specified within this text box. The valid values that may be entered are numbers between **1** and **999**.

If a user is blocked, only the **bal** user or other users with **All Permissions** set can unblock a blocked user.

If the **bal** user is blocked, there is a 'cool-down' period of ten minutes before the bal user can login again.

Idle Session Timeout

The length of time (in seconds) a user can be idle (no activity recorded) before they are logged out of the session. The valid values that may be entered are numbers between **60** and **86400** (between one minute and 24 hours).

Limit Concurrent Logins


This option gives LoadMaster administrators the ability to limit the maximum number of concurrent login sessions to the LoadMaster WUI at any one time.

The values which can be selected range from 0 – 9.

A value of 0 allows an unlimited number of logins.

The value entered represents the total number and is inclusive of any **bal** user logins.

8.8 OCSP Configuration



OCSP Server Settings	
OCSP Server	10.11.0.35 Set Address
OCSP Server Port	443 Set Port
OCSP URL	/ Set Path
Use SSL	<input type="checkbox"/>
Allow Access on Server Failure	<input type="checkbox"/>

OCSP Server

The address of the OCSP server. This can either be in IP address or Fully Qualified Domain Name (FQDN) format.

OCSP Server Port

The port of the OCSP server.

OCSP URL


The URL to access on the OCSP server.

Use SSL

Select this to use SSL to connect to the OCSP server.

Allow Access on Server Failure

Treat an OCSP server connection failure or timeout as if the OCSP server had returned a valid response, that is, treat the client certificate as valid.




OCSP Checking

Enable OCSP Checking ☐

OCSP Checking

Select the **Enable OCSP Checking** check box to enable the LoadMaster to perform OCSP checks on certain outbound connections. This is disabled by default.



OCSP Stapling

Enable OCSP Stapling ☐

OCSP Refresh Interval 1 Hour ▼

Enable OCSP Stapling

Select this check box to enable the LoadMaster to respond to OCSP stapling requests. If a client connects using SSL and asks for an OCSP response, this is returned. Only Virtual Service certificates are validated. The system holds a cache of OCSP responses that are sent back to the client. This cache is maintained by the OCSP daemon. When the OCSP daemon sends a request to the server, it uses the name specified in the certificate (in the **Authority Information Access** field). If it cannot resolve this name, then it uses the default OCSP server specified in the **OCSP Server** text box.

OCSP Refresh Interval

Specify how often the LoadMaster should refresh the OCSP stapling information. The OCSP daemon caches the entry for up to the amount of time specified here, after which it is refreshed. Valid values range from 1 hour (default) to 24 hours.

8.9 LDAP Configuration

To get to the **LDAP Configuration** screen, expand **Certificates & Security** and click **LDAP Configuration**. This screen provides a management interface for LDAP endpoints. These LDAP endpoints may be used in three different areas:

- Health checks
- SSO domains
- WUI authentication

LDAP Endpoints

Name	Operation
LDAP_EXAMPLE	<button>Modify</button> <button>Delete</button>

Add new LDAP Endpoint

Add

Any existing **LDAP Endpoints** are listed here, with an option to **Modify** and **Delete**. If an LDAP endpoint is in use, it cannot be deleted.

There is also an option to add a new LDAP endpoint. Type a name for the endpoint and click **Add**. Spaces and special characters are not permitted in the LDAP endpoint name.

LDAP Endpoint EXAMPLE

LDAP Server(s)	<input type="text" value="10.154.11.103 10.154."/>	<button>LDAP Server(s)</button>
LDAP Protocol	<input type="text" value="Unencrypted"/>	
Validation Interval	<input type="text" value="60"/>	<button>Set Interval</button>
Referral Count	<input type="text" value="0"/>	<button>Set Referral Count</button>
Server Timeout	<input type="text" value="5"/>	<button>Set Timeout</button>
Admin User	<input type="text" value="ExampleUser"/>	<button>Set Admin User</button>
Admin User Password	<input type="password" value="•••••"/>	<button>Set Admin User Password</button>

LDAP Server(s)

Specify a space-separated list of LDAP servers to be used. Port numbers can also be specified if required. If you have multiple domains and are using **Permitted Groups**, sometimes it is necessary to include the Global Catalog port number, otherwise the **Permitted Groups** will fail. The default port is **3628**. For example, **10.110.20.23:3268**.

LDAP Protocol

Select the transport protocol to use when communicating with the LDAP server.

If you create an SSO domain with the **Authentication Protocol** set to **Certificates**, ensure to set the **LDAP Protocol** to **LDAPS** in the LDAP endpoint.

Validation Interval

Specify how often you should revalidate the user with the LDAP server.

Referral Count

The LoadMaster offers beta functionality to support LDAP referral replies from Active Directory Domain Controllers. If this is set to **0**, referral support is not enabled. Set this field to a value between **1** and **10** to enable referral chasing. The number specified will limit the number of hops (referrals chased).

Multiple hops may increase authentication latency. There is a performance impact that depends on the number and depth of referrals required in your configuration.

You must have intimate knowledge of your Active Directory structure to set the referral limit appropriately. The same credentials are used for all lookups, and so on.

The use of Active Directory Global Catalog (GC) is the preferred configuration as the primary means of resolution instead of enabling LDAP referral chasing. A GC query can be used to query the GC cache instead of relying on LDAP and the referral process. Using Active Directory GC has little or no performance drag on the LoadMaster. For steps on how to add/remove the GC, refer to the following TechNet article:

[https://technet.microsoft.com/en-us/library/cc755257\(v=ws.11\).aspx](https://technet.microsoft.com/en-us/library/cc755257(v=ws.11).aspx)

Server Timeout

Specify the LDAP server timeout in seconds. The default value is **5**. Valid values range from **5** to **60**.

Admin User

Type the username of an administrator user.

Admin User Password

Type the password for the specified administrator user.

9 System Configuration

9.1 Network Setup

9.1.1 Interfaces

Describes the external network and internal network interfaces. The screen has the same information for the **eth0** and **eth1** Ethernet ports. The example below is for **eth0** on a non-HA (High Availability) unit.

Network Interface 0	
Interface Address (address/prefix)	<input type="text" value="10.154.11.70/16"/> Set Address
Cluster Shared IP address	<input type="text" value="10.154.11.90"/> Set Shared address
Use for Cluster checks	<input checked="" type="checkbox"/>
Use for Cluster Updates	<input checked="" type="checkbox"/>
Use for GEO Responses and Requests	<input checked="" type="checkbox"/>
Link Status	Speed: 10000Mb/s, Full Duplex <input type="text" value="Automatic"/> Force Link
MTU:	<input type="text" value="1500"/> Set MTU
Additional addresses (address/prefix)	<input type="text"/> Add Address

[VLAN Configuration](#) [Interface Bonding](#)

Interface Address

Within the **Interface Address (address[/prefix])** text box you can specify the Internet address of this interface. When **Allow Multi Interface Access** is enabled in **Certificates & Security > Remote Access**, and you set an IP address on another interface (other than eth0), a pop-up appears asking "Would you like to enable admin WUI access for this interface?". Click **OK** to enable the **Allow Administrative WUI Access** check box. If you click **Cancel**, the **Allow Administrative WUI Access** check box remains disabled and WUI access is not granted on that interface until that option gets enabled.

Cluster Shared IP address

Specify the shared IP address which can be used to access the cluster. This is also used as the default source address when using Server NAT.

The clustering options will only be available on LoadMasters which have a clustering license. To add the clustering feature to

your license, please contact a Kemp representative. For further information on clustering, refer to the **LoadMaster Clustering, Feature Description** on the [Kemp Documentation Page](#).

Use for Cluster checks

Use this option to enable cluster health checking between the nodes. At least one interface must be enabled.

Use for Cluster Updates

Select this option to use this interface to synchronize the configuration with all of the other nodes in the cluster.

Speed

By default, the **Speed** of the link is automatically detected. In certain configurations, this speed is incorrect and must be forced to a specific value.

On AWS Elastic Network Adapter (ENA) interfaces, no speed is displayed when it cannot be read from the interface.

For ENA driver interfaces, the speed displayed behaves similar to bonded interfaces in that the speed of the overall interface is the aggregate of the number of separate logical interfaces that have been defined on that interface is displayed.

Use for Default Gateway

The **Use for Default Gateway** check box is only available if the **Enable Alternate GW support** is selected in the **Network Options** screen. If the settings being viewed are for the default interface this option is grayed out and selected. To enable this option on another interface, go to the other interface by clicking it in the main menu on the left. Then this option is available to select. Once you select this option, the **Default Gateway** screen appears. Set the new default gateway. A notification displays to inform you that the default gateway has changed.

If you reboot before setting the new default gateway, the gateway is removed from the configuration.

Allow Administrative WUI Access

This option is only available when the **Allow Multi Interface Access** check box is enabled in **Certificates & Security > Remote Access**.

When both of these options are enabled, the WUI can be accessed from the IP address of the relevant interface, and any **Additional addresses** set up for that interface.

There is only one interface attached to all of these addresses so there may be issues with this unless the certificate used is a wildcard certificate. For more information on certificates, refer to the **SSL Accelerated Services, Feature Description** on the [Kemp Documentation Page](#).

There is a maximum of 64 network interfaces that can be tracked and a maximum of 1024 total addresses where the system will listen on.

Use for GEO Responses and Requests

By default, only the default gateway interface is used to listen for and respond to DNS requests. This field gives you the option to listen on additional interfaces.

This option cannot be disabled on the interface containing the default gateway. By default, this is eth0.

When this option is enabled, GEO also listens on any **Additional addresses** that are configured for the interface.

MTU

Within the **MTU** field you can specify the maximum size of Ethernet frames that will be sent from this interface. The valid range is **512 - 9216**.

The valid range of **512 - 9216** may not apply to VLMs as the range will be dependent on the hardware the VLM is running on. It is advised to check your hardware restrictions.

Additional addresses


Using the **Additional addresses** field allows the LoadMaster to give multiple addresses to each interface, as aliases. This is sometimes referred to as a “router on a stick”. It allows both IPv4 and IPv6 addresses in standard IP+CIDR format, so this can also be used to do a mixed mode of IPv4 and

9 System Configuration

IPv6 addresses on the same interface. Any of the subnets that are added here will be available for both virtual IPs and real server IPs.

HA

If the unit is part of a HA configuration, the following screen will be displayed when one of the interfaces is clicked.



Network Interface Management A X [ib100] 02:38:02 PM

Network Interface 0

Interface Address (address/prefix): [Set Address](#)

HA Shared IP address: [Set Shared address](#)

HA Partner IP address: [Set Partner address](#)

Use for HA checks ☒

Use for GEO Responses and Requests ☒

Link Status: Speed: 10000Mb/s, Full Duplex Automatic [Force Link](#)

MTU: [Set MTU](#)

Additional addresses (address/prefix): [Add Address](#)

[VLAN Configuration](#) [VXLAN Configuration](#) [Interface Bonding](#)

[Reboot Now](#)

This screen tells the user:

- This is the **Master** machine of the pair (top-right of the screen)
- This LoadMaster is up and the paired machine is down (green and red icons)
- The IP address of this LoadMaster
- The **HA Shared IP address**. This is the IP address used to configure the pair.
- The IP address of the paired machine
- This interface is enabled for HA health checking
- This interface is used as the Default Gateway
- The speed of the link is automatically detected
- Any alternate addresses on this interface

Creating a Bond/Team

Before creating a bonded interface please note the following:

- You can only bond interfaces higher than the parent, so if you choose to start with eth1, you can then bond eth2, eth3 and above, but you cannot bond eth0 (unless you start with eth0)
- Bond links first if you need VLAN tagging then add VLANs after the bond has been configured

- To add a link to a bonded interface, any IP addressing must first be removed from the link to be added
- Enabling the Active-Backup mode generally does not require switch intervention
- Bonding **eth0** with **eth1** can lead to serious issues and is not allowed to occur

Click **Interface Bonding** to request the bond.

Confirm the bond creation by clicking **Create a bonded interface**.

Acknowledge the warning dialogs.

Using the Web User Interface (WUI) select the **System Configuration > Interfaces > bndx** menu option.

If you do not see the **bndX** interface, refresh your browser, then select the bonded interface and click the **Bonded Devices** button.

Select the desired bonding mode.

Add the additional interfaces to this bond.

Configure the IP and Subnet Mask on the bonded interface.

Removing a Bond/Team

Remove all VLANs on the bonded interface first; if you do not remove them they will automatically be assigned to the physical port at which the bond started.


Select the **System Configuration > Interfaces > bndx** menu option. If you do not see the **bndX** interface refresh your browser, then select the bonded interface, then click the **Bonded Devices** button.

Unbind each port by clicking **Unbind Port**, repeat until all ports have been removed from bond.

Once all child ports have been unbounded, you can unbond the parent port by clicking **Unbond this interface** button.

Adding a VLAN

Select the interface and then select the **VLAN Configuration** button.

A screenshot of the 'Add New VLAN' form. It has a title 'Add New VLAN' at the top. Below the title is a single text input field. To the right of the input field is a blue button labeled 'Add New VLAN'. Below the input field is another blue button labeled '<-Back'.

Add the **VLAN Id** value and select the **Add New VLAN** menu option.

Repeat as needed. To view the VLANs, select the **System Configuration > Network Setup** menu option and expand the drop-down list.

Removing a VLAN

Before removing a VLAN, please ensure that the interface is not being used for other purposes, for example as a multicast interface, WUI interface, SSH interface or a GEO interface.


To remove a VLAN select the **System Configuration > Network Setup** menu option and select the appropriate VLAN ID from the drop-down list.

Once selected, delete the IP and then click **Set Address**. Once the IP has been removed you will have the option to delete the VLAN, by clicking the **Delete this VLAN** button.

Repeat as needed. To view the VLANs select the **System Configuration > Interfaces** menu option and select the appropriate VLAN ID from the drop-down list.

Adding a VXLAN

Select the relevant interface and then click the **VXLAN Configuration** button.

A screenshot of the 'Add New VXLAN' form. It has a title 'Add New VXLAN' at the top. Below the title are two text input fields. The first field is labeled 'VNI' and the second is labeled 'Group or Remote address'. To the right of the second input field is a blue button labeled 'Add New VXLAN'. Below the input fields is another blue button labeled '<-Back'.

Enter a new VXLAN Network Identifier (VNI) in the **VNI** text box. Enter the multicast group or remote address in the **Group or Remote address** text box. Click **Add New VXLAN**.

To modify the VXLAN, go to **System Configuration > Interfaces** and select the VXLAN from the drop-down list.

VXlan 2 (eth0)

Interface Address (address[/prefix])

Set Address

VLAN Configuration

Delete this VXLAN

On this screen, the interface address of the VXLAN can be specified. The VXLAN can also be deleted from this screen.

If HA is enabled, HA parameters can be set in the VXLAN:

- The **HA Shared IP address**. This is the IP address used to configure the HA pair.
- The IP address of the partner machine
- Specify whether or not this interface is used for HA health checking

9.1.2 Host & DNS Configuration

Set Hostname

Hostname Set Hostname

DNS NameServer (IP Address)	Operation
8.8.8.8	Delete
8.8.4.4	Delete

Add Nameserver

IP Address Add

DNS Search Domains	Operation
Kemp.LAB.INTRA	Delete

Add Search Domain

Domain Add

DNS Resolver Options

Enable DNSSEC Resolver ☐

Automatically Update DNS Entries ☒

DNS Update Interval Set Update Interval

Reload DNS Entries for RS Errors ☐

Resolve DNS Names now Run Resolver Now

Host IP Address	Host FQDN	Operation
10.154.33.233	example.com	Delete

Add/Modify Hosts for Local Resolution

IP Address Host FQDN Add/Modify

Set Hostname

Set the hostname of the local machine by entering the hostname in the **Hostname** text box and clicking **Set Hostname**. Only alphanumeric characters are allowed.

Add NameServer (IP Address)

Enter the IP address of a DNS server to resolve names locally on the LoadMaster in this field and click **Add**. A maximum of three DNS servers are allowed.

It is not possible to delete the last remaining NameServer if the DNSSEC client is enabled. You can disable the DNSSEC client on the **Host & DNS Configuration** screen.

Add Search Domain

Specify the domain name to prepend to requests to the DNS NameServer in this field and click **Add**. A maximum of six Search Domains are allowed.

Add/Modify Hosts for Local Resolution

These fields provide the ability to manipulate the host file from the LoadMaster WUI. Specify the IP address and the host FQDN for the entry.

Enable DNSSEC Resolver

By default, the LoadMaster DNSSEC client is disabled. Only enable this option if needed. In some circumstances, the DNSSEC validation takes a significant amount of time to fail. This can cause the LoadMaster to appear to freeze or hang.

Selecting this option enables DNSSEC capabilities on the LoadMaster. You must add at least one **Nameserver** before DNSSEC can be enabled. The LoadMaster must be rebooted after changing the DNSSEC option to activate/deactivate the feature. When the setting is changed, it cannot be changed again until the LoadMaster has been rebooted.

When using HA – the DNSSEC option must be configured on both devices separately.

DNSSEC works with the following utilities in the LoadMaster:

- Vipdump
- Ping and ping6
- Syslog
- SNMP
- Wget
- NTP
- SMTP
- Real Servers

Automatically Update DNS Entries

When this option is enabled, the LoadMaster attempts to automatically update any changed DNS names (based on the **DNS Update Interval**):

- If the address is not found, or if it is the same as before – nothing is done (except a log entry is generated).
- If the address is different, the Real Server entry is updated with the new address, if possible.
- If the new address is invalid for some reason, for example if it is a non-local address and the **Enable Non-Local Real Servers** option is disabled, no changes are made and a log is generated.

DNS Update Interval

Set the update interval for DNS entries. Valid values range from 1 to 60 (minutes). The default value is 60.

Reload DNS Entries for RS Errors

When this option is enabled, DNS entries are reloaded when health checks have errors and an FQDN is associated with the Real Server IP address.

Resolve DNS Names now

Clicking the **Run Resolver Now** button forces a new resolution of DNS names. The behavior is the same as the **Automatically Update DNS Entries** option, except this is a manual (not an automatic) check.

9.1.3 Default Gateway

The network interface addresses must be set before configuring the default gateway.

The LoadMaster requires a default gateway through which it can communicate with the Internet.

The IPv4 default gateway must be on the 10.154.0.0/16 network

IPv4 Default Gateway Address Set IPv4 Default Gateway

If both IPv4 and IPv6 addresses are being used on the LoadMaster, then both an IPv4 and IPv6 Default Gateway Address are required.

IPv4 and IPv6 default gateways must be on the same interface.

9.1.4 Additional Routes

Fixed Static Routes

Add New Route

Destination Gateway Add Route

Further routes can be added. These routes are static and the gateways must be on the same network as the LoadMaster. To segment traffic you can also leverage the Virtual Service level default gateway.

9.1.5 Packet Routing Filter

Packet Routing Filter ☒ Enable ☐ Disable

Rejection method ☒ Drop ☐ Reject

Restrict traffic to Interfaces ☐

Include WUI in Black/White lists ☐

Add Blocked Address(es)

IP Address Comment Block Address(es)

Add Allowed Address(es)

IP Address Comment Allow Address(es)

Packet Routing Filter

If GEO is enabled, the **Packet Routing Filter** is enabled by default and cannot be disabled. If GEO is disabled, the **Packet Routing Filter** is configurable – it can be either enabled or disabled. To disable GEO, on a LoadMaster which has GEO functionality, in the main menu, select **Global Balancing** and **Disable GSLB**.

If the filter is not activated, the LoadMaster also acts as a simple IP-forwarder.

When the filter is activated, it restricts traffic to the LoadMaster but client access to services running on the interface addresses (SSH 22, HTTPS 443, SNMP 161, and DNS 53) is unaffected. Enabling SNAT prevents you from blocking traffic to a Virtual Service that has the same IP address as the

LoadMaster's default gateway interface. This can affect Azure or any cloud platforms that use a single IP address.

The **Reject/Drop blocked packets** and **Restrict traffic to Interfaces** fields will not be displayed if the **Packet Routing Filter** is disabled.

Reject/Drop blocked packets

When an IP packet is received from a host, which is blocked using the Access Control Lists (ACLs), the request is normally ignored (dropped). The LoadMaster may be configured to return an ICMP reject packet, but for security reasons it is usually best to drop any blocked packets silently.

Restrict traffic to Interfaces

This setting enforces restrictions upon routing between attached subnets.

Include WUI in Black/White lists

If this option is enabled, access to the WUI is also controlled by the packet filter. The IP address of the client that enables the **Include WUI in Black/White lists** option to the packet filter will still have access (and be on the whitelist internally) - a message appears next to the check box saying **Access allowed from <IPAddress>**. This protects you from locking yourself out of the WUI.

If the **Include WUI in Black/White lists** option is disabled, access to the WUI is not affected by the packet filter.

Enabling the **Include WUI in Black/White lists** option does not affect Virtual Service connectivity.

Add Blocked Address(es)

The LoadMaster supports a “blacklist” Access Control List (ACL) system. Any host or network entered into the ACL will be blocked from accessing any service provided by the LoadMaster.

The ACL is only enabled when the Packet Filter is enabled. The whitelist allows a specific IP address or address range access. If the address or range is part of a larger range in the blacklist, the whitelist will take precedence for the specified addresses.

If a user does not have any addresses listed in their blacklist and only has addresses listed in their whitelist, then only connections from addresses listed on the whitelist are allowed and connections from all other addresses are blocked.

This option allows a user to add or delete a host or network IP address to the Access Control List. In addition to IPv4 addresses - IPv6 addresses are allowed in the lists if the system is configured with an IPv6 address family. Using a network specifier specifies a network.

For example, specifying the address **192.168.200.0/24** in the blacklist will block all hosts on the 192.168.200 network.

A static port Virtual Service, with an access list defined to block particular traffic, will not work correctly if you also have a wildcard Virtual Service on the same IP address. The wildcard Virtual Service will accept the traffic after the static port Virtual Service denies it.

It is recommended to use a separate IP address in this case to avoid unexpected behavior resulting from this interaction.

9.1.6 VPN Management

The **VPN Management** link/screen will only be available if the LoadMaster is licensed for IPsec tunneling.

For further information on IPsec tunneling, including step-by-step instructions on how to set it up, refer to the .

Connection Endpoints Configuration			Refresh	
Connection Name	Status	Operation		
AWS2	Down	View/Modify	Delete	
vCloudAir	Down	View/Modify	Delete	
Azure	Up	View/Modify	Delete	
AWS1	Up	View/Modify	Delete	
Connection Name <input type="text"/> <input type="button" value="Create"/>				

Connection Name

Specify a unique name to identify the connection.

Create

Create a uniquely identifiable connection with the specified name.

View/Modify

View or modify the configuration parameters for this connection.

Delete

Delete this connection.

All associated configuration will be permanently deleted. A connection can be deleted at any time, even if it is running.

9.1.6.1 View/Modify VPN Connection

Connection Details	
Local IP Address	<input type="text" value="10.154.11.10"/> Set Local IP Address
Local Subnet(s)	<input type="text" value="10.154.11.10/32"/> Set Local Subnet(s)
Remote IP Address	<input type="text" value="10.154.11.20"/> Set Remote IP Address
Remote Subnet(s)	<input type="text" value="10.154.11.30/32"/> Set Remote Subnet(s)
Perfect Forward Secrecy	<input type="checkbox"/>

Connection Secrets	
Local ID	<input type="text" value="10.154.11.10"/>
Remote ID	<input type="text" value="10.154.11.20"/>
Pre Shared Key(PSK)	<input type="text"/>
Save Secret Information	

[<-Back](#)

When initially creating a connection, or when modifying a connection, the **View/Modify VPN Connection** screen appears.

Local IP Address

Set the IP address for the local side of the connection.

In non-HA mode, the **Local IP Address** should be the LoadMaster IP address, that is, the IP address of the default gateway interface.

In HA-mode, the **Local IP Address** should be the shared IP address. This will be automatically populated if HA has already been configured. For more information on setting up tunneling in a HA configuration, refer to the next section.

Local Subnet Address

When the **Local IP Address** is set the **Local Subnet Address** text box is automatically populated. The local IP can be the only participant if applicable, given the /32 CIDR. Review the **Local Subnet Address** and update it if needed. Ensure to click **Set Local Subnet Address** to apply the setting, whether the address has been changed or not. Multiple local subnets can be specified using a comma-separated list. Up to 10 IP addresses can be specified.

Remote IP Address

Set the IP address for the remote side of the connection. In the context of an Azure endpoint, this IP address is expected to be the public-facing IP address for the Virtual Private Network (VPN) Gateway device.

Remote Subnet Address

Set the subnet for the remote side of the connection. Multiple remote subnets can be specified using a comma-separated list. Up to 10 IP addresses can be specified.

Perfect Forward Secrecy

Activate or deactivate the Perfect Forward Secrecy option.

The cloud platform being used will determine what the **Perfect Forward Secrecy** option should be set to. **Perfect Forward Secrecy** is needed for some platforms but is unsupported on others. To find out what will work with your cloud platform, refer to the [document](#).

Local ID

Identification for the local side of the connection. This may be the local IP address. This field is automatically populated with the same address as the **Local IP Address** if the LoadMaster is not in HA mode.

If the LoadMaster is in HA mode, the **Local ID** field will be automatically set to **%any**. This value cannot be updated when the LoadMaster is in HA mode.

Remote ID

Identification for the remote side of the connection. This may be the remote IP address.

Pre Shared Key (PSK)

Enter the pre-shared key string.

Save Secret Information

Generate and save the connection identification and secret information.

9.2 HA and Clustering

Confirm

☐ HA Mode

An HA configuration requires two LoadMasters, only one of which is active and processing traffic at any time. The other passive unit continuously monitors the health of the active unit and will begin serving traffic when the active unit becomes unavailable. Once you configure HA mode, clustering options will be unavailable.

☐ Clustering

A Clustering configuration requires the following:

1. At least three LoadMasters (four or more are recommended). All LoadMasters in a cluster actively process traffic.
2. All hardware LoadMasters must be the same model. Virtual LoadMasters must have the same CPU, RAM and disk storage assigned. You cannot mix hardware and virtual LoadMasters in a cluster.
3. All LoadMasters should be set to use factory-default settings, with the exception of networking.

Once you configure clustering, HA mode options will be unavailable.

Confirm

Cancel

This section in the WUI is only called **HA and Clustering** if you have a LoadMaster license with clustering enabled. If you do not have clustering, this section will be called **HA Parameters** and you will not see the screen shown above. If clustering has been configured, this section will be called **Cluster Control**.

This screen describes both **HA Mode** and **Clustering**. Select the relevant option and click **Confirm** to continue.

Once clustering is configured, the HA mode options will be unavailable.

9.2.1 HA Mode


If you are using the LoadMaster in a cloud environment, refer to the **Azure HA Parameters** or **AWS HA Parameters** section.

If you are using the LoadMaster for AWS product, refer to the **AWS HA Parameters**

The role of the appliance can be changed by setting the HA Mode. If **HA (First) Mode** or **HA (Second) Mode** is selected as the **HA Mode**, a prompt will appear reminding to add a shared IP. Changing the HA Mode will require a reboot, so after the details are set, click the **Reboot** button provided. Once the LoadMaster has rebooted, the HA menu option will be available in the **System Configuration** section provided the role is not “Non HA Mode”. HA will NOT work if both machines are specified the same.

When logged into the HA cluster, use the shared IP address to view and set full functionality to the pair. If you log into the direct IP address of either one of the devices the menu options are quite different (see menus below). Logging into one of the LoadMaster directly is usually reserved for maintenance.

After upgrading from firmware version 7.1-24b or below, if using the FIPS cavium card 1610 FW 2.2 and the LoadMaster is in HA mode, regenerate the web server SSL key in order to access the WUIs of the individual LoadMasters.



When a LoadMaster is in HA mode, the following screen appears when you select the **HA Parameters** menu option.






HA Mode	HA (First) Mode	
HA Timeout	9 Seconds	
HA Initial Wait Time	0	Set Delay (Valid Values: 0, 10-180)
HA Virtual ID	1	Set Virtual ID (Valid Values: 1-255)
Switch to Preferred Server	No Preferred Host	
HA Update Interface	eth0: 172.21.11.100	
Force Partner Update	Force Update	
Pair FIPS hardware	Pair hardware	
Inter HA L4 TCP Connection Updates	<input type="checkbox"/>	
Inter HA L7 Persistency Updates	<input type="checkbox"/>	
Use Virtual MAC addresses	<input type="checkbox"/>	

HA Status

At the top of the screen, next to the time, icons are shown to denote the real-time status of the LoadMaster units in the cluster. There will be an icon for each unit in the cluster. You can open the WUI for the first or second HA unit by clicking the relevant status icon.



The possible icons are:

Green (with 'A')		The unit is online and operational and the HA units are correctly paired. The A in the middle of the square indicates that this is the master (active) unit.
Green (without 'A')		The unit is online and operational and the HA units are correctly paired. The absence of an 'A' in the middle of the square indicates that this is not the master unit (standby).
Red/Yellow		The unit is not operational. It may be offline or misconfigured. The unit is not ready to take over. It may be offline or incorrectly paired.
Blue		When the unit reboots more than 3 times in 5 minutes it moves into a pacified state. In this state the machine is only accessible using the direct machine WUI (not the shared WUI), and, it is not participating in any HA activity, that is, no changes from the master are received and it will not take over if the master fails. To remove the unit from the pacified state, log in to the pacified LoadMaster through SSH or the console and reboot.
Grey		The machine is in an indeterminate state and may require a reboot to return to operation. In some cases, this may mean Both machines are active, that is, both are set to master, and something has gone seriously wrong. CALLall Kemp Support for assistance with this issue, if rebooting does not solve it.
No HA icons		If the HA status squares are not appearing in the WUI, it probably means that HA is not enabled. Go to System Administration and select the HA option. Ensure the HA Mode is set to either First or Second .

In HA mode each LoadMaster will have its own IP address used only for diagnostic purposes directly on the unit. The HA pair have a shared IP address over which the WUI is used to configure and manage the pair as a single entity.

Both HA1 and HA2 must be on the same subnet with the same default gateway and be in the same physical site. They must

not be separated by an intra-site link and must use the same gateway to return traffic.

HA Mode

If using a single LoadMaster, select Non-HA Mode. When setting up HA mode, one LoadMaster must be set to HA (First) and the other HA (Second). If they are both set to the same option, HA will not operate.

HA Timeout

The time that the Master machine must be unavailable before a switchover occurs. With this option, the time it takes an HA cluster to detect a failure can be adjusted from 3 seconds to 15 seconds in 3 second increments. The default value is 9 seconds. A lower value will detect failures sooner, whereas a higher value gives better protection against a DOS attack.

HA Initial Wait Time

How long after the initial boot of a LoadMaster, before the machine decides that it should become active. If the partner machine is running, then this value is ignored. This value can be changed to mitigate the time taken for some intelligent switches to detect that the LoadMaster has started and to bring up the link.

HA Virtual ID

When using multiple HA LoadMaster clusters on the same network, this value uniquely identifies each cluster so that there are no potential unwanted interactions.

All LoadMasters on the network that are or will be configured into HA pairs must be assigned unique **HA Virtual ID** numbers.

As of the 7.2.36 release, the LoadMaster selects a virtual ID based on the shared IP address of the first configured interface (the last 8 bits). It is selected and displayed once both the shared address and the partner address have been set. You can change the value to whatever you want (in the range 1 – 255) or you can keep it at the value it already selected. Please ensure the virtual ID is unique on each LoadMaster on the network.

Use Broadcast IP address

By default, the LoadMaster uses an IP multicast address when sending CARP packets. Enabling this option forces the use of the IP broadcast address instead.

Switch to Preferred Server

By default, neither partner in a HA cluster has priority. So that when a machine restarts after a switchover, the machine becomes the slave and stays in that state until forced to Master. Specifying a preferred host means that when this machine restarts, it will always try to become master and the partner will revert to slave mode. If a preferred server is specified, this will result in a double failover event because if the master unit fails, the slave unit will take over as master and when the preferred unit comes back up it will take over as master.

HA Update Interface

The interface used to synchronize the HA information within the HA cluster.

Force Partner Update

Immediately forces the configuration from the active to standby unit without waiting for a normal update.

Pair FIPS hardware

Before certificates can be used on LoadMaster HA units the FIPS cards on the HA units must be paired. To pair the FIPS cards on both HA machines together, click **Pair Hardware**.

Inter HA L4 TCP Connection Updates

When using L4 services, enabling updates will allow L4 connections to be maintained across a HA switchover by sharing the connection table. This option is ignored for L7 services.

Inter HA L7 Persistence Updates

When using L7 services, enabling this option will allow persistence information to be shared between the HA partners. If an HA failover occurs, the persistence information will not be lost. Enabling this option can have a significant performance impact.

HA Multicast Interface

The network interface used for multicast traffic which is used to synchronize Layer 4 and Layer 7 traffic when Inter-HA Updates are enabled.

Use Virtual MAC Addresses

Enabling this option forces the MAC address to switch between a HA pair during a switchover which is useful when gratuitous ARPs (used in communicating changes in HA IP addresses to switches) are not allowed.

This option is only available for hardware LoadMasters.

9.2.1.1 Azure HA Parameters

This screen is only available in LoadMaster for Azure products.

Azure HA Mode	Master HA Mode ▼	
Switch to Preferred Server	No Preferred Host ▼	
Partner Name/IP	10.0.0.37	Set Partner Name/IP
Health Check Port	8444	Set Health Check Port
Health Check on All Interfaces	<input type="checkbox"/>	

Azure HA Mode

Select the required HA mode for this unit. There are three options:

- Master HA Mode
- Slave HA Mode
- Non HA Mode

If you are only using a single LoadMaster, select **Non HA Mode**.

When using HA mode, one machine must be specified as the **Master** and the second machine must be specified as the **Slave**.

HA will not work if both units have the same value selected for the **Azure HA Mode**.

Synchronization of Virtual Service settings only occurs from the master to the slave. Changes made to the master will be replicated to the slave. However, changes made to the slave are never replicated to the master.

If the master unit fails, connections will be directed to the slave unit. The master unit is the master and will never become the slave, even if it fails. Similarly, the slave unit will never become the master. When the master unit comes back up, connections will automatically be directed to the master unit again.



You can tell, at a glance, which unit is the master, and which is the slave, by checking the mode in the top bar of the LoadMaster.

Switch to Preferred Server

There are two possible values to select:

- **No Preferred Host:** Each unit takes over when the other unit fails. No switchover is performed when the partner is restarted.
- **Prefer Master:** The HA1 (master) unit always takes over. This is the default option.

Partner Name/IP


Specify the host name or IP address of the HA partner unit.

Health Check Port

Set the port over which the health check will be run. The port must be the same on both the master and slave unit for HA to function correctly.

Health Check on All Interfaces


When this option is enabled, the health check listens on all interfaces. This is required when using a multi-arm configuration. If this is disabled, the health check listens on the primary eth0 address (this is the default behavior).



If a unit is in standby mode, WUI access is restricted to **Local Administration** only. Full WUI access is available if the unit is in an active or unchecked state.

9.2.1.2 AWS HA Parameters

This screen is only available in LoadMaster for Amazon Web Services (AWS) products.



AWS HA Mode	Master HA Mode
Switch to Preferred Server	No Preferred Host
Partner Name/IP	10.0.0.37
Health Check Port	8444
Health Check on All Interfaces	<input type="checkbox"/>

AWS HA Mode

Select the required HA mode for this unit. There are three options:

- Master HA Mode
- Slave HA Mode
- Non HA Mode

If you are only using a single LoadMaster, select **Non HA Mode**.

When using HA mode, one machine must be specified as the **Master** and the second machine must be specified as the **Slave**.

HA will not work if both units have the same value selected for the **AWS HA Mode**.

Synchronization of Virtual Service settings only occurs from the master to the slave. Changes made to the master will be replicated to the slave. However, changes made to the slave are never replicated to the master.

If the master unit fails, connections will be directed to the slave unit. The master unit is the master and will never become the slave, even if it fails. Similarly, the slave unit will never become the master. When the master unit comes back up, connections will automatically be directed to the master unit again.

MASTER (ACTIVE) 04:12:10 PM

You can tell, at a glance, which unit is the master, and which is the slave, by checking the mode in the top bar of the LoadMaster.

Switch to Preferred Server

There are two possible values to select:

- **No Preferred Host:** Each unit takes over when the other unit fails. No switchover is performed when the partner is restarted.
- **Prefer Master:** The HA1 (master) unit always takes over. This is the default option.

Partner Name/IP


Specify the host name or IP address of the HA partner unit.

Health Check Port

Set the port over which the health check will be run. The port must be the same on both the master and slave unit for HA to function correctly.

Health Check on All Interfaces


When this option is enabled, the health check listens on all interfaces. This is required when using a multi-arm configuration. If this is disabled, the health check listens on the primary eth0 address (this is the default behavior).



If a unit is in standby mode, WUI access is restricted to **Local Administration** only. Full WUI access is available if the unit is in an active or unchecked state.

9.2.2 Cluster Control

The **Cluster Control** option will only be available on LoadMasters which have a clustering license. To add the clustering feature to your license, please contact a Kemp representative. For further information on clustering, refer to the **LoadMaster Clustering Feature Description** on the [Kemp Documentation Page](#).



Create New Cluster: If setting up a new cluster, click this button.

Add to Cluster: Add this LoadMaster to an already existing cluster.

Convert to Cluster

Cluster Shared Address

When the **Create New Cluster** button is clicked, the screen above will appear which prompts to set the shared IP address of the cluster. The shared IP address is the address which will be used to administer the cluster.


Reboot

Rebooting and switching to the Shared Address to finish the conversion to Cluster mode

Please reconnect to 10.154.11.91

When the **Create a New Cluster** button is clicked, the LoadMaster reboots. A message will appear asking to reconnect to the shared IP address that was just set.



Current Cluster Configuration

ID	Address	Status	Operation
1	10.154.11.90	 Admin	<input type="button" value="Disable"/> <input type="button" value="Delete"/>

IP Address

After creating a cluster, the **Cluster Control** screen in the WUI of the shared IP address will allow the addition of LoadMaster nodes into the cluster.

A LoadMaster can only be added to a cluster when the cluster is available and the LoadMaster is waiting to join the cluster. Refer to the **LoadMaster Clustering Feature Description** on the [Kemp Documentation Page](#) for further information and steps.







ID	Address	Status	Operation
1	10.154.11.90	 Admin	<button>Disable</button> <button>Delete</button>
2	10.154.11.80	 Up	<button>Disable</button> <button>Delete</button>

The **Cluster Control** screen, in the shared IP address WUI, displays details for each of the nodes in the cluster.

Show Options: Clicking the **Show Options** button will display the **Cluster Parameters** section which contains two additional fields which can be used to set the **Cluster Virtual ID** and **Node Drain Time**. For further information, refer to the **LoadMaster Clustering Feature Description** on the [Kemp Documentation Page](#).

ID: The cluster ID.

Address: The IP address of the LoadMaster node. If a second IP address appears in brackets after the first one - the second IP address is the IP address of the interface port. Icons are displayed depending on the status:

Icon	Status	Description
	Admin	The node is the primary control node.
	Disabled	The node is disabled - connections will not be sent to that node.
	Starting	The node is starting (enabling).
	Up	The node is up.
	Down	The node is down.
	Draining	The node has been disabled and the connections are being shut down in an orderly fashion. Drain stopping lasts for 10 seconds by default. This can be updated by changing the Node Drain Time value on the Cluster Control screen. For more information, refer to the LoadMaster Clustering Feature Description on the Kemp Documentation Page .

Operation: The different operations that can be performed in relation to the notes:

- **Disable:** Disable the node. Nodes that are disabled will first go through drain stopping. During the drain stopping time, the connections are shut down in an orderly fashion. After the drain, the node will be disabled and no traffic will be directed to that node.
- **Enable:** Enable the node. When a node comes up, it will not be immediately brought into rotation. It will only come online after it has been up for 30 seconds.
- **Delete:** Delete a node from the cluster. When a node is deleted it becomes a regular single LoadMaster instance. If the LoadMaster is later added back in to the cluster, any configuration changes that have been made in the shared IP address will propagate to the node LoadMaster.
- **Reboot:** When performing a cluster-wide firmware update, a **Reboot** button will appear on this screen after uploading the firmware update patch. For step-by-step instructions on how to perform a cluster-wide firmware update, refer to the **LoadMaster Clustering Feature Description** on the [Kemp Documentation page](#).

Add New Node: Add a new node with the specified IP address to the cluster.

9.2.2.1 Cluster Parameters

Cluster Parameters			
Cluster Virtual ID	<input type="text" value="1"/>	Set Cluster Virtual ID	(Valid Values: 1-255)
Node Drain Time	<input type="text" value="10"/>	Set Node Drain Time	(Valid Values: 1-600)

When the **Show Options** button is clicked, the **Cluster Parameters** section appears. This section contains two additional WUI options - **Cluster Virtual ID** and **Node Drain Time**.

Cluster Virtual ID

When using multiple clusters or LoadMaster HA systems on the same network, the virtual ID identifies each cluster so that there are no potential unwanted interactions. The cluster virtual ID is set to **1** by default, but it can be changed if required. Valid IDs range from 1 to 255. Changes made to an admin Loadmaster propagate across all nodes in the cluster.

Node Drain Time

When a node is disabled, the connections that are still being served by the node are allowed to continue for the amount of seconds specified in the **Node Drain Time** text box. No new connections will be handled by the node during this time. The **Node Drain Time** is set to **10** seconds by default, but it can be changed if required. Valid values range from 1 to 600 (seconds).

During the drain time the status changes to Draining until the specified drain time elapses.

When the drain time has elapsed the status changes to disabled.

9.3 System Administration

These options control the base-level operation of the LoadMaster. It is important to know that applying changes to these parameters in a HA pair must be done using the floating management IP. Many of these options will require a system reboot. When configuring these parameters, only the active system in a pair is affected.

9.3.1 User Management

The content below describes the different user management WUI fields. For further information on user management and WUI authentication, refer to the **User Management Feature Description** on the [Kemp Documentation Page](#).

Change Password

Current Password

New Password

Re-enter New Password

Set Password

The **Change Password** section can be used to change the appliance password. This is a local change only and does not affect the password of the partner appliance in a HA deployment.

Minimum Password length

Minumum password length

8

Minimum Password length

Set the minimum password length for all local user passwords. After selecting a different value for this field, you must refresh the page for the new value to be enforced.

Local Users		
User	Permissions	Operation
ExampleUser	Read Only	<div>ModifyDelete</div>

The **Local Users** section lists any existing local users. Two options are available for existing users:

- **Modify:** Change details for an existing local user, such as their permissions and password. For further information, refer to the **Modify User** section.
- **Delete:** Delete the relevant user.

Add User

User
Password
Use RADIUS Server ☐

New users can be added in the **Add User** section.

Username can be a maximum of 64 characters long. Username can start with a digit and can contain alphanumeric characters, in addition to the following special characters:

=~^._+#@/-

The minimum password length is defined by what is set in the **Minimum password length** field. All characters are allowed.

When Session Management is enabled, a check box called **No Local Password** will be displayed in the **Add User** section. This option can be enabled if client certificate authentication will be used to authenticate this user when they are accessing the LoadMaster. To enable client certificate authentication, set the **Admin Login Method** in the **Remote Access** screen. For further information, refer to the **Remote Access** section or the **User Management Feature Description** on the [Kemp Documentation Page](#).

Certificate-based authentication will be deprecated at some point in the future.

API Keys		
API Key	Operation	
ogSLq4qWN7c49E3DDu3PkdadNIq5hHdQzLpmZA8M5g0z	<input type="button" value="Delete"/>	<input type="button" value="Generate New APIKey"/>
8nv2c4ts8pj1w3oiQ5T6QUUMk7bkPM2kAb1618ax9k4z	<input type="button" value="Delete"/>	
DAJuxFXUvQDJsxYRQepwFA4H7APku28HA60xb5m2o4z	<input type="button" value="Delete"/>	
nZOi41P0mj9vNJ3eUIPqdCvJGudxOHcEpDUry9hqQPgz	<input type="button" value="Delete"/>	

When running API commands, you can authenticate using an API key. An API key is a unique identifier used to authenticate a user.

The **API Keys** section on the **User Management** screen displays any API keys currently generated for the logged in user. You can have up to 16 API keys per user - if you try to create more, the oldest is silently deleted. The oldest API key is listed at the top.

To generate an API key for a specific user, go to the **Modify** screen for that particular user.

Remote User Groups

Group	Permissions	Operation
ExampleGroup2	Certificate Creation, Intermediate Certificates, Certificate Backup	Modify Delete
ExampleRemoteUserGroup	Real Servers, Virtual Services, Certificate Creation, Intermediate Certificates, Certificate Backup	Modify Delete

Add Remote User Group

Group [Add Group](#)

The **Remote User Groups** section displays any remote user groups that have been created. The group name and associated permissions are displayed. These groups can be selected for LDAP WUI authentication in the following location: **Certificates & Security > Remote Access > WUI Authorization Options**. For further information, refer to the **WUI Authentication and Authorization** section.

It is important to select and apply the group, or groups. If there are no groups selected, no group checking is performed and remote users can log in without a group check.

You can add a new remote user group by entering a name and clicking **Add Group**.

The following characters are permitted in the group name: alphanumeric characters, spaces, or the following special symbols: `=~^._+#,@/`.

Click **Modify** to edit the group permissions.

Permissions for User testuser

Real Servers

Virtual Services

Rules

System Backup

Certificate Creation

Intermediate Certificates

Certificate Backup

User Administration

GEO Control

ALL Permissions

☒

☒

☒

Set Permissions

For further information regarding group permissions, refer to the **User Management Feature Description** on the [Kemp Documentation Page](#).

Extended Permissions

Allow Extended Permissions ☐

Enabling the **Allow Extended Permissions** option makes an additional permission called **Add Virtual Services** visible on the user permissions screen. For details on this, refer to the **User Management Feature Description** on the [Kemp Documentation Page](#).

9.3.1.1 Modify User

Permissions for User ExampleUser

Real Servers

Virtual Services

Rules

System Backup

Certificate Creation

Intermediate Certificates

Certificate Backup

User Administration

GEO Control

ALL Permissions

☒

In this screen you may set the level of user permissions. This determines what configuration changes the user is allowed to perform. The primary user (**bal**) always has full permissions. Secondary users may be restricted to certain functions.

For further information regarding user permissions, please refer to the **User Management Feature Description** on the [Kemp Documentation Page](#).

Change Password

New Password

Re-enter New Password

Use RADIUS Server

☐

Change Password

The **Change Password** section can be used to modify a user’s password. It is also possible to enable and disable RADUIS server authentication for a user.

When Session Management is enabled, a check box called **No Local Password** will be displayed in the **Change Password** section. This option can be enabled if client certificate authentication will be used to authenticate this user when they are accessing the LoadMaster. To enable client certificate authentication, set the **Admin Login Method** in the **Remote Access** screen. For further information, refer to the **Remote Access** or the **User Management Feature Description** on the [Kemp Documentation Page](#).

Named users, even those without User Administration privileges, can change their own passwords. When a named user clicks the **System Administration > User Management** menu option the **Change Password** screen appears.

Current Password

New Password

Re-enter New Password

Reset

Set Password

From within this screen, users can change their own password. The minimum password length is defined by what is set in the **Minimum password length** field. All characters are allowed, except \”`’. Once changed, a confirmation screen appears after which the users will be forced to log back in to the LoadMaster using their new password.

API Keys

API Key

gMd2Ce1NExmuUqfBCecRVlX2cVYVPvt8OOZyte7xpP8z

Operation


Delete

Generate New APIKey

When running API commands, you can authenticate using an API key. An API key is a unique identifier used to authenticate a user.

The **API Keys** section on the **Modify** user screen displays any API keys currently generated for that specific user. You can have up to 16 API keys per user - if you try to create more, the oldest is silently deleted. The oldest API key is listed at the top.

To generate an API key for a specific user, click **Generate New APIKey**.



The image shows a screenshot of the 'Local Certificate' section in the WUI. It features three buttons: 'Download Certificate' (with a 'Download' button next to it), 'Generate Certificate' (with a 'Generate' button next to it), and 'Delete Certificate' (with a 'Delete' button next to it). To the right of the 'Generate' button is a text input field labeled 'Passphrase'.

In the **Local Certificate** section, a certificate can be generated for the user. A **Passphrase** can be optionally set which is used to encrypt the private key. Once that certificate has been downloaded, it can be used as a client certificate to allow password-less access to the LoadMaster API. Users with 'User Administration' permissions are able to manage local certificates for themselves and other users.

To enable client certificate authentication to the LoadMaster, set the **Admin Login Method** in the **Remote Access** screen. For further information, please refer to the **Remote Access** section or the **User Management Feature Description** on the [Kemp Documentation Page](#).

9.3.2 Update License

This screen displays the activation date and the expiration date of the current license. You would use the **Update License** function if your license has changed, for example if:

- You have renewed support
- You have renewed your license
- You have changed your license type

Before updating the license in the LoadMaster, you must either contact your Kemp representative, or use the **Upgrade** option. After you have contacted Kemp or used the upgrade option, there are two ways to update a license – using the **Online** method and using the **Offline** method. Refer to the sections below to find out details about the screens for each method.

For more information and instructions, refer to the **Licensing Feature Description** on the [Kemp Documentation Page](#).

A **Kill License** button may appear on the **Update License** screen:

- If your LoadMaster license is either a Permanent (PERM), Temporary (TEMP), or Service Provider License Agreement (SPLA) license that was obtained from the Kemp Licensing Server (either online or offline), then clicking the **Kill License** button will invalidate your license on the Kemp licensing server and in the inventory of the Kemp ID that was used to license the LoadMaster.
- If your LoadMaster license is a Service Provider License Agreement (SPLA) or Metered Licensing Agreement (MELA) license that was obtained from a local Kemp 360 Central instance in your configuration, then clicking the **Kill License** button will return the LoadMaster license to the available license pool on Kemp 360 Central, and the LoadMaster will return to an unlicensed state.

Do not click **Kill License** unless instructed to by Kemp Support.

9.3.2.1 Online Method

License Update

Online Licensing ▼

Kemp Identifier:

Password:

Order ID (optional):

To upgrade the license using the online method, the LoadMaster must be connected to the internet. You will need to enter your **Kemp ID** and **Password** to license using the online method.

A reboot is recommended after updating the license.

Do not click **Kill License** unless instructed to by Kemp Support.

9.3.2.2 Offline Method

Current License

Uuid: 084e4095-8219-4007-9fd5-71eb1f697b97
Activation date: June 30 2016
Licensed until: July 31 2016

License Update

Please obtain your new license from your KEMP representative or by visiting [Get License](#)

Offline Licensing ▾
Upgrade ⬆

Access Code: mmw14-txw5w-mrmhg-6k4hg

License:

Update License

To upgrade the license using the offline method, you need to enter license text in the LoadMaster. You can either get this from Kemp or using the **Get License** link.

A reboot is recommended after updating the license. If upgrading to an ESP license, a reboot is required after the update.

9.3.2.3 Debug Checks


If you try to license and there are any issues, a number of checks are performed automatically and the results and associated error message are displayed.



These checks perform the following tasks:

- Ping Default Gateway
- Ping DNS Servers
- Ping Licensing Server

9.3.3 System Reboot



Reboot

Reboot the appliance.

Shutdown

Clicking this button attempts to power down the LoadMaster. If, for some reason, the power down fails, it will at a minimum halt the CPU.


Reset Machine

Reset the configuration of the appliance with exception of the license and username and password information. This only applies to the active appliance in a HA pair.

Zeroize FIPS Hardware

For security purposes, you may be asked to “zeroize” the HSM. This operation will completely erase the internal memory of the HSM card of all the private keys stored there. This must be performed on each unit of the HA pair. However you can zeroize the active and standby units without forcing a failover.

9.3.4 Update Software

A screenshot of a web form titled 'Update LoadMaster Software'. It contains two rows of input fields. The first row is for the 'Software Update File' with a 'Choose File' button and the text 'No file chosen'. The second row is for the 'Verification File' with a 'Choose File' button and the text 'No file chosen'. To the right of the second row is an 'Update Machine' button.

You can download firmware patches from the [Kemp Downloads page](#).

Upload the patch file and the XML verification file that is used to check the integrity of the patch file.

Update Machine

After you have downloaded the firmware you can browse to the file and upload the firmware directly into LoadMaster. The firmware will be unpacked and validated on LoadMaster. If the patch is validated successfully you will be asked to confirm the release information. To complete the update you will need to reboot the appliance. This reboot can be deferred if needed.

Update Cluster

The **Update Cluster** option will only be available on LoadMasters which have a clustering license. To add the clustering feature to your license, please contact a Kemp representative. For further information on clustering, refer to the **LoadMaster Clustering Feature Description** on the [Kemp Documentation Page](#).

The firmware on all LoadMasters in a cluster can be updated using the shared IP address by clicking the **Update Cluster** button. For step-by-step instructions on how to perform a cluster-wide software update, refer to the **LoadMaster Clustering Feature Description** on the [Kemp Documentation Page](#).

Restore Software

If you have completed an update of LoadMasters firmware you can use this option to revert to the previous build.

Installed Addon Packages

Package	Version	Installation Date	Operation
Vmtoolsd	7.2.48.0.17807.DEV	Fri Sep 27 01:56:14 2019	Delete

Install new Addon Package

Addon Package File: [Choose File](#) No file chosen

Verification File: [Choose File](#) No file chosen [Install Addon Package](#)

Installed Addon Packages

Add-on packages can be installed in the Kemp LoadMaster. Add-on packages provide features that are additional to those already included in the LoadMaster. Kemp plan on creating further add-on packages in the future.

Add-On packages can be downloaded from the Kemp website: www.kemptechnologies.com

To install an add-on package, click the **Choose File** buttons, browse to and select the relevant add-on package and verification files and click **Install Addon Package**. A reboot is required for the add-on package to be fully installed. If an add-on package of the same name is uploaded, the existing one will be overwritten/updated.

If an installed add-on package cannot be started, the text will display in red and the hover text will show that the package could not be started.

9.3.5 Backup/Restore

Create a Backup

Backup the LoadMaster [Create Backup File](#)

Restore Backup

Backup File [Choose File](#) No file chosen

LoadMaster Base Configuration ☐

VS Configuration ☐

GEO Configuration ☐

ESP SSO Configuration ☐

[Restore Configuration](#)

Automated Backups

Enable Automated Backups ☒

When to perform backup : Day of week [Set Backup Time](#)

Backup Method

Remote user [Set Remote User](#)

Private Key File (Unset) [Choose File](#) No file chosen [Set Private Key](#)

Remote host [Set Remote Host](#)

Remote Pathname [Set Remote Pathname](#)

Test Automated Backups [Test Backup](#)

Create Backup File

Generate a backup that contains the Virtual Service configuration, the local appliance information and statistics data. License information and SSL Certificate information is not contained in the backup.

For ease of identification, the Backup file name includes the LoadMaster's hostname.

By default, the LoadMaster includes a Netstat output in backups taken. When this is included, backups take longer to complete. You can stop the Netstat output from being included by disabling the **Include Netstat in Backups** option in the **Debug Options** screen (**System Configuration > Logging Options > System Log Files > Debug Options**).

Restore Backup

205

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

When performing a restore (from a remote machine), the user may select what information should be restored:

- **VS Configuration**
- **LoadMaster Base Configuration**
- **GEO Configuration**
- **ESP SSO Configuration** (This restores the SSO domains, LDAP endpoints and SSO custom image sets. This does not restore the Virtual Service settings - use the **VS Configuration** option to restore those.)
- A combination of the options

It is not possible to restore a single machine configuration onto a HA machine or restore a HA configuration onto a single machine.

It is not possible to restore a configuration with ESP-enabled Virtual Services onto a machine which is not enabled for ESP.

Automated Backups

If the **Enable Automated Backups** check box is selected, the system may be configured to perform automated backups on a daily or weekly basis.

For ease of identification, the Backup file name includes the LoadMaster's hostname.

If the automated backups are not being performed at the correct time, ensure the NTP settings are configured correctly. For further information, refer to the **Date/Time** section.

When to perform backup

Specify the time (24 hour clock) of backup. Also select whether to backup daily or on a specific day of the week. When ready, click the **Set Backup Time** button.

In some situations, spurious error messages may be displayed in the system logs, such as:

```
Dec 8 12:27:01 Kemp_1 /usr/sbin/cron[2065]: (system) RELOAD (/etc/crontab)
Dec 8 12:27:01 Kemp_1 /usr/sbin/cron[2065]: (CRON) bad
```

minute (/etc/crontab)

These can be safely ignored and the automated backup will likely still complete successfully.

Backup Method

Select the file transfer method for automated backups:

- **Ftp (insecure)**
- **scp (secure)**
- **sftp (secure)**

If using scp or sftp, the **Private Key File** must be supplied.

Remote user

Set the username required to access remote host.

Private Key File

If using scp as the backup method, the **Private Key File** must be provided. This is the SSH private key generated using ssh-keygen on the remote scp server.

Remote password

The **Remote password** is used when the **Backup Method** is set to **Ftp (insecure)**. Set the password required to access remote host. This field accepts alphanumeric characters and most non-alphanumeric characters. Disallowed characters are as follows:

- Control characters
- ' (apostrophe)
- ` (grave)
- The delete character

Remote host

Set the remote host name.


Remote Pathname

Set the location on the remote host to store the file.

Test Automated Backups

Clicking the **Test Backup** button performs a test to check if the automated backup configuration is working correctly. The results of the test can be viewed within the System Message File.

9.3.6 Date/Time



You can manually configure the date and time of LoadMaster or leverage an NTP server.

NTP host(s)

Specify the host which is to be used as the NTP server. NTP is a strongly preferred option for a HA cluster. For a single unit it is at the user's discretion. Clicking the **Set NTP host** button will refresh the time based on the details configured.

If you do not have a local NTP server, refer to www.pool.ntp.org for a list of public NTP server pools which can be used.

The time zone must always be set manually.

Show NTP Authentication Parameters/Disable NTP Authentication

The LoadMaster supports NTPv4 which uses cryptographic signing to query a secure NTP server. This uses a simple authorization scheme which uses a shared secret and key to validate that the response from the server is actually valid. Enable the **Show NTP Authentication Parameters** check box to display the parameters that are needed to support NTP authenticated requests. If you select the **Show NTP Authentication Parameters** checkbox and change any of the parameters, the name of the check box changes to **Disable NTP Authentication**.

NTP Key Type

Select either the MD5 or SHA-1 NTP key type.

For the NTPv4 feature to work, a file must be created on the server (/etc/ntp.keys), which has the following format:

```
<keyid> M <secret string>
```

...

<keyid> M <secret string>

To enable the use of the key, specify the keyid in the trustedkey line of /etc/ntp.conf, for example, if the keyid is 5 then you have to specify “trustedkey5”. The trustedkey value can take multiple values, for example trustedkey 1 2 3 4 5 9 10).

NTP Shared Secret

The NTP shared secret string. The NTP secret can be a maximum of 20 ASCII characters long or 40 hexadecimal characters long.

NTP Key ID

Select the NTP key ID. The values range from 1 to 99. Different key IDs can be used for different servers.

Set Date

Set the date on the LoadMaster.

Set Time

Set the time on the LoadMaster.


Set time zone

Set the time zone where the LoadMaster is located.

9.4 Logging Options

Logging of LoadMaster events can be both pushed and also pulled from the appliance. It is important to note that log files on LoadMaster are not historical, if the appliance reboots the logs are reset. It is important to keep a record of events generated on LoadMaster on a remote facility.

9.4.1 System Log Files



If debugging is required, but there is no network connection to the LoadMaster, log in using the console and enable debugging by running the following command:

```
echo "7" > /proc/sys/kernel/printk
```

This allows debug logs to output to the console.

If possible, please contact Kemp Support before using these commands.

Disk Usage - This section provides an indication of the percentage used/free of the log partition. Color-coding is used to highlight different usage levels:

- 0% to 50%: green
- 50% to 90%: orange
- 90% to 100%: red

Boot.msg File - contains information, including the current version, during the initial starting of LoadMaster.

Warning Message File - contains warnings logged during the operation of LoadMaster.

System Message File - contains system events logged during the operation of LoadMaster. This includes both operating system-level and LoadMaster internal events.

Nameserver Log File - show the DNS name server log.

Nameserver Statistics - show the latest name server statistics.

IPsec IKE Log - show the IPsec IKE log.

The **IPsec IKE Log** button does not appear if **VPN Management** is not configured under **System Configuration > Network Setup > VPN Management**.

WAF Event Log - contains logs for most recently triggered WAF rules.

The **WAF Event Log** button does not appear if there are no WAF event logs.

Audit LogFile - contains a log for each action which is performed by a user; either using the API or the WUI. This will only function if session management is enabled. For further information on session management, refer to the **Admin WUI Access** section.

Clear Logs - clears the warning and system message logfiles. You can either click **Clear All** to clear all the system log files or click the arrow to select specific log files to clear.

Save Logs - you can use this option if you need to send logs to Kemp support as part of a support effort. Click **Save All** to save all system log files to your computer and forward them to Kemp support. Click the arrow to select specific log files to save.

For information on logrotate, refer to <https://linux.die.net/man/8/logrotate>. Alternatively, run **man logrotate** on a Linux machine. To cross check that with the logrotate configuration on the LoadMaster, look at the configuration files in /etc/logrotate.d/, especially **syslog** and **userlogs**.

9.4.1.1 Debug Options

The LoadMaster has a range of features that will help you and Kemp Support staff with diagnosing connectivity issues. Clicking **Debug Options** brings up the screen shown below.

Debug Options

Disable All Transparency	Disable Transparency
Enable L7 Debug Traces	Enable Traces
Enable Extended L7 Debug	Enable Extended Debug
Enable IRQ Pinning	Enable IRQ Pinning
Perform an l7adm	l7adm
Enable WAF Debug Logging	Enable Logging
Enable IRQ Balance	Enable IRQ Balance
Enable TSO	Enable TSO
Enable TCP SACK	Enable TCP SACK
Disable CLI VS Management	Disable CLI VS Management
Enable Bind Debug Traces	Enable Bind Traces
Perform a PS	ps
Perform Top	top Iterations <input type="text" value="10"/> Interval <input type="text" value="1"/> sec <input type="checkbox"/> Show Threads <input type="checkbox"/> Sort by Memory usage
Include Top in Backups	<input type="checkbox"/>
Display Meminfo	Meminfo
Display Slabinfo	Slabinfo
Perform an Ifconfig	Ifconfig
Perform a Netstat	Netstat
Include Netstat in Backups	<input checked="" type="checkbox"/>
Reset Statistic Counters	Reset Statistics
Flush OCSPD Cache	Flush Cache
Enable SSOMGR Debug Traces	Enable Traces
Flush SSO Authentication Cache	Flush SSO Cache
Linear SSO Logfiles	<input type="checkbox"/>
Start IPsec IKE Daemon	Start IPsec IKE Daemon
Perform an IPsec Status	IPsec Status
Enable IKE Debug Level Logs	Enable Logs
Netconsole Host	<input type="text"/> Interface <input type="text" value="eth0"/> Set Netconsole Host
Ping Host	<input type="text"/> Interface <input type="text" value="eth0"/> Ping
Ping6 Host	<input type="text"/> Interface <input type="text" value="Automatic"/> Ping6
Traceroute Host	<input type="text"/> Traceroute
Kill LoadMaster (261718)	<input type="text"/> Kill LoadMaster

WARNING – Kemp does not recommend using debug commands during normal operation. They should ideally only be used in conjunction with a Kemp Support Technician's recommendations.

Note: Debug commands have performance impacts on the LoadMaster and may expose your system to additional security vulnerabilities during the time they are running.

Disable All Transparency

Disables transparency on every Virtual Service and forces them to use Layer 7. Use with caution.

This option is only for debugging and does not replace the normal controls to enable and disable transparency on a per-Virtual Service basis.

Using this option to disable transparency saves a copy of the configuration file before disabling transparency. When transparency is turned back on (not all Virtual Services may have had transparency turned on before the change), the original configuration is restored. Therefore, any changes to the configuration during this time are lost. This includes creating new Virtual Services.

Enable L7 Debug Traces

Generates log traffic in the message files. Due to the large amount of files being logged it slows down L7 processing.

Enable IRQ Pinning

Click the button to enable Interrupt Request Line (IRQ) pinning. This is disabled by default.

Only enable this option in consultation with Kemp Support.

When you change the IRQ pinning option from off to on, IRQ pinning is enabled on all network interfaces that are assigned an IP address. When IRQ pinning is enabled and you add an IP address to an unconfigured interface, that interface will not have IRQ pinning enabled until you either toggle the IRQ pinning off and back on again, or the system is rebooted.

Perform an l7adm

Displays raw statistics about the L7 subsystem.

Enable WAF Debug Logging

Enable WAF debug traces.

This generates a lot of log traffic. It also slows down WAF processing. Only enable this option when requested to do so by Kemp Technical Support. Kemp does not recommend enabling this option in a production environment.

The WAF debug logs are never closed and they are rotated if they get too large. WAF needs to be disabled and re-enabled in all WAF-enabled Virtual Service settings to re-enable the debug logs. Alternatively, perform a rule update, with rules that are relevant for the Virtual Service(s).

Enable IRQ Balance

Enable this option only after consulting with Kemp support staff.

Enable TSO

Enable TCP Segmentation Offload (TSO).

Only modify this option after consultation with Kemp Technical Support. Changes to this option will only take effect after a reboot.

Enable TCP SACK

Click this button to enable TCP SACK (Selective ACKnowledgement) processing. This is a global setting that affects all Layer 7 Virtual Services. It only works if TCP SACK is enabled on a Virtual Service client and the LoadMaster.

Enable/Disable CLI VS Management

Enable or disable the Command Line Interface (CLI) Service Management function.

Enable Bind Debug Traces

Enable bind debug trace logs for GEO.

Perform a PS

Performs a **ps** on the system.

Perform a Top

Performing a **top** command displays memory, CPU, and I/O usage for the LoadMaster. You can specify the number of samples and an interval between them (the default is 10 samples and a 1 second interval). You can also show threads and/or sort by memory usage by selecting the appropriate check boxes. By default the results are sorted by CPU usage.

Include Top in Backups

By default, the LoadMaster does not include a top output in backups. This can be enabled by selecting this check box. When included in backups, **top** is run using the default parameters (regardless of what is configured in the WUI) and is sorted by memory usage.

Display Meminfo

Displays raw memory statistics.

Display RAID Information

The **Display RAID Information** and **Display RAID Disks Information** buttons only appear if a RAID controller is installed on the LoadMaster.

Display the Redundant Array of Independent Disks (RAID) controller details. Some example information is below:

```
-----
Controller details
-----
- Chip ID.....: 10
- Parent Controller Index: 255
- OS Physical Name.....: /dev/sda
- Serial Number.....: 427491329
- AES Power on State.....: 0
- Sata Ports.....: 2
-----
Raid Port 0 details
-----
- Raid Model Name.....: H/W RAID1
- Raid Serial Number.....: OUEYEXCXTQ53GE1BSOSN
- EZBackup Disk Support.....: 0
- Port Multiplier port.....: 0
- Raid Capacity.....: 953 (29 GB)
```

9 System Configuration

- Raid Capacity low word.....: 0
- Raid State.....: 1 (Active)
- Raid Status.....: 3 (Normal)
- Raid Level.....: 1 (Raid 1 (mirror))
- Mark Type.....: 0
- Active Member.....: 15
- Active Level.....: 0
- Rebuild Priority.....: 3
- Standby Timer.....: 0
- Total members in the RAID....: 2

Member disk 0

- Ready.....: 1
- Lba 48 Bit Support.....: 1
- SATA Page.....: 0
- SATA Port.....: 0
- SATA Base.....: 0
- SATA Size.....: 953

Member disk 1

- Ready.....: 1
- Lba 48 Bit Support.....: 1
- SATA Page.....: 0
- SATA Port.....: 1
- SATA Base.....: 0
- SATA Size.....: 953

Display RAID Disks Information

Display details about the RAID disks. Some example information is below:

Sata Port 0 details

- Disk Model Name.....: 32GB SATA Flash Drive
- Disk Serial Number.....: C0122916B01000000074
- Disk Firmware Version.....: SFDC001D
- EZBackup Disk Support.....: 1
- Port Multiplier port.....: 15

9 System Configuration

- Disk Capacity.....: 954 (29 GB)
- Port Type.....: 2 (RAID)
- Port Speed.....: 2 (GB)
- Page 0 State.....: 2
- Page 0 Raid Index.....: 0
- Page 0 Member Index.....: 0
- Page 0 Raid Name.....:
- Page 0 Raid Serial Number.....:
- Page 0 Raid Segment Base.....: 0
- Page 0 Raid Size.....: 953
- Page 0 Raid EZ Backup Support: 0
- Page 1 State.....: 0
- Page 1 Raid Index.....: 0
- Page 1 MemberIndex.....: 0
- Page 1 Raid Name.....:
- Page 1 Raid Serial Number.....:
- Page 1 Raid Segment Base.....: 0
- Page 1 Raid Size.....: 0
- Page 1 Raid EZ Backup Support: 0
- PortErrorStatus.....: 0

Sata Port 1 details

- Disk Model Name.....: 32GB SATA Flash Drive
- Disk Serial Number.....: E011321290100000005A
- Disk Firmware Version.....: SFDC001D
- EZBackup Disk Support.....: 1
- Port Multiplier port.....: 15
- Disk Capacity.....: 954 (29 GB)
- Port Type.....: 2 (RAID)
- Port Speed.....: 2 (GB)
- Page 0 State.....: 2
- Page 0 Raid Index.....: 0
- Page 0 Member Index.....: 1
- Page 0 Raid Name.....:
- Page 0 Raid Serial Number.....:
- Page 0 Raid Segment Base.....: 0

- Page 0 Raid Size.....: 953
- Page 0 Raid EZ Backup Support: 0
- Page 1 State.....: 0
- Page 1 Raid Index.....: 0
- Page 1 MemberIndex.....: 0
- Page 1 Raid Name.....:
- Page 1 Raid Serial Number.....:
- Page 1 Raid Segment Base.....: 0
- Page 1 Raid Size.....: 0
- Page 1 Raid EZ Backup Support: 0
- PortErrorStatus.....: 0

Display Slabinfo

Displays raw slab statistics.

Perform an Ifconfig

Displays raw Ifconfig output.

Perform a Netstat

Displays Netstat output.

Include Netstat in Backups

By default, the LoadMaster includes a Netstat output in backups taken. When this is included, backups take longer to complete. You can stop the Netstat output from being included by disabling this option.

Reset Statistic Counters

Reset all statistics counters to zero and delete any old graphs. This also deletes the Round Robin Database (RRD) files but these files are automatically recreated when needed.

Flush OCSPD Cache

When using OCSP to verify client certificates, OCSPD caches the responses it gets from the OCSP server. This cache can be flushed by pressing this button. Flushing the OCSPD cache can be useful when testing, or when the Certificate Revocation List (CRL) has been updated.

Stop IPsec IKE Daemon

Stop the IPsec IKE daemon on the LoadMaster.

If this button is clicked, the connection for all tunnels will go down.

Perform an IPsec Status

Display the raw IPsec status output.

Enable IKE Debug Level Logs

Control the IPsec IKE log level.

Flush SSO Authentication Cache

Clicking the **Flush SSO Cache** button flushes all Single Sign-On (SSO) records, resets all authentication server statuses, resets the KCD domain (if relevant) and re-reads the configuration. This has the effect of logging off all clients using Single Sign-On to connect to the LoadMaster.

SSO LDAP server timeout

Set the SSO LDAP server timeout value in seconds (default value is 5 seconds).

Linear SSO Logfiles

By default, older log files are deleted to make room for newer log files, so that the filesystem does not become full. Selecting the **Linear SSO Logfiles** check box prevents older files from being deleted.

When using Linear SSO Logging, if the log files are not periodically removed and the file system becomes full, access to ESP-enabled Virtual Services will be blocked, preventing unlogged access to the virtual service. Access to non-ESP enabled Virtual Services are unaffected by the Linear SSO Logfile feature.

Netconsole Host

If directed by a Kemp support engineer, you can use this feature to send critical kernel logs to a syslog server in the event of the LoadMaster failing or crashing. A syslog server configured as the Netconsole Host receives all critical kernel messages.

You can select which interface the **Netconsole Host** is set to using the **Interface** dropdown.

Please ensure that the **Netconsole Host** IP specified is on the selected interface as errors may occur if it is not.

The **Netconsole Host** parameter can be set to either an IPv4 or IPv6 address, the only restriction being that the Netconsole IP address must be in the same address family as the LoadMaster's IP address on the selected **Interface**. In other words, if the LoadMaster's IP address on the selected **Interface** is an IPv4 address, then the **Netconsole Host** IP address must be an IPv4 address as well. If you want to use an IPv6 address for **Netconsole Host**, then you must select an **Interface** on which the LoadMaster has an IPv6 address.

Netconsole is not configurable on a bonded interface.

Ping Host

Performs a ping on the specified host. The interface which the ping should be sent from can be specified in the **Interface** drop-down list. The **Automatic** option selects the correct interface to ping an address on a particular network.

The interface tries to determine if the address to ping is an IPv4 or IPv6 address and selects the correct command to perform the ping. For an address in numeric form this is simple, however this is not possible for non-numeric addresses so they will always be treated as an IPv4 address.

Ping6 Host

Perform a ping6 of a specific IPv6 host.

Traceroute Host


Perform a traceroute of a specific host.

Kill LoadMaster

Permanently disables all LoadMaster functions. The LoadMaster can be re-enabled by being relicensed.

Please do not kill your LoadMaster without consulting Kemp Technical Support.

The **Kill LoadMaster** option will not be available in LoadMasters which are tenants of the Kemp Condor.



TCP dump

A TCP dump can be captured either by one or all Ethernet ports. Address and port parameters, as well as optional parameters may be specified. The maximum number of characters permitted in the **Options** text box is **255**.

You can stop and start the dump. You can also download it to a particular location. The results of the TCP dump can then be analysed in a packet trace analyser tool such as [Wireshark](#).


For more information, refer to the **Packet Trace Guide Technical Note** on the [Kemp Documentation Page](#).

9.4.2 Extended Log Files

The **Extended Log Files** screen provides options for logs relating to the ESP and WAF features.

To get to the **Extended Log Files** screen – in the LoadMaster WUI, go to **System Configuration > Logging Options > Extended Log Files**.

The WAF logs are not generated in real time – they can be up to two minutes behind what the WAF engine is actually processing.





Disk Usage - This section provides an indication of the percentage used/free of the log partition. Color-coding is used to highlight different usage levels:

- 0% to 50%: green
- 50% to 90%: orange
- 90% to 100%: red

There are multiple log files relating to ESP stored on the LoadMaster. These are listed below the **Disk Usage** section. These logs are persistent across LoadMaster reboots.

You can select one of the **View** or **Save Action** buttons with the default filter options to apply the action to the various log files (Connection Logs, Security Logs, and so on). For the **Clear** button, you must first select which logs to clear using the **Selection** controls.

To access the **Selection Controls**, click one of the right caret icons  at the right of the buttons. For example, clicking on the icon to the right of the **Clear** and **Save** buttons, displays these controls.



You can filter the logs to clear or save by date, using the **from** and **to** controls, and also select a subset of log files from the multiple pick list on the right.

- **ESP Connection Logs:** logs recording each connection.
- **ESP Security Logs:** logs recording all security alerts.

- **ESP User Logs:** logs recording all user logins.
- **WAF Audit Logs:** recording WAF logs based on what has been selected for the **Audit mode** drop-down list in the **WAF Options** section of the Virtual Service modify screen. The number listed in each log entry corresponds to the ID of the Virtual Service. To get the Virtual Service ID, first ensure that the API interface is enabled (**Certificates & Security > Remote Access > Enable API Interface**). Then, in a web browser address bar, enter **https://<LoadMasterIPAddress>/access/listvs**. Check the **index** of the Virtual Service. This is the number that corresponds to the number on the audit log entry.

To view the logs, please select the relevant options and click the relevant **View** button.

Some of the logs can be filtered by a number of methods. To filter log messages by date, select the relevant dates in the **from** and **to** fields and click the **View** button.

When selecting dates for ESP logs, include the next date in the list to include all records for the desired dates (because the next day file may contain logs for the previous date).

One or more archived log files can be viewed by selecting the relevant file(s) from the list of file names and clicking **View**. You can filter the log files by entering a word(s) or regular expression in the **filter** field and clicking **View**.

Clear Extended Logs

All extended logs can be deleted by clicking **Clear**.

Specific log files can be deleted by filtering on a specific date range, selecting one or more individual log files in the log file list or selecting a specific log type (for example connection, security or user) in the log file list and clicking the **Clear** button. Click **OK** on any warning messages.

Save Extended Logs

Click the arrow to expand the options. Select a file type (for example, **connection**) or enter a date range. All extended logs can be saved to a file by clicking **Save**. This saves a file to your machine.

Specific log files can be saved by filtering on a specific date range, selecting one or more individual log files in the log file list or selecting a specific log type (for example connection, security or user) in the log file list and clicking **Save**.

Disable Local Extended ESP Logs

If **Disable Local Extended ESP Logs** is disabled (the default option), messages are written to the extended ESP logs expediently and are not sent to any remote syslog servers that are defined.

If **Disable Local Extended ESP Logs** is enabled, no messages are written to the extended ESP logs and messages are only sent to the remote logger (if one is defined). If a remote logger is not defined, no logs are recorded.

You can no longer configure the system to both populate the local extended ESP logs and send the same messages to remote syslog servers, as it was in previous releases.

Clear Temporary WAF Remote Log Data

Clear the temporary WAF remote log data.

Save Temporary WAF Remote Logs Data

Save the temporary WAF remote log data.

9.4.3 Syslog Options

The LoadMaster can produce various warning and error messages using the syslog protocol. Syslog messages include a full timestamp and the LoadMaster host name in every message. Syslog messages comply with RFC5424. These messages are normally stored locally.

Syslog Hosts

Host	Syslog Level
10.154.11.26	Emergency ▼
10.154.11.39	Critical ▼
10.154.131.126	Informational ▼
10.154.153.94	Informational ▼

Add Syslog Host

Syslog host

Select Severity ▼

Add Syslog Host

Syslog Port

Remote Syslog Port

Set Port

It is also possible to configure the LoadMaster to transmit these error messages to a remote syslog server by entering the relevant IP address in the **Syslog host** text box, selecting the severity and clicking **Add Syslog Host**. Syslog messages are transmitted securely using TLS to remote servers.

To delete a hosts entry, set the severity level to **None**.

Six different error message levels are defined and each message level may be sent to a different server. Notice messages are sent for information only; Emergency messages normally require immediate user action.

Up to 10 individual IP addresses can be specified. If there were more than 10 hosts configured in a previous LoadMaster version, after upgrading - all entries are displayed but no more can be added.

Examples of the type of message that may be seen are shown below:

- **Emergency:** Kernel-critical error messages
- **Critical:** Unit 1 has failed and unit 2 is taking over as master (in a HA setup)
- **Error:** Authentication failure for root from 192.168.1.1
- **Warn:** Interface is up/down
- **Notice:** Time has been synced
- **Info:** Local advertised Ethernet address

One point to note about syslog messages is they cascade in an upwards direction. Thus, if a host is set to receive WARN messages, the message file includes messages from all levels above WARN but none for levels below.

If you enter the same host address again, the old entry for the same host is replaced. There is no need to have multiple entries for the same host because a single entry covers the syslog level that is defined, plus all other levels that are of higher priority. So, you only need to include one entry with the lowest level priority required.

You can also specify a non-standard port for syslog transfer by entering it into the **Remote Syslog Port** text box and clicking **Set Port**:

- If the **Remote Syslog Port** is not configured, logging is done on UDP on port 514.
- If the **Remote Syslog Port** is configured as 601, logging is done on TCP on port 601.
- If the **Remote Syslog Port** is configured as any port other than 601, logging is done on secured TCP, that is, over SSL on the configured port.

To enable a syslog process on a remote Linux server to receive syslog messages from the LoadMaster, the syslog must be started with the “-r” flag.

9.4.4 SNMP Options

With this menu, the SNMP configuration can be modified.

On Dell LoadMasters, you can retrieve hardware statistics such as temperature, fan speed, power supply voltage current, and so on, using SNMP. These values are only available using SNMP.

Enable SNMP	<input checked="" type="checkbox"/>
Enable SNMP V3	<input checked="" type="checkbox"/>
Username	<input type="text"/>
Password	<input type="text"/>
Authentication protocol	SHA ▼
Privacy protocol	DES ▼
SNMP Clients	<input type="text"/>
Community String	public
Contact	<input type="text"/>
Location	<input type="text"/>
Enable SNMP Traps	<input checked="" type="checkbox"/>
SNMP Trap Sink1	<input type="text"/>
SNMP Trap Sink2	<input type="text"/>

Enable SNMP

This check box enables or disables SNMP metrics. For example, this option allows the LoadMaster to respond to SNMP requests.

By default, SNMP is disabled.

There is a significant performance hit when SNMP is enabled.

When the feature is enabled, the following traps are generated:

- **ColdStart:** generic (start/stop of SNMP sub-system)
- **VsStateChange:** (Virtual Service state change)
- **RsStateChange:** (Real Server state change)
- **HaStateChange:** (HA configuration only: LoadMaster failover)

When using SNMP monitoring of ESP-enabled Virtual Services that were created using a template, ensure to monitor each SubVS directly rather than relying on the master service. This is because the Authentication Proxy sub-service will always be marked as up and, as a consequence, so will the master service.

The information regarding all LoadMaster-specific data objects is stored in the below enterprise-specific MIBs (Management Information Base).

MIB file	Related Data
IPVS-MIB.txt	Virtual Server stats
B100-MIB.txt	L7 LoadMaster configuration and status info
ONE4NET-MIB.txt	Enterprise ID
CERTS-MIB.txt	SSL certificate information

These MIBs (located on the Kemp documentation page - <http://kemptechnologies.com/documentation>) need to be installed on the SNMP manager machine to be able to request the performance/config-data of the LoadMaster using SNMP.

The description of the counters can be taken from the LoadMaster MIBs (the description clause). Apart from just reading the MIB this can be done for Linux (and ucdsnmp) with the command:

snmptranslate -Td -OS <oid>

where <oid> is the object identifier in question.

Example: <oid> = .1.3.6.1.4.1.one4net.ipvs.ipvsRSTable.rsEntry.rSConns

snmptranslate -Td -Ov

.1.3.6.1.4.1.one4net.ipvs.ipvsRSTable.rsEntry.rSConns.1.3.6.1.4.1.12196.12.2.1.12

rSConns OBJECT-TYPE

-- FROM IPVS-MIB

SYNTAXCounter32

MAX-ACCESSread-only

STATUScurrent

DESCRIPTION"the total number of connections for this RS"

::= { iso(1) org(3) dod(6) internet(1) private(4) enterprises(1) one4net(12196) ipvs(12)
ipvsRSTable(2) rsEntry(1) 12 }

The Kemp OID is called **one4net** for legacy reasons.

The data object defined in the LoadMaster MIBS is a superset to the counters displayed by the WUI.

The data objects on the LoadMaster are not writable, so only GET requests (GET, GET-NEXT, GET-BULK, and so on) should be used.

You can retrieve SSL certificate information including the file name, certificate Subject Name, certificate serial number, certificate start date, certificate end date, and certificate issuer information using the **CERTS-MIB.txt** file. SNMP can display this information for up to 256 SSL certificates.

You can also retrieve disk space usage details using SNMP. The /var/log and /var/log/userlog partition information is available.

Regarding the data partitions, these are not under the Kemp OID, they are under a standard OID. The details are as follows:

- Path where the disk is mounted: .1.3.6.1.4.1.2021.9.1.2.1
- Path of the device for the partition: .1.3.6.1.4.1.2021.9.1.3.1
- Total size of the disk/partition (kBytes): .1.3.6.1.4.1.2021.9.1.6.1
- Available space on the disk: .1.3.6.1.4.1.2021.9.1.7.1
- Used space on the disk: .1.3.6.1.4.1.2021.9.1.8.1
- Percentage of space used on disk: .1.3.6.1.4.1.2021.9.1.9.1
- Percentage of inodes used on disk: .1.3.6.1.4.1.2021.9.1.10.1

Enable SNMP V3

This check box enables SNMPv3 metrics. SNMPv3 primarily added security and remote configuration enhancements to SNMP.

When this option is enabled, two additional fields become available - **Username** and **Password**.

The **Username** and **Password** must be set for SNMPv3 to work.

The password must be at least 8 characters long.

Authentication protocol

Select the relevant **Authentication protocol** - **MD5** or **SHA**. **SHA** is recommended.

Privacy protocol

Select the relevant **Privacy protocol** - **AES** or **DES**. **AES** is recommended.

SNMP Clients

With this option, the user can specify from which SNMP management hosts the LoadMaster will respond to.

If no client has been specified, the LoadMaster will respond to SNMP management requests from any host.

SNMP Community String

This option allows the SNMP community string to be changed. The default value is “public”.

Allowed characters in the **Community String** are as follows: **a-z, A-Z, 0-9, _.-@()?#%^+~!**.

Contact

This option allows the SNMP Contact string to be changed. For example, this could be e-mail address of the administrator of the LoadMaster.

SNMP Location

This option allows the SNMP location string to be changed.

This field accepts the following characters:

a-z A-Z 0-9 _ . - ; , = : { } @ () ? # % ^ + ~ !

Do not enter a hashtag symbol (#) as the first character in the Location.

SNMP traps

When an important event happens to a LoadMaster a Virtual Service or to a Real Server, a trap is generated. These are sent to the SNMP trap sinks. If a change is made, the LoadMaster waits for all changes to finish and then waits five seconds before reading it. At that point, all changes will have stabilized and SNMP traps can then be sent. If there are any state changes within the five second wait, the state changes are handled and then the wait is restarted.

Enable/Disable SNMP Traps

This toggle option enables and disables the sending of SNMP traps.

SNMP traps are disabled by default.

Send SNMP traps from the shared address

This check box is only visible when the LoadMaster is in HA mode.

By default, SNMP traps are sent using the IP address of the master HA unit as the source IP address. Enabling this option will send SNMP traps from the master HA unit using the shared IP address.

SNMP Trap Sink1

This option allows the user to specify a list of hosts to which a SNMPv1 trap will be sent when a trap is generated.

SNMP Trap Sink2

This option allows the user to specify a list of hosts to which a SNMPv2 trap will be sent when a trap is generated.

9.4.5 Email Options

This screen permits the configuration of email alerting for LoadMaster events. Email notification can be delivered for six predefined informational levels. Each level can have a distinct email address and each level supports multiple email recipients. Email alerting depends on a mail server, support for both an open relay mail server and a secure mail server is provided.



A sample email alert is above. This is from the **Info** level. Syslog emails contain one or more lines of syslogs (they are grouped together if possible).

Enable Email Logging	<input checked="" type="checkbox"/>
SMTP Server	<input type="text"/> Set Server Port <input type="text"/> Set Port
Server Authorization (Username)	<input type="text"/> Set
Authorization Password	<input type="password"/> Set Password
Local Domain	<input type="text"/> Set Domain
Connection Security	<input type="text" value="None"/>
Emergency Recipients <input type="text"/>	
Critical Recipients <input type="text"/>	
Error Recipients <input type="text"/>	
Warn Recipients <input type="text"/>	
Notice Recipients <input type="text"/>	
Info Recipients <input type="text"/>	
Send Test Email to All Recipients	

SMTP Server

Enter the FQDN or IP address of the mail server. If you are using FQDN please make sure to set the DNS Server.

Port

Specify the port of the SMTP server which will handle the email events.

Server Authorization (Username)

Enter the email address to use as the 'From' address in the email headers.

Authorization Password

Enter the password if your mail server requires authorization for mail delivery. This is not a required if you mail server does not require authorization.

Local Domain

Enter the top-level domain, if your mail server is part of a domain. This is not a required parameter.

Connection Security

Select the type of security for the connection;

- None
- STARTTLS, if available
- STARTTLS
- SSL/TLS

Set Email Recipient

In the various **Recipients** text boxes, enter the email address that corresponds with the level of notification desired. Notifications will be sent for the level of severity, plus anything with a higher severity – so there is no need to enter the email address in multiple text boxes as that will lead to duplicate notifications being sent. For example, any email address entered into the **Critical Recipients** text box will get critical emails, but will also get emergency emails.

Multiple email addresses are supported by a comma-separated list, such as:

Info Recipients: info@kemptechnologies.com, sales@kemptechnologies.com

Error Recipients: support@kemptechnologies.com

Clicking the **Send Test Email to All Recipients** button sends a test email to all the listed email recipients.




An example email alert is shown above. The **Subject** of the email contains the relevant highest alert level. There can be multiple alerts in a single email - they are collated together for a period of 30 seconds to avoid flooding inboxes.

9.5 Miscellaneous Options

9.5.1 WUI Settings

Only the **bal** user or users with 'All Permissions' set can use this functionality. Users with different permissions can view the screen but all buttons and input fields are greyed out.



WUI Configuration

- Enable Hover Help ☒
- Enable Auto-Save ☒
- Message of the Day **Set MotD**
- Set Statistics Display Size **Set Display Length** (Range 10 - 100)
- End User License **Show EULA**
- Enable Historical Graphs ☒
- Collect All Statistics ☐


Enable Hover Help

Enables blue hover notes shown when the pointer is held over a field.

Enable Auto-Save

Auto-save is enabled by default. When auto-save is enabled, changes you make in the LoadMaster WUI are applied instantly. For example, if you select an option in a drop-down list, the change is applied instantly.

If auto-save is disabled, several default WUI behaviors are modified. These are detailed below.




Standard Options

- Transparency Disabled
- Persistence Options Mode: **Set Persist**
- Scheduling Method **Set Method**
- Idle Connection Timeout (Default 660) **Set Idle Timeout**
- Use Address for Server NAT ☒

Unsaved changes are highlighted by a background color change.

You must confirm drop-down selections by clicking the associated button (when auto-save is enabled, there is no button for some fields - the change is automatically applied once selected).



10.35.47.34 says

Items have changed on this page.
Leaving the page will discard the changes.
Do you want to continue?

OK Cancel

You are warned if you attempt to navigate away from a page with unsaved changes.

Disabling auto-save is currently a beta feature.

If auto-save is disabled and you use the browser's back or refresh buttons - the WUI will not display any warnings about changes made on the current page and they are lost if not committed.

If auto-save is disabled and you downgrade the LoadMaster firmware to a version older than 7.2.49, you cannot enable the auto-save feature because the check box will be unavailable.

Most of the Kemp documentation is written with auto-save enabled.

Message of the Day (MOTD)

Type in text into the field and click the Set MotD button. This message will be displayed on the login screen.

The maximum allowed message length is 5,000 characters. HTML is supported, but not required. Single quotes (') and double quotes (") are not allowed, though you can use the equivalent HTML character codes, for example, entering "it's allowed" would result in a MOTD of "it's allowed".

Set Statistics Display Size

This sets the maximum number of rows that can be displayed in the Statistics page. The allowable range is between 10 and 100 rows being displayed on the page.

End User License

Click the **Show EULA** button to display the LoadMaster End User License Agreement.

Enable Historical Graphs

Enable the gathering of historical statistics for the Virtual Services and Real Servers.

Collect All Statistics

By default, this option is disabled. This means that only the statistics for the Virtual Services and Real Servers that are configured to be displayed on the home page are collected. Enabling this option will force the LoadMaster to collect statistics for all Virtual Services and Real Servers.

If there are a large number of Virtual Services and Real Servers this option can cause CPU utilization to become very high.

9.5.2 L7 Configuration

Allow connection scaling over 64K Connections	<input type="checkbox"/>
Always Check Persist	<input type="text" value="No"/>
Add Port to Active Cookie	<input type="checkbox"/>
Conform to RFC	<input checked="" type="checkbox"/>
Close on Error	<input type="checkbox"/>
Add Via Header In Cache Responses	<input type="checkbox"/>
Real Servers are Local	<input type="checkbox"/>
Drop Connections on RS failure	<input type="checkbox"/>
Drop at Drain Time End	<input type="checkbox"/>
L7 Connection Drain Time (secs)	<input type="text" value="300"/> Set Time (Valid values:0, 60 - 86400)
L7 Authentication Timeout (secs)	<input type="text" value="30"/> Set Timeout (Valid values:30 - 300)
L7 Client Token Timeout (secs)	<input type="text" value="120"/> Set Timeout (Valid values:60 - 300)
Additional L7 Header	<input type="text" value="X-Forwarded-For"/>
100-Continue Handling	<input type="text" value="RFC-7231 Compliant"/>
Allow Empty POSTs	<input type="checkbox"/>
Allow Empty HTTP Headers	<input type="checkbox"/>
Force Complete RS Match	<input type="checkbox"/>
Least Connection Slow Start	<input type="text" value="0"/> Set Slow Start (Valid values:0 - 600)
Share SubVS Persistence	<input type="checkbox"/>
Log Insight Message Split Interval	<input type="text" value="10"/> Set Log Split Interval (Valid values:1 - 100)
Include User Agent Header in User Logs	<input type="checkbox"/>
Use CEF Log Format	<input type="checkbox"/>

Allow Connection Scaling over 64K Connections

Under very high load situations, Port Exhaustion can occur. Enabling this option will allow the setting of Alternate Source Addresses which can be used to expand the number of local ports available.

If more than 64K concurrent connections are required, enable the **Allow Connection Scaling over 64K Connections** option and set the Virtual Service IP as the alternate address in the **Alternate Source Addresses** input field. This allows each Virtual Service to have its own pool of source ports.

Transparent Virtual Services are capped at 64K concurrent connections. This limit is on a per Virtual Service basis.

If, after selecting this option, you set some Alternate Source Addresses, you will not be able to deselect the **Allow connection scaling over 64K Connections** option.

Always Check Persist

By default, the L7 module will only check persist on the first request of a HTTP/1.1 connection. Selecting **Yes** for this option will check the persistence on every request. Selecting **Yes – Accept Changes** means that all persistence changes will be saved, even in the middle of a connection.

Add Port to Active Cookie

When using active cookies, the LoadMaster creates the cookie from (among other things) the IP address of the client. However, if many clients are behind a proxy server, all of those clients come from the same IP address. Turning this on adds the clients source port to the string as well, making it more random.

Conform to RFC

This option addresses parsing the header of a HTTP request in conformance with RFC 1738.

The request consists of 3 parts: GET /pathname HTTP/1.1 and when "conform" is on, the LoadMaster scans through the pathname until it finds a space. It then presumes that the next thing is HTTP/1.x. If the pathname contains spaces and the browser is conformant to the RFC, the pathname will have the spaces escaped to "%20" so the scan for a space will function correctly.

However, on some non-conformant browsers, spaces are not escaped and the wrong pathname is processed. And since the system cannot find the HTTP/1.x, the LoadMaster will reject the request.

Turning off this feature forces the LoadMaster to assume that the pathname extends to the last space on the line. It is then assumed that what follows is HTTP/1.x. So making pathnames with spaces in them useable – however, it is non-conformant to the RFC 1738.

Close on Error

If the LoadMaster has to send back a failure report to the client, for example if a file is newer in the cache; this forces the LoadMaster to close the connection after sending the response. You can continue using the connection after sending a failure report, but some systems could become confused. This option forces the close instead of continuing.

Add Via Header In Cache Responses

The relevant HTTP RFC states that proxies should add a Via header to indicate that something came from the cache. Unfortunately, older LoadMaster versions did not do this. This check box is used to enable backward compatibility with older versions (if needed).

Real Servers are Local

The LoadMaster has an automatic detection of local/non-local clients for the purpose of transparency (selective transparency). This works well in most cases, but it does not work well if the client is actually a Real Server. Turning this option on helps the LoadMaster to determine that a Real Server is actually local, therefore making selective transparency work.

When this option is enabled in a two-armed environment (with clients and Real Servers on the second interface) the Real Servers are treated as if they are local to the clients, that is, non-transparent. If the Real Servers are on a completely different network, then they cannot be local and will always be treated as not local. Local is defined as being on the same network.

Enabling this option requires careful network topology planning and should not be attempted before contacting the Kemp Support team.

Drop Connections on RS Failure

This is useful for Microsoft Outlook users whereby it closes the connection immediately when a Real Server failure is detected.

Exchange users should always select this option. The **Idle Connection Timeout** option is also set to 86400 at the same time. For further information, refer to the **Microsoft Exchange 2010 Deployment Guide** on the [Kemp Documentation Page](#).

Drop at Drain Time End

If enabled, all open connections to disabled Real Servers will be dropped at the end of the Real Servers Drain Stop Time or immediately if there are no persist entries associated with the Real Server.

L7 Authentication Timeout (secs)

This option supports the integration with 3rd party, multi-factor, authentication solutions which may have secondary processes such as SMS or telephone verification. This setting determines how long (in seconds) the SSO form waits for authentication verification to complete before timing out.

L7 Client Token Timeout (secs)

The duration of time (in seconds) to wait for the client token while the process of authentication is ongoing (used for RSA SecurID authentication). The range of valid values is 60 to 300. The default value is 120.

L7 Connection Drain Time (secs)

L7 Connection Drain Time impacts only new connections. Existing connections continue relaying application data to a disabled server until that connection is terminated, unless the **Drop at Drain Time End** checkbox is selected.

Setting the **L7 Connection Drain Time (secs)** to **0** forces all the connections to be dropped immediately when a Real Server is disabled.

If the service is operating at Layer 4, drain stop does not apply. In this case, the persistence record is discarded, the connection is scheduled to an enabled and healthy server and a new persistence record is created.

When you disable the Real Server, it does not close all connections immediately - it is a gentle close down. New connections will not go to the Real Server during the drain time unless there is a valid persistence record for it. When the drain time expires, if **Drop at Drain Time End** is selected, all existing connections are forcibly removed. Otherwise, the connection remains open. The drain stop timer does not impact existing connections unless **Drop at Drain Time End** is enabled.

The drain stop timer does not impact existing connections.

Additional L7 Header

This enables Layer 7 header injection for HTTP/HTTPS Virtual Services. Header injection can be set to **X-ClientSide** (Kemp LoadMaster specific), **X-Forwarded-For**, or **None**. The default value is **X-Forwarded-For**.

100-Continue Handling

Determines how **100-Continue Handling** messages are handled. The available options are:

- **RFC-2616 Compliant:** conforms with the behavior as outlined in RFC-2616
- **Require 100-Continue:** forces the LoadMaster to wait for the 100-Continue message

- **RFC-7231 Compliant:** ensures the LoadMaster does not wait for 100-Continue messages. This is the default value.

Modifying how 100 Continue messages are handled by the system requires an understanding of the relevant technologies as described in the RFCs listed above. It is recommended that you speak with a Kemp Technical Support engineer before making changes to these settings.

Allow Empty POSTs

By default the LoadMaster blocks POSTs that do not contain a Content-Length or Transfer-Encoding header to indicate the length of the requests payload. When the **Allow Empty POSTs** option is enabled, such requests are assumed to have no payload data and are therefore not rejected.

In version 7.1-24 and later releases, the supported Content-Length limit has been increased to 2TB (from 2GB).

Force Complete RS Match

By default, when the LoadMaster is trying to locate a Real Server for use with content switching, it tries to use the same Real Server as currently selected, even if the port is not the same. Enabling this option forces the port to also be compared.

Least Connection Slow Start

When using the **Least Connection** or **Weighted Least Connection** scheduling methods, a period can be specified during which the number of connections are restricted to a Real Server which has come online and gradually increased. This ensures that the Real Server is not overloaded with an initial flood of connections.

The value of this **Slow Start** period can be between **0** and **600** seconds.

Share SubVS Persistence

By default, each SubVS of a Virtual Service has an independent persistence table. Enabling this option will allow the SubVS to share this information. For this to work, the persistence mode must be the same on all SubVSs within that Virtual Service. A reboot is required to activate this option.

The only **Persistence Mode** that cannot be shared is **SSL Session ID**.

When setting up shared SubVS persistence, there are some requirements to get this feature fully functional:

- All Real Servers in the SubVS need to be the same
- The **Persistence Mode** needs to be the same across all SubVSs
- The timeouts need to be set with the same timeout value

If the above requirements are not correct, the persistence may not work correctly either within the SubVS or across the SubVSs.

Log Insight Message Split Interval

The **Log Insight Split Interval** value controls how many syslog messages should be sent to each server in the pool before moving to the next server. For example, if there are three Log Insight nodes and the **Log Insight Message Split Interval** is set to **1** - a single message is sent to server A, and then to server B and then server C before again distributing a message to server A.

Include User Agent Header in User Logs

When enabled, the User Agent header field gets added to the User Logs.

Use CEF Log Format

When enabled, the ESP logs are generated in Common Event Format (CEF). CEF log format is easily consumable for Security Information and Event Management (SIEM) tools, such as; Splunk, SolarWinds, LogRhythm, AlienVault, and so on.

9.5.3 Network Options

Enable Server NAT	<input checked="" type="checkbox"/>
Connection Timeout (secs)	660 Set Time (Valid values:0, 60-86400)
Enable Non-Local Real Servers	<input checked="" type="checkbox"/>
Enable Alternate GW support	<input type="checkbox"/>
Enable TCP Timestamps	<input type="checkbox"/>
Enable TCP Keepalives	<input checked="" type="checkbox"/>
Enable Reset on Close	<input type="checkbox"/>
Subnet Originating Requests	<input type="checkbox"/>
Enforce Strict IP Routing	<input type="checkbox"/>
Handle non HTTP Uploads	<input type="checkbox"/>
Enable Connection Timeout Diagnostics	<input type="checkbox"/>
Legacy TCP Timewait handling	<input type="checkbox"/>
Enable SSL Renegotiation	<input checked="" type="checkbox"/>
Force Real Server Certificate Checking	<input type="checkbox"/>
Size of SSL Diffie-Hellman Key Exchange	2048 Bits ▼
Use Default Route Only	<input type="checkbox"/>
HTTP(S) Proxy	<input type="text"/> Set HTTP(S) Proxy

Enable Server NAT

This option enables Server Network Address Translation (SNAT). If this is disabled, the Real Server IP address is used when connecting.

If this is enabled, addresses that are of the same address family (IPv4/IPv6) as the primary address of the default gateway are NATed to the “primary address”. If the **Use Address for Server NAT** is enabled in the Virtual Service, the Virtual Service address will be used. For further information on the **Use Address for Server NAT** option, refer to the **Standard Options** section.

If the source address is not in the same family as the primary address, then the address will be SNATed to the first additional address which is on the same network as the default gateway for that address family.

For example, if the primary address of the default interface is an IPv6 address, then IPv6 addresses will be SNATed to that address. If the primary address is an IPv4 address, then IPv6 addresses will be SNATed to the first additional address (IPv6) which is on the same network as the IPv6 default gateway.

Similarly, if the primary address of the default interface is an IPv4 address, then IPv4 addresses will be SNATed to that address. If the primary address is an IPv6 address, then IPv4 addresses will be SNATed to the first additional address (IPv4) which is on the same network as the IPv4 default gateway.

Connection Timeout (secs)

The length of time (in seconds) that a connection may remain idle before it is closed. This value is independent of the Persistence Timeout value.

Setting a value of **0** will reset the value to the default setting of **660** seconds.

Enable Non-Local Real Servers

Allow non-local Real Servers to be assigned to Virtual Services. This may be needed if the LoadMaster can only have one interface and the Real Servers are on a different network to the interface. This option is enabled by default.

Enable Alternate GW support

If there is more than one interface enabled, this option provides the ability to move the default gateway to a different interface.

Enabling this option adds another option to the **Interfaces** screen – **Use for Default Gateway**.

The **Enable Alternate GW support** option will appear on a different screen in GEO only LoadMasters.

Alternate default gateway support is not permitted in a cloud environment.

Enable TCP Timestamps

The LoadMaster can include timestamps in the SYN on both connections from clients and connections to Real Servers.

Note this may impact connections that are NATed and should only be enabled on consultation with Kemp Customer Support.

Enable TCP Keepalives

By default the TCP keepalives are enabled which improves the reliability of TCP connections that are long lived (SSH sessions). Keepalives are not usually required for normal HTTP/HTTPS services, but may be required for FTP services, for example.

The keepalive messages are sent from the LoadMaster to the Real Server and to the client. Therefore, if the client is on a mobile network, there may be an issue with additional data traffic.

Enable Reset on Close

When this setting is disabled (the default), unencrypted and encrypted TCP connections to the LoadMaster on both the client and server sides are closed using the standard TCP exchange of FIN and ACK packets. In situations where a Virtual Service is under a high incoming connection load, the ability to establish new connections to the Virtual Service can be improved by turning on **Enable Reset on Close**; this tells the LoadMaster to close TCP connections with a single TCP RST (reset) packet, rather than the normal TCP closing exchange.

Subnet Originating Requests

With this option enabled, the source IP address of non-transparent requests will come from the LoadMaster's address on the relevant subnet, that is, the subnet where the Real Server is located or the subnet of the gateway that can route to the Real Server (if the Real Server is non-local and configured to use static route). For more information on configuring a static route, refer to the following Kemp knowledge base article: [Creating a Static Route](#).

This is the global option/setting.

It is recommended that the **Subnet Originating Requests** option is enabled on a per-Virtual Service basis.

When the global option is disabled, the per Virtual Service **Subnet Originating Requests** option takes precedence, that is, it can be enabled or disabled per Virtual Service. This can be set in the **Standard Options** section of the Virtual Services properties screen (if **Transparency** is disabled). For more information on the per Virtual Service option, refer to the **Standard Options** section.

If this option is switched on for a Virtual Service that has SSL re-encryption enabled, all connections currently using the Virtual Service will be terminated because the process that handles the connection must be killed and restarted.

Enable Strict IP Routing

When this option is selected, only packets which arrive at the machine over the same interface as the outbound interface are accepted.

The **Use Default Route Only** option may be a better way to achieve this.

Handle non HTTP Uploads

Enabling this option ensures that non HTTP uploads (such as FTP uploads) function correctly.

Enable Connection Timeout Diagnostics

By default, connection timeout logs are not enabled. This is because they may cause too many unnecessary logs. If you wish to generate logs relating to connection timeouts, select the **Enable Connection Timeout** check box.

Legacy TCP Timewait Handling

Enable this option to revert to the legacy mode of reusing TCP timewait connections.

Only enable the **Legacy TCP Timewait Handling** option after consulting with Kemp Support.

Enable SSL Renegotiation

By default, the LoadMaster allows a client to automatically renegotiate during an SSL transaction. Unchecking this option causes SSL connections to terminate if a renegotiation is requested by the client.

Force Real Server Certificate Checking

By default, when re-encrypting traffic the LoadMaster does not check the certificate provided by the Real Server. This option forces the LoadMaster to verify that the certificate on the Real Server is valid, that is, the certificate authority and expiration are OK. This includes all intermediate certificates.

Size of SSL Diffie-Hellman Key Exchange

Select the strength of the key used in the Diffie-Hellman key exchanges. If this value is changed, a reboot is required to use the new value. The default value is **2048 Bits**.

Log SSL errors

Set the level of SSL error reporting in the logs. By default, this is set to the recommended setting of **Fatal errors only**, which means that only errors that indicate an SSL failure (such as a failed SSL handshake) are logged. You can increase the verbosity of SSL error logging by setting this value to either of the following:

- **Include Client errors** – this setting logs all client errors reported to the LoadMaster.
- **All errors** – this setting logs all SSL errors observed in the LoadMaster, including all common alerts and warnings that may or may not indicate an actual issue.

Use Default Route Only

Forces traffic from Virtual Services that have default route entries set, to be only routed to the interface where the Virtual Service's default route is located. This setting can allow the LoadMaster to be directly connected to client networks without returning traffic directly using the adjacent interface.

Enabling this option affects all Virtual Services in the same network.

HTTP(S) Proxy

This option allows clients to specify the HTTP(S) proxy server and port the LoadMaster will use to access the internet.

9.5.4 AFE Configuration

Cache Configuration	
Maximum Cache Size	<input type="text" value="100"/> <input type="button" value="Set Size"/> (Valid values:1 - 409)
Cache Virtual Hosts	<input checked="" type="checkbox"/>
File extensions that should not be cached:	<input type="text"/> <input type="button" value="Add"/>
.aspx .jsp .php .shtml	<input type="button" value="No Entry"/> <input type="button" value="Delete"/>
Compression Options	
File extensions that should not be compressed:	<input type="text"/> <input type="button" value="Add"/>
.asf .gif .gz .jpeg .jpg .mov .mp3 .mp4 .mpe .mpeg .mpg .pdf .png .swf .tgz .wav .wma .wmv .z .zip	<input type="button" value="No Entry"/> <input type="button" value="Delete"/>
Intrusion Detection Options	
Detection Rules	<input type="button" value="Choose File"/> No file chosen <input type="button" value="Install new Rules"/>
Detection level	<input type="text" value="Default - Only Critical problems are rejected"/>
Client Limiting	
Client Connection Limiter	<input type="text" value="0"/> <input type="button" value="Set Limit"/> (Valid values:0 - 1000000)

Maximum Cache Size

This defines how much memory can be utilized by the cache in megabytes. The **Maximum Cache Size** defines how much of the main memory should be assigned to the cache. It can never be more than one fifth of the total memory of the machine. Assigning more memory for the cache will reduce the amount of memory available for connections and persist entries. In a system that is correctly configured, there should be enough memory for a full cache and all connections that the system that is expected to handle. If this is not the case, the system could run out of memory.

Cache Virtual Hosts

When this option is disabled, the cache presumes there is only one virtual host supported on the Real Server. Enabling this option allows the cache to support multiple virtual hosts which have different content.

File Extensions Not to Cache

A list of files types that should not be cached.

File Extensions Not to Compress

A list of file types that should not be compressed.

Detection Rules

Select the relevant detection rules and click the **Install New Rules** button to install them.

If you are implementing SNORT rules, please remember the following:

- The destination port must be \$HTTP_PORTS
- A 'msg' may be optionally set
- The flow must be set to 'to_server,established'
- The actual filter may be either 'content' or 'pcre'
- Additional 'http_' parameters may be set
- The classtype must be set to a valid value

To get updated or customized SNORT rules, please refer to the SNORT website: <https://www.snort.org/>.

Detection Level

Supports four levels of what to do when problems are encountered:

- **Low** – only logging with no rejection
- **Default** – only critical problems rejected
- **High** – Serious and critical problems rejected
- **Paranoid** – All detected problems rejected

The four levels of severity are classified according to the classtype value in the SNORT rules configuration file. If the severity is less than the configured value, a diagnostic is generated and the call is dropped. The levels of severity correspond to the following values - **Low** = 1, **Default** = 2, and **High** = 3. You can view the SNORT rule classtypes and their corresponding values in the table below.

Classtype	Value
not-suspicious	3
unknown	3
bad-unknown	2
attempted-recon	2

successful-recon-limited	2
successful-recon-largescale	2
attempted-dos	2
successful-dos	2
attempted-user	1
unsuccessful-user	1
successful-user	1
attempted-admin	1
successful-admin	1
rpc-portmap-decode	2
shellcode-detect	1
string-detect	3
suspicious-filename-detect	2
suspicious-login	2
system-call-detect	2
trojan-activity	1
unusual-client-port-connection	2
network-scan	3
denial-of-service	2
non-standard-protocol	2
protocol-command-decode	3
web-application-activity	2
web-application-attack	1
misc-activity	3
misc-attack	2
icmp-event	3

kickass-porn	1
inappropriate-content	1
policy-violation	1
default-login-attempt	2
sdf	2

Client Limiting

It is possible to set a limit of the number of connections per second from a given host (limits up to 100K are allowed). After setting the "default limit" to a value, the system allows you to set different limits for specific hosts/networks so you can limit a network and/or host.

If you set a network and a host on that network, the host should be placed first since the list is processed in the order that it is displayed.

To turn client limiting off, set the **Client Connection Limiter** value to **0**.

9.5.5 Kemp 360 Central Activation Settings

Kemp 360 Central Address

Host:

Port:

Activate

✓ Last activation check: 07/30/19 09:52:08

Deactivate VLM instance

Deactivate

To view the Kemp 360 Central Activation Settings, click **System Configuration > Miscellaneous Options > Kemp 360 Central Activation Settings**. If the LoadMaster is already licensed from Kemp 360 Central, the Kemp 360 Central IP address and port appear here. If blank, you can use the controls on this page to provide the IP address and port of a Kemp 360 Central deployment from which you want to request a license. By activating your LoadMaster here, it is automatically added to Kemp 360 Central and the system can start obtaining statistics from it immediately.

The **Deactivation** button removes the current license from the LoadMaster, returning the LoadMaster to an unlicensed state. This stops any active traffic to the LoadMaster, and so should be invoked with great caution.

For more information, refer to the [Kemp 360 Central Feature Description](#) on the [Kemp Documentation Page](#).

10 Help

Documentation

Technical documentation for LoadMaster including technical notes, configuration guides and deployment guides are available on Kemp's Help Center.
[Documentation](#)

Knowledge Base

Learn from Kemp Customer Support and your peers how to get the most out of your products and solve common challenges.
[Knowledge Base](#)

Customer Support

Engage with our customer support team to open a ticket or get help optimizing your application deployment.
[Contact Support](#)

Software Updates

Get the latest information about firmware releases, hotfixes and new application templates.
[Get the Latest](#)

Feature Requests

Have an idea about how to make Kemp products better? We'd love to hear about it.
[Submit Feature Request](#)

Kemp 360

Learn how Kemp 360 can help you streamline application delivery automation, management, outage prevention and time to resolution.
[Kemp 360](#)

The **Help** screen provides a consolidated location for access to external Kemp services.

Documentation

Access the Kemp technical documentation, including Deployment Guides, Installation Guides, Feature Descriptions, Technical Notes, Overviews, Release Notes, and Interface Descriptions.

Knowledge Base

Access Knowledge Base articles on a variety of subjects such as SSO/ESP, Fault Tolerance, Operational Maintenance, Applications, Security, Platforms, Routing/Switching, and Content Delivery.

Customer Support

Open a ticket with Kemp's Customer Support team.

Software Updates

Get the latest information about firmware releases, hot fixes and new application templates.

Feature Requests

Take a look at existing feature requests submitted by other customers, and raise your own feature request.

Kemp 360

Learn about our Kemp 360 products, which can help to streamline application delivery automation, outage prevention, and time to resolution.

References

Unless otherwise specified, the below documents can be found on <http://kemptechnologies.com/documentation>.

Virtual Services and Templates, Feature Description

RSA Two Factor Authentication, Feature Description

Content Rules, Feature Description

LoadMaster 5.1 to 6.0 Migration, Technical Note

Header Modification Guide, Technical Note

GEO, Feature Description

GEO Sticky DNS, Feature Description

Packet Trace Guide, Technical Note

VMware Tools Add-On Package, Feature Description

Custom Authentication Form, Technical Note

Port Following, Feature Description

SSL Accelerated Services, Feature Description

Kerberos Constrained Delegation, Feature Description

IPsec Tunneling, Feature Description

Kemp LoadMaster, Product Overview

DoD Common Access Card (CAC) Authentication, Feature Description

RESTful API, Interface Description

Licensing, Feature Description

LoadMaster Clustering, Feature Description

MS Exchange 2010, Deployment Guide

User Management, Feature Description

Last Updated Date

This document was last updated on 27 July 2023.