



Blackboard Learn

Deployment Guide

UPDATED: 27 July 2023

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

These materials and all Progress® software products are copyrighted and all rights are reserved by Progress Software Corporation. The information in these materials is subject to change without notice, and Progress Software Corporation assumes no responsibility for any errors that may appear therein. The references in these materials to specific platforms supported are subject to change.

#1 Load Balancer in Price/Performance, 360 Central, 360 Vision, Chef, Chef (and design), Chef Habitat, Chef Infra, Code Can (and design), Compliance at Velocity, Corticon, Corticon.js, DataDirect (and design), DataDirect Cloud, DataDirect Connect, DataDirect Connect64, DataDirect XML Converters, DataDirect XQuery, DataRPM, Defrag This, Deliver More Than Expected, DevReach (and design), Driving Network Visibility, Flowmon, Inspec, Ipswitch, iMacros, K (stylized), Kemp, Kemp (and design), Kendo UI, Kinvey, LoadMaster, MessageWay, MOVEit, NativeChat, OpenEdge, Powered by Chef, Powered by Progress, Progress, Progress Software Developers Network, SequeLink, Sitefinity (and Design), Sitefinity, Sitefinity (and design), Sitefinity Insight, SpeedScript, Stylized Design (Arrow/3D Box logo), Stylized Design (C Chef logo), Stylized Design of Samurai, TeamPulse, Telerik, Telerik (and design), Test Studio, WebSpeed, WhatsConfigured, WhatsConnected, WhatsUp, and WS_FTP are registered trademarks of Progress Software Corporation or one of its affiliates or subsidiaries in the U.S. and/or other countries.

Analytics360, AppServer, BusinessEdge, Chef Automate, Chef Compliance, Chef Desktop, Chef Workstation, Corticon Rules, Data Access, DataDirect Autonomous REST Connector, DataDirect Spy, DevCraft, Fiddler, Fiddler Classic, Fiddler Everywhere, Fiddler Jam, FiddlerCap, FiddlerCore, FiddlerScript, Hybrid Data Pipeline, iMail, InstaRelinker, JustAssembly, JustDecompile, JustMock, KendoReact, OpenAccess, PASOE, Pro2, ProDataSet, Progress Results, Progress Software, ProVision, PSE Pro, Push Jobs, SafeSpaceVR, Sitefinity Cloud, Sitefinity CMS, Sitefinity Digital Experience Cloud, Sitefinity Feather, Sitefinity Thunder, SmartBrowser, SmartComponent, SmartDataBrowser, SmartDataObjects, SmartDataView, SmartDialog, SmartFolder, SmartFrame, SmartObjects, SmartPanel, SmartQuery, SmartViewer, SmartWindow, Supermarket, SupportLink, Unite UX, and WebClient are trademarks or service marks of Progress Software Corporation and/or its subsidiaries or affiliates in the U.S. and other countries. Java is a registered trademark of Oracle and/or its affiliates. Any other marks contained herein may be trademarks of their respective owners.

Please refer to the NOTICE.txt or Release Notes – Third-Party Acknowledgements file applicable to a particular Progress product/hosted service offering release for any related required third-party acknowledgements.

Table of Contents

1 Introduction	4
1.1 Document Purpose	4
1.2 Intended Audience	4
1.3 Prerequisites	4
2 Template	5
3 Load Balancing Blackboard Learn™	6
3.1 Configure the LoadMaster	7
3.1.1 Configure Global Settings	7
3.1.1.1 L7 Configuration	7
3.1.1.2 Enable Subnet Originating Requests Globally	8
3.1.2 Configure a Content Rule for the HTTPS Virtual Service	9
3.1.3 Configure the Virtual Services	10
3.1.3.1 Configure a HTTP Virtual Service	10
3.1.3.2 Configure a HTTPS Virtual Service	12
References	16
Last Updated Date	17

1 Introduction

Blackboard Learn™ is a Learning Management System (LMS) developed by Blackboard Inc. It is web-based server software which features course management, customizable open architecture and scalable design that allows integration with student information systems and authentication protocols. Its main purpose is to add online elements to courses which are traditionally delivered face-to-face and develop completely online courses with little or no face-to-face meetings.

To improve performance and provide High Availability (HA), Blackboard Learn™ supports using a hardware or software load balancer and multiple application servers. The Kemp LoadMaster can be used to load balance Blackboard Learn™ traffic.

1.1 Document Purpose

The purpose of this document is to describe how to configure the LoadMaster to load balance Blackboard Learn™. This document is based on Blackboard Learn 9.1 SP8. Kemp supports other versions of Learn, but there may be some features that do not work with older versions of Learn.

1.2 Intended Audience

This document is intended to be used by anyone who is interested in finding out how to configure the LoadMaster to load balance Blackboard Learn™.

1.3 Prerequisites

The following prerequisites must be satisfied before configuring the LoadMaster to work with Blackboard Learn™:

- The Blackboard Learn™ application must be deployed and successfully tested
- The Application Servers must have the relevant JDK and JRE installed.
- A Microsoft SQL Server must be installed

For additional information about the prerequisites, please refer to the [Blackboard Learn, Installation Guide](#).

2 Template


Kemp has developed a template containing our recommended settings for this workload. You can install this template to help create Virtual Services (VSs) because it automatically populates the settings. You can use the template to easily create the required VSs with the recommended settings. For some workloads, additional manual steps may be required such as assigning a certificate or applying port following, these steps are covered in the document, if needed.

You can remove templates after use and this will not affect deployed services. If needed, you can make changes to any of the VS settings after using the template.

Download released templates from the following page: [LoadMaster Templates](#).

For more information and steps on how to import and use templates, refer to the [Virtual Services and Templates, Feature Description](#) on the Kemp Documentation page.

3 Load Balancing Blackboard Learn™



The above diagram depicts a typical load-balanced configuration. Load-balanced configurations include multiple application servers, a database server (or failover cluster), a file system server and a collaboration server. A network switch is used to handle communications from the client machines to the application servers and the collaboration server. A separate switch is used to handle a secure, private connection between the application servers and the file system and database servers. The database and file system must be on a secure, private network.

The LoadMaster is primarily used for load balancing and providing HA for the web/application servers and collaboration servers. The collaboration server can also be optionally load balanced. For more information on how to load balance the collaboration server, refer to this link:

https://help.blackboard.com/en-us/Learn/9.1_2014_04/Administrator/070_Server_Management_and_Integrations/Performance_Optimization/Load_Balancing_-_Configuration_and_Best_Practices

The diagram above also shows integration with an LDAP server (or servers) to handle authentication and a Student Information System (SIS) to share data with Blackboard Learn™.

3.1 Configure the LoadMaster

The following sections describe how to configure the LoadMaster and associated Virtual Services.

3.1.1 Configure Global Settings

The following sections explain how to configure various settings globally.

3.1.1.1 L7 Configuration

The **Additional L7 Header** field in the LoadMaster must be set to **X-Forwarded-For**. To do this, follow the steps below in the LoadMaster Web User Interface (WUI):

1. In the main menu of the WUI, go to **System Configuration > Miscellaneous Options > L7 Configuration**.

3 Load Balancing Blackboard Learn™

Allow connection scaling over 64K Connections	<input type="checkbox"/>
Always Check Persist	No ▼
Add Port to Active Cookie	<input type="checkbox"/>
Conform to RFC	<input checked="" type="checkbox"/>
Close on Error	<input type="checkbox"/>
Add Via Header In Cache Responses	<input type="checkbox"/>
Real Servers are Local	<input type="checkbox"/>
Drop Connections on RS failure	<input type="checkbox"/>
Drop at Drain Time End	<input type="checkbox"/>
L7 Connection Drain Time (secs)	300 Set Time (Valid values:0, 60 - 86400)
L7 Authentication Timeout (secs)	30 Set Timeout (Valid values:30 - 300)
L7 Client Token Timeout (secs)	120 Set Timeout (Valid values:60 - 300)
Additional L7 Header	X-Forwarded-For ▼
100-Continue Handling	RFC-7231 Compliant ▼
Allow Empty POSTs	<input type="checkbox"/>
Allow Empty HTTP Headers	<input type="checkbox"/>
Force Complete RS Match	<input type="checkbox"/>
Least Connection Slow Start	0 Set Slow Start (Valid values:0 - 600)
Share SubVS Persistence	<input type="checkbox"/>
Log Insight Message Split Interval	10 Set Log Split Interval (Valid values:1 - 100)
Include User Agent Header in User Logs	<input type="checkbox"/>
Use CEF Log Format	<input type="checkbox"/>

2. Select **X-Forwarded-For** as the **Additional L7 Header**.

The Blackboard Learn™ server must be configured to look at this header. If you are using IIS, an Internet Server Application (ISAPI) filter must be used to see the X-Forwarded-For header.

3.1.1.2 Enable Subnet Originating Requests Globally

It is best practice to enable the **Subnet Originating Requests** option globally.

In a one-armed setup (where the Virtual Service and Real Servers are on the same network/subnet) **Subnet Originating Requests** is usually not needed. However, enabling **Subnet Originating Requests** should not affect the routing in a one-armed setup.


In a two-armed setup where the Virtual Service is on network/subnet A, for example, and the Real Servers are on network B, **Subnet Originating Requests** should be enabled on LoadMasters with firmware version 7.1-16 and above.

When **Subnet Originating Requests** is enabled, the LoadMaster routes traffic so that the Real Server sees traffic arriving from the LoadMaster interface that is in that network/subnet.

When **Subnet Originating Requests** is enabled globally, it is automatically enabled on all Virtual Services. If the **Subnet Originating Requests** option is disabled globally, you can choose whether to enable **Subnet Originating Requests** on a per-Virtual Service basis.

To enable **Subnet Originating Requests** globally, follow the steps below:

1. In the main menu of the LoadMaster Web User Interface (WUI), go to **System Configuration > Miscellaneous Options > Network Options**.



The screenshot shows the 'Network Options' configuration page in the LoadMaster WUI. The 'Subnet Originating Requests' checkbox is checked. Other visible options include 'Enable Server NAT' (checked), 'Connection Timeout (secs)' (660), 'Enable Non-Local Real Servers' (checked), 'Enable Alternate GW support' (unchecked), 'Enable TCP Timestamps' (unchecked), 'Enable TCP Keepalives' (checked), 'Enable Reset on Close' (unchecked), 'Enforce Strict IP Routing' (unchecked), 'Handle non HTTP Uploads' (unchecked), 'Enable Connection Timeout Diagnostics' (unchecked), 'Legacy TCP Timewait handling' (unchecked), 'Enable SSL Renegotiation' (checked), 'Force Real Server Certificate Checking' (unchecked), 'Size of SSL Diffie-Hellman Key Exchange' (2048 Bits), 'Log SSL errors' (Fatal errors only), 'Use Default Route Only' (unchecked), and 'HTTP(S) Proxy' (empty).

2. Select the **Subnet Originating Requests** check box.

3.1.2 Configure a Content Rule for the HTTPS Virtual Service

To add a content rule, make the following selections:

1. In the main menu, select **Rules & Checking > Content Rules**.
2. Click the **Create New...** button.

Create Rule

Rule Name	<input type="text" value="X_Forwarded_Proto"/>
Rule Type	<input type="text" value="Add Header"/>
Header Field to be Added	<input type="text" value="X_Forwarded_Proto"/>
Value of Header Field to be Added	<input type="text" value="https"/>
Perform If Flag Set	<input type="text" value="[Unset]"/>
Perform If Flag is NOT Set	<input type="text" value="[Unset]"/>

3. In the Create Rule screen, make the following selections:

- Enter **X_Forwarded_Proto** as the **Rule Name**.
- Select **Add Header** from the **Rule Type** drop-down list.
- Enter **X_Forwarded_Proto** in the **Header Field to be Added** text field.
- Enter **https** as the **Value of Header Field to be Added**.
- Click the **Create Rule** button.

3.1.3 Configure the Virtual Services

Either a HTTP or HTTPS Virtual Service needs to be created and configured in the LoadMaster to load balance Blackboard Learn™. Refer to the relevant section below for step-by-step instructions on how to create the relevant Virtual Service.

3.1.3.1 Configure a HTTP Virtual Service

To configure a HTTP Virtual Service, follow the steps below in the LoadMaster WUI:

1. In the main menu, select **Virtual Services > Add New**.

Please Specify the Parameters for the Virtual Service.

Virtual Address	<input type="text" value="10.154.11.131"/>
Port	<input type="text" value="80"/>
Service Name (Optional)	<input type="text" value="Blackboard Learn HTTP"/>
Use Template	<input type="text" value="Select a Template"/>
Protocol	<input type="text" value="tcp"/>

2. Enter a valid IP address in the **Virtual Address** text box.
3. Enter **80** as the **Port**.
4. Enter a recognizable **Service Name**, such as Blackboard Learn HTTP.
5. Click **Add this Virtual Service**.
6. Expand the **Standard Options** section.
7. Enter the details shown in the following table:

Section	Option	Value	Comments
Standard Options	Transparency	Disabled	
	Persistence Mode	Active Cookie	
	Timeout	4 Hours	If the default timeout (3 hours) in Blackboard Learn™ is increased, the timeout value in the LoadMaster should be higher.
	Cookie name	KempBBCookie	
	Scheduling Method	least connection	
Advanced Properties	Enable Caching	Enabled	
	Maximum	20%	

Section	Option	Value	Comments
	Cache usage		
	Enable Compression	Enabled	
	Add HTTP Headers	X-Forwarded-For (+Via)	
Real Servers	Real Server Check Parameters	HTTP Protocol	
	URL	/webapps/portal/healthCheck	Click Set URL then click New .

8. Enter the relevant **Real Server Address**.

This is the address of the backend server.

9. Enter **80** as the **Port**.

The **Port**, **Forwarding method** and **Weight** values are set by default. These can be changed by an administrator.

10. Click **Add This Real Server**.

11. Repeat steps **8** to **10** to add more Real Servers, as needed.

3.1.3.2 Configure a HTTPS Virtual Service

SSL offloading must also be configured on the Blackboard Learn™ servers. To find out how to configure SSL offloading on the Blackboard Learn™ servers, refer to the following page:

http://library.blackboard.com/ref/df5b20ed-ce8d-4428-a595-a0091b23dda3/Content/_admin_server_ssl/ssl_about.htm

Kemp only supports SSL offloading on Blackboard Learn version 9.1 SP8 and above.

To configure a HTTPS Virtual Service, follow the steps below in the LoadMaster WUI:

12. In the main menu, select **Virtual Services > Add New**.

Please Specify the Parameters for the Virtual Service.

Virtual Address	<input type="text" value="10.11.0.34"/>
Port	<input type="text" value="443"/>
Service Name (Optional)	<input type="text" value="Blackboard Learn HTTP"/>
Use Template	<input type="text" value="Select a Template"/>
Protocol	<input type="text" value="tcp"/>

13. Enter a valid **Virtual Address**.

14. Enter **443** as the **Port**.

15. Enter a recognizable **Service Name**, for example **Blackboard Learn HTTPS**.

16. Click **Add this Virtual Service**.

17. Enter the details shown in the following table:

Section	Option	Value	Comments
SSL Properties	Enabled	Selected	
Standard Options	Transparency	Disabled	
	Persistence Mode	Active Cookie	
	Timeout	4 Hours	If the default timeout (3 hours) in Blackboard Learn™ is increased, the timeout value in the LoadMaster should be higher.
	Cookie name	KempBBCookie	Click Set Cookie .
	Scheduling Method	least connection	
Real Servers	Real Server Check Parameters	HTTP Protocol	
	URL	/webapps/portal/healthCheck	Click Set URL then click New .

18. Enter the relevant **Real Server Address**.

This is the address of the backend server.

19. Enter **80** as the **Port**.

The **Forwarding method** and **Weight** values are set by default. These can be changed by an administrator.

20. Click **Add This Real Server**.

21. Repeat steps **7** to **9** to add any other Real Servers as needed.

22. Expand the **Advanced Properties** section.

▼ Advanced Properties

Content Switching

Disabled **Enable**

HTTP Selection Rules

Show Selection Rules

HTTP Header Modifications

Show Header Rules (1 Request)

Response Body Modification

Show Body Modification Rules

Support HTTP/2

☐

Enable Caching

☒ Maximum Cache usage Current usage assigned 20%

Enable Compression

☒

Detect Malicious Requests

☐

Add Header to Request

: **Set Header**

Copy Header in Request

To Header **Set Headers**

Add HTTP Headers

Set Server Address

"Sorry" Server

Port **Set Server Address**

Not Available Redirection Handling

Error Code: **Set Redirect URL**

Redirect URL:

Set Redirect URL

Default Gateway

Set Default Gateway

Service Specific Access Control

Access Control

In the **Advanced Properties** section, make the following selections:

23. Select **No VIP Selected** from the **Port Following** drop-down list.

24. Select the **Enable Caching** check box.

Request Rules

Add Rule

Rule:

25. Add the content rule added in the **Configure a Content Rule for the HTTPS Virtual Service** section.

- Click the **Show Header Rules** button.
- In the **Request Rules** section, expand the **Rule** drop-down list.
- Select the **X_Forwarded_Proto** rule.
- Click **Add**.

26. Select **20%** as the **Maximum Cache** usage.

27. Select the **Enable Compression** check box.

28. Select **X-Forwarded-For (+Via)** from the **Add HTTP Headers** drop-down list.

29. Click the **Add HTTP Redirector** button.

30. Expand the **Real Servers** section.

▼ Real Servers

Real Server Check Parameters

HTTP Protocol

Checked Port

Set Check Port

URL:

/webapps/portal/healthCheck

Set URL

Status Codes:

Set Status Codes

Use HTTP/1.1:

☐

HTTP Method:

HEAD

Custom Headers:

Show Headers

Enhanced Options:

☐

References

For further information, refer to the following links:

Blackboard Learn Performance Optimization Guide

<http://library.blackboard.com/d/?6692a745-b472-4360-b004-3c69b58c2b44>

Blackboard Load Balancer Guidelines

http://library.blackboard.com/ref/df5b20ed-ce8d-4428-a595-a0091b23dda3/Content/_admin_server_planning/planning_load_balance.htm

Blackboard – About SSL and SSL Choice

http://library.blackboard.com/ref/df5b20ed-ce8d-4428-a595-a0091b23dda3/Content/_admin_server_ssl/ssl_about.htm

Blackboard – Load Balancing – Configuration and Best Practices

https://help.blackboard.com/en-us/Learn/9.1_2014_04/Administrator/070_Server_Management_and_Integrations/Performance_Optimization/Load_Balancing_-_Configuration_and_Best_Practices

Blackboard – Set up the Hardware Load Balancer

http://library.blackboard.com/ref/df5b20ed-ce8d-4428-a595-a0091b23dda3/Content/_admin_server_install/install_load_balancer.htm

Web User Interface (WUI), Configuration Guide

[Web User Interface \(WUI\), Configuration Guide](#)

Blackboard Learn, Installation Guide

<http://www.google.com/url?sa=t&rct=j&q=blackboard%20learn%209.1%20installation%20guide&source=web&cd=1&ved=0CBoQFjAA&url=http%3A%2F%2Flibrary.blackboard.com%2Fd%2F%3F6968c5f7-7cb7-4251-87a0-d36f2b4c5bf5&ei=gWq8TpSqJcGlgwfgg9SjBw&usg=AFQjCNHnEqRJdrzNJJO8Ss7YVxgaMEwMVw&cad=rja>

Last Updated Date

This document was last updated on 27 July 2023.