

MS Lync 2013

Deployment Guide

UPDATED: 28 July 2023

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

These materials and all Progress® software products are copyrighted and all rights are reserved by Progress Software Corporation. The information in these materials is subject to change without notice, and Progress Software Corporation assumes no responsibility for any errors that may appear therein. The references in these materials to specific platforms supported are subject to change.

#1 Load Balancer in Price/Performance, 360 Central, 360 Vision, Chef, Chef (and design), Chef Habitat, Chef Infra, Code Can (and design), Compliance at Velocity, Corticon, Corticon.js, DataDirect (and design), DataDirect Cloud, DataDirect Connect, DataDirect Connect64, DataDirect XML Converters, DataDirect XQuery, DataRPM, Defrag This, Deliver More Than Expected, DevReach (and design), Driving Network Visibility, Flowmon, Inspec, Ipswitch, iMacros, K (stylized), Kemp, Kemp (and design), Kendo UI, Kinvey, LoadMaster, MessageWay, MOVEit, NativeChat, OpenEdge, Powered by Chef, Powered by Progress, Progress, Progress Software Developers Network, SequeLink, Sitefinity (and Design), Sitefinity, Sitefinity (and design), Sitefinity Insight, SpeedScript, Stylized Design (Arrow/3D Box logo), Stylized Design (C Chef logo), Stylized Design of Samurai, TeamPulse, Telerik, Telerik (and design), Test Studio, WebSpeed, WhatsConfigured, WhatsConnected, WhatsUp, and WS_FTP are registered trademarks of Progress Software Corporation or one of its affiliates or subsidiaries in the U.S. and/or other countries.

Analytics360, AppServer, BusinessEdge, Chef Automate, Chef Compliance, Chef Desktop, Chef Workstation, Corticon Rules, Data Access, DataDirect Autonomous REST Connector, DataDirect Spy, DevCraft, Fiddler, Fiddler Classic, Fiddler Everywhere, Fiddler Jam, FiddlerCap, FiddlerCore, FiddlerScript, Hybrid Data Pipeline, iMail, InstaRelinker, JustAssembly, JustDecompile, JustMock, KendoReact, OpenAccess, PASOE, Pro2, ProDataSet, Progress Results, Progress Software, ProVision, PSE Pro, Push Jobs, SafeSpaceVR, Sitefinity Cloud, Sitefinity CMS, Sitefinity Digital Experience Cloud, Sitefinity Feather, Sitefinity Thunder, SmartBrowser, SmartComponent, SmartDataBrowser, SmartDataObjects, SmartDataView, SmartDialog, SmartFolder, SmartFrame, SmartObjects, SmartPanel, SmartQuery, SmartViewer, SmartWindow, Supermarket, SupportLink, Unite UX, and WebClient are trademarks or service marks of Progress Software Corporation and/or its subsidiaries or affiliates in the U.S. and other countries. Java is a registered trademark of Oracle and/or its affiliates. Any other marks contained herein may be trademarks of their respective owners.

Please refer to the NOTICE.txt or Release Notes – Third-Party Acknowledgements file applicable to a particular Progress product/hosted service offering release for any related required third-party acknowledgements.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

Table of Contents

1 Introduction **8**

1.1 Microsoft Lync 2013 8

1.2 Document Purpose 8

1.3 Prerequisites 9

2 Load Balancing Lync 2013 ..... **10**

3 Template **12**

4 General Configuration **13**

4.1 Disable SNAT Globally 13

4.2 Subnet Originating Requests 13

4.3 Change Drop Connections Settings 14

4.4 Increase the Connection Timeout 15

4.5 Connection Scaling For Large Scale Deployments 17

5 Configuring Virtual Services for Lync 2013 ..... **19**

5.1 DNS Only Configuration 19

5.1.1 Director DNS 19

5.1.1.1 Deploy Director DNS Template 20

5.1.1.2 Configure Director DNS Virtual Service 20

5.1.1.2.1 Director DNS Virtual Service Recommended API Settings (optional) 21

5.1.2 Front-End Internal DNS 21

5.1.2.1 Deploy Front-End Internal DNS Template 21

5.1.2.2 Configure Front-End Internal WebSvc HTTP Virtual Service 22

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

5.1.2.2.1 Front-End Internal WebSvc HTTP Virtual Service Recommended API Settings (optional) 22

5.1.2.3 Configure Front-End Internal WebSvc HTTPS Virtual Service 23

5.1.2.3.1 Front-End Internal WebSvc HTTPS Virtual Service Recommended API Settings (optional) 24

5.2 HLB Only Configuration 24

5.2.1 Director HLB Only 24

5.2.1.1 Deploy Director HLB Only Template 24

5.2.1.2 Configure Director Virtual Service 25

5.2.1.2.1 Director HLB Only Virtual Service Recommended API Settings (optional) 25

5.2.1.3 Configure Director SIP Virtual Service 26

5.2.1.3.1 Director SIP Virtual Service Recommended API Settings (optional) 27

5.2.2 Internal Front End HLB Only 27

5.2.2.1 Deploy Internal Front-End HLB Only Template 27

5.2.2.2 Configure Internal Front-End WebSvc HTTP Virtual Service 27

5.2.2.2.1 Internal Front-end WebSvc HTTP Virtual Service Recommended API Settings (optional) 28

5.2.2.3 Configure Internal Front-End WebSvc HTTPS Virtual Service 29

5.2.2.3.1 Internal Front-End WebSvc HTTPS Virtual Service Recommended API Settings (optional) 29

5.2.2.4 Configure Internal Front-End SIP Virtual Service 30

5.2.2.4.1 Internal Front-End SIP Virtual Service Recommended API Settings (optional) 30

5.2.2.5 Configure Internal Front-End DCOM Virtual Service 31

5.2.2.5.1 Internal Front-End DCOM Virtual Service Recommended API Settings 32

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

(optional) .....
5.2.3 Mediation HLB Only 32
5.2.3.1 Deploy Mediation 2013 HLB Only Template 32
5.2.3.2 Configure Mediation Virtual Service 33
5.2.3.2.1 Mediation Virtual Service Recommended API Settings (optional) 33
5.2.4 Edge Internal HLB Only 34
5.2.4.1 Deploy Edge Internal 2013 HLB Only Template 34
5.2.4.2 Configure Edge Internal AV Media TCP Virtual Service 35
5.2.4.2.1 Edge Internal AV Media TCP Virtual Service Recommended API Settings (optional) 35
5.2.4.3 Configure Edge Internal AV Media UDP Virtual Service 36
5.2.4.3.1 Edge Internal AV Media UDP Virtual Service Recommended API Settings (optional) 37
5.2.4.4 Configure Edge Internal SIP Virtual Service_D39 37
5.2.4.4.1 Edge Internal SIP Virtual Service Recommended API Settings (optional) 38
5.3 Edge Configuration 38
5.3.1 Edge External HLB Only 39
5.3.1.1 Deploy Edge External HLB Only Template 39
5.3.1.2 Configure Edge External SIP Virtual Service 39
5.3.1.2.1 Edge External SIP Virtual Service Recommended API Settings (optional) 40
5.3.1.3 Configure Edge External SIP Federation Virtual Service 40
5.3.1.3.1 Edge External SIP Federation Virtual Service Recommended API Settings (optional) 41
5.3.1.4 Configure Edge External XMPP Virtual Service 41

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

5.3.1.4.1 Edge External XMPP Virtual Service Recommended API Settings (optional) 42
5.3.2 Edge External AV HLB Only 43
5.3.2.1 Deploy Edge External AV HLB Only Template 43
5.3.2.2 Configure Edge External AV Media TCP Virtual Service 43
5.3.2.2.1 Edge External AV Media TCP Virtual Service Recommended API Settings (optional) 44
5.3.2.3 Configure Edge External AV Media UDP Virtual Service 44
5.3.2.3.1 Edge External AV Media UDP Virtual Service Recommended API Settings (optional) 45
5.3.3 Edge External Conferencing HLB Only 45
5.3.3.1 Deploy Edge External Conferencing HLB Only Template 45
5.3.3.2 Configure Edge External Conferencing Virtual Service 46
5.3.3.2.1 Edge External Conferencing Virtual Service Recommended API Settings (optional) 46
5.4 Common to Both 47
5.4.1 Office Web App 47
5.4.1.1 Deploy Office Web App Server Template 47
5.4.1.2 Configure Office Web App Virtual Service 48
5.4.1.2.1 Office Web App Servers Virtual Service Recommended API Settings (optional) 48
5.4.2 Director Reverse Proxy 49
5.4.2.1 Deploy Director Reverse Proxy Template 50
5.4.2.2 Configure Director Reverse Proxy HTTP Virtual Service 50
5.4.2.2.1 Director Reverse Proxy HTTP Virtual Service Recommended API Settings (optional) 51

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

5.4.2.3 Configure Director Reverse Proxy HTTPS Virtual Service 51

5.4.2.3.1 Director Reverse Proxy HTTPS Virtual Service Recommended API Settings (optional) 52

5.4.3 Front-End Reverse Proxy 52

5.4.3.1 Deploy Front-End Reverse Proxy Template 53

5.4.3.2 Configure Front-End Reverse Proxy HTTP Virtual Service 53

5.4.3.2.1 Front End Reverse Proxy HTTP Virtual Service Recommended API Settings (optional) 54

5.4.3.3 Configure Front-End Reverse Proxy HTTPS Virtual Service 54

5.4.3.3.1 Front End Reverse Proxy HTTPS Virtual Service Recommended API Settings (optional) 55

6 References **56**

Last Updated Date **57**

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

1 Introduction

Kemp's LoadMaster family of purpose-built hardware and Virtual Appliances (VLM) offer advanced Layer 4 and Layer 7 server load balancing, content switching, SSL Acceleration and a multitude of other advanced Application Delivery and Optimization (ADC) features.

Kemp's LoadMaster fully supports Microsoft's key solutions and are approved by Microsoft (Kemp is a Microsoft Gold partner). The LoadMaster efficiently distributes user traffic for Microsoft Lync 2013 so that users get the best experience possible.

The entire Kemp LoadMaster product family, including the Virtual LoadMaster (VLM) supports Microsoft Lync 2013.

For more information about Kemp, visit us online at www.kemptechnologies.com.

1.1 Microsoft Lync 2013

Microsoft Lync is a communications tool that provides services such as audio/video conferencing, Instant Messaging (IM) and Voice over Internet Protocol (VoIP). These services can all be accessible from the Internet, or from an internal network. Microsoft Lync allows companies to enhance collaboration amongst employees.

A number of enhancements have been made in Microsoft Lync 2013. The network topology setup is quite similar to the previous version but with a number of small differences. Changes include the consolidation of the archiving and monitoring features towards the front-end servers (optional feature). The Lync 2010 Director role is now optional and is not recommended anymore. Less servers are needed because front-end servers can now take the role of Director.

1.2 Document Purpose

This documentation is intended to provide guidance on how to configure Kemp LoadMaster products to provide high availability for a Microsoft Lync Server 2013 environment. This documentation is created using a representative sample environment described later in the document. As this documentation is not intended to cover every possible deployment scenario it may not address unique setup or requirements. The Kemp Support Team is available to provide solutions for scenarios not explicitly defined.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

1.3 Prerequisites

It is assumed that the reader is a network administrator or a person otherwise familiar with networking and general computer terminology. It is further assumed that the Microsoft Lync Server 2013 environment has been set up and the Kemp LoadMaster has been installed.


Other LoadMaster documentation can be referred to as needed from the Kemp Documentation page..

The minimum requirements that should be met before proceeding are as follows:

- Installed LoadMaster LTS firmware version or above
- Configured and published Microsoft Lync Server architecture with Lync Topology builder
- Installed the Microsoft Servers, Active Directories and followed other Microsoft requirements
- Configured internal and external DNS entries for Front-End, Director and Edge pools
- Established access to the LoadMaster Web User Interface (WUI)

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

2 Load Balancing Lync 2013



© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

Deploying a Microsoft Lync environment can require multiple servers in Front-End pools and Edge server pools. Load balancing is necessary in this situation to distribute the traffic amongst these servers.

Microsoft Lync Server 2013 supports two load balancing solutions: DNS load balancing and Hardware Load Balancing (HLB). Hardware load balancers are also required to provide load balancing for the internal and external web services when DNS load balancing is used.

Different load balancing methods cannot be used on the Edge internal and Edge external interfaces, for example, DNS load balancing cannot be used on the Edge internal interface when hardware load balancing is being used on the Edge external interface. Health checking at the LoadMaster ensures that, if one of the servers becomes inaccessible, the load balancer will take the sever offline and automatically re-route and reconnect users to other functioning servers.

Kemp Technology recommend the configuration as depicted in the above diagram**.** If your configuration differs from the recommended configuration and there are issues deploying the LoadMaster, please contact the local Kemp Support Team for assistance.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

3 Template

Kemp has developed a template containing our recommended settings for this workload. You can install this template to help create Virtual Services (VSs) because it automatically populates the settings. You can use the template to easily create the required VSs with the recommended settings. For some workloads, additional manual steps may be required such as assigning a certificate or applying port following, these steps are covered in the document, if needed.

You can remove templates after use and this will not affect deployed services. If needed, you can make changes to any of the VS settings after using the template.

Download released templates from the following page: LoadMaster Templates.

For more information and steps on how to import and use templates, refer to the Virtual Services and Templates, Feature Description on the Kemp Documentation page.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

4 General Configuration

Some recommended general LoadMaster configuration settings are outlined below. These options can be set within the LoadMaster WUI.

4.1 Disable SNAT Globally

By default, global Server Network Address Translation (SNAT) is enabled in the LoadMaster settings. Kemp recommends disabling SNAT globally when using the LoadMaster with a Lync 2013 Edge deployment. To disable SNAT globally, follow the steps below:

1. In the main menu, select **System Configuration**.
2. Select **Miscellaneous Options**.
3. Select **Network Options**.



4. Clear the **Enable Server NAT** check box.

4.2 Subnet Originating Requests

When the LoadMaster is deployed in a two-armed configuration, Kemp recommends enabling **Subnet Originating Requests**. When this option is enabled, the LoadMaster will use its local IP address, instead of the IP address of the Virtual Service, when communicating to the Real Servers.


Subnet Originating Requests can be enabled on a per-Virtual Service or a global basis.

> It is recommended that the **Subnet Originating Requests** option is enabled on a per-Virtual Service basis.

To enable **Subnet Originating Requests** globally, follow the steps below:

1. In the main menu of the LoadMaster WUI, select **System Configuration > Miscellaneous Options > Network Options**.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.




2. Select the **Subnet Originating Requests** check box.

4.3 Change Drop Connections Settings

The LoadMaster must be configured to drop connections on Real Server Failure to have fast failover for clients to another Real Server.

1. To configure dropping connections, click **System Configuration**.
2. Click **Miscellaneous Options**.
3. Click **L7 Configuration**.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.



4. Select the **Drop Connections on RS failure** checkbox.


4.4 Increase the Connection Timeout

The Loadmaster Connection Timeout must be set to one day. The reason why this value can be set so high is because the LoadMaster monitors client connection to Real Servers and if a server fails then the LoadMaster can drop the associated client connections to that real server. Clients are disconnected from the LoadMaster and then reconnected to the LoadMaster to connect to another Real Server.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

One day is the maximum value for this setting and it must be used in conjunction with the **Drop Connections on RS failure** option.

1. To configure the Connection Timeout, click **System Configuration**.
2. Click **Miscellaneous Options**.
3. Click **L7 Configuration**.



4. Enter **86400** (1 day) in the **L7 Connection Drain Time (secs)** field and click **Set Time**.


© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

4.5 Connection Scaling For Large Scale Deployments

Execution of this procedure is optional and should be used only in cases where network traffic is expected to be greater than 64,000 server connections at any one particular time.

L7 Transparency must be disabled to use connection scaling.


1. To use connection scaling, click **System Configuration**.
2. Click **Miscellaneous Options**.
3. Click **L7 Configuration**.



4. Select the **Allow connection scaling over 64K Connections** checkbox.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

5. Click **Virtual Services**.
6. Click **View/Modify Services**.
7. Click the **Modify** button of the appropriate Virtual IP Address.
8. Expand the **Advanced Properties** section.



9. In the **Advanced Properties** panel, input a list of **Alternate Source Addresses**. Multiple IPV4 addresses must be separated with a space; each must be unallocated and allow 64K connections.
10. Click the **Set Alternate Source Addresses** button.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

5 Configuring Virtual Services for Lync 2013

This deployment guide covers three types of Virtual Service; **DNS Only**, **HLB only** and those that are common to both types of environment. To configure the Virtual Services using the Application Programming Interface (API), refer to the RESTful API on the Kemp Documentation Page.

The table in each section outlines the API settings and values. You can use this information when using the Kemp LoadMaster API and automation tools.

5.1 DNS Only Configuration

Refer to the sections below for settings when using a DNS only configuration.

Microsoft recommends that DNS load balancing is used for Session Initiation Protocol (SIP) traffic. Microsoft also recommend that web services are configured to override FQDN for internal web services.

Source-IP Persistence

Source IP persistence can be used but take care before enabling it because:

- Clients from behind a NAT device show up as a single IP
- It can result in uneven connection distribution

Cookies

If cookies are used, there is no negative impact. However, there are some requirements:

- The cookie must be named **MS-WSMAN**
- It must not expire
- It must not be marked httpOnly
- Cookie optimization should be turned off

To find out the recommended API parameter settings for the various Front-End Virtual Services, refer to the sections below.

5.1.1 Director DNS

The **Lync Director DNS** template contains one Virtual Service:


© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

- Lync Director 2013

5.1.1.1 Deploy Director DNS Template

To add the Virtual Services for Lync Director DNS with the template, follow the steps below:

1. Click the **Add New** button.




2. Enter a Virtual Address.
3. Select the **Lync Director 2013 DNS** template from the **Use Template** drop-down list.
4. Click **Add This Virtual Service**.

5.1.1.2 Configure Director DNS Virtual Service

To configure the Lync Director Virtual Service, follow the steps below:

1. Select **View/Modify Services** under **Virtual Services** in the left-hand navigation.



2. Click **Modify** on the **Lync Director** Virtual Service.
3. Expand the **Real Servers** section.
4. Click **Add New**.
5. Enter the **Real Server Address**.
6. Confirm that **Port 443** is entered.
7. Click **Add This Real Server**.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

8. Add additional Real Servers as needed.

5.1.1.2.1 Director DNS Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. These settings can be used with scripts and automation tools.

API Parameters	API Value
port	443
prot	tcp
ForceL7	1
ExtraPorts	444,4443
Transparent	0
Persist	src
PersistTimeout	1200
Useforsnat	1
Schedule	rr
Idletime	1800
CheckType	tcp
CheckPort	5061

5.1.2 Front-End Internal DNS

The **Lync Front-End Internal DNS** template contains two Virtual Service


- Lync Internal WebSvc HTTP
- Lync Internal WebSvc HTTPS

5.1.2.1 Deploy Front-End Internal DNS Template

To add the Virtual Services for Lync Front-End Internal DNS with the template, follow the steps below:

1. Click the **Add New** button.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.




2. Enter a **Virtual Address**.
3. Select the **Lync Internal 2013 DNS** template from the **Use Template** drop-down list.
4. Click **Add This Virtual Service**.

5.1.2.2 Configure Front-End Internal WebSvc HTTP Virtual Service

To configure the Lync Front-End Internal Virtual Service, follow the steps below:

1. Select **View/Modify Services** under **Virtual Services** in the left-hand navigation.



2. Click **Modify** on the **Lync Internal WebSvc HTTP** Virtual Service.
3. Expand the **Real Servers** section.
4. Click **Add New**.
5. Enter the **Real Server Address**.
6. Confirm that **Port 80** is entered.
7. Click **Add This Real Server**.
8. Add additional Real Servers as needed.

5.1.2.2.1 Front-End Internal WebSvc HTTP Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. These settings can be used with scripts and automation tools.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

API Parameter	API Value
port	80
prot	tcp
Transparent	0
Extra Ports	8080
Persist	src
PersistTimeout	1200
Useforsnat	1
Schedule	rr
Idletime	1800
CheckType	tcp
CheckPort	5061

5.1.2.3 Configure Front-End Internal WebSvc HTTPS Virtual Service

To configure the Lync Front-End Internal WebSvc HTTPS Virtual Service, follow the steps below:

1. Select **View/Modify Services** under Virtual Services in the left-hand navigation.



2. Click **Modify** on the **Lync Internal WebSvc HTTPS** Virtual Service.
3. Expand the **Real Servers** section.
4. Click **Add New**.
5. Enter the Real Server Address.
6. Confirm that **Port 443** is entered.
7. Click **Add This Real Server**.
8. Add additional Real Servers as needed.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

5.1.2.3.1 Front-End Internal WebSvc HTTPS Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. These settings can be used with scripts and automation tools.

API Parameter	API Value
port	443
prot	tcp
ExtraPorts	4443
Transparent	0
Persist	src
PersistTimeout	1200
Useforsnat	1
Schedule	rr
Idletime	1800
CheckType	tcp
CheckPort	5061

5.2 HLB Only Configuration

Refer to the sections below for settings using an HLB only configuration.

5.2.1 Director HLB Only

The Lync Director HLB Only template contains two Virtual Services:


- Lync Director
- Lync Internal Director SIP

5.2.1.1 Deploy Director HLB Only Template

To add the Virtual Services for Lync Director HLB Only with the template, follow the steps below:

1. Click the **Add New** button.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.



2. Enter a **Virtual Address**.

3. Select the **Lync Director 2013 HLB Only** template from the **Use Template** drop-down list.

4. Click **Add This Virtual Service**.

5.2.1.2 Configure Director Virtual Service

To configure the Lync Director Virtual Service, follow the steps below:

1. Select **View/Modify Services** under **Virtual Services** in the left-hand navigation.



2. Click **Modify** on the **Lync Director** Virtual Service.

3. Expand the **Real Servers** section.

4. Click **Add New**.

5. Enter the **Real Server Address**.

6. Confirm that **Port 443** is entered.

7. Click **Add This Real Server**.

8. Add additional Real Servers as needed.

5.2.1.2.1 Director HLB Only Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. These settings can be used with scripts and automation tools.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

API Parameter	API Value
port	443
prot	tcp
ExtraPorts	444,4443
Transparent	0
Persist	src
PersistTimeout	1200
Useforsnat	1
Schedule	rr
Idletime	1800
CheckType	tcp
CheckPort	5061

5.2.1.3 Configure Director SIP Virtual Service

To configure the Lync Director SIP Virtual Service, follow the steps below:

1. Select **View/Modify Services** under **Virtual Services** in the left-hand navigation.



2. Click **Modify** on the **Lync Internal Director SIP** Virtual Service.
3. Expand the **Real Servers** section.
4. Click **Add New**.
5. Enter the **Real Server Address**.
6. Confirm that **Port 5061** is entered.
7. Click **Add This Real Server**.
8. Add additional Real Servers as needed.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

5.2.1.3.1 Director SIP Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. These settings can be used with scripts and automation tools.

5.2.2 Internal Front End HLB Only


The **Lync Internal 2013 HLB Only** template contains four Virtual Services:

- Lync Internal WebSvc HTTP
- Lync Internal WebSvc HTTPS HLB Only
- Lync Internal Front-End SIP
- Lync Internal Front-End DCOM

5.2.2.1 Deploy Internal Front-End HLB Only Template

To add the Virtual Services for Lync Internal HLB Only with the template, follow the steps below:

1. Click the **Add New** button.




2. Enter a **Virtual Address**.
3. Select the **Lync Internal 2013 HLB Only** template from the **Use Template** drop-down list.
4. Click **Add This Virtual Service**.

5.2.2.2 Configure Internal Front-End WebSvc HTTP Virtual Service

To configure the Lync Internal Front-End WebSvc HTTP Virtual Service, follow the steps below:

1. Select **View/Modify Services** under **Virtual Services** in the left-hand navigation.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.



2. Click **Modify** on the **Lync Internal WebSvc HTTP** Virtual Service.
3. Expand the **Real Servers** section.
4. Click **Add New**.
5. Enter the **Real Server Address**.
6. Confirm that **Port 80** is entered.
7. Click **Add This Real Server**.
8. Add additional Real Servers as needed.

5.2.2.2.1 Internal Front-end WebSvc HTTP Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. These settings can be used with scripts and automation tools.

API Parameters	API Value
port	80
prot	tcp
Transparent	0
ExtraPorts	8080
Persist	src
PersistTimeout	1200
Useforsnat	1
Schedule	rr
Idletime	1800
CheckType	tcp


© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

API Parameters	API Value
CheckPort	5061

5.2.2.3 Configure Internal Front-End WebSvc HTTPS Virtual Service

To configure the Lync Internal Front-End WebSvc HTTPS Virtual Service, follow the steps below:

1. Select **View/Modify Services** under **Virtual Services** in the left-hand navigation.



2. Click **Modify** on the **Lync Internal WebSvc HTTPS HLB Only** Virtual Service.
3. Expand the **Real Servers** section.
4. Click **Add New**.
5. Enter the **Real Server Address**.
6. Confirm that **Port 443** is entered.
7. Click **Add This Real Server**.
8. Add additional Real Servers as needed.

5.2.2.3.1 Internal Front-End WebSvc HTTPS Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. These settings can be used with scripts and automation tools.

Option	Value
port	443
prot	tcp
ForceL7	0
ExtraPorts	444,4443
Transparent	0


© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

Option	Value
Persist	src
PersistTimeout	1200
Useforsnat	1
Schedule	rr
Idletime	1800
CheckType	tcp
CheckPort	5061

5.2.2.4 Configure Internal Front-End SIP Virtual Service

To configure the Lync Front-End SIP Virtual Service, follow the steps below:

1. Select **View/Modify Services** under **Virtual Services** in the left-hand navigation.



2. Click **Modify** on the **Lync Internal Front-End SIP** Virtual Service.
3. Expand the **Real Servers** section.
4. Click **Add New**.
5. Enter the **Real Server** Address.
6. Confirm that **Port 5061** is entered.
7. Click **Add This Real Server**.
8. Add additional Real Servers as needed.

5.2.2.4.1 Internal Front-End SIP Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. These settings can be used with scripts and automation tools.


© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

API Parameter	API Value
port	5061
prot	tcp
VStype	gen
ForceL7	1
ExtraPorts	448,5070-5073,5075,5076,5080
Transparent	0
ServerInit	0
Persist	src
PersistTimeout	1200
Useforsnat	1
Schedule	rr
Idletime	1800
CheckType	tcp
CheckPort	5061

5.2.2.5 Configure Internal Front-End DCOM Virtual Service

To configure the Lync Front End DCOM Virtual Service, follow the steps below:

1. Select **View/Modify Services** under **Virtual Services** in the left-hand navigation.



2. Click **Modify** on the **Lync Internal Front-End DCOM** Virtual Service.
3. Expand the **Real Servers** section.
4. Click **Add New**.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

5. Enter the **Real Server Address**.
6. Confirm that **Port 135** is entered.
7. Click **Add This Real Server**.
8. Add additional Real Servers as needed.

5.2.2.5.1 Internal Front-End DCOM Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. These settings can be used with scripts and automation tools.

API Parameters	API Value
port	135
prot	tcp
VSType	Gen
ForceL7	1
Transparent	0
ServerInit	0
Persist	src
PersistTimeout	1200
Useforsnat	1
Schedule	rr
Idletime	1800
CheckType	tcp
CheckPort	5061

5.2.3 Mediation HLB Only

The **Lync Mediation 2013 HLB Only** template contains one Virtual Services:


- Lync Mediation

5.2.3.1 Deploy Mediation 2013 HLB Only Template

To add the Virtual Services for Lync Mediation HLB Only with the template, follow the steps below:

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

1. Click the **Add New** button.



2. Enter a **Virtual Address**.


3. Select the **Lync Mediation 2013 HLB Only** template from the **Use Template** drop-down list.

4. Click **Add This Virtual Service**.

5.2.3.2 Configure Mediation Virtual Service

To configure the Lync Mediation Virtual Service, follow the steps below:

1. Select **View/Modify Services** under **Virtual Services** in the left-hand navigation.



2. Click **Modify** on the **Lync Mediation** Virtual Service.

3. Expand the **Real Servers** section.

4. Click **Add New**.

5. Enter the **Real Server Address**.

6. Confirm that **Port 5070** is entered.

7. Click **Add This Real Server**.

8. Add additional Real Servers as needed.

5.2.3.2.1 Mediation Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. These settings can be used with scripts and automation tools.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

API Parameters	API Value
port	5070
prot	tcp
VStype	gen
ForceL7	1
Transparent	0
ServerInit	0
Persist	src
PersistTimeout	1200
Useforsnat	1
Schedule	rr
Idletime	1800
CheckType	tcp
CheckPort	5070

5.2.4 Edge Internal HLB Only

The Lync Edge Internal 2013 HLB Only template contains three Virtual Services:


- Lync Edge Internal AV Media TCP
- Lync Edge Internal AV Media UDP
- Lync Edge Internal SIP

5.2.4.1 Deploy Edge Internal 2013 HLB Only Template

To add the Virtual Services for Lync Edge Internal 2013 HLB Only with the template, follow the steps below:

1. Click the **Add New** button.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.



2. Enter a **Virtual Address**.


3. Select the **Lync Edge Internal 2013 HLB Only** template from the **Use Template** drop-down list.

4. Click **Add This Virtual Service**.

5.2.4.2 Configure Edge Internal AV Media TCP Virtual Service

To configure the Lync Edge Internal AV Media TCP Virtual Service, follow the steps below:

1. Select **View/Modify Services** under **Virtual Services** in the left-hand navigation.



2. Click **Modify** on the **Lync Edge Internal AV Media TCP** Virtual Service.

3. Expand the **Real Servers** section.

4. Click **Add New**.

5. Enter the **Real Server Address**.

6. Confirm that **Port 443** is entered.

7. Click **Add This Real Server**.

8. Add additional Real Servers as needed.

5.2.4.2.1 Edge Internal AV Media TCP Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. These settings can be used with scripts and automation tools.


© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

API Parameters	API Value
port	443
prot	tcp
VStype	gen
ForceL7	1
Transparent	0
ServerInit	0
Persist	src
PersistTimeout	1200
Useforsnat	1
Schedule	rr
Idletime	1800
CheckType	TCP Connection Only
CheckPort	5061

5.2.4.3 Configure Edge Internal AV Media UDP Virtual Service

To configure the Lync Edge Internal AV Media UDP Virtual Service, follow the steps below:

1. Select **View/Modify Services** under **Virtual Services** in the left-hand navigation.



2. Click **Modify** on the **Lync Edge Internal AV Media UDP** Virtual Service.
3. Expand the **Real Servers** section.
4. Click **Add New**.
5. Enter the **Real Server Address**.
6. Confirm that **Port 3478** is entered.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

7. Click **Add This Real Server**.

8. Add additional Real Servers as needed.

5.2.4.3.1 Edge Internal AV Media UDP Virtual Service Recommended API Settings (optional)


This table outlines the API parameters and values set using the Kemp application template. These settings can be used with scripts and automation tools.

API Parameter	API Value
port	3478
prot	udp
ForceL7	0
Transparent	1
Persist	src
PersistTimeout	1200
Schedule	rr
Idletime	1800
CheckType	icmp

5.2.4.4 Configure Edge Internal SIP Virtual Service_D39

To configure the Lync Edge Internal SIP Virtual Service, follow the steps below:

1. Select **View/Modify Services** under **Virtual Services** in the left-hand navigation.



2. Click **Modify** on the **Lync Edge Internal SIP** Virtual Service.

3. Expand the **Real Servers** section.

4. Click **Add New**.

5. Enter the **Real Server Address**.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

6. Confirm that **Port 5061** is entered.
7. Click **Add This Real Server**.
8. Add additional Real Servers as needed.

5.2.4.4.1 Edge Internal SIP Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. These settings can be used with scripts and automation tools.

API Parameter	API Value
port	5061
prot	tcp
VStype	gen
Transparent	0
ExtraPorts	5062
ServerInit	0
Persist	src
PersistTimeout	1200
Useforsnat	1
Schedule	rr
Idletime	1800
CheckType	tcp
CheckPort	5061

5.3 Edge Configuration

Refer to the sections below for settings using a Lync Edge configuration.

When load balancing external interfaces of Edge pools, the shared interface IP should be used as the default gateway on all

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

> Edge interfaces. Also, a publicly routable IP with no NAT or port translation must be used.

5.3.1 Edge External HLB Only


The Lync Edge External HLB Only template contains three Virtual Services:

- Lync Edge External SIP
- Lync Edge External SIP Federation
- Lync Edge External XMPP

5.3.1.1 Deploy Edge External HLB Only Template

To add the Virtual Services for Lync Edge External HLB Only with the template, follow the steps below:

1. Click the **Add New** button.



2. Enter a **Virtual Address**.


3. Select the **Lync Edge External 2013 HLB Only** template from the **Use Template** drop-down list.

4. Click **Add This Virtual Service**.

5.3.1.2 Configure Edge External SIP Virtual Service

To configure the Lync Edge External SIP Virtual Service, follow the steps below:

1. Select **View/Modify Services** under **Virtual Services** in the left-hand navigation.



2. Click **Modify** on the **Lync Edge External SIP** Virtual Service.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

3. Expand the **Real Servers** section.
4. Click **Add New**.
5. Enter the **Real Server Address**.
6. Confirm that **Port 443** is entered.
7. Click **Add This Real Server**.
8. Add additional Real Servers as needed.

5.3.1.2.1 Edge External SIP Virtual Service Recommended API Settings (optional)


This table outlines the API parameters and values set using the Kemp application template. These settings can be used with scripts and automation tools.

API Parameters	API Value
port	443
prot	tcp
ForceL7	1
Transparent	0
Persist	src
PersistTimeout	1200
Schedule	rr
Idletime	1800
CheckType	tcp
CheckPort	5061

5.3.1.3 Configure Edge External SIP Federation Virtual Service

To configure the Lync Edge External SIP Federation Virtual Service, follow the steps below:

1. Select **View/Modify Services** under **Virtual Services** in the left-hand navigation.



© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

2. Click **Modify** on the **Lync Edge External SIP Federation** Virtual Service.
3. Expand the **Real Servers** section.
4. Click **Add New**.
5. Enter the **Real Server Address**.
6. Confirm that **Port 5061** is entered.
7. Click **Add This Real Server**.
8. Add additional Real Servers as needed.

5.3.1.3.1 Edge External SIP Federation Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. These settings can be used with scripts and automation tools.

API Parameters	API Value
port	5061
prot	tcp
ForceL7	1
Transparent	0
Persistent	src
PersistTimeout	1200
Schedule	rr
Idletime	1800
CheckType	tcp
CheckPort	5061

5.3.1.4 Configure Edge External XMPP Virtual Service

To configure the Lync Edge External XMPP Virtual Service, follow the steps below:

1. Select **View/Modify Services** under **Virtual Services** in the left-hand navigation.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.



2. Click **Modify** on the **Lync Edge External XMPP** Virtual Service.
3. Expand the **Real Servers** section.
4. Click **Add New**.
5. Enter the **Real Server Address**.
6. Confirm that **Port 5269** is entered.
7. Click **Add This Real Server**.
8. Add additional Real Servers as needed.

5.3.1.4.1 Edge External XMPP Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. These settings can be used with scripts and automation tools.

API Parameter	API Value
port	5269
prot	tcp
ForceL7	1
Transparent	0
Persist	src
PersistTimeout	1200
Schedule	rr
Idletime	1800
CheckType	tcp
CheckPort	5061

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

5.3.2 Edge External AV HLB Only


The **Lync Edge External AV HLB Only** template contains two Virtual Services:

- Lync Edge External AV Media TCP
- Lync Edge External AV Media UDP

5.3.2.1 Deploy Edge External AV HLB Only Template

To add the Virtual Services for Lync Edge External AV HLB Only with the template, follow the steps below:

1. Click the **Add New** button.



2. Enter a **Virtual Address**.
3. Select the **Lync Edge External AV 2013 HLB Only** template from the **Use Template** drop-down list.
4. Click **Add This Virtual Service**.

5.3.2.2 Configure Edge External AV Media TCP Virtual Service

To configure the Lync Edge External AV Media TCP Virtual Service, follow the steps below:

1. Select **View/Modify Services** under **Virtual Services** in the left-hand navigation.



2. Click **Modify** on the **Lync Edge External AV Media TCP** Virtual Service.
3. Expand the **Real Servers** section.
4. Click **Add New**.
5. Enter the **Real Server Address**.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

6. Confirm that **Port 443** is entered.
7. Click **Add This Real Server**.
8. Add additional Real Servers as needed.

5.3.2.2.1 Edge External AV Media TCP Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. These settings can be used with scripts and automation tools.

API Parameter	API Value
port	443
prot	tcp
Transparent	1
ForceL7	1
Persist	src
PersistTimeout	1200
Schedule	rr
Idletime	1800
CheckType	tcp
CheckPort	5061

5.3.2.3 Configure Edge External AV Media UDP Virtual Service

To configure the Lync Edge External AV Media UDP Virtual Service, follow the steps below:

1. Select **View/Modify Services** under **Virtual Services** in the left-hand navigation.



2. Click **Modify** on the **Lync Edge External AV Media UDP** Virtual Service.
3. Expand the **Real Servers** section.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

4. Click **Add New**.
5. Enter the **Real Server Address**.
6. Confirm that **Port 3478** is entered.
7. Click **Add This Real Server**.
8. Add additional Real Servers as needed.

5.3.2.3.1 Edge External AV Media UDP Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. These settings can be used with scripts and automation tools.

Option	Value
port	3478
prot	udp
Transparent	1
Persist	src
PersistTimeout	1200
Schedule	rr
Useforsnat	1
CheckType	icmp

5.3.3 Edge External Conferencing HLB Only

The Lync Edge External Conferencing HLB Only template contains one Virtual Services:


- Lync Edge External Conferencing

5.3.3.1 Deploy Edge External Conferencing HLB Only Template

To add the Virtual Services for Lync Edge External Conferencing HLB Only with the template, follow the steps below:

1. Click the **Add New** button.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.



2. Enter a **Virtual Address**.


3. Select the **Lync Edge External Conferencing 2013 HLB Only** template from the **Use Template** drop-down list.

4. Click **Add This Virtual Service**.

5.3.3.2 Configure Edge External Conferencing Virtual Service

To configure the Lync Edge External Conferencing Virtual Service, follow the steps below:

1. Select **View/Modify Services** under **Virtual Services** in the left-hand navigation.



2. Click **Modify** on the **Lync Edge External Conferencing** Virtual Service.

3. Expand the **Real Servers** section.

4. Click **Add New**.

5. Enter the **Real Server Address**.

6. Confirm that **Port 443** is entered.

7. Click **Add This Real Server**.

8. Add additional Real Servers as needed.

5.3.3.2.1 Edge External Conferencing Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. These settings can be used with scripts and automation tools.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

API Parameter	API Value
port	443
prot	tcp
ForceL7	1
Transparent	0
PersistTimeout	1200
Schedule	rr
Idletime	1800
CheckType	tcp
CheckPort	5061

5.4 Common to Both

The Virtual Services listed below are common to both DNS and HLB configurations.

5.4.1 Office Web App


The Lync Office Web App template contains one Virtual Services:

- Office Web App Servers

5.4.1.1 Deploy Office Web App Server Template

To add the Virtual Services for Lync Office Web App Servers with the template, follow the steps below:

1. Click the **Add New** button.



2. Enter a Virtual Address.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

3. Select the **Lync Office Web App Servers 2013** template from the **Use Template** drop-down list.

4. Click **Add This Virtual Service**.

5.4.1.2 Configure Office Web App Virtual Service

These steps assume a TLS Certificate has already been added to the LoadMaster. More information on certification, refer to the SSL Accelerated Services document on the Kemp Support Site.

To configure the Lync Office Web App Virtual Service, follow the steps below:

1. Select **View/Modify Services** under **Virtual Services** in the left-hand navigation.



2. Click **Modify** on the **Office Web App Server** Virtual Service.

3. Expand the **SSL Properties** section.

4. Select a valid certificate that was previously imported and click the > button to assign the certificate.

5. Click **Set Certificate**.

6. Expand the **Real Servers** section.

7. Click **Add New**.

8. Enter the **Real Server Address**.

9. Confirm that **Port 443** is entered.

10. Click **Add This Real Server**.

11. Add additional Real Servers as needed.

5.4.1.2.1 Office Web App Servers Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. These settings can be used with scripts and automation tools.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

API Parameters	API Value
port	443
prot	tcp
Transparent	0
SSLAcceleration	1
SSLReencrypt	1
Persist	super and src
PersistTimeout	1800
Schedule	rr
Idletime	1800
CheckType	https
CheckPort	443
CheckURL	/hosting/discovery
CheckUse	1
CheckUseGet	GET

It is optional to add a HTTP redirector Virtual Service. Whether you require one or not depends on your environment.

5.4.2 Director Reverse Proxy

The Lync Reverse Proxy template can be used for both Director and Front-End. If using both roles in Lync 2013 you must rename the Virtual Services such as **Lync Director Reverse Proxy** and **Lync Front-End Reverse Proxy** as shown in the steps below.

The **Lync Directory Reverse Proxy** template contains one Virtual Services:


- Lync Director Reverse Proxy HTTP
- Lync Director Reverse Proxy HTTPS

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

5.4.2.1 Deploy Director Reverse Proxy Template

To add the Virtual Services for Lync Director Reverse Proxy with the template, follow the steps below:

1. Click the **Add New** button.



2. Enter a **Virtual Address**.
3. Select the **Lync Office Web App Servers 2013** template from the **Use Template** drop-down list.
4. Click **Add This Virtual Service**.
5. Rename Virtual Service to **Lync Director Reverse Proxy 2013**.

5.4.2.2 Configure Director Reverse Proxy HTTP Virtual Service

To configure the Lync Director Reverse Proxy HTTP Virtual Service, follow the steps below:

1. Select **View/Modify Services** under **Virtual Services** in the left-hand navigation.



2. Click **Modify** on the **Lync Director Reverse Proxy HTTP** Virtual Service.
3. Expand the **SSL Properties**.
4. Expand the **Real Servers** section.
5. Click **Add New**.
6. Enter the **Real Server Address**.
7. Confirm that **Port 8080** is entered.
8. Click **Add This Real Server**.
9. Add additional Real Servers as needed.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

Ensure that port tcp/80 is not used for the Real Servers.

5.4.2.2.1 Director Reverse Proxy HTTP Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. These settings can be used with scripts and automation tools.

API Parameters	API Value
port	80
prot	tcp
ForceL7	1
Transparent	0
Persist	src
PersistTimeout	1200
Schedule	rr
Idletime	1800
CheckType	tcp
CheckPort	5061

5.4.2.3 Configure Director Reverse Proxy HTTPS Virtual Service

These steps assume a TLS Certificate has already been added to the LoadMaster. More information on certification can be found in the SSL Accelerated Services document on the Kemp Support Site.

To configure the Lync Director Reverse Proxy HTTPS Virtual Service, follow the steps below:

1. Select **View/Modify Services** under **Virtual Services** in the left-hand navigation.



2. Click **Modify** on the **Lync Director Reverse Proxy HTTPS** Virtual Service.
3. Expand the **SSL Properties** section.
4. Expand the **Real Servers** section.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

5. Click **Add New**.
6. Enter the **Real Server Address**.
7. Confirm that **Port 4443** is entered.
8. Click **Add This Real Server**.
9. Add additional Real Servers as needed.

> Ensure that port tcp/443 is not used for the Real Servers.

5.4.2.3.1 Director Reverse Proxy HTTPS Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. These settings can be used with scripts and automation tools.

API Parameter	API Value
port	443
prot	tcp
Transparent	0
SSLAcceleration	1
SSLReencrypt	1
Persist	src
PersistTimeout	1200
Schedule	rr
Idletime	1800
CheckType	tcp
CheckPort	5061

5.4.3 Front-End Reverse Proxy

The Lync Reverse Proxy template can be used for both Director and Front-End. If using both roles in Lync 2013, you must rename the Virtual Services such as **Lync Director Reverse Proxy** and **Lync Front-End Reverse Proxy** as shown in the steps below.

The Lync Front-End Reverse Proxy template contains two Virtual Services:


© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

- Lync Front-End Reverse Proxy HTTP
- Lync Front-End Reverse Proxy HTTPS

5.4.3.1 Deploy Front-End Reverse Proxy Template

To add the Virtual Services for Lync Front-End Reverse Proxy with the template, follow the steps below:

1. Click the **Add New** button.



2. Enter a **Virtual Address**.
3. Select the **Lync Reverse Proxy 2013** template from the **Use Template** drop-down list.
4. Click **Add This Virtual Service**.
5. Rename Virtual Service to **Lync Front-End Reverse Proxy 2013**.

5.4.3.2 Configure Front-End Reverse Proxy HTTP Virtual Service

To configure the Lync Front-End Reverse Proxy Virtual Service, follow the steps below:

1. Select **View/Modify Services** under **Virtual Services** in the left-hand navigation.



2. Click **Modify** on the **Lync Front-End Reverse Proxy HTTP** Virtual Service.
3. Expand the **SSL Properties** section.
4. Expand the **Real Servers** section.
5. Click **Add New**.
6. Enter the **Real Server Address**.
7. Confirm that **Port 8080** is entered.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

8. Click **Add This Real Server**.

9. Add additional Real Servers as needed.

> Ensure that port tcp/80 is not used for the Real Servers.

5.4.3.2.1 Front End Reverse Proxy HTTP Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. These settings can be used with scripts and automation tools.

API Parameter	API Value
port	80
prot	tcp
ForceL7	1
Schedule	rr
Transparent	0
Persist	src
PersistTime	1200
Idletime	1800
Useforsnat	1
CheckType	tcp
CheckPort	5061

5.4.3.3 Configure Front-End Reverse Proxy HTTPS Virtual Service

These steps assume a TLS Certificate has already been added to the LoadMaster. More information on certification can be found in the SSL Accelerated Services document on the Kemp Support site.

To configure the Lync Front-End Reverse Proxy HTTPS Virtual Service, follow the steps below:

1. Select **View/Modify Services** under **Virtual Services** in the left-hand navigation.



© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

2. Click **Modify** on the **Lync Front-End Reverse Proxy HTTP** Virtual Service.
3. Expand the **SSL Properties** section.
4. Expand the **Real Servers** section.
5. Click **Add New**.
6. Enter the **Real Server** Address.
7. Confirm that **Port 4443** is entered.
8. Click **Add This Real Server**.
9. Add additional Real Servers as needed.

> Ensure that port tcp/443 is not used for the Real Servers.

5.4.3.3.1 Front End Reverse Proxy HTTPS Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. These settings can be used with scripts and automation tools.

API Parameter	API Value
port	443
prot	tcp
Transparent	1
SSLAcceleration	1
SSLReencrypt	1
Persist	src
PersistTimeout	1200
Schedule	rr
Idletime	1800
CheckType	tcp
CheckPort	5061

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

6 References

The following sources are referred to in this document:

Kemp website

www.kemptechnologies.com

Kemp Documentation page

http://kemptechnologies.com/loadmaster-documentation.

MS Lync 2013 Single Pair Addendum, Deployment Guidehttp://www.kemptechnologies.com/documentation

Web User Interface (WUI), Configuration Guide

http://www.kemptechnologies.com/documentation

Virtual Services and Templates, Feature Description

http://www.kemptechnologies.com/documentation

Ports and Protocols for Internal Servers

http://technet.microsoft.com/en-us/library/gg398833.aspx

Port Summary - Scaled Consolidated Edge with Hardware Load Balancers

http://technet.microsoft.com/en-us/library/gg398739.aspx

Scaled Consolidated Edge with Hardware Load Balancers

http://technet.microsoft.com/en-us/library/gg398478.aspx

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

Last Updated Date

This document was last updated on 28 July 2023.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.