

HTTP2

Feature Description

UPDATED: 28 July 2023

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

These materials and all Progress® software products are copyrighted and all rights are reserved by Progress Software Corporation. The information in these materials is subject to change without notice, and Progress Software Corporation assumes no responsibility for any errors that may appear therein. The references in these materials to specific platforms supported are subject to change.

#1 Load Balancer in Price/Performance, 360 Central, 360 Vision, Chef, Chef (and design), Chef Habitat, Chef Infra, Code Can (and design), Compliance at Velocity, Corticon, Corticon.js, DataDirect (and design), DataDirect Cloud, DataDirect Connect, DataDirect Connect64, DataDirect XML Converters, DataDirect XQuery, DataRPM, Defrag This, Deliver More Than Expected, DevReach (and design), Driving Network Visibility, Flowmon, Inspec, Ipswitch, iMacros, K (stylized), Kemp, Kemp (and design), Kendo UI, Kinvey, LoadMaster, MessageWay, MOVEit, NativeChat, OpenEdge, Powered by Chef, Powered by Progress, Progress, Progress Software Developers Network, SequeLink, Sitefinity (and Design), Sitefinity, Sitefinity (and design), Sitefinity Insight, SpeedScript, Stylized Design (Arrow/3D Box logo), Stylized Design (C Chef logo), Stylized Design of Samurai, TeamPulse, Telerik, Telerik (and design), Test Studio, WebSpeed, WhatsConfigured, WhatsConnected, WhatsUp, and WS_FTP are registered trademarks of Progress Software Corporation or one of its affiliates or subsidiaries in the U.S. and/or other countries.

Analytics360, AppServer, BusinessEdge, Chef Automate, Chef Compliance, Chef Desktop, Chef Workstation, Corticon Rules, Data Access, DataDirect Autonomous REST Connector, DataDirect Spy, DevCraft, Fiddler, Fiddler Classic, Fiddler Everywhere, Fiddler Jam, FiddlerCap, FiddlerCore, FiddlerScript, Hybrid Data Pipeline, iMail, InstaRelinker, JustAssembly, JustDecompile, JustMock, KendoReact, OpenAccess, PASOE, Pro2, ProDataSet, Progress Results, Progress Software, ProVision, PSE Pro, Push Jobs, SafeSpaceVR, Sitefinity Cloud, Sitefinity CMS, Sitefinity Digital Experience Cloud, Sitefinity Feather, Sitefinity Thunder, SmartBrowser, SmartComponent, SmartDataBrowser, SmartDataObjects, SmartDataView, SmartDialog, SmartFolder, SmartFrame, SmartObjects, SmartPanel, SmartQuery, SmartViewer, SmartWindow, Supermarket, SupportLink, Unite UX, and WebClient are trademarks or service marks of Progress Software Corporation and/or its subsidiaries or affiliates in the U.S. and other countries. Java is a registered trademark of Oracle and/or its affiliates. Any other marks contained herein may be trademarks of their respective owners.

Please refer to the NOTICE.txt or Release Notes – Third-Party Acknowledgements file applicable to a particular Progress product/hosted service offering release for any related required third-party acknowledgements.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

Table of Contents

1 Introduction **4**

1.1 Document Purpose 5

1.2 Intended Audience 6

1.3 Limitations 6

1.4 Support 6

2 Enable HTTP/2 in a Virtual Service **7**

2.1 HTTP/2 Pass Through Service Type 9

3 Evaluating HTTP/2 ..... **10**

3.1 Example Test Environment 10

3.1.1 Create the HTTP 1.1 Virtual Service 11

3.1.2 Create the HTTP/2 Virtual Service 12

3.1.3 Performing Tests 16

References **17**

Last Updated Date **18**

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

1 Introduction

Full HTTP/2 support is available across all Kemp Application Delivery Controllers (ADCs) and can be enabled at the push of a button. Kemp's HTTP/2 support greatly improves user experience on applications and websites, simplifying the performance upgrade path for site administrators.

HTTP/2 is the latest version of Hypertext Transfer Protocol (HTTP) and is designed to optimize the delivery of content on everything from websites to mobile apps leading to a much better end user experience. It is supported across modern browsers including the latest versions of Google Chrome, Mozilla Firefox, Apple Safari, Microsoft Internet Explorer, and Edge.

HTTP/2 has huge potential. There are a number of inflexibility, inefficiency and performance challenges with HTTP/1 that are solved by HTTP/2. Several of the benefits of HTTP/2 are below:

- **Multiplexing and concurrency:** Several requests can be sent in rapid succession in the same TCP connection. Responses can be received out of order – eliminating the need for multiple connections between the client and the server.
- **Stream dependencies:** The client can indicate to the server which of the resources are more important than others
- **Header compression:** HTTP header size is drastically reduced
- **Server push:** The server can send resources that the client has not yet requested

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.



The LoadMaster also supports HTTP/2 – the LoadMaster can convert HTTP/2 traffic to HTTP/1.1 traffic in the back-end before it hits the Real Servers. These Real Servers do not need to have SSL enabled.

The HTTP/2 functionality in the LoadMaster provides optimizations, such as request pipelining and request multiplexing to reduce the request load on back-end servers. This results in a significantly improved end user experience when using a browser with HTTP/2 support. HTTP/2 works with a number of LoadMaster features, such as content switching, content caching, advanced persistence, header injection and the Web Application Firewall (WAF).

1.1 Document Purpose

The purpose of this document is to show you how to enable HTTP/2 in the LoadMaster and provide test website content for you to test the functionality against.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

1.2 Intended Audience

This document is intended to be used by anyone interested in enabling HTTP/2 in the LoadMaster.

1.3 Limitations

Some limitations are listed below:

- Certain ciphers are not supported when using HTTP/2 – but these are automatically disabled when HTTP/2 support is enabled in the LoadMaster.
- If either NT LAN Manager (NTLM) or Kerberos authentication is enabled on a Virtual Service, HTTP/2 will be disabled. Similarly, if HTTP/2 support is enabled on a Virtual Service, NTLM/Kerberos authentication will be disabled.
- SAML authentication does not currently work correctly with HTTP/2.
- **TLS 1.2** must be enabled in the **Supported Protocols** in the **SSL Properties** section for HTTP/2 to work
- The **Process Responses** option in the **WAF Options** section cannot be enabled if HTTP/2 is enabled
- Content switching when matching inside a POST does not work with HTTP/2.
- When using HTTP/2, after killing a session the HTTP/2 client still has access to the application until the underlying connection is closed. Examples of closing the underlying connection are; the user closes the browser, the user does a hard reset (**Ctrl + F5**), or the connection reaches an idle timeout.
- When using HTTP/2, transparency is not used even if it is enabled. This is because one connection is mapped to multiple connections. HTTP/1.1 clients are still transparent when HTTP/2 and transparency are both enabled.
- Packet counts are not reported when using HTTP/2.

1.4 Support

If you have any questions or need assistance, please contact Kemp Support: https://support.kemptechnologies.com.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

2 Enable HTTP/2 in a Virtual Service

Follow the steps below to enable HTTP/2 in a Virtual Service in the LoadMaster:

1. In the LoadMaster Web User Interface (WUI), go to **Virtual Services > View/Modify Services**.
2. Click **Modify** on the relevant Virtual Service.
3. Expand the **SSL Properties** section.



4. Select the **Enabled** check box.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

HTTP/2 is only available if **SSL Acceleration** is **Enabled**.

HTTP/2 also works with SSL re-encryption, which helps with applications that require both encrypted flows in addition to L7 functionality.

5. Select **BestPractices** as the **Cipher Set**.
6. Expand the **Advanced Properties** section.



7. Select the **Enable HTTP/2 Stack**check box.
8. Configure any other settings as needed.

As with HTTP/1, enabling caching improves performance.

For details on each of the options in the WUI, refer to the Web User Interface (WUI), Configuration Guide.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

2.1 HTTP/2 Pass Through Service Type

In addition to the **Enable HTTP/2 Stack** option in **Advanced Properties**, there is also a **HTTP/2 Pass Through** Virtual Service Type. However, this only offers generic pass through. This option has no impact and should not be selected.

HTTP/2 does not support transparency. Subnet originating, alternate source address functionality, caching, compression and body rewrites all work, as required.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

3 Evaluating HTTP/2

To assist with the evaluation of HTTP/2, Kemp have provided a simple web page that consists of an image made up of 1024 individual image 'tiles'. This page provides a visual guide to the optimization available with HTTP/2 as the tiled image renders much faster with HTTP/2. The sections below provide details about the test environment setup but to access the test page refer to the **Performing Tests** section.

3.1 Example Test Environment



The test environment is focused on providing a visual comparison of the same page being loaded using HTTP/2 and HTTP 1.1. A web page is hosted on a Real Server and the LoadMaster is configured

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

with a Virtual Service for HTTP/2 and a Virtual Service for HTTP 1.1. Both Virtual Services use the same Real Server.

The following are recommended in order to evaluate HTTP/2 correctly:

- **Browser:** Google Chrome is probably the best browser to use for HTTP/2 testing. To check what browsers support HTTP/2, please visit the following website: http://caniuse.com/#feat=http2
- **LoadMaster:** Use LoadMaster firmware version 7.1.35 or later.
- **Web Server:** Any HTTP 1.1 capable server will suffice. The sample page provided is a simple web page with multiple images.

For the test, Kemp created a:

- HTTP 1.1 Virtual Service on port 80 with **SSL Acceleration** disabled.
- HTTP/2 Virtual Service on port 8080 with **SSL Acceleration** enabled.

In the example below, the Virtual Services are on 192.168.0.9 and the Real Server is on 192.168.0.10.

3.1.1 Create the HTTP 1.1 Virtual Service

To create the HTTP 1.1 Virtual Service, follow the steps below:

1. In the main menu of the LoadMaster WUI, go to **Virtual Services > Add New**.



2. Enter a valid IP address in the **Virtual Address** text box.
3. Enter **80** in the **Port** text box.
4. Enter a **Service Name**, for example **HTTP 1.1**.
5. Click **Add this Virtual Service**.
6. Configure any other details as needed.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

7. Expand the **Real Servers** section.
8. Click **Add New**.



9. Enter the **Real Server Address**.
10. Enter **80** as the **Port**.
11. Click **Add This Real Server**.

3.1.2 Create the HTTP/2 Virtual Service

To create the HTTP/2 Virtual Service, follow the steps below:

1. In the main menu of the LoadMaster WUI, go to **Virtual Services > Add New**.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.



2. Enter a valid IP address in the **Virtual Address** text box.
3. Enter **8080** (or any other available port) in the **Port** text box.
4. Enter a **Service Name**, for example **HTTP2 Test**.
5. Click **Add this Virtual Service**.
6. Expand the **SSL Properties** section.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.



7. Tick the **Enabled** check box.

> SSL is mandatory for HTTP/2.

8. Select **BestPractices** as the **Cipher Set**.

9. Expand the **Advanced Properties** section.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.



10. Select the **Enable HTTP/2 Stack** check box.
11. Configure any other details as needed.

    As with HTTP/1, enabling caching improves performance.

12. Expand the **Real Servers** section.
13. Click **Add New**.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.



14. Enter the **Real Server Address**.
15. Enter **80** as the **Port**.
16. Click **Add This Real Server**.

The HTTP/2 Virtual Service on the LoadMaster will communicate with the server using HTTP 1.1.

3.1.3 Performing Tests

To test the performance gains from HTTP/2, the simplest way is to visualize the impact by using a web page which contains a large number of elements, such as images. Kemp have provided a sample web page that displays an image made up of 1024 image 'tiles'. Simply browse to the HTTP/2 and HTTP 1.1 Virtual Services to see the difference in performance. Ensure you use a HTTP/2-enabled browser, such as Chrome, when performing this test.

The Kemp HTTP/2 test page is available here: http://kemptechnologies.com/files/assets/tools/Kemp-TechPreview-HTTP2-TestPage.zip

Other tools and utilities for testing HTTP/2 are listed here: https://blog.cloudflare.com/tools-for-debugging-testing-and-using-http-2/

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

References

Unless otherwise specified, the following documents can be found at http://kemptechnologies.com/documentation.

Web User Interface (WUI), Configuration Guide

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

Last Updated Date

This document was last updated on 28 July 2023.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.