



VMware vRealize Orchestrator

Feature Description

UPDATED: 30 July 2023

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

These materials and all Progress® software products are copyrighted and all rights are reserved by Progress Software Corporation. The information in these materials is subject to change without notice, and Progress Software Corporation assumes no responsibility for any errors that may appear therein. The references in these materials to specific platforms supported are subject to change.

#1 Load Balancer in Price/Performance, 360 Central, 360 Vision, Chef, Chef (and design), Chef Habitat, Chef Infra, Code Can (and design), Compliance at Velocity, Corticon, Corticon.js, DataDirect (and design), DataDirect Cloud, DataDirect Connect, DataDirect Connect64, DataDirect XML Converters, DataDirect XQuery, DataRPM, Defrag This, Deliver More Than Expected, DevReach (and design), Driving Network Visibility, Flowmon, Inspec, Ipswitch, iMacros, K (stylized), Kemp, Kemp (and design), Kendo UI, Kinvey, LoadMaster, MessageWay, MOVEit, NativeChat, OpenEdge, Powered by Chef, Powered by Progress, Progress, Progress Software Developers Network, SequeLink, Sitefinity (and Design), Sitefinity, Sitefinity (and design), Sitefinity Insight, SpeedScript, Stylized Design (Arrow/3D Box logo), Stylized Design (C Chef logo), Stylized Design of Samurai, TeamPulse, Telerik, Telerik (and design), Test Studio, WebSpeed, WhatsConfigured, WhatsConnected, WhatsUp, and WS_FTP are registered trademarks of Progress Software Corporation or one of its affiliates or subsidiaries in the U.S. and/or other countries.

Analytics360, AppServer, BusinessEdge, Chef Automate, Chef Compliance, Chef Desktop, Chef Workstation, Corticon Rules, Data Access, DataDirect Autonomous REST Connector, DataDirect Spy, DevCraft, Fiddler, Fiddler Classic, Fiddler Everywhere, Fiddler Jam, FiddlerCap, FiddlerCore, FiddlerScript, Hybrid Data Pipeline, iMail, InstaRelinker, JustAssembly, JustDecompile, JustMock, KendoReact, OpenAccess, PASOE, Pro2, ProDataSet, Progress Results, Progress Software, ProVision, PSE Pro, Push Jobs, SafeSpaceVR, Sitefinity Cloud, Sitefinity CMS, Sitefinity Digital Experience Cloud, Sitefinity Feather, Sitefinity Thunder, SmartBrowser, SmartComponent, SmartDataBrowser, SmartDataObjects, SmartDataView, SmartDialog, SmartFolder, SmartFrame, SmartObjects, SmartPanel, SmartQuery, SmartViewer, SmartWindow, Supermarket, SupportLink, Unite UX, and WebClient are trademarks or service marks of Progress Software Corporation and/or its subsidiaries or affiliates in the U.S. and other countries. Java is a registered trademark of Oracle and/or its affiliates. Any other marks contained herein may be trademarks of their respective owners.

Please refer to the NOTICE.txt or Release Notes – Third-Party Acknowledgements file applicable to a particular Progress product/hosted service offering release for any related required third-party acknowledgements.

Table of Contents


1 Introduction	6
1.1 Document Purpose	6
1.2 Intended Audience	7
1.3 Prerequisites	7
2 Install the Kemp Orchestrator Plugin	8
3 Using the Kemp Orchestrator Plugin	12
3.1 Inventory	12
3.2 Workflows	13
3.3 Files	14
3.3.1 Delete Files	14
3.3.2 Upload Files	18
3.3.2.1 Uploading Files which are Bigger than 2MB	21
3.3.2.1.1 Using SCP to Copy a File to the Orchestrator Server	22
3.3.2.1.2 Use cURL to Download the File	22
3.3.2.1.3 Configuring Permissions	23
3.4 LoadMasters	23
3.4.1 Add LoadMaster	23
3.4.2 Add Certificate	25
3.4.3 Backup Certificates	31
3.4.4 Backup LoadMaster	35
3.4.5 Delete Certificate	39

3.4.6 Disable API	42
3.4.7 Enable API	45
3.4.8 Get Parameter	48
3.4.9 Install Patch	52
3.4.10 Reboot LoadMaster	55
3.4.11 Remove LoadMaster	57
3.4.12 Restore Certificates	59
3.4.13 Restore LoadMaster	65
3.4.14 Set Credentials	69
3.4.15 Set Parameter	71
3.5 Virtual Services	76
3.5.1 Add Virtual Service	76
3.5.2 Assign Virtual Service Certificates	78
3.5.3 Modify Virtual Service Name	83
3.5.4 Remove Virtual Service	86
3.6 Sub Virtual Services	89
3.6.1 Add SubVS	89
3.6.2 Modify SubVS Name	92
3.6.3 Remove SubVS	95
3.7 Real Servers	98
3.7.1 Add Real Server to Sub Virtual Service	98
3.7.2 Add Real Server to Virtual Service	101

3.7.3 Remove Real Server	104
4 Uninstall the Kemp Orchestrator Plugin	108
4.1 Uninstall the Workflows	108
4.2 Remove the Kemp Orchestrator Plugin	109
4.3 Restart the Service	110
5 Appendix A - Get and Set Parameters	113
6 Appendix B - Memory and CPU Usage Details	119
References	121
Last Updated Date	122

1 Introduction

VMware vRealize Orchestrator allows administrators to develop complex automation tasks, then quickly access and launch workflows from the VMware vSphere client or various triggering mechanisms such as vROPs, vCAC, and so on.



Kemp have developed a plugin for Orchestrator which acts as a front-end for the Kemp Java API commands. When this plugin is installed, users can perform a number of tasks on the LoadMaster using the Orchestrator interface. The plugin allows Orchestrator to send commands (via workflows) to and receive information back from the Kemp LoadMaster and GEO products.

1.1 Document Purpose

The purpose of this document is to describe how to install and use the Kemp Orchestrator plugin. The document provides step-by-step instructions on how to run the various Kemp workflows which are added when the plugin is installed.

1.2 Intended Audience

This document is intended to be used by anyone who would like to use Orchestrator to manage their LoadMasters.

1.3 Prerequisites

Below are some prerequisites to be aware of before using the Kemp Orchestrator plugin:

- If using the default self-signed certificate which is generated by the LoadMaster, please ensure it is registered properly with the systems and that it is trusted. Please refer to VMware documentation, or your Operating System documentation, for instructions on how to do this.

If the certificate is not trusted there may be issues running the workflows.

- If using an FQDN as opposed to an IP address, please ensure that the DNS is properly configured.

2 Install the Kemp Orchestrator Plugin

Before using Orchestrator to manage a Kemp LoadMaster, the Kemp Orchestrator plugin must be installed. To do that, first download the Kemp Orchestrator plugin. Then, follow the steps below:


1. In a web browser, navigate to the IP address of the Orchestrator server followed by the :8281 port.

Configure the Orchestrator Server

To make additional configuration changes to the Orchestrator server, use the Orchestrator configuration interface:

- [Orchestrator Configuration](#)
- [Orchestrator Control Center \(Beta\)](#)


2. Click the **Orchestrator Configuration** link.



The screenshot shows the VMware vRealize Orchestrator login interface. At the top is a blue header with the text "VMware vRealize™ Orchestrator™". Below the header, the word "Welcome" is displayed. A message states: "Enter your username and password to login in **VMware vRealize Orchestrator Configuration**". There are two input fields: "Username:" with the text "vmware" entered, and "Password:" with masked characters (dots). A "Login" button is located at the bottom right of the form.


3. Enter the Orchestrator credentials and click **Login**.

2 Install the Kemp Orchestrator Plugin



4. Select the **Install Application** tab.

5. Click the magnifying glass icon.



6. Browse to and select the Kemp Orchestrator plugin file (.vmo app file).

If you cannot see the plugin file, you may need to select **All Files** in the bottom-right corner.

7. Click **Install** in the bottom-right.

It might take a few seconds to upload the plugin before moving on to the next screen.

2 Install the Kemp Orchestrator Plugin

I accept the terms of the License Agreement

I do NOT accept the terms of the License Agreement

8. To accept the license agreement, click **I accept the terms of the License Agreement**.

 **General**

 **Network**

 **Authentication**

 **Database**

 **Server Certificate**

 **Licenses**

 **Startup Options**

 **Server Availability**

9. The plugin is now installed, but before it can be used the Orchestrator service needs to be restarted. To do this, click **Startup Options** on the left.

Server startup options


vRO Server


Status

Running


 Refresh

 Start service

 Stop service


 Restart service

vRO Configuration Server


 Restart the vRO configuration server

10. Click **Restart service**.

2 Install the Kemp Orchestrator Plugin



11. Wait for the service to restart.



12. A message will appear when the service has been restarted.

The Kemp Orchestrator plugin should now be installed and ready to use.

3 Using the Kemp Orchestrator Plugin

3.1 Inventory


There is an **Inventory** section in Orchestrator which will list any LoadMasters that have been added to Orchestrator. There are also a number of Kemp directories which are created when the Kemp Orchestrator plugin is installed. To view these, follow the steps below:



1. Select the **Run** mode from the drop-down in the top-left.



2. Select the **Inventory** tab (icon of a jigsaw puzzle piece with a page behind it).



When any Kemp files are uploaded to the Orchestrator, for example certificate or patch files, Kemp recommends saving those files in the relevant Kemp directories. The certificate and LoadMaster backups will automatically save into the relevant directories when the related workflows are run.

3.2 Workflows

After the plugin has been installed, a number of Kemp workflows will be available. These workflows can be used to perform various tasks in the LoadMaster.


The workflows can be accessed by following the steps below:



1. Select the **Run** mode from the drop-down in the top-left.



2. Select the **Workflows** tab (blue icon).



3. Expand the **Library** directory.
4. Expand the **Kemp** directory.
5. Each of the sub-directories within the **Kemp** directory contain various workflows that can be run. To run a workflow:

- a) Expand the relevant directory.
- b) Select the relevant workflow.




- c) Click the green play icon (Start workflow) in the top-left.
- d) A screen will then appear which will contain relevant fields relating to that workflow. Fill out the fields and click Submit.

The steps to run each of the workflows are the same, but the fields that appear on each of the screens will differ. Refer to the sections below for more information. The section names correspond to the directory names in Orchestrator.


3.3 Files

Files can be uploaded to and deleted from Orchestrator. For further details, refer to the sections below:

3.3.1 Delete Files




1. Click **Not set**.



2. Click **Insert value**.

3 Using the Kemp Orchestrator Plugin




- 3. Expand the **Kemp** directory.
- 4. Expand the relevant directory where the file is located.
- 5. Select the relevant file to be deleted.
- 6. Click **Add**.

Inventory ID	File Name
F Certificates > certificate.pem	certificate.pem
<div>Cancel Select</div>	


- 7. Click **Select**.

3 Using the Kemp Orchestrator Plugin




8. Click **Accept**.

3 Using the Kemp Orchestrator Plugin




9. Click **Submit**.



10. Wait for the deletion to complete.

3.3.2 Upload Files



The dialog box titled "Start Workflow : Upload Files" has a "Common Parameters" tab. It contains three fields: "Select the files to be uploaded" (value: Not set), "Select the directory to store these files" (value: Not set), and "Replace existing files with the same name?" (radio buttons: Yes, No, with "No" selected).

1. Click **Not set** in the **Select files to be uploaded** field.



The dialog box titled "Array of MimeAttachment" shows the "New value" field with the text "Not set". To the right of the field are two icons (a folder and a document) and an "Insert value" button.

2. Click **Not set**.
3. Browse to and select the relevant file to be uploaded.




The dialog box titled "Array of MimeAttachment" shows the "New value" field with the text "certificate.pem (application/octet-stream)". To the right of the field are two icons (a folder and a document) and an "Insert value" button.


4. Click **Insert value**.

Multiple files can be uploaded at the same time, if needed.
Simply browse to and select another file and click **Insert value**
to add it to the list of files to be uploaded.

3 Using the Kemp Orchestrator Plugin




5. Click **Accept**.




6. Click **Not set** in the **Select the directory to store these files** field.

3 Using the Kemp Orchestrator Plugin




- 7. Expand the **Kemp** directory.
- 8. Select the relevant directory to store the file in.
- 9. Click **Select**.



- 10. If you want to replace an existing file of the same name, select **Yes**.

11. Click **Submit** to upload.



The file will then be visible in the **Inventory** tab in the relevant directory.

3.3.2.1 Uploading Files which are Bigger than 2MB

There is a limit of 2MB on the file sizes that can be uploaded via the Kemp Orchestrator plugin. This means that firmware upgrade patch files are not able to be uploaded using the method listed in the section above. This section outlines a workaround that can be used to upload files greater than 2MB in size.

The following are valid LoadMaster directories on the Orchestrator server:

- lm_config_backups
- lm_certs
- lm_certs_backups
- lm_patches

3 Using the Kemp Orchestrator Plugin

You can use a number of options to copy/download the file to the Orchestrator Server. Two of the options - using SCP or using cURL, are outlined below.

3.3.2.1.1 Using SCP to Copy a File to the Orchestrator Server

This process requires SSH access to be enabled when deploying the Orchestrator appliance. Follow the steps below:

1. Navigate to the directory containing the file to transfer on the source machine.
2. Run the following command:

```
scp <File_To_Transfer> root@<Orchestrator_Server_IP_Address>:/var/lib/vco/app-server/temp/<LoadMaster_Directory>/<Filename>
```

In order for the files to be visible in the Orchestrator client, one of the four directories listed in the **Uploading Files which are Bigger than 2MB** section must be used in place of **<LoadMaster_Directory>**.

3. After authenticating with the server, the file transfer should proceed.

3.3.2.1.2 Use cURL to Download the File

The file must then be downloaded using a cURL command:

1. Connect to the Orchestrator server via SSH.

Unless additional users have been configured on the server, you must log in as **root**.

2. Navigate to /var/lib/vco/app-server/temp/<LoadMasterDirectory>

Replace **<LoadMasterDirectory>** with one of the directories listed in the **Uploading Files which are Bigger than 2MB** section.

3. Invoke cURL with the **-o <Filename>** parameter to transfer the output of the command to a file, for example:

```
curl -u user:password -o <NewFilename> <URL>/<File_To_Download>
```

3.3.2.1.3 Configuring Permissions

After the file has been successfully transferred, the permissions of the file must be modified in order for it to be accessible to the Orchestrator client. To modify the permissions, run the following command:

chown vco <FileName>

If this step is not performed, the files in question will not be visible in the Orchestrator client.


3.4 LoadMasters

In the **LoadMasters** directory, there are a number of workflows that can be executed which relate to managing LoadMasters, such as adding and removing LoadMasters from Orchestrator. For details on each of the LoadMaster workflows, refer to the sections below.

Before any of the other LoadMaster workflows can be run on a LoadMaster, the relevant LoadMaster needs to be added to Orchestrator. The first section below provides details on the **Add LoadMaster** workflow.

3.4.1 Add LoadMaster

A LoadMaster can be added to Orchestrator using the **Add LoadMaster** workflow. A LoadMaster must be added to Orchestrator before any workflows can be run on that LoadMaster.



Start Workflow : Add LoadMaster

1 Authentication

2 LoadMaster Configuration

* Enter the username for the LoadMaster

bal

* Enter the password for the LoadMaster


Select the SSL certificate provided by the LoadMaster (optional)

Not set

1. Enter the username and password to access the LoadMaster.
2. Specifying the SSL certificate is optional - this is the certificate file used to authenticate to the LoadMaster (the root LoadMaster certificate).

3 Using the Kemp Orchestrator Plugin

3. Click **LoadMaster Configuration**.




4. Enter a recognizable name in the **Enter a unique identifier for the LoadMaster** text box. This is a friendly name for the LoadMaster, which appears in Orchestrator.

5. Enter the IP address of the LoadMaster to be added.

6. Enter the HTTPS port to use to connect to the LoadMaster.


If you cannot see the port field, you may need to install the latest Kemp package. To do this, select the **Administer** option from the drop-down at the top, go to the **Packages** tab on the left, select the **com.kempttechnologies** package, click the **Import package** icon and import the latest Kemp package. Both the .dar and the .package files must be updated. The latest Kemp package is available on the Kemp website.

7. Click **Submit**.



8. Wait for the LoadMaster to be added.

3 Using the Kemp Orchestrator Plugin



The LoadMaster will then be listed in the **Kemp** directory in the **Inventory** tab.

3.4.2 Add Certificate

Before uploading a certificate to the LoadMaster, the certificate file must first be uploaded to Orchestrator. For step-by-step instructions on how to upload a file, refer to the **Upload Files** section.

3 Using the Kemp Orchestrator Plugin

```


1  -----BEGIN CERTIFICATE-----
2  MIICyzCCAjQCCQD9Zrq+3HKfJDANBgqhkiG9w0BAQsFADCBqTELMakGA1UEBhMC
3  SUUxEDA0BgNVBAgMB011bnN0ZXIxETAPBgNVBACMEExpbWVyaWNrMR0wGAYDVQK
4  DBFLRU1QIFRlY2hub2xvZ2llcy5jb20wHhcNMjU1MTQ4WhcNMjU1MTQ4WjCB
5  dDEOMAwGA1UEAwwFamFtZXN0MzZlcy5jb20wHhcNMjU1MTQ4WhcNMjU1MTQ4WjCB
6  Y2hub2xvZ2llcy5jb20wHhcNMjU1MTQ4WhcNMjU1MTQ4WjCB
7  qTELMakGA1UEBhMCSUxEDA0BgNVBAgMB011bnN0ZXIxETAPBgNVBACMEExpbWVya
8  aWNrMR0wGAYDVQKDBFLRU1QIFRlY2hub2xvZ2llcy5jb20wHhcNMjU1MTQ4WhcNMjU1MTQ4WjCB
9  dCBEZXZlbnB9bWVudDEOMAwGA1UEAwwFamFtZXN0MzZlcy5jb20wHhcNMjU1MTQ4WhcNMjU1MTQ4WjCB
10 YnJpZW5Aa2VtcHRlY2hub2xvZ2llcy5jb20wHhcNMjU1MTQ4WhcNMjU1MTQ4WjCB
11 MIGJAoGBAPZyfvEy+JeX4JT336h3IZqd022E8jsSMShZazcuI/GICrBbAGowhBtf
12 kVoESNpq7PsyQR0PYfqJii41HUwqJo/Wx/8ulBoewYzoLAGzYfpAe6Rax+lKTc7
13 7mlKoQ3zheBk9Hj3fw1RT0SgU9F5oiQJT3jT6zprt0sFuBp+UC8JAgMBAAEwDQYJ
14 KoZIHvcNAQELBQADgYEAeoGA22dXIVAI20G8uYOne/KOg7QhV+RXlB6a9j5lQW6E
15 H72GzQaI3K1lTgkP/UKUTCTjQgVw+4tHx3eU+7Dq9BXA4fx30bvqfONCxBHG8eXy
16 N6gw8BAapDftliwRcklZjBjRtdpP+G8kk7OmPh2ZZOvCY4ylSeWZPDgLCy0tYsw=
17 -----END CERTIFICATE-----
18 -----BEGIN RSA PRIVATE KEY-----
19 Proc-Type: 4, ENCRYPTED
20 DEK-Info: DES-EDE3-CBC, 59951F4DADCDF43D
21
22 /8x45hW4xrUpX6eDal2fNDFVN8AUx+saxRYnRYvPSuic463o5UhxRUXi+TUE6eeF
23 CqOB5k5ZeFn2n7x45AHRXlauVGvt4g6oaFZH+GXPvdWCSQWES2TrcQp7KCXy7zth
24 +rn5qsFVqCIXsfdw2ZEV4intoysSj89Fxbqqs8BME9WETCu2w7NN2lBS6ji3fv/f
25 uMSS/cOOuv2jPCpMAvaDgmqCKtOy8dKfJlySKhWFacOCjdGyU7uw+SrP/IpzljBV
26 YWyyxmXsXzmRdsN2d0L1Az8L3h921amHIRCmXs8Hc2vNGDnN9zdJ+SF3vKs256FN
27 OvmScty9zs362nl+nUWTPSqFhDsb6bWY7hMJMARGVTfi/Qjw75XoEQpj0jdDy4oq
28 hCvsliaWU+FC9I1j+bKUU4z3J7CSEkFdtJk4iRsfszk9oGC8gdj6zOfsV090SyIQs
29 2RxKXo1U0RrsAwmYdpQPK5TRLWDnyyIajsHjI2fh3wHOPcwTilWkv+VzOClohKzK
30 dExxW6GAoUgDbbsLuqT4y93x9E+IWA1OBpJ4Z5s4LKkyaiD0jzSvP5OG+Mo17+jg
31 dcKvyJcWuXqs6wI7m/hIeS4GhhqlJjDiuARX60Ws3NcyX4ntWXq8edx1PXvR2+cW
32 oesvuxzqFBncwgnBw01jryWt+7u8TIuOQVUjJlMtaeSYifjofKPP3c/Xud0FE8ck
33 1SEKK+wDTQp8/j7iDxkfyzlh0Ti+NneY2TLsIF+YhLqSvbu2rHkITEBn6PLiTH5k
34 V789ENrdQJU50b+riVKyzZhh2YsWuD3xWK/5RAT83FSi5+N37PQIMA==
35 -----END RSA PRIVATE KEY-----
36

```

When uploading a certificate file via Orchestrator (or via the Kemp API), both the certificate and key must be concatenated into the one file. The certificate file must be listed on top, followed by the private key at the bottom - this is the format which is required by the API which is what the Kemp Orchestrator plugin is based upon. An example file is shown in the screenshot above.

3 Using the Kemp Orchestrator Plugin

After a certificate file has been uploaded to Orchestrator, it can then be uploaded to the LoadMaster using the **Add Certificate** workflow.




1. Enter the username and password to access the LoadMaster.
2. Specifying the SSL certificate is optional - this is the certificate file used to authenticate to the LoadMaster (the root LoadMaster certificate).

This is the certificate file used to authenticate to the LoadMaster - this is not the field used to upload a new certificate.

3. Click **Not set** in the **Select the LoadMaster to add the certificate to** field.

3 Using the Kemp Orchestrator Plugin



4. Expand the **Kemp** directory.
5. Select the relevant LoadMaster.
6. Click **Select**.

3 Using the Kemp Orchestrator Plugin

Start Workflow : Add Certificate

1 Authentication

2 Certificate Configuration

* Enter the username for the LoadMaster


bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)

Not set

* Select the LoadMaster to add the certificate to

 Example Load Master

7. Click **Certificate Configuration**.

Start Workflow : Add Certificate

✓ **1 Authentication**

2 Certificate Configuration

* Select the certificate file to be added

Not set

* Enter the passphrase for this certificate


* Enter a LoadMaster identifier for this certificate

Replace any existing certificate that uses this identifier?


☐ Yes ☒ No

8. Click **Not set**.

3 Using the Kemp Orchestrator Plugin



9. Expand the **Kemp** directory.
10. Expand the **Certificates** directory.
11. Select the relevant certificate.
12. Click **Select**.



Start Workflow : Add Certificate

✓ 1 Authentication

2 Certificate Configuration

* Select the certificate file to be added

Certificates > Testcert Crt

* Enter the passphrase for this certificate

* Enter a LoadMaster identifier for this certificate

Example Certificate

Replace any existing certificate that uses this identifier?

☐ Yes ☒ No

Cancel Back Next Submit

13. Enter the passphrase which was used when creating the certificate in the **Enter the passphrase for this certificate** text box.

14. Enter a recognizable name for the certificate in the **Enter a LoadMaster identifier for this certificate** text box. This is a friendly name for the certificate which will be displayed in the LoadMaster.


15. If replacing an existing certificate of the same name, select **Yes**.

16. Click **Submit**.

3.4.3 Backup Certificates

The certificates on a LoadMaster can be backed up via Orchestrator. To do this, run the **Backup Certificates** workflow.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Backup Certificates


Common Parameters

- * Enter the username for the LoadMaster
bal
- * Enter the password for the LoadMaster

- Select the SSL certificate provided by the LoadMaster (optional)
Not set
- * Select the LoadMaster to perform the backup on.
Not set
- * Enter a passphrase to secure this backup file.


1. Enter the username and password to access the LoadMaster.
2. Specifying the SSL certificate is optional - this is the certificate file used to authenticate to the LoadMaster (the root LoadMaster certificate).
3. Click **Not set** in the **Select the LoadMaster to perform the backup on** field.

3 Using the Kemp Orchestrator Plugin



4. Expand the **Kemp** directory.
5. Select the relevant LoadMaster.
6. Click **Select**.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Backup Certificates

Common Parameters

* Enter the username for the LoadMaster

bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)

Not set

* Select the LoadMaster to perform the backup on.


Example Load Master

* Enter a passphrase to secure this backup file.

Cancel Submit


7. Enter a passphrase to secure this backup file.

8. Click **Submit**.



9. Wait for the backup to complete.

3 Using the Kemp Orchestrator Plugin




The backup will be saved to the **LoadMaster Backups** directory in the **Inventory** tab.

3.4.4 Backup LoadMaster

The LoadMaster configuration can be backed up via Orchestrator. To do this, run the **Backup LoadMaster** workflow.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Backup LoadMaster

Common Parameters

* Enter the username for the LoadMaster

bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)


Not set

* Select the LoadMaster to perform this backup on.

Not set


1. Enter the username and password to access the LoadMaster.
2. Specifying the SSL certificate is optional - this is the certificate file used to authenticate to the LoadMaster (the root LoadMaster certificate).
3. Click **Not set** in the **Select the LoadMaster to perform this backup on** field.

3 Using the Kemp Orchestrator Plugin



4. Expand the **Kemp** directory.
5. Select the relevant LoadMaster.
6. Click **Select**.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Backup LoadMaster

Common Parameters

* Enter the username for the LoadMaster

bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)

Not set


* Select the LoadMaster to perform this backup on.

Example Load Master

Cancel Submit

7. Click **Submit**.


3 Using the Kemp Orchestrator Plugin



The backup will be stored in the **LoadMaster Backups** directory in the **Inventory** tab. The backup can be restored to a LoadMaster via Orchestrator. For instructions on how to do this, refer to the **Reboot LoadMaster** section.

3.4.5 Delete Certificate

Certificates can be deleted from the LoadMaster by running the **Delete Certificates** workflow.



Start Workflow : Delete Certificate


Common Parameters

- * Enter the username for the LoadMaster
bal
- * Enter the password for the LoadMaster

- Select the SSL certificate provided by the LoadMaster (optional)
Not set
- * Select the LoadMaster to delete a certificate from
Not set
- * Enter the identifier of the certificate to be deleted


1. Enter the username and password to access the LoadMaster.
2. Specifying the SSL certificate is optional - this is the certificate file used to authenticate to the LoadMaster (the root LoadMaster certificate).
3. Click **Not set** in the **Select the LoadMaster to delete a certificate from** field.

3 Using the Kemp Orchestrator Plugin



4. Expand the **Kemp** directory.
5. Select the relevant LoadMaster.
6. Click **Select**.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Delete Certificate

Common Parameters


- * Enter the username for the LoadMaster
bal
- * Enter the password for the LoadMaster

- Select the SSL certificate provided by the LoadMaster (optional)
Not set
- * Select the LoadMaster to delete a certificate from
Example Load Master
- * Enter the identifier of the certificate to be deleted
Example Certificate

Cancel Submit

7. Enter the identifier of the certificate to be deleted.

8. Click **Submit**.




9. Wait for the deletion to finish.

3.4.6 Disable API

The API interface on the LoadMaster can be disabled via Orchestrator.

If the API is disabled, most of the workflows will not work. The only workflows that will work when the API is disabled are **Add LoadMaster** and **Enable API**.



Start Workflow : Disable API


Common Parameters

- * Enter the username for the LoadMaster
bal
- * Enter the password for the LoadMaster

- Select the SSL certificate provided by the LoadMaster (optional)
Not set
- * Select the LoadMaster to disable the API of
Not set


1. Enter the username and password to access the LoadMaster.
2. Specifying the SSL certificate is optional - this is the certificate file used to authenticate to the LoadMaster (the root LoadMaster certificate).
3. Click **Not set** in the **Select the LoadMaster to disable the API of** field.

3 Using the Kemp Orchestrator Plugin



4. Expand the **Kemp** directory.
5. Select the relevant LoadMaster.
6. Click **Select**.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Disable API

Common Parameters

* Enter the username for the LoadMaster
bal


* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)
Not set

* Select the LoadMaster to disable the API of
Example Load Master

Cancel Submit

7. Click **Submit**.




8. Wait for the API to be disabled.

3.4.7 Enable API

The API interface of a LoadMaster which exists in Orchestrator can be enabled via Orchestrator. The API interface needs to be enabled on a LoadMaster for most of the workflows to run. To enable the API, run the **Enable API** command.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Enable API

Common Parameters

* Enter the username for the LoadMaster

bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)


Not set

* Select the LoadMaster to enable the API of

Not set


1. Enter the username and password to access the LoadMaster.
2. Specifying the SSL certificate is optional - this is the certificate file used to authenticate to the LoadMaster (the root LoadMaster certificate).
3. Click **Not set** in the **Select the LoadMaster to enable the API of** field.

3 Using the Kemp Orchestrator Plugin



4. Expand the **Kemp** directory.
5. Select the relevant LoadMaster.
6. Click **Select**.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Enable API

Common Parameters

* Enter the username for the LoadMaster

bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)

Not set

* Select the LoadMaster to enable the API of

Example Load Master


Cancel Submit

7. Click **Submit**.

3.4.8 Get Parameter

The **Get Parameter** workflow can be used to retrieve a number of LoadMaster field values. For a list of parameter names that can be retrieved, refer to **Appendix A - Get and Set Parameters**.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Get Parameter


Common Parameters

- * Enter the username for the LoadMaster
bal
- * Enter the password for the LoadMaster

- Select the SSL certificate provided by the LoadMaster (optional)
Not set
- * Select the LoadMaster to be queried
Not set
- * Enter the name of the parameter to be read

1. Enter the username and password to access the LoadMaster.
2. Specifying the SSL certificate is optional - this is the certificate file used to authenticate to the LoadMaster (the root LoadMaster certificate).
3. Click **Not set** in the **Select the LoadMaster to be queried** field.

3 Using the Kemp Orchestrator Plugin



4. Expand the **Kemp** directory.
5. Select the LoadMaster to retrieve the value from.
6. Click **Select**.

3 Using the Kemp Orchestrator Plugin

Start Workflow : Get Parameter

Common Parameters

* Enter the username for the LoadMaster

bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)

Not set

* Select the LoadMaster to be queried

Example Load Master

* Enter the name of the parameter to be read

motd

Cancel

Submit

7. Enter the relevant parameter name in the **Enter the name of the parameter to be read** field.

8. Click **Submit**.

General Variables Logs		
Name	Type	Value
username	string	bal
password	SecureString	
certFile	KEMP:LoadMasterFile	Not set
loadMaster	KEMP:LoadMaster	Example Load Master
paramName	string	motd
paramValue	string	Example Message of the Day


9. To view the value, select the **Variables** tab at the bottom.

10. The parameters and their values will be displayed.

3.4.9 Install Patch

The LoadMaster firmware can be updated with a firmware patch file via Orchestrator. Before uploading the firmware patch file to the LoadMaster, first it must be uploaded to Orchestrator. For step-by-step instructions on how to upload a file, refer to the **Upload Files** section.

After a firmware patch file has been uploaded to Orchestrator, run the **Install Patch** workflow to update the LoadMaster.



Start Workflow : Install Patch


Common Parameters

- * Enter the username for the LoadMaster
bal
- * Enter the password for the LoadMaster


- Specify the SSL certificate provided by the LoadMaster (optional)
Not set
- * Select the LoadMaster to be patched
Not set
- * Select the patch to apply
Not set
- Reboot the LoadMaster after the patch is applied?
☐ Yes ☒ No

1. Enter the username and password to access the LoadMaster.
2. Specifying the SSL certificate is optional - this is the certificate file used to authenticate to the LoadMaster (the root LoadMaster certificate).
3. Click **Not set** in the **Select the LoadMaster to be patched** field.

3 Using the Kemp Orchestrator Plugin



4. Expand the **Kemp** directory.
5. Select the LoadMaster to be patched.
6. Click **Select**.



Start Workflow : Install Patch

Common Parameters

* Enter the username for the LoadMaster
bal

* Enter the password for the LoadMaster

Specify the SSL certificate provided by the LoadMaster (optional)
Not set

* Select the LoadMaster to be patched
Example Load Master

* Select the patch to apply
Not set

Reboot the LoadMaster after the patch is applied?
☐ Yes ☒ No


7. Click **Not set** in the **Select the patch to apply** field.
8. Expand the **Kemp** directory.
9. Expand the **Patches** directory.
10. Select the relevant patch file.
11. Click **Select**.
12. Select **Yes** to reboot the LoadMaster after the patch has been uploaded.

The LoadMaster must be rebooted after the patch file has been installed in order for the changes to be applied correctly.

13. Click **Submit**.
14. Wait for the installation and reboot to complete.

3.4.10 Reboot LoadMaster

A LoadMaster which exists in Orchestrator can be rebooted via Orchestrator. To reboot a LoadMaster, run the **Reboot LoadMaster** workflow.



Start Workflow : Reboot LoadMaster

Common Parameters

* Enter the username for the LoadMaster

bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)


Not set

* Select the LoadMaster to be rebooted

Not set


1. Enter the username and password to access the LoadMaster.
2. Specifying the SSL certificate is optional - this is the certificate file used to authenticate to the LoadMaster (the root LoadMaster certificate).
3. Click **Not set** in the **Select the LoadMaster to be rebooted** field.

3 Using the Kemp Orchestrator Plugin



- 4. Select the relevant LoadMaster to be rebooted.
- 5. Click **Select**.

3 Using the Kemp Orchestrator Plugin



The dialog box is titled "Start Workflow : Reboot LoadMaster". It features a "Common Parameters" tab on the left. The main area contains four fields with red asterisk icons indicating required fields:

- "Enter the username for the LoadMaster": A text box containing "bal".
- "Enter the password for the LoadMaster": A password box containing "*****".
- "Select the SSL certificate provided by the LoadMaster (optional)": A dropdown menu showing "Not set".
- "Select the LoadMaster to be rebooted": A dropdown menu showing "Example Load Master".


At the bottom right, there are "Cancel" and "Submit" buttons.

6. Click **Submit**.

7. Wait for the LoadMaster to reboot.

3.4.11 Remove LoadMaster

A LoadMaster can be removed from Orchestrator by running the **Remove LoadMaster** command.




The dialog box is titled "Start Workflow : Remove LoadMaster". It features a "Common Parameters" tab on the left. The main area contains one field with a red asterisk icon indicating a required field:

- "Select the LoadMaster to remove from the inventory": A dropdown menu showing "Not set".


1. Click **Not set**.

3 Using the Kemp Orchestrator Plugin




- 2. Select the relevant LoadMaster.
- 3. Click **Select**.

3 Using the Kemp Orchestrator Plugin




4. Click **Submit**.



5. Wait for the LoadMaster to be removed.

3.4.12 Restore Certificates

If a certificate backup file exists in Orchestrator, it can be restored to a LoadMaster. To back up the certificates on a LoadMaster, refer to the **Backup Certificates** section. To restore the certificates, run the **Restore Certificates** command.



Start Workflow : Restore Certificates

1 Authentication

2 Backup Options

* Enter the username for the LoadMaster

bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)


Not set

* Select the LoadMaster to restore

Not set

1. Enter the username and password to access the LoadMaster.
2. Specifying the SSL certificate is optional - this is the certificate file used to authenticate to the LoadMaster (the root LoadMaster certificate).
3. Click **Not set**.

3 Using the Kemp Orchestrator Plugin



- 4. Expand the **Kemp** directory.
- 5. Select the relevant LoadMaster.
- 6. Click **Select**.

Start Workflow : Restore Certificates

1 Authentication

2 Backup Options

* Enter the username for the LoadMaster

bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)

Not set

* Select the LoadMaster to restore

Example Load Master

7. Click **Backup Options**.

Start Workflow : Restore Certificates

✓ 1 Authentication

2 Backup Options

* Select the certificate backup to be restored

Not set

* Enter the passphrase used to secure the backup file

Restore Virtual Service certificates?

Yes

No


Restore intermediate certificates?

Yes

No


8. Click **Not set**.

3 Using the Kemp Orchestrator Plugin



9. Expand the **Kemp** directory.
10. Expand the **Certificate Backups** directory.
11. Select the relevant backup.
12. Click **Select**.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Restore Certificates

✓ 1 Authentication

2 Backup Options

* Select the certificate backup to be restored

Certificate Backups > Example Load Master 2015 08 21 10 11

* Enter the passphrase used to secure the backup file

Restore Virtual Service certificates?

☒ Yes ☐ No

Restore intermediate certificates?


☒ Yes ☐ No

Cancel Back Next Submit

13. Enter the passphrase used to secure the backup file.

14. Specify which certificates to restore.

15. Click **Submit**.




16. Wait for the certificates to restore.

3.4.13 Restore LoadMaster

Before restoring a LoadMaster configuration, a backup configuration must be available in Orchestrator. To back up a LoadMaster configuration in Orchestrator, refer to the **Backup LoadMaster** section.

When a backup configuration exists in Orchestrator, run the **Restore LoadMaster** workflow to restore the configuration.

A GEO LoadMaster backup configuration cannot be restored on a non-GEO LoadMaster configuration



Start Workflow : Restore LoadMaster

1 Authentication

2 Backup Options

* Enter the username for the LoadMaster

bal

* Enter the password for the LoadMaster

Specify the SSL certificate provided by the LoadMaster (optional)


Not set

* Select the LoadMaster to restore

Not set


1. Enter the username and password to access the LoadMaster.
2. Specifying the SSL certificate is optional - this is the certificate file used to authenticate to the LoadMaster (the root LoadMaster certificate).
3. Click **Not set** in the **Select the LoadMaster to restore** field.

3 Using the Kemp Orchestrator Plugin



4. Expand the **Kemp** directory.
5. Select the relevant LoadMaster.
6. Click **Select**.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Restore LoadMaster

1 Authentication

2 Backup Options

* Enter the username for the LoadMaster

bal

* Enter the password for the LoadMaster


Specify the SSL certificate provided by the LoadMaster (optional)

Not set

* Select the LoadMaster to restore

Example Load Master

7. Click **Backup Options**.



Start Workflow : Restore LoadMaster

✓ **1 Authentication**

2 Backup Options

* Select the backup configuration to be restored

Not set

Restore the base LoadMaster configuration?

☐ Yes ☒ No

Restore the Virtual Service configuration?


☐ Yes ☒ No

Restore the GEO configuration?


☐ Yes ☒ No

8. Click **Not set**.

3 Using the Kemp Orchestrator Plugin



9. Expand the **Kemp** directory.
10. Expand the **LoadMaster Backups** directory.
11. Select the relevant backup.
12. Click **Select**.



Start Workflow : Restore LoadMaster

✓ 1 Authentication

2 Backup Options

* Select the backup configuration to be restored

Load Master Backups > Loadmaster 2015 08 20 15 29

Restore the base LoadMaster configuration?

☒ Yes ☐ No

Restore the Virtual Service configuration?

☒ Yes ☐ No

Restore the GEO configuration?

☐ Yes ☒ No

Reboot the LoadMaster after restoration?

☒ Yes ☐ No

Cancel Back Next Submit

13. Specify the configurations to be restored by selecting **Yes** for the relevant options.

14. If restoring the base LoadMaster configuration, another field will appear asking if the LoadMaster should be rebooted after restoration. If restoring the base configuration, please set this to **Yes** as the LoadMaster needs to be rebooted for the changes to be applied.

15. Click **Submit**.

16. Wait for the restoration to complete.

3.4.14 Set Credentials

When a LoadMaster is added to Orchestrator via the **Add LoadMaster** command, the credentials are set. If, for any reason, the LoadMaster credentials which are saved in Orchestrator need to be updated (for example if the credentials have changed), the **Set Credentials** workflow can be run.

Start Workflow : Set Credentials

Common Parameters

* Select the LoadMaster to set the credentials of

Not set

* Enter the username for the LoadMaster

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)

Not set

1. Click **Not set** in the **Select the LoadMaster to set the credentials of** field.

Select (KEMP:LoadMaster)

KEMP

Example Load Master

Loadmaster

D Certificate Backups

D Certificates

D Load Master Backups

D Patches

LoadMaster - Example Load Master

General

Custom properties

Inventory ID	Example LoadMaster
Administrative Access IP	10.154.11.60
Virtual Services	[VS 1 (10.154.178.151:80/tc


Cancel

Select

2. Expand the **Kemp** directory.

3 Using the Kemp Orchestrator Plugin

3. Select the relevant LoadMaster.
4. Click **Select**.



Start Workflow : Set Credentials

Common Parameters

* Select the LoadMaster to set the credentials of
Example Load Master

* Enter the username for the LoadMaster
bal

* Enter the password for the LoadMaster


Select the SSL certificate provided by the LoadMaster (optional)
Not set

Cancel Submit

5. Enter the updated LoadMaster credentials.
6. Click **Submit**.

3.4.15 Set Parameter

The **Set Parameter** workflow can be used to set a number of LoadMaster field values. For a list of parameter names that can be set, refer to **Appendix A - Get and Set Parameters**.



Start Workflow : Set Parameter

1 Authentication

2 Parameter Configuration

* Enter the username for the LoadMaster

bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)


Not set

* Select the LoadMaster to be modified

Not set

1. Enter the username and password to access the LoadMaster.
2. Specifying the SSL certificate is optional - this is the certificate file used to authenticate to the LoadMaster (the root LoadMaster certificate).
3. Click **Not set** in the **Select the LoadMaster to be modified** field.

3 Using the Kemp Orchestrator Plugin



4. Expand the **Kemp** directory.
5. Select the relevant LoadMaster.
6. Click **Select**.

3 Using the Kemp Orchestrator Plugin

Start Workflow : Set Parameter

1 Authentication
2 Parameter Configuration


* Enter the username for the LoadMaster

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)


Not set

* Select the LoadMaster to be modified

 [Example Load Master](#)

7. Click **Parameter Configuration**.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Set Parameter

✓ 1 Authentication

2 Parameter Configuration

* Enter the parameter name to be modified

motd

* Enter the new value for the specified parameter


Updated Example Message of the Day

Cancel Back Next Submit

8. Enter the name of the parameter to be modified.

9. Enter the new value for the specified parameter.

10. Click **Submit**.




11. Wait for the parameter to be set.

3.5 Virtual Services


A number of tasks can be performed in relation to Virtual Services, such as adding and removing them. Refer to the sections below for further details.

3.5.1 Add Virtual Service

A Virtual Service can be added to a LoadMaster via Orchestrator by running the **Add Virtual Service** command.




1. Enter the username and password to access the LoadMaster.
2. Specifying the SSL certificate is optional - this is the certificate file used to authenticate to the LoadMaster (the root LoadMaster certificate).
3. Click **Virtual Service Configuration**.




4. Click **Not set**.

3 Using the Kemp Orchestrator Plugin



5. Expand the **Kemp** directory.
6. Select the relevant LoadMaster.
7. Click **Select**.



Start Workflow : Add Virtual Service

✓ 1 Authentication

2 Virtual Service Configur...

* Select the LoadMaster to add the Virtual Service to

Example Load Master

* Enter the IP address of the Virtual Service

10.154.11.61

* Enter the port of the Virtual Service

80

* Select the protocol of the Virtual Service

TCP

Cancel Back Next Submit

8. Enter a valid IP address in the Enter the IP address of the Virtual Service text box.
9. Enter the desired port in the **Enter the port of the Virtual Service** text box.
10. Select the relevant protocol from the drop-down list.
11. Click **Submit**.

3.5.2 Assign Virtual Service Certificates

Certificates can be assigned to a Virtual Service via Orchestrator. To do this, run the **Assign Virtual Service Certificates** command.



Start Workflow : Assign Virtual Service Certificates

Common Parameters

* Enter the username for the LoadMaster

bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)

Not set

* Select the Virtual Service to assign certificates to


Not set

Enter the certificate identifiers to assign to the Virtual Service

Not set


1. Enter the username and password to access the LoadMaster.
2. Specifying the SSL certificate is optional - this is the certificate file used to authenticate to the LoadMaster (the root LoadMaster certificate).
3. Click **Not set** in the Select the **Virtual Service to assign certificates to** field.

3 Using the Kemp Orchestrator Plugin



- 4. Expand the **Kemp** directory.
- 5. Expand the relevant LoadMaster.
- 6. Select the relevant Virtual Service.
- 7. Click **Select**.

3 Using the Kemp Orchestrator Plugin

 Start Workflow : Assign Virtual Service Certificates

Common Parameters

* Enter the username for the LoadMaster


bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)

Not set

* Select the Virtual Service to assign certificates to


 Example Load Master > Vs 3 (10 154 11 61)

Enter the certificate identifiers to assign to the Virtual Service

Not set

8. Click **Not set** in the **Enter the certificate identifiers to assign to the Virtual Service** field.

3 Using the Kemp Orchestrator Plugin




9. In the **New value** text box, enter the certificate identifier (friendly name) of the certificate to be assigned.

10. Click **Insert value**.

11. Click **Accept**.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Assign Virtual Service Certificates

Common Parameters

* Enter the username for the LoadMaster
bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)
Not set

* Select the Virtual Service to assign certificates to
Example Load Master > Vs 3 (10 154 11 61)

Enter the certificate identifiers to assign to the Virtual Service
Array [Example Certificate]


Cancel Submit

12. Click **Submit**.

3.5.3 Modify Virtual Service Name

The name of a Virtual Service can be modified using the **Modify Virtual Service Name** workflow.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Modify Virtual Service Name

Common Parameters

* Enter the username for the LoadMaster

bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)

Not set


* Select the Virtual Service to be renamed

Not set

Enter the new name for the Virtual Service


1. Enter the username and password to access the LoadMaster.
2. Specifying the SSL certificate is optional - this is the certificate file used to authenticate to the LoadMaster (the root LoadMaster certificate).
3. Click **Not set** in the **Select the Virtual Service to be renamed** field.

3 Using the Kemp Orchestrator Plugin



- 4. Expand the **Kemp** directory.
- 5. Expand the relevant LoadMaster.
- 6. Select the relevant Virtual Service.
- 7. Click **Select**.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Modify Virtual Service Name

Common Parameters

* Enter the username for the LoadMaster
bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)
Not set

* Select the Virtual Service to be renamed
Example Load Master > Vs 3 (10 154 11 61)

Enter the new name for the Virtual Service
Example Service Name

Cancel Submit


8. Enter the new name for the Virtual Service.

9. Click **Submit**.

3.5.4 Remove Virtual Service

A Virtual Service can be deleted via Orchestrator by running the **Remove Virtual Service** workflow.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Remove Virtual Service

Common Parameters

* Enter the username for the LoadMaster

bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)


Not set

* Select the Virtual Service to be removed


Not set

1. Enter the username and password to access the LoadMaster.
2. Specifying the SSL certificate is optional - this is the certificate file used to authenticate to the LoadMaster (the root LoadMaster certificate).
3. Click **Not set** in the **Select the Virtual Service to be removed** field.

3 Using the Kemp Orchestrator Plugin



- 4. Expand the **Kemp** directory.
- 5. Expand the relevant LoadMaster.
- 6. Select the relevant Virtual Service.
- 7. Click **Select**.



Start Workflow : Remove Virtual Service

Common Parameters

* Enter the username for the LoadMaster
bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)
Not set

* Select the Virtual Service to be removed
Example Load Master > Vs 3 (10 154 11 61)

Cancel Submit

8. Click **Submit**.


3.6 Sub Virtual Services

A number of tasks can be performed in relation to SubVSes, such as adding and removing a SubVS. Refer to the sections below for further details.

3.6.1 Add SubVS

A SubVS can be added by running the **Add SubVS** workflow.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Add SubVS


Common Parameters

- * Enter the username for the LoadMaster
bal
- * Enter the password for the LoadMaster

- Select the SSL certificate provided by the LoadMaster (optional)
Not set
- * Select the Virtual Service to add a SubVS to
Not set


1. Enter the username and password to access the LoadMaster.
2. Specifying the SSL certificate is optional - this is the certificate file used to authenticate to the LoadMaster (the root LoadMaster certificate).
3. Click **Not set** in the **Select the Virtual Service to add a SubVS to** field.

3 Using the Kemp Orchestrator Plugin



- 4. Expand the **Kemp** directory.
- 5. Expand the relevant LoadMaster.
- 6. Select the relevant Virtual Service.
- 7. Click **Select**.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Add SubVS

Common Parameters

* Enter the username for the LoadMaster

bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)

Not set

* Select the Virtual Service to add a SubVS to


Example Load Master > Vs 1 (10 154 178 151)

Cancel Submit

8. Click **Submit**.

3.6.2 Modify SubVS Name

The name of a SubVS can be modified using the **Modify SubVS Name** workflow.



Start Workflow : Modify SubVS Name

Common Parameters

* Enter the username for the LoadMaster

bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)

Not set


* Select the SubVS to be renamed

Not set

Enter the new name for the SubVS


1. Enter the username and password to access the LoadMaster.
2. Specifying the SSL certificate is optional - this is the certificate file used to authenticate to the LoadMaster (the root LoadMaster certificate).
3. Click **Not set** in the **Select the SubVS to be renamed** field.

3 Using the Kemp Orchestrator Plugin



- 4. Expand the **Kemp** directory.
- 5. Expand the relevant LoadMaster.
- 6. Select the relevant SubVS.
- 7. Click **Select**.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Modify SubVS Name

Common Parameters

* Enter the username for the LoadMaster

bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)

Not set

* Select the SubVS to be renamed

Example Load Master > Vs 1 (10 154 178 151) > Sub Vs 2

Enter the new name for the SubVS

Example SubVS Name

Cancel Submit


8. Enter the new name for the SubVS.

9. Click **Submit**.

3.6.3 Remove SubVS

A SubVS can be deleted via Orchestrator by running the **Remove SubVS** command.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Remove SubVS

Common Parameters

* Enter the username for the LoadMaster

bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)


Not set

Select the SubVS to be removed


Not set

1. Enter the username and password to access the LoadMaster.
2. Specifying the SSL certificate is optional - this is the certificate file used to authenticate to the LoadMaster (the root LoadMaster certificate).
3. Click **Not set** in the **Select the SubVS to be removed** field.

3 Using the Kemp Orchestrator Plugin



4. Expand the **Kemp** directory.
5. Expand the relevant LoadMaster.
6. Expand the relevant Virtual Service.
7. Select the relevant SubVS.
8. Click **Select**.



Start Workflow : Remove SubVS

Common Parameters

* Enter the username for the LoadMaster

bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)

Not set

Select the SubVS to be removed

Example Load Master > Vs 1 (10 154 178 151) > Sub Vs 3

Cancel Submit

9. Click **Submit**.


3.7 Real Servers

A number of tasks can be performed in relation to Real Servers, such as adding a Real Server to a Virtual Service or removing a Real Server. Refer to the sections below for further details.

3.7.1 Add Real Server to Sub Virtual Service

A Real Server can be added to a SubVS by running the **Add Real Server to Sub Virtual Service** workflow.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Add Real Server To SubVS

1 Authentication

2 Real Server Configuration

* Enter the username for the LoadMaster


bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)

Not set

1. Enter the username and password to access the LoadMaster.
2. Specifying the SSL certificate is optional - this is the certificate file used to authenticate to the LoadMaster (the root LoadMaster certificate).
3. Click **Real Server Configuration**.



Start Workflow : Add Real Server To SubVS

✓ **1 Authentication**

2 Real Server Configuration

* Select the SubVS to add this Real Server to


Not set

* Enter the IP address of the Real Server

* Enter the port of the Real Server


4. Click **Not set**.

3 Using the Kemp Orchestrator Plugin



5. Expand the **Kemp** directory.
6. Expand the relevant LoadMaster.
7. Expand the relevant Virtual Service.
8. Select the relevant **SubVS**.
9. Click **Select**.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Add Real Server To SubVS

✓ 1 Authentication

2 Real Server Configuration

* Select the SubVS to add this Real Server to
Example Load Master > Vs 1 (10 154 178 151) > Sub Vs 2

* Enter the IP address of the Real Server
10.154.11.62

* Enter the port of the Real Server
80

Cancel Back Next Submit

10. Enter the IP address of the Real Server to be added.


11. Enter the port of the Real Server.

12. Click **Submit**.

3.7.2 Add Real Server to Virtual Service

A Real Server can be added to a Virtual Service via Orchestrator by running the **Add Real Server to Virtual Service** workflow.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Add Real Server To Virtual Service

1 Authentication

2 Real Server Configuration

* Enter the username for the LoadMaster


bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)

Not set

1. Enter the username and password to access the LoadMaster.
2. Specifying the SSL certificate is optional - this is the certificate file used to authenticate to the LoadMaster (the root LoadMaster certificate).
3. Click **Real Server Configuration**.



Start Workflow : Add Real Server To Virtual Service

✓ **1 Authentication**

2 Real Server Configuration

* Select the Virtual Service to add the Real Server to


Not set

* Enter the IP address of the Real Server

* Enter the port of the Real Server


4. Click **Not set**.

3 Using the Kemp Orchestrator Plugin



- 5. Expand the **Kemp** directory.
- 6. Expand the relevant LoadMaster.
- 7. Select the relevant Virtual Service.
- 8. Click **Select**.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Add Real Server To Virtual Service

✓ 1 Authentication

2 Real Server Configuration

* Select the Virtual Service to add the Real Server to

i Example Load Master > Vs 1 (10 154 178 151)

* Enter the IP address of the Real Server

10.154.11.63

* Enter the port of the Real Server

80

Cancel Back Next Submit

9. Enter the IP address of the Real Server.


10. Enter the port of the Real Server.

11. Click **Submit**.

3.7.3 Remove Real Server

A Real Server can be removed by running the **Remove Real Server** workflow.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Remove Real Server

Common Parameters

* Enter the username for the LoadMaster

bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)


Not set

* Select the Real Server to be removed

Not set


1. Enter the username and password to access the LoadMaster.
2. Specifying the SSL certificate is optional - this is the certificate file used to authenticate to the LoadMaster (the root LoadMaster certificate).
3. Click **Not set** in the **Select the Real Server to be removed** field.

3 Using the Kemp Orchestrator Plugin



- 4. Expand the **Kemp** directory.
- 5. Expand the relevant LoadMaster.
- 6. Expand the Virtual Service and/or SubVS.
- 7. Select the relevant Real Server.
- 8. Click **Select**.

3 Using the Kemp Orchestrator Plugin



Start Workflow : Remove Real Server

Common Parameters

* Enter the username for the LoadMaster

bal

* Enter the password for the LoadMaster

Select the SSL certificate provided by the LoadMaster (optional)

Not set

* Select the Real Server to be removed

Example Load Master > Vs 1 (10 154 178 151) > Sub Vs 2 > 10 154 11 62 80

Cancel Submit

9. Click **Submit**.

4 Uninstall the Kemp Orchestrator Plugin

There are three steps that need to be completed in order to uninstall the Kemp Orchestrator plugin. Refer to the sections below for step-by-step instructions.

4.1 Uninstall the Workflows


The first step is to uninstall the workflows. To do this, follow the steps below:



1. Select **Design** from the drop-down menu in the top-left of the screen.




2. Select the packages tab (orange icon).




4 Uninstall the Kemp Orchestrator Plugin

3. Right-click **com.kemptechnologies** and select **Delete element with content**.



4. Click **DELETE ALL**.



5. Wait for the deletion to complete.

Now that the workflows have been uninstalled, the Kemp plugin can be uninstalled. Follow the steps in the next section to do this.

4.2 Remove the Kemp Orchestrator Plugin

Then, after uninstalling the workflows - follow these steps:

1. Remotely connect to the Orchestrator server.
2. Navigate to the Orchestrator plugins folder:

```
cd /var/lib/vco/app-server/plugins
```

3. Remove the Kemp Orchestrator plugin by running the following command:

```
rm <KempPluginFilename>.dar
```

Now that the Kemp Orchestrator plugin has been removed, the service needs to be restarted for the changes to be applied.

4.3 Restart the Service

After uninstalling, restart the service to complete the uninstallation. To do that, follow the steps below:


1. In a web browser, navigate to the IP address of the Orchestrator server followed by the :8281 port.

Configure the Orchestrator Server

To make additional configuration changes to the Orchestrator server, use the Orchestrator configuration interface:

- [Orchestrator Configuration](#)
- [Orchestrator Control Center \(Beta\)](#)

2. Click the **Orchestrator Configuration** link.




The screenshot shows the VMware vRealize Orchestrator Configuration login page. At the top is a blue header with the VMware vRealize Orchestrator logo. Below the header, the page has a 'Welcome' section followed by the instruction 'Enter your username and password to login in VMware vRealize Orchestrator Configuration'. There are two input fields: 'Username:' with the text 'vmware' and 'Password:' with masked characters. A 'Login' button is positioned below the password field.

3. Enter the Orchestrator credentials and click **Login**.


4 Uninstall the Kemp Orchestrator Plugin



4. Click **Startup Options** on the left.



5. Click **Restart service**.



6. Wait for the service to restart.

4 Uninstall the Kemp Orchestrator Plugin



A message will appear when the service has been restarted.

5 Appendix A - Get and Set Parameters

A number of LoadMaster fields can be retrieved and set using the **Get Parameter** and **Set Parameter** workflows. The fields are retrieved and set using API parameters. The list of API parameters that can be used are listed below. For descriptions of what each of the parameters correspond to, please refer to the [RESTful API, Interface Description](#).

- dfltgw
- dfltgwv6
- admingw
- snat
- hatimeout
- hawait
- haprefered
- hamode
- haif
- havhid
- hastyle
- hainitial
- tcpfailover
- cookieupdate
- vmac
- sshaccess
- sshport
- sshv1prot

- wuiaccess
- mcast
- wuiiface
- wuiport
- sshiface
- hoverhelp
- routefilter
- transparent
- alwayspersist
- expect100
- localbind
- addcookieport
- subnetoriginating
- nonlocalrs
- multigw
- addforwardheader
- conntimeout
- authtimeout
- finalpersist
- tcptimestamp
- paranoia
- cachesize
- hostcache
- resetclose
- rfconform
- keepalive

- backupday
- backupenable
- backuphost
- backuphour
- backupminute
- backuppassword
- backuppath
- backupuser
- backupuser
- emailuser
- emaildomain
- emailpassword
- emailserver
- emailsslmode
- emailport
- emailcritical
- emailemergency
- emailerror
- emailinfo
- emailnotice
- emailwarn
- addvia
- allowupload
- dropatdrainend
- droponfail
- closeonerror

- limitinput
- rsarelocal
- slowstart
- subnetorigin
- syslogcritical
- syslogemergency
- syslogerror
- sysloginfo
- syslognotice
- syslogwarn
- sslrenegotiate
- emailenable
- irqbalance
- snmpenable
- snmpV3enable
- snmpv3user
- snmpv3userpasswd
- snmpcontact
- snmpcommunity
- snmplocation
- snmpHaTrap
- snmpv1sink
- snmpv2sink
- snmpclient
- snmptrapenable
- motd

- wuidisplaylines
- linearesplogs
- onlydefaultroutes
- sessionauthmode
- sessionidletime
- sessionmaxfailattempts
- sessioncontrol
- sessionlocalauth
- ntphost
- netconsole
- netconsoleinterface
- namserver
- radiusbackupport
- radiusbackupsecret
- radiusbackupserver
- radiusport
- radiussecret
- radiusserver
- radiusrevalidateinterval
- ldapserver
- ldapbackupserver
- ldapsecurity
- ldaprevalidateinterval
- geoclients
- geopartners
- geosshport

- ha1hostname
- ha2hostname
- hostname
- searchlist
- timezone
- admincert
- localcert
- time
- ntphost
- version
- Tethering
- multihomedwui
- logsplitinterval
- allowemptyposts
- OCSPPort
- OCSPUseSSL
- OCSPOnServerFail
- OCSPServer
- OCSPUrl
- SSLStapling
- SSLRefreshInterval
- L7LimitInput
- sdnstatsmode

6 Appendix B - Memory and CPU Usage Details

The memory and CPU utilization details relating to the Kemp Orchestrator plugin are summarized in the tables below.

The below table shows the specifications of the Orchestrator server that was used when running the tests.

Specification	Type
Hypervisor	VMware vSphere
Memory	3GB
CPU	Dual-core @ 2.0GHz

The below table shows the approximate range of memory usage when the plugin is and is not installed.

Plugin Installed?	Memory Usage
Without plugin installed	381MB -> 395MB
With plugin installed	394MB -> 410MB
With plugin installed (load: ~600 objects)	454MB -> 463MB

The below table shows the CPU usage percentages in various states.

State	CPU Usage
Without plugin installed	~1%
With plugin installed	~1%
Expanding tree view (load: ~100 objects)	~8%
Expanding tree view (load: ~500 objects)	~19%
Empty workflow	~13%

Configure Server Availability workflow	~17%
Add LoadMaster workflow (load: 0 objects)	~17%
Add LoadMaster workflow (load: ~500 objects)	~40%
Remove LoadMaster workflow (load: 0 objects)	~17%
Remove LoadMaster workflow (load: ~500 objects)	~28%

References

Unless otherwise specified, the following documents can be found at <http://kemptechnologies.com/loadmaster-documentation>.

Java API, Interface Description

RESTful API, Interface Description

Last Updated Date

This document was last updated on 30 July 2023.