



Domino

Deployment Guide

UPDATED: 29 July 2023

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

These materials and all Progress® software products are copyrighted and all rights are reserved by Progress Software Corporation. The information in these materials is subject to change without notice, and Progress Software Corporation assumes no responsibility for any errors that may appear therein. The references in these materials to specific platforms supported are subject to change.

#1 Load Balancer in Price/Performance, 360 Central, 360 Vision, Chef, Chef (and design), Chef Habitat, Chef Infra, Code Can (and design), Compliance at Velocity, Corticon, Corticon.js, DataDirect (and design), DataDirect Cloud, DataDirect Connect, DataDirect Connect64, DataDirect XML Converters, DataDirect XQuery, DataRPM, Defrag This, Deliver More Than Expected, DevReach (and design), Driving Network Visibility, Flowmon, Inspec, Ipswitch, iMacros, K (stylized), Kemp, Kemp (and design), Kendo UI, Kinvey, LoadMaster, MessageWay, MOVEit, NativeChat, OpenEdge, Powered by Chef, Powered by Progress, Progress, Progress Software Developers Network, SequeLink, Sitefinity (and Design), Sitefinity, Sitefinity (and design), Sitefinity Insight, SpeedScript, Stylized Design (Arrow/3D Box logo), Stylized Design (C Chef logo), Stylized Design of Samurai, TeamPulse, Telerik, Telerik (and design), Test Studio, WebSpeed, WhatsConfigured, WhatsConnected, WhatsUp, and WS_FTP are registered trademarks of Progress Software Corporation or one of its affiliates or subsidiaries in the U.S. and/or other countries.

Analytics360, AppServer, BusinessEdge, Chef Automate, Chef Compliance, Chef Desktop, Chef Workstation, Corticon Rules, Data Access, DataDirect Autonomous REST Connector, DataDirect Spy, DevCraft, Fiddler, Fiddler Classic, Fiddler Everywhere, Fiddler Jam, FiddlerCap, FiddlerCore, FiddlerScript, Hybrid Data Pipeline, iMail, InstaRelinker, JustAssembly, JustDecompile, JustMock, KendoReact, OpenAccess, PASOE, Pro2, ProDataSet, Progress Results, Progress Software, ProVision, PSE Pro, Push Jobs, SafeSpaceVR, Sitefinity Cloud, Sitefinity CMS, Sitefinity Digital Experience Cloud, Sitefinity Feather, Sitefinity Thunder, SmartBrowser, SmartComponent, SmartDataBrowser, SmartDataObjects, SmartDataView, SmartDialog, SmartFolder, SmartFrame, SmartObjects, SmartPanel, SmartQuery, SmartViewer, SmartWindow, Supermarket, SupportLink, Unite UX, and WebClient are trademarks or service marks of Progress Software Corporation and/or its subsidiaries or affiliates in the U.S. and other countries. Java is a registered trademark of Oracle and/or its affiliates. Any other marks contained herein may be trademarks of their respective owners.

Please refer to the NOTICE.txt or Release Notes – Third-Party Acknowledgements file applicable to a particular Progress product/hosted service offering release for any related required third-party acknowledgements.

Table of Contents

1 Introduction	5
1.1 Document Purpose	5
1.2 Intended Audience	5
2 Template	6
3 Architecture	7
4 Configure the LoadMaster	8
4.1 Enable Subnet Originating Requests Globally	8
4.2 Enable Check Persist Globally	9
4.3 Create the Domino Virtual Services	9
4.3.1 Create a Domino HTTP Virtual Service	9
4.3.2 Create a Domino HTTP LDAP Virtual Service	10
4.3.3 Create a Domino HTTPS Virtual Service	11
4.3.4 Create a Domino HTTPS LDAP Virtual Service	13
4.3.5 Create a Domino HTTPS Offloaded Virtual Service	14
4.3.6 Create a Domino HTTPS Offloaded LDAP Virtual Service	15
4.3.7 Create a Domino HTTPS Re-encrypt Virtual Service	17
4.3.8 Create a Domino HTTPS Re-encrypt LDAP Virtual Service	18
4.3.9 Create a Domino IMAP Virtual Service	20
4.3.10 Create a Domino POP Virtual Service	21
4.3.11 Create a Domino SMTP Virtual Service	22
References	24

Last Updated Date **25**

1 Introduction

IBM® Domino is an advanced platform for hosting social business applications. It delivers scalable, security rich applications at a low cost. This improves productivity and enhances decision making. Its main features include:

- Low ownership costs: By minimizing administration requirements through automation, staff can focus on higher value tasks
- Minimal infrastructure: By using less power for providing data storage, network band width and servers, you reduce costs
- Rich application environment: Supporting workflow-driven and people-oriented applications that help a wide variety of business operations deliver enhanced results
- High availability: Features advanced clustering, replication, server fault recovery and automated diagnostic tools

The Kemp LoadMaster is used to load balance the Domino workload. The LoadMaster offers advanced Layer 4 and Layer 7 server load balancing, SSL Acceleration and a multitude of other advanced Application Delivery Controller (ADC) features. The LoadMaster intelligently and efficiently distributes user traffic among the application servers so that users get the best experience possible.

1.1 Document Purpose

This document provides the recommended LoadMaster settings used when load balancing the Domino workload. The Kemp Support Team is available to provide solutions for scenarios not explicitly defined. The Kemp support site can be found at: <https://support.kemptechnologies.com>

1.2 Intended Audience

This document is intended to be read by anyone who is interested in configuring the LoadMaster to optimize Domino Application Server.

2 Template


Kemp has developed a template containing our recommended settings for this workload. You can install this template to help create Virtual Services (VSs) because it automatically populates the settings. You can use the template to easily create the required VSs with the recommended settings. For some workloads, additional manual steps may be required such as assigning a certificate or applying port following, these steps are covered in the document, if needed.

You can remove templates after use and this will not affect deployed services. If needed, you can make changes to any of the VS settings after using the template.

Download released templates from the following page: [LoadMaster Templates](#).

For more information and steps on how to import and use templates, refer to the [Virtual Services and Templates, Feature Description](#) on the Kemp Documentation page.

3 Architecture



4 Configure the LoadMaster


The deployed Domino environment determines which of the following setups is used.

4.1 Enable Subnet Originating Requests Globally

It is best practice to enable the **Subnet Originating Requests** option globally.

In a one-armed setup (where the Virtual Service and Real Servers are on the same network/subnet) **Subnet Originating Requests** is usually not needed. However, enabling **Subnet Originating Requests** should not affect the routing in a one-armed setup.

In a two-armed setup where the Virtual Service is on network/subnet A, for example, and the Real Servers are on network B, **Subnet Originating Requests** should be enabled on LoadMasters with firmware version 7.1-16 and above.



When **Subnet Originating Requests** is enabled, the Real Server sees traffic originating from 10.20.20.21 (LoadMaster eth1 address) and responds correctly in most scenarios.

With **Subnet Originating Requests** disabled, the Real Server sees traffic originating from 10.0.0.15 (LoadMaster Virtual Service address on **eth0**) and responds to **eth0** which could cause asymmetric routing.

When **Subnet Originating Requests** is enabled globally, it is automatically enabled on all Virtual Services. If the **Subnet Originating Requests** option is disabled globally, you can choose whether to enable **Subnet Originating Requests** on a per-Virtual Service basis.

To enable **Subnet Originating Requests** globally, follow the steps below:

1. In the main menu of the LoadMaster User Interface (UI), go to **System Configuration > Miscellaneous Options > Network Options**.
2. Select the **Subnet Originating Requests** check box.

4.2 Enable Check Persist Globally

It is recommended that you change the **Always Check Persist** option to **Yes – Accept Changes**. Use the following steps:

1. Go to **System Configuration > Miscellaneous Options > L7 Configuration**.
2. Click the **Always Check Persist** drop-down arrow and select **Yes – Accept Changes**.

4.3 Create the Domino Virtual Services

The following sections describe the recommended settings for the Domino Virtual Services.

4.3.1 Create a Domino HTTP Virtual Service

The following are the steps involved and the recommended settings to configure the Domino HTTP Virtual Service:

1. In the main menu of the LoadMaster Web User Interface (WUI), go to **Virtual Services > Add New**.

Please Specify the Parameters for the Virtual Service.

Virtual Address	<input type="text" value="10.154.11.146"/>
Port	<input type="text" value="80"/>
Service Name (Optional)	<input type="text" value="Domino HTTP"/>
Use Template	<input type="text" value="Select a Template"/>
Protocol	<input type="text" value="tcp"/>

2. Type a valid **Virtual Address**.
3. Type **80** as the **Port**.
4. Enter a recognizable **Service Name**, such as **Domino HTTP**.
5. Click **Add this Virtual Service**.
6. Configure the settings as recommended in the following table:

4 Configure the LoadMaster

Section	Option	Value	Comment
Standard Options	Persistence Mode	Source IP Address	
	Timeout	5 minutes	
	Scheduling Method	least connection	
Real Servers	URL	/	

7. Add the Real Servers:

- Expand the **Real Servers** section.
- Click **Add New**.
- Type the address of the relevant real server.
- Complete the other fields as required.
- Click **Add this Real Server** then click **OK** to the pop-up message.
- Repeat the steps above to add more Real Servers as needed, based on your environment.

4.3.2 Create a Domino HTTP LDAP Virtual Service

The following are the steps involved and the recommended settings to configure the Domino LDAP Virtual Service:

- In the main menu of the LoadMaster WUI, go to **Virtual Services > Add New**.

Please Specify the Parameters for the Virtual Service.

Virtual Address

Port

Service Name (Optional)

Use Template

Select a Template ▼

Protocol

tcp ▼

Cancel

Add this Virtual Service

- Type a valid **Virtual Address**.

- Type **389** as the **Port**.

4 Configure the LoadMaster

4. Type a recognizable **Service Name**, such as **Domino HTTP LDAP**.
5. Click **Add this Virtual Service**.
6. Configure the settings as recommended in the following table:

Section	Option	Value	Comment
Standard Options	Persistence Mode	Source IP Address	
	Timeout	5 minutes	
	Scheduling Method	least connection	
	Idle Connection Timeout	660 (seconds)	Click Set Idle Timeout.
Real Servers	Checked Port	389	

7. Add the Real Servers:
 - a) Expand the **Real Servers** section.
 - b) Click **Add New**.
 - c) Enter the address of the relevant Real Server.
 - d) Complete the other fields as required.
 - e) Click **Add this Real Server** then click **OK** to the pop-up message.
 - f) Repeat the steps above to add more Real Servers as needed, based on your environment.

4.3.3 Create a Domino HTTPS Virtual Service

The following are the steps involved and the recommended settings to configure the Domino HTTPS Virtual Service:

1. In the main menu of the LoadMaster WUI, go to **Virtual Services > Add New**.

4 Configure the LoadMaster

Please Specify the Parameters for the Virtual Service.

Virtual Address

Port

Service Name (Optional)

Use Template

Protocol

2. Type a valid **Virtual Address**.
3. Type **443** as the **Port**.
4. Enter a recognizable **Service Name**, such as **Domino HTTPS**.
5. Click **Add this Virtual Service**.
6. Configure the settings as recommended in the following table:

Section	Option	Value	Comment
Standard Options	Persistence Mode	Source IP Address	
	Timeout	1 Hour	
	Scheduling Method	least connection	
	Idle Connection Timeout	900 (seconds)	Click Set Idle Timeout.
Advanced Properties	Add a Port 80 Redirector VS		Click the Add HTTP Redirector button. This automatically creates a redirect on port 80.
Real Servers	URL	/	

7. Add the Real Servers:
 - a) Expand the **Real Servers** section.
 - b) Click **Add New**.

4 Configure the LoadMaster

- c) Enter the address of the relevant Real Server.
- d) Complete the other fields as required.
- e) Click **Add this Real Server** then click **OK** to the pop-up message.
- f) Repeat the steps above to add more Real Servers as needed, based on your environment.

Create a Domino HTTPS HTTP Redirect Virtual Service

Clicking the **Add HTTP Redirector** button automatically creates a port 80 redirect Virtual Service. This is optional, but the purpose of this Virtual Service is to redirect any clients who have connected using HTTP to the HTTPS Virtual Service. Kemp also recommends changing the **Persistence Mode** and **Real Server Check Method** to **None**.

4.3.4 Create a Domino HTTPS LDAP Virtual Service

The following are the steps involved and the recommended settings to configure the Domino HTTPS LDAP Virtual Service:

1. In the main menu of the LoadMaster WUI, go to **Virtual Services > Add New**.
2. Enter a valid **Virtual Address**.
3. Enter **389** as the **Port**.
4. Enter a recognizable **Service Name**, such as **Domino HTTPS LDAP**.
5. Click **Add this Virtual Service**.
6. Configure the settings as recommended in the following table:

Section	Option	Value
Standard Options	Persistence Mode	Source IP Address
	Timeout	5 minutes
	Scheduling Method	least connection
Real Servers	Check Method	TCP Connection Only
	Checked Port	389

7. Add the Real Servers:
 - a) Expand the **Real Servers** section.

4 Configure the LoadMaster

- b) Click **Add New**.
- c) Enter the address of the relevant Real Server.
- d) Complete the other fields as required.
- e) Click **Add this Real Server** then click **OK** to the pop-up message.
- f) Repeat the steps above to add more Real Servers as needed, based on your environment.

4.3.5 Create a Domino HTTPS Offloaded Virtual Service

The following are the steps involved and the recommended settings to configure the Domino HTTPS Offloaded Virtual Service:

1. In the main menu of the LoadMaster WUI, go to **Virtual Services > Add New**.

Please Specify the Parameters for the Virtual Service.

Virtual Address

Port

Service Name (Optional)

Use Template

Protocol

Cancel
Add this Virtual Service

2. Type a valid **Virtual Address**.
3. Type **443** as the **Port**.
4. Type a recognizable Service Name, such as **Domino HTTPS Offloaded**.
5. Click **Add this Virtual Service**.
6. Configure the settings as recommended in the following table:

Section	Option	Value	Comment
Standard Options	Persistence Mode	Source IP Address	

4 Configure the LoadMaster

Section	Option	Value	Comment
	Timeout	1 Hour	
	Scheduling Method	least connection	
	Idle Connection Timeout	900 seconds	
SSL Properties	Enabled	Selected	
	Cipher Set	BestPractices	
Advanced Properties	Add a Port 80 Redirector VS		Click the Add HTTP Redirector button. This automatically creates a redirect on port 80.
Real Servers	URL	/	

7. Add the Real Servers:

- a) Expand the **Real Servers** section.
- b) Click **Add New**.
- c) Type the address of the relevant Real Server.
- d) Complete the other fields as required.
- e) Click **Add this Real Server** then click **OK** to the pop-up message.
- f) Repeat the steps above to add more Real Servers as needed, based on your environment.

Create a Domino HTTPS HTTP Redirect Virtual Service

Clicking the **Add HTTP Redirector** button automatically creates a port 80 redirect Virtual Service. This is optional, but the purpose of this Virtual Service is to redirect any clients who have connected using HTTP to the HTTPS Virtual Service. Kemp also recommends changing the **Persistence Mode** and **Real Server Check Method** to **None**.

4.3.6 Create a Domino HTTPS Offloaded LDAP Virtual Service

The following are the steps involved and the recommended settings to configure the Domino HTTPS Offloaded LDAP Virtual Service:

1. In the main menu of the LoadMaster WUI, go to **Virtual Services > Add New**.

4 Configure the LoadMaster

Please Specify the Parameters for the Virtual Service.

Virtual Address

10.154.11.143

Port

389

Service Name (Optional)

Domino HTTPS Offlo

Use Template

Select a Template

Protocol

tcp

Cancel

Add this Virtual Service

2. Type a valid **Virtual Address**.
3. Type **389** as the **Port**.
4. Type a recognizable Service Name, such as **Domino HTTPS Offloaded LDAP**.
5. Click **Add this Virtual Service**.
6. Configure the settings as recommended in the following table:

Section	Option	Value
Standard Options	Persistence Mode	Source IP Address
	Timeout	5 Minutes
	Scheduling Method	least connection
Real Servers	Checked Port	389

7. Add the Real Servers:
 - a) Expand the **Real Servers** section.
 - b) Click **Add New**.
 - c) Type the address of the relevant Real Server.
 - d) Complete the other fields as required.
 - e) Click **Add this Real Server** then click **OK** to the pop-up message.
 - f) Repeat the steps above to add more Real Servers as needed, based on your environment.

4 Configure the LoadMaster

4.3.7 Create a Domino HTTPS Re-encrypt Virtual Service

The following are the steps involved and the recommended settings to configure the Domino HTTPS Re-encrypt Virtual Service:

1. In the main menu of the LoadMaster WUI, go to **Virtual Services > Add New**.

Please Specify the Parameters for the Virtual Service.

Virtual Address

Port

Service Name (Optional)

Use Template

Protocol

Cancel

Add this Virtual Service

2. Type a valid **Virtual Address**.
3. Type **443** as the **Port**.
4. Type a recognizable **Service Name**, such as **Domino HTTPS Re-encrypt**.
5. Click **Add this Virtual Service**.
6. Configure the settings as recommended in the following table:

Section	Option	Value	Comment
Standard Options	Persistence Mode	Source IP Address	
	Timeout	1 hour	
	Scheduling Method	least connection	
	Idle Connection Timeout	900 seconds	Click Set Idle Timeout.
SSL Properties	Enabled	Selected	

4 Configure the LoadMaster

Section	Option	Value	Comment
	Reencrypt	Selected	
	Cipher Set	BestPractices	
Advanced Properties	Add a Port 80 Redirector VS		Click the Add HTTP Redirector button. This automatically creates a redirect on port 80.
Real Servers	Check Method	HTTPS Protocol	
	URL	/	

7. Add the Real Servers:

- a) Expand the **Real Servers** section.
- b) Click **Add New**.
- c) Type the address of the relevant Real Server.
- d) Complete the other fields as required.
- e) Click **Add this Real Server** then click **OK** to the pop-up message.
- f) Repeat the steps above to add more Real Servers as needed, based on your environment.

Create a Domino HTTPS HTTP Redirect Virtual Service

Clicking the **Add HTTP Redirector** button automatically creates a port 80 redirect Virtual Service. This is optional, but the purpose of this Virtual Service is to redirect any clients who have connected using HTTP to the HTTPS Virtual Service. Kemp also recommends changing the **Persistence Mode** and **Real Server Check Method** to **None**.

4.3.8 Create a Domino HTTPS Re-encrypt LDAP Virtual Service

The following are the steps involved and the recommended settings to configure the Domino HTTPS Re-encrypt LDAP Virtual Service:

1. In the main menu of the LoadMaster WUI, go to **Virtual Services > Add New**.

4 Configure the LoadMaster

Please Specify the Parameters for the Virtual Service.

Virtual Address

Port

Service Name (Optional)

Use Template ▼

Protocol ▼

2. Type a valid **Virtual Address**.
3. Type **389** as the **Port**.
4. Type a recognizable **Service Name**, such as **Domino HTTPS Re-encrypt LDAP**.
5. Click **Add this Virtual Service**.
6. Configure the settings as recommended in the following table:

Section	Option	Value	Comment
Standard Options	Persistence Mode	Source IP Address	
	Timeout	5 Minutes	
	Scheduling Method	least connection	
	Idle Connection Timeout	660 seconds	Click Set Idle Timeout.
Real Servers	Checked Port	389	

7. Add the Real Servers:
 - a) Expand the **Real Servers** section.
 - b) Click **Add New**.
 - c) Type the address of the relevant Real Server.
 - d) Complete the other fields as required.
 - e) Click **Add this Real Server** then click **OK** to the pop-up message.

f) Repeat the steps above to add more Real Servers as needed, based on your environment.

4.3.9 Create a Domino IMAP Virtual Service

The following are the steps involved and the recommended settings to configure the Domino IMAP Virtual Service:

1. In the main menu of the LoadMaster WUI, go to **Virtual Services > Add New**.

Please Specify the Parameters for the Virtual Service.

Virtual Address

Port

Service Name (Optional)

Use Template

Protocol

Cancel

Add this Virtual Service

2. Type a valid **Virtual Address**.
3. Type **143** as the **Port**.
4. Type a recognizable **Service Name**, such as **Domino IMAP**.
5. Click **Add this Virtual Service**.
6. Configure the settings as recommended in the following table:

Section	Option	Value
Standard Options	Scheduling Method	least connection
	Idle Connection Timeout	3600 seconds
Real Servers	Checked Port	143

7. Add the Real Servers:
 - a) Expand the **Real Servers** section.
 - b) Click **Add New**.
 - c) Type the address of the relevant Real Server.

4 Configure the LoadMaster

- d) Complete the other fields as required.
- e) Click **Add this Real Server** then click **OK** to the pop-up message.
- f) Repeat the steps above to add more Real Servers as needed, based on your environment.

4.3.10 Create a Domino POP Virtual Service

The following are the steps involved and the recommended settings to configure the Domino POP Virtual Service:

1. In the main menu of the LoadMaster WUI, go to **Virtual Services > Add New**.

Please Specify the Parameters for the Virtual Service.

Virtual Address

10.154.11.145

Port

110

Service Name (Optional)

Domino POP

Use Template

Select a Template ▼

Protocol

tcp ▼

Cancel
Add this Virtual Service

2. Type a valid **Virtual Address**.
3. Type **110** as the **Port**.
4. Type a recognizable **Service Name**, such as **Domino POP**.
5. Click **Add this Virtual Service**.
6. Configure the settings as recommended in the following table:

Section	Option	Value
Standard Options	Scheduling Method	Least connection
	Persistence Options	Source IP Address
	Timeout	1 Minute
	Idle Connection Timeout	3600 seconds

4 Configure the LoadMaster

Section	Option	Value
Real Servers	Checked Port	110

7. Add the Real Servers:

- Expand the **Real Servers** section.
- Click **Add New**.
- Type the address of the relevant Real Server.
- Complete the other fields as required.
- Click **Add this Real Server** then click **OK** to the pop-up message.
- Repeat the steps above to add more Real Servers as needed, based on your environment.

4.3.11 Create a Domino SMTP Virtual Service

The following are the steps involved and the recommended settings to configure the Domino SMTP Virtual Service:

- In the main menu of the LoadMaster WUI, go to **Virtual Services > Add New**.

Please Specify the Parameters for the Virtual Service.

Virtual Address

Port

Service Name (Optional)

Use Template

Select a Template ▾

Protocol

tcp ▾

Cancel

Add this Virtual Service

- Type a valid **Virtual Address**.
- Type **25** as the **Port**.
- Type a recognizable **Service Name**, such as **Domino SMTP**.
- Click Add this Virtual Service.

4 Configure the LoadMaster

6. Configure the settings as recommended in the following table:

Section	Option	Value
Standard Options	Persistence Options	Source IP Address
	Timeout	1 Hour
	Scheduling Method	least connection
	Idle Connection Timeout	120 seconds
Real Servers	Checked Port	25

7. Add the Real Servers:

- Expand the **Real Servers** section.
- Click **Add New**.
- Type the address of the relevant Real Server.
- Complete the other fields as required.
- Click **Add this Real Server** then click **OK** to the pop-up message.
- Repeat the steps above to add more Real Servers as needed, based on your environment.

References

Unless otherwise specified, the following documents can be found at _
<http://kemptechnologies.com/documentation>.

Virtual Services and Templates, Feature Description

Last Updated Date

This document was last updated on 29 July 2023.