

Common Event Format (CEF) Logs

Technical Note

UPDATED: 28 July 2023

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

These materials and all Progress® software products are copyrighted and all rights are reserved by Progress Software Corporation. The information in these materials is subject to change without notice, and Progress Software Corporation assumes no responsibility for any errors that may appear therein. The references in these materials to specific platforms supported are subject to change.

#1 Load Balancer in Price/Performance, 360 Central, 360 Vision, Chef, Chef (and design), Chef Habitat, Chef Infra, Code Can (and design), Compliance at Velocity, Corticon, Corticon.js, DataDirect (and design), DataDirect Cloud, DataDirect Connect, DataDirect Connect64, DataDirect XML Converters, DataDirect XQuery, DataRPM, Defrag This, Deliver More Than Expected, DevReach (and design), Driving Network Visibility, Flowmon, Inspec, Ipswitch, iMacros, K (stylized), Kemp, Kemp (and design), Kendo UI, Kinvey, LoadMaster, MessageWay, MOVEit, NativeChat, OpenEdge, Powered by Chef, Powered by Progress, Progress, Progress Software Developers Network, SequeLink, Sitefinity (and Design), Sitefinity, Sitefinity (and design), Sitefinity Insight, SpeedScript, Stylized Design (Arrow/3D Box logo), Stylized Design (C Chef logo), Stylized Design of Samurai, TeamPulse, Telerik, Telerik (and design), Test Studio, WebSpeed, WhatsConfigured, WhatsConnected, WhatsUp, and WS_FTP are registered trademarks of Progress Software Corporation or one of its affiliates or subsidiaries in the U.S. and/or other countries.

Analytics360, AppServer, BusinessEdge, Chef Automate, Chef Compliance, Chef Desktop, Chef Workstation, Corticon Rules, Data Access, DataDirect Autonomous REST Connector, DataDirect Spy, DevCraft, Fiddler, Fiddler Classic, Fiddler Everywhere, Fiddler Jam, FiddlerCap, FiddlerCore, FiddlerScript, Hybrid Data Pipeline, iMail, InstaRelinker, JustAssembly, JustDecompile, JustMock, KendoReact, OpenAccess, PASOE, Pro2, ProDataSet, Progress Results, Progress Software, ProVision, PSE Pro, Push Jobs, SafeSpaceVR, Sitefinity Cloud, Sitefinity CMS, Sitefinity Digital Experience Cloud, Sitefinity Feather, Sitefinity Thunder, SmartBrowser, SmartComponent, SmartDataBrowser, SmartDataObjects, SmartDataView, SmartDialog, SmartFolder, SmartFrame, SmartObjects, SmartPanel, SmartQuery, SmartViewer, SmartWindow, Supermarket, SupportLink, Unite UX, and WebClient are trademarks or service marks of Progress Software Corporation and/or its subsidiaries or affiliates in the U.S. and other countries. Java is a registered trademark of Oracle and/or its affiliates. Any other marks contained herein may be trademarks of their respective owners.

Please refer to the NOTICE.txt or Release Notes – Third-Party Acknowledgements file applicable to a particular Progress product/hosted service offering release for any related required third-party acknowledgements.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

Table of Contents

1 Common Event Format (CEF) Logs 4

2 CEF Header 6

3 CEF Extension 9

References 20

Last Updated Date 21

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

1 Common Event Format (CEF) Logs

This document outlines the details of the Kemp Common Event Format (CEF) logs for the Edge Security Pack (ESP) feature. CEF logs were introduced in LoadMaster firmware version 7.2.50.



To enable the CEF log format, go to **System Configuration > Miscellaneous Options > L7 Configuration** and select the **Use CEF Log Format** check box.

CEF is an open log management standard that improves the interoperability of security-related information from different security and network devices and applications. CEF was developed by ArcSight and uses UTF-8 Unicode.

The CEF logs are composed of a header and an extension. The header is well-defined within the specification and the extension is a key-value pair vendor-specific segment. The format of the logs is as follows:

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

```
CEF:Version|Device Vendor|Device Product|Device Version|Device Event Class
ID|Name|Severity|[Extension]
```


© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

2 CEF Header

The CEF header comprises of everything bar the [Extension]. ArcSight describes the CEF Header as follows:

Version

This is an integer and identifies the version of the CEF format. Event consumers use this information to determine what the following fields represent. The current CEF version is 0 (CEF:0).

The Kemp Version is '0'.

Device Vendor, Device Product, and Device Version

These are strings that uniquely identify the type of sending device. No two products may use the same device-vendor and device-product pair. There is no central authority managing these pairs. Event producers must ensure that they assign unique name pairs.

The Kemp Device Vendor is 'Kemp', the Device Product is 'LM' and the Device Version is '0'.

> LM is an abbreviation for LoadMaster.

Device Event Class ID

This is a unique identifier per event-type. This can be a string or an integer. The Device Event Class ID identifies the type of event reported. In the Intrusion Detection System (IDS) world, each signature or rule that detects certain activity has a unique Device Event Class ID assigned. This is a requirement for other types of devices too, and helps correlation engines to process the events. This is also known as the Signature ID.

Name

This is a string representing a human-readable and understandable description of the event. The event name should not contain information that is specifically mentioned in other fields.

Severity

This is a string or integer and reflects the importance of the event.

The valid string values are Unknown, Low, Medium, High, and Very-High.

The valid integer values are 0-3=Low, 4-6=Medium, 7-8=High, and 9-10=Very-High.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

The Kemp Device Event Class ID, Name, and Severity are outlined in the table below. These all correlate together to provide a full understanding of the type and severity of the CEF log.

L7 ESP CEF Logs

Device Event Class ID	Name	Severity
0	Accept	0 (Low)
1	Slave accept	0 (Low)
2	SSL accept	0 (Low)
3	Connection timed out	1 (Low)
4	Connected	1 (Low)
5	Connection failed	3 (Low)
6	Logged off	1 (Low)
7	User interaction	2 (Low)
8	Logged on	1 (Low)
9	Access Denied	6 (Medium)
10	Access Blocked	6 (Medium)
11	Access Locked	
12	Access Disabled	6 (Medium)
13	Password Expired	6 (Medium)
14	Request	1 (Low)
15	Attempt	2 (Low)
16	Attempted XSS attack	9 (Very High)
17	SMTP parse failure	7 (High)

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

Device Event Class ID	Name	Severity
18	SMTP Blocked	6 (Medium)
19	Blocked access to directory	6 (Medium)
20	Blocked access to host	6 (Medium)

SSOMGR CEF Logs

Device Event Class ID	Name	Severity
100	User AAA	0 (Low)
101	User session timeout	0 (Low)
102	User session kill	0 (Low)
103	Kill all sessions	0 (Low)
104	Flush SSO cache	1 (Low)

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

3 CEF Extension

The Kemp Technologies CEF Extension is a key-value pairing of information providing extra details based on the 'Device Event Class ID'. This is clarified through the use of examples below.

L7 ESP CEF Logs

The following example shows an 'Accept' message with 'Device Event Class ID' of '0'.

```
CEF:0|Kemp|LM|1.0|0|Accept|0|vs=10.35.46.238:80 event=Accept srcip=10.35.2.98
srcport=61518 msg=Accept
```

The CEF Extension comprises of:

Extension key-value pair	Description
vs	This is the Virtual Service IP address
event	This is a string describing the event type; typically, the same as the 'Name' field in the CEF header
srcip	This is the source IP address that originated the request
srcport	This is the source port that originated the request
msg	This is a free-form string providing extra details

The following example shows a 'Slave Accept' message with 'Device Event Class ID' of '1':

```
CEF:0|Kemp|LM|1.0|1|Slave accept|0|vs=10.35.46.238:80 event=Slave accept
srcip=10.35.2.98 srcport=57432 msg=Slave accept
```

The CEF Extension comprises of:

Extension key-value pair	Description
vs	This is the Virtual Service IP address: Port combination
event	This is a string describing the event type; typically, the same as the 'Name' field in the CEF header
srcip	This is the source IP address that originated the request
srcport	This is the source port that originated the request
msg	This is a free-form string providing extra details

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

The following example shows an 'SSL Accept' message with 'Device Event Class ID' of '2':

```
CEF:0|Kemp|LM|1.0|2|SSL accept|0|vs=10.35.46.238:443 event=SSL accept
srcip=10.35.2.98 srcport=51639 msg=SSL accept
```

The CEF Extension comprises of:

Extension key-value pair	Description
vs	This is the Virtual Service IP address: Port combination
event	This is a string describing the event type; typically, the same as the 'Name' field in the CEF header
srcip	This is the source IP address that originated the request
srcport	This is the source port that originated the request

The following example shows a 'Connection Timed Out' message with 'Device Event Class ID' of '3':

```
CEF:0|Kemp|LM|1.0|3|Connection timed out|1|vs=10.35.46.235:443
event=Connection timed out srcip=10.35.2.98 srcport=51723 msg=waiting for
initial client request await_remaddr=0
```

The CEF Extension comprises of:

Extension key-value pair	Description
vs	This is the Virtual Service IP address: Port combination
event	This is a string describing the event type; typically, the same as the 'Name' field in the CEF header
srcip	This is the source IP address that originated the request
srcport	This is the source port that originated the request
msg	This is a free-form string providing extra details
await_remaddr	Internal flag - likely to be zero

The following example shows an 'Connected' message with 'Device Event Class ID' of '4':

```
CEF:0|Kemp|LM|1.0|4|Connected|1|vs=10.35.46.235:443 event=Connected
srcip=10.35.2.98 srcport=51675 dstip=172.20.0.129 dstport=80
```

The CEF Extension comprises of:

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

Extension key-value pair	Description
vs	This is the Virtual Service IP address: Port combination
event	This is a string describing the event type; typically, the same as the 'Name' field in the CEF header
srcip	This is the source IP address that originated the request
srcport	This is the source port that originated the request
dstip	This is the destination IP address for this connection
dstport	This is the destination port for this connection

The following example shows a 'Connection Failed' message with 'Device Event Class ID' of '5':

```
CEF:0|Kemp|LM|1.0|5|Connection failed|3|vs=10.35.46.238:80 event=Connection failed srcip=10.35.2.98 srcport=57378 dstip=172.20.0.129 dstport=82
```

The CEF Extension comprises of:

Extension key-value pair	Description
vs	This is the Virtual Service IP address: Port combination
event	This is a string describing the event type; typically, the same as the 'Name' field in the CEF header
srcip	This is the source IP address that originated the request
srcport	This is the source port that originated the request
dstip	This is the destination IP address for this connection
dstport	This is the destination port for this connection

The following example shows a 'Logged off' message with 'Device Event Class ID' of '6':

```
CEF:0|Kemp|LM|1.0|6|Logged off|1|vs=10.35.46.238:443 event=Logged off user=mohit@kpauto.net srcip=10.35.2.98
```

The CEF Extension comprises of:

Extension key-value pair	Description
vs	This is the Virtual Service IP address: Port combination
event	This is a string describing the event type; typically, the same as

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

Extension key-value pair	Description
	the 'Name' field in the CEF header
user	The user that was entered in the ESP form and logged on
srcip	This is the source IP address that originated the request

The following example shows an 'User Interaction' message with 'Device Event Class ID' of '7':

```
CEF:0|Kemp|LM|1.0|7|User interaction|2|vs=10.35.46.238:443 event=User
interaction srcip=10.35.2.98 user=mohit@kpauto.net msg=requires password reset
```

Extension key-value pair	Description
vs	This is the Virtual Service IP address: Port combination
event	This is a string describing the event type; typically, the same as the 'Name' field in the CEF header
srcip	This is the source IP address that originated the request
srcport	This is the source port that originated the request
msg	This is a free form string providing extra details

The following example shows a 'Logged On' message with 'Device Event Class ID' of '8':

```
CEF:0|Kemp|LM|1.0|8|Logged on|1|vs=10.35.46.157:443 event=Logged on
srcip=10.35.2.45 user=mgupta@kempqaesp.net msg=logged on
```

The CEF Extension comprises of:

Extension key-value pair	Description
vs	This is the Virtual Service IP address
event	This is a string describing the event type; typically, the same as the 'Name' field in the CEF header
srcip	This is the source IP address that originated the request
user	The username of the user who attempted to log on
msg	This is a free-form string providing extra details

The following example shows an 'Access Denied' message with 'Device Event Class ID' of '9':

```
CEF:0|Kemp|LM|1.0|9|Access Denied|6|vs=10.35.46.252:443 event=Access Denied
srcip=10.35.8.8 user=mohit@kempqaesp.net msg=denied access
```


© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

The CEF Extension comprises of:

Extension key-value pair	Description
vs	This is the Virtual Service IP address: Port combination
event	This is a string describing the event type; typically, the same as the 'Name' field in the CEF header
srcip	This is the source IP address that originated the request
user	The username of the user who attempted to log on
msg	This is a free-form string providing extra details

The following example shows an 'Access Blocked' message with 'Device Event Class ID' of '10':

```
CEF:0|Kemp|LM|1.0|10|Access Blocked|6|vs=10.35.46.242:443 event=Access Blocked
srcip=10.35.2.98 user=mohit msg=blocked access
```

The CEF Extension comprises of:

Extension key-value pair	Description
vs	This is the Virtual Service IP address: Port combination
event	This is a string describing the event type; typically, the same as the 'Name' field in the CEF header
srcip	This is the source IP address that originated the request
user	The user that was entered into the ESP form and logged on
msg	This is a free-form string providing extra details

The following example shows an 'Access Locked' message with 'Device Event Class ID' of '11':

TBD

The following example shows an 'Access Disabled' message with 'Device Event Class ID' of '12':

```
CEF:0|Kemp|LM|1.0|12|Access Disabled|6|vs=10.35.46.252:443 event=Access
Disabled srcip=10.35.2.45 user=mohit@kempqaesp.net msg=account disabled
```

The CEF Extension comprises of:

Extension key-value pair	Description
vs	This is the Virtual Service IP address: Port combination

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

Extension key-value pair	Description
event	This is a string describing the event type; typically, the same as the 'Name' field in the CEF header
srcip	This is the source IP address that originated the request
user	The user that was entered into the ESP form and logged on
msg	This is a free-form string providing extra details

The following example shows an 'Password Expired' message with 'Device Event Class ID' of '13':

```
CEF:0|Kemp|LM|1.0|13|Password Expired|6|vs=10.35.46.252:443 event=Password
Expired srcip=10.35.8.8 user=mohit@kempqaesp.net msg=password expired
```

The CEF Extension comprises of:

Extension key-value pair	Description
vs	This is the Virtual Service IP address: Port combination
event	This is a string describing the event type; typically, the same as the 'Name' field in the CEF header
srcip	This is the source IP address that originated the request
user	The user that was entered into the ESP form and logged on
msg	This is a free-form string providing extra details

The following example shows a 'Request' message with 'Device Event Class ID' of '14':

```
CEF:0|Kemp|LM|1.0|14|Request|1|vs=10.35.46.157:443 event=Request
srcip=10.35.2.45 srcport=54548 method=GET url=https://10.35.46.157/
user=mgupta@kempqaesp.net useragent=Mozilla/5.0
```

The CEF Extension comprises of:

Extension key-value pair	Description
vs	This is the Virtual Service IP address: Port combination
event	This is a string describing the event type; typically, the same as the 'Name' field in the CEF header
srcip	This is the source IP address that originated the request

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

Extension key-value pair	Description
srcport	This is the source port that originated the request
method	The HTML method, for example GET or POST.
URL	The URL that the user is trying to access.
user	The user making the request.
useragent	The user agent that process the user request

The following example shows an 'Attempt' message with 'Device Event Class ID' of '15':

```
CEF:0|Kemp|LM|1.0|15|Attempt|2|vs=10.35.46.252:443 event=Attempt
srcip=10.35.2.98 srcport=56593 method=GET url=https://10.35.46.252/owa/
useragent=Mozilla/5.0 (Macintosh; Intel Mac OS X 10.15; rv:91.0)
Gecko/20100101 Firefox/91.0
```

The CEF Extension comprises of:

Extension key-value pair	Description
vs	This is the Virtual Service IP address: Port combination
event	This is a string describing the event type; typically, the same as the 'Name' field in the CEF header
srcip	This is the source IP address that originated the request
srcport	This is the source port that originated the request
method	The HTML method, for example GET or POST.
URL	The URL that the user is trying to access.
useragent	The user agent that process the user request.

The following example shows an 'Attempted XSS attack' message with 'Device Event Class ID' of '16':

```
CEF:0|Kemp|LM|1.0|16|Attempted XSS attack|9|vs=10.35.46.238:443
event=Attempted XSS attack srcip=10.35.2.98 srcport=61038 dtcode=6
```

The CEF Extension comprises of:

Extension key-value pair	Description
vs	This is the Virtual Service IP address: Port combination

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

Extension key-value pair	Description
event	This is a string describing the event type; typically, the same as the 'Name' field in the CEF header
srcip	This is the source IP address that originated the request
srcport	This is the source port that originated the request
dtcode	This only appears if someone is trying to access an ESP Virtual Service in a way that suggests they are trying to hack the system (for example, there are missing fields or bad characters in the request)

The following example shows an 'SMTP Parse Failure' message with 'Device Event Class ID' of '17':

```
CEF:0|Kemp|LM|1.0|17|SMTP parse failure|7|vs=10.1.133.11:25 event=SMTP parse failure src=10.0.71.175:61401
```

The CEF Extension comprises of:

Extension key-value pair	Description
vs	This is the Virtual Service IP address: Port combination
event	This is a string describing the event type; typically, the same as the 'Name' field in the CEF header
src	This is the Source IP address: Port that originated the request

The following example shows an 'SMTP Blocked' message with 'Device Event Class ID' of '18':

```
CEF:0|Kemp|LM|1.0|18|SMTP Blocked|6|vs=10.1.133.11:25 event=SMTP Blocked src=10.0.71.175:61401 resource=ktest.com
```

The CEF Extension comprises of:

Extension key-value pair	Description
vs	This is the Virtual Service IP address: Port combination
event	This is a string describing the event type; typically, the same as the 'Name' field in the CEF header
src	This is the Source IP address: Port that originated the request
resource	The URL that someone is trying to access.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

The following example shows a 'Blocked access to directory' message with 'Device Event Class ID' of '19':

```
CEF:0|Kemp|LM|1.0|19|Blocked access to directory|6|vs=10.35.46.238:443
event=Blocked access to directory srcip=10.35.2.98 srcport=61108 resource=/
```

The CEF Extension comprises of:

Extension key-value pair	Description
vs	This is the Virtual Service IP address: Port combination
event	This is a string describing the event type; typically, the same as the 'Name' field in the CEF header
srcip	This is the source IP address that originated the request
srcport	This is the source port that originated the request
resource	The URL or IP that someone is trying to access.

The following example shows a 'Blocked access to host' message with 'Device Event Class ID' of '20':

```
CEF:0|Kemp|LM|1.0|20|Blocked access to host|6|vs=10.35.46.238:443
event=Blocked access to host srcip=10.35.2.98 srcport=61096
resource=10.35.46.238
```

The CEF Extension comprises of:

Extension key-value pair	Description
vs	This is the Virtual Service IP address: Port combination
event	This is a string describing the event type; typically, the same as the 'Name' field in the CEF header
srcip	This is the source IP address that originated the request
srcport	This is the source port that originated the request
resource	The URL or IP address that someone is trying to access.

SSOMGR CEF Logs

The following example shows a 'User AAA' message with 'Device Event Class ID' of '100':

```
CEF:0|Kemp|LM|1.0|100|User AAA|0|vs=10.35.46.235:443 event=User AAA
user=mohit@parent.net domain=parent.net server=172.21.135.103 protocol=LDAP
Unencrypted result=0:Success
```


© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

The CEF Extension comprises of:

Extension key-value pair	Description
vs	This is the Virtual Service IP address: Port combination
event	This is a string describing the event type; typically, the same as the 'Name' field in the CEF header
user	The username of the user who attempted to log on
domain	The name of the domain to be used
server	This is the address of the server
protocol	This is the type of selected protocol
result	This is the result for this connection

The following example shows a 'User session timeout' message with 'Device Event Class ID' of '101':

```
CEF:0|Kemp|LM|1.0|101|User session timeout|0|vs=10.35.46.242:443 event=User session timeout user=mohit@parent.net domain=MULLTIDOMAIN msg=Deleted expired user session, start time:1629182393 duration:69 seconds
```

The CEF Extension comprises of:

Extension key-value pair	Description
vs	This is the Virtual Service IP address: Port combination
event	This is a string describing the event type; typically, the same as the 'Name' field in the CEF header
user	The username of the user who attempted to log on
domain	The name of the domain to be used
msg	This is a free-form string providing extra details

The following example shows a 'User session kill' message with 'Device Event Class ID' of '102':

```
CEF:0|Kemp|LM|1.0|102|User session kill|0|vs=10.35.46.235:443 event=User session kill user=mohit@parent.net domain=MULLTIDOMAIN msg=Deleted user session, start time:1629378587 duration:8 seconds
```

The CEF Extension comprises of:

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

Extension key-value pair	Description
vs	This is the Virtual Service IP address: Port combination
event	This is a string describing the event type; typically, the same as the 'Name' field in the CEF header
user	The username of the user who attempted to log on
domain	The name of the domain to be used
msg	This is a free-form string providing extra details

The following example shows a 'Kill all sessions' message with 'Device Event Class ID' of '103':

CEF:0|Kemp|LM|1.0|103|Kill all sessions|0|event=Kill all sessions domain=MULLTIDOMAIN msg=Deleted 1 user session(s) associated with domain

The CEF Extension comprises of:

Extension key-value pair	Description
event	This is a string describing the event type; typically, the same as the 'Name' field in the CEF header
domain	The name of the domain to be used
msg	This is a free-form string providing extra details

The following example shows a 'Flush SSO cache' message with 'Device Event Class ID' of '104':

CEF:0|Kemp|LM|1.0|104|Flush SSO cache|1|event=Flush SSO cache msg=SSO cache being flushed user sessions:1 cookie sessions:1

The CEF Extension comprises of:

Extension key-value pair	Description
event	This is a string describing the event type; typically, the same as the 'Name' field in the CEF header
msg	This is a free-form string providing extra details

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

References

The following document provides further details about CEF logs:

https://community.microfocus.com/t5/ArcSight-Connectors/ArcSight-Common-Event-Format-CEF-Implementation-Standard/ta-p/1645557?attachment-id=68077

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

Last Updated Date

This document was last updated on 28 July 2023.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.