

# Apache HTTP

## Deployment Guide

UPDATED: 27 July 2023

**© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.**

These materials and all Progress® software products are copyrighted and all rights are reserved by Progress Software Corporation. The information in these materials is subject to change without notice, and Progress Software Corporation assumes no responsibility for any errors that may appear therein. The references in these materials to specific platforms supported are subject to change.

#1 Load Balancer in Price/Performance, 360 Central, 360 Vision, Chef, Chef (and design), Chef Habitat, Chef Infra, Code Can (and design), Compliance at Velocity, Corticon, Corticon.js, DataDirect (and design), DataDirect Cloud, DataDirect Connect, DataDirect Connect64, DataDirect XML Converters, DataDirect XQuery, DataRPM, Defrag This, Deliver More Than Expected, DevReach (and design), Driving Network Visibility, Flowmon, Inspec, Ipswitch, iMacros, K (stylized), Kemp, Kemp (and design), Kendo UI, Kinvey, LoadMaster, MessageWay, MOVEit, NativeChat, OpenEdge, Powered by Chef, Powered by Progress, Progress, Progress Software Developers Network, SequeLink, Sitefinity (and Design), Sitefinity, Sitefinity (and design), Sitefinity Insight, SpeedScript, Stylized Design (Arrow/3D Box logo), Stylized Design (C Chef logo), Stylized Design of Samurai, TeamPulse, Telerik, Telerik (and design), Test Studio, WebSpeed, WhatsConfigured, WhatsConnected, WhatsUp, and WS_FTP are registered trademarks of Progress Software Corporation or one of its affiliates or subsidiaries in the U.S. and/or other countries.

Analytics360, AppServer, BusinessEdge, Chef Automate, Chef Compliance, Chef Desktop, Chef Workstation, Corticon Rules, Data Access, DataDirect Autonomous REST Connector, DataDirect Spy, DevCraft, Fiddler, Fiddler Classic, Fiddler Everywhere, Fiddler Jam, FiddlerCap, FiddlerCore, FiddlerScript, Hybrid Data Pipeline, iMail, InstaRelinker, JustAssembly, JustDecompile, JustMock, KendoReact, OpenAccess, PASOE, Pro2, ProDataSet, Progress Results, Progress Software, ProVision, PSE Pro, Push Jobs, SafeSpaceVR, Sitefinity Cloud, Sitefinity CMS, Sitefinity Digital Experience Cloud, Sitefinity Feather, Sitefinity Thunder, SmartBrowser, SmartComponent, SmartDataBrowser, SmartDataObjects, SmartDataView, SmartDialog, SmartFolder, SmartFrame, SmartObjects, SmartPanel, SmartQuery, SmartViewer, SmartWindow, Supermarket, SupportLink, Unite UX, and WebClient are trademarks or service marks of Progress Software Corporation and/or its subsidiaries or affiliates in the U.S. and other countries. Java is a registered trademark of Oracle and/or its affiliates. Any other marks contained herein may be trademarks of their respective owners.

Please refer to the NOTICE.txt or Release Notes – Third-Party Acknowledgements file applicable to a particular Progress product/hosted service offering release for any related required third-party acknowledgements.


© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

# Table of Contents

**1 Introduction** ..... **4**

1.1 Document Purpose ..... 4

1.2 Intended Audience ..... 4

**2 Apache HTTP Template** ..... **5**

**3 Architecture** ..... **6**

**4 Configure the LoadMaster** ..... **7**

4.1 Enable Subnet Originating Requests Globally ..... 7

4.2 Enable Check Persist Globally ..... 8

4.3 Create the Apache HTTP Virtual Services ..... 8

4.3.1 Create an Apache HTTP Virtual Service ..... 8

4.3.2 Create an Apache HTTPS Virtual Service ..... 9

4.3.3 Create an Apache HTTPS Offloaded Virtual Service ..... 11

4.3.4 Create an Apache HTTPS Re-encrypt Virtual Service ..... 12

**References** ..... **15**

**Last Updated Date** ..... **16**



© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

# 1 Introduction

The Apache HTTP Server is the world's most used web server software. Apache development began in 1995 and played a key role in the initial growth of the World Wide Web and quickly became the dominant HTTP server. It has remained most popular since 1996 and in 2009 it became the first web server software to serve more than 100 million websites.

The Kemp LoadMaster is used to load balance the Apache HTTP workload. The LoadMaster offers advanced Layer 4 and Layer 7 server load balancing, SSL Acceleration and a multitude of other advanced Application Delivery Controller (ADC) features. The LoadMaster intelligently and efficiently distributes user traffic among the application servers so that users get the best experience possible.

## 1.1 Document Purpose

This document provides the recommended LoadMaster settings used when load balancing the Apache HTTP workload. The Kemp Support Team is available to provide solutions for scenarios not explicitly defined. The Kemp support site can be found at: https://support.kemptechnologies.com

## 1.2 Intended Audience

This document is intended to be read by anyone who is interested in configuring the LoadMaster to optimize the Apache HTTP server.


© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

# 2 Apache HTTP Template

Kemp has developed a template containing our recommended settings for Apache HTTP. You can install this template on the LoadMaster and use it when creating Virtual Services. Using a template automatically populates the settings in the Virtual Services, which is quicker and easier than manually configuring each Virtual Service. If needed, you can make changes to any of the Virtual Service settings after using the template.

Download released templates from the following page: LoadMaster Templates.

For more information and steps on how to import and use templates, refer to the Virtual Services and Templates, Feature Description.

For steps on how to manually add and configure each of the Virtual Services, refer to the **Configure the LoadMaster** section of this document**.**


© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

# 3 Architecture





© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

# 4 Configure the LoadMaster

The deployed Apache HTTP environment determines which of the following setups is used.

## 4.1 Enable Subnet Originating Requests Globally

It is best practice to enable the **Subnet Originating Requests** option globally.

In a one-armed setup (where the Virtual Service and Real Servers are on the same network/subnet) **Subnet Originating Requests** is usually not needed. However, enabling **Subnet Originating Requests** should not affect the routing in a one-armed setup.

In a two-armed setup where the Virtual Service is on network/subnet A, for example, and the Real Servers are on network B, **Subnet Originating Requests** should be enabled on LoadMasters with firmware version 7.1-16 and above.




When **Subnet Originating Requests** is enabled, the Real Server sees traffic originating from 10.20.20.21 (LoadMaster eth1 address) and responds correctly in most scenarios.

With **Subnet Originating Requests** disabled, the Real Server sees traffic originating from 10.0.0.15 (LoadMaster Virtual Service address on **eth0**) and responds to **eth0** which could cause asymmetric routing.

When **Subnet Originating Requests** is enabled globally, it is automatically enabled on all Virtual Services. If the **Subnet Originating Requests** option is disabled globally, you can choose whether to enable **Subnet Originating Requests** on a per-Virtual Service basis.

To enable **Subnet Originating Requests** globally, follow the steps below:

1. In the main menu of the LoadMaster User Interface (UI), go to **System Configuration > Miscellaneous Options > Network Options**.
2. Select the **Subnet Originating Requests** check box.


© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

## 4.2 Enable Check Persist Globally

It is recommended that you change the **Always Check Persist** option to **Yes – Accept Changes**. Use the following steps:

1. Go to **System Configuration > Miscellaneous Options > L7 Configuration**.
2. Click the **Always Check Persist** drop-down arrow and select **Yes – Accept Changes**.

## 4.3 Create the Apache HTTP Virtual Services

The following sections describe the recommended settings for the Apache HTTP Virtual Services.

### 4.3.1 Create an Apache HTTP Virtual Service

The following are the steps involved and the recommended settings to configure the Apache HTTP Virtual Service:

1. In the main menu of the LoadMaster Web User Interface (WUI), go to **Virtual Services > Add New**.




2. Type a valid **Virtual Address**.
3. Type **80** as the **Port**.
4. Enter a recognizable **Service Name**, such as Apache HTTP Virtual Service.
5. Click **Add this Virtual Service**.
6. Configure the settings as recommended in the following table:


© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

| Section | Option | Value |
|---|---|---|
| Standard Options | Persistence Mode | Active Cookie |
| | Timeout | 1 Hour |
| | Cookie name | JSESSIONID |
| | Scheduling Method | least connection |
| | Idle Connection Timeout | 900 |

7. Add the Real Servers:

   a) Expand the **Real Servers** section.

   b) Click **Add New**.

   c) Enter the address of the relevant Real Server.

   d) Complete the other fields as required.

   e) Click **Add this Real Server** then click **OK** to the pop-up message.

   f) Repeat the steps above to add more Real Servers as needed, based on your environment.

### 4.3.2 Create an Apache HTTPS Virtual Service

The following are the steps involved and the recommended settings to configure the Apache HTTPS Virtual Service:

1. In the main menu of the LoadMaster WUI, go to **Virtual Services > Add New**.





© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

2. Type a valid **Virtual Address**.
3. Type **443** as the **Port**.
4. Enter a recognizable **Service Name**, such as Apache HTTPS Virtual Service.
5. Click **Add this Virtual Service**.
6. Configure the settings as recommended in the following table:

| Section | Option | Value | Comment |
|---|---|---|---|
| Standard Options | Persistence Mode | Source IP Address | |
| | Timeout | 1 Hour | |
| | Scheduling Method | least connection | |
| | Idle Connection Timeout | 900 | |
| Advanced Properties | Add a Port 80 Redirector VS | https://%h%s | Click **Add HTTP Redirector**. This automatically creates a redirect on port 80. |

7. Add the Real Servers:
   a) Expand the **Real Servers** section.
   b) Click **Add New**.
   c) Enter the address of the relevant Real Server.
   d) Complete the other fields as required.
   e) Click **Add this Real Server** then click **OK** to the pop-up message.
   f) Repeat the steps above to add more Real Servers as needed, based on your environment.

**Create an Apache HTTPS Redirect Virtual Service**

Clicking the **Add HTTP Redirector** button automatically creates a port 80 redirect Virtual Service. This is optional, but the purpose of this Virtual Service is to redirect any clients who have connected using HTTP to the HTTPS Virtual Service. Kemp also recommends changing the **Real Server Check Method** and **Persistence Mode** to **None**.


© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

### 4.3.3 Create an Apache HTTPS Offloaded Virtual Service

The following are the steps involved and the recommended settings to configure the Apache HTTPS Offloaded Virtual Service:

1. In the main menu of the LoadMaster WUI, go to **Virtual Services > Add New**.




2. Type a valid **Virtual Address**.
3. Type **443** as the **Port**.
4. Enter a recognizable Service Name, such as **Apache HTTPS Offloaded** Virtual Service.
5. Click **Add this Virtual Service**.
6. Configure the settings as recommended in the following table:

| Section | Option | Value | Comments |
|---|---|---|---|
| Standard Options | Persistence Mode | Active Cookie | |
| | Timeout | 1 Hour | |
| | Cookie name | JSESSSIONID | |
| | Scheduling Method | least connection | |
| | Idle Connection Timeout | 900 | |


© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

| Section | Option | Value | Comments |
|---|---|---|---|
| SSL Properties | SSL Acceleration | Enabled | |
| | Cipher Set | BestPractices | |
| Advanced Properties | Add a Port 80 Redirector VS | https://%h%s | Click **Add HTTP Redirector**. This automatically creates a redirect on port 80. |

7. Add the Real Servers:

   a) Expand the **Real Servers** section.

   b) Click **Add New**.

   c) Enter the address of the relevant Real Server.

   d) Complete the other fields as required.

   e) Click **Add this Real Server** then click **OK** to the pop-up message.

   f) Repeat the steps above to add more Real Servers as needed, based on your environment.

**Create an Apache HTTPS Offloaded Redirect Virtual Service**

Clicking the **Add HTTP Redirector** button automatically creates a port 80 redirect Virtual Service. This is optional, but the purpose of this Virtual Service is to redirect any clients who have connected using HTTP to the HTTPS Virtual Service. Kemp also recommends changing the **Persistence Mode** to **None**.

### 4.3.4 Create an Apache HTTPS Re-encrypt Virtual Service

The following are the steps involved and the recommended settings to configure the Apache HTTPS Re-encrypt Virtual Service:

1. In the main menu of the LoadMaster WUI, go to **Virtual Services > Add New**.


© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.




2. Type a valid **Virtual Address**.
3. Type **443** as the **Port**.
4. Enter a recognizable **Service Name**, such as Apache HTTPS Re-encrypt Virtual Service.
5. Click **Add this Virtual Service**.
6. Configure the settings as recommended in the following table:

| Section | Option | Value | Comments |
|---|---|---|---|
| Standard Options | Persistence Mode | Active Cookie | |
| | Timeout | 1 Hour | |
| | Cookie name | JSESSSIONID | |
| | Scheduling Method | least connection | |
| | Idle Connection Timeout | 900 | |
| SSL Properties | SSL Acceleration | Enabled | |
| | Cipher Set | Best Practices | |
| Advanced Properties | Add a Port 80 Redirector VS | https://%h%s | Click **Add HTTP Redirector**. This automatically creates a redirect on port 80. |


© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

7. Add the Real Servers:

    a) Expand the **Real Servers** section.

    b) Click **Add New**.

    c) Enter the address of the relevant Real Server.

    d) Complete the other fields as required.

    e) Click **Add this Real Server** then click **OK** to the pop-up message.

    f) Repeat the steps above to add more Real Servers as needed, based on your environment.

**Create an Apache HTTPS Re-encrypt Redirect Virtual Service**

Clicking the **Add HTTP Redirector** button automatically creates a port 80 redirect Virtual Service. This is optional, but the purpose of this Virtual Service is to redirect any clients who have connected using HTTP to the HTTPS Virtual Service. Kemp also recommends changing the **Real Server Check Method** and **Persistence Mode** to **None**.


© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

# References

Unless otherwise specified, the following documents can be found at http://kemptechnologies.com/documentation.

**Virtual Services and Templates, Feature Description**


© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

# Last Updated Date

This document was last updated on 27 July 2023.


© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.