

PASOE

Deployment Guide

UPDATED: 27 July 2023

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

These materials and all Progress® software products are copyrighted and all rights are reserved by Progress Software Corporation. The information in these materials is subject to change without notice, and Progress Software Corporation assumes no responsibility for any errors that may appear therein. The references in these materials to specific platforms supported are subject to change.

#1 Load Balancer in Price/Performance, 360 Central, 360 Vision, Chef, Chef (and design), Chef Habitat, Chef Infra, Code Can (and design), Compliance at Velocity, Corticon, Corticon.js, DataDirect (and design), DataDirect Cloud, DataDirect Connect, DataDirect Connect64, DataDirect XML Converters, DataDirect XQuery, DataRPM, Defrag This, Deliver More Than Expected, DevReach (and design), Driving Network Visibility, Flowmon, Inspec, Ipswitch, iMacros, K (stylized), Kemp, Kemp (and design), Kendo UI, Kinvey, LoadMaster, MessageWay, MOVEit, NativeChat, OpenEdge, Powered by Chef, Powered by Progress, Progress, Progress Software Developers Network, SequeLink, Sitefinity (and Design), Sitefinity, Sitefinity (and design), Sitefinity Insight, SpeedScript, Stylized Design (Arrow/3D Box logo), Stylized Design (C Chef logo), Stylized Design of Samurai, TeamPulse, Telerik, Telerik (and design), Test Studio, WebSpeed, WhatsConfigured, WhatsConnected, WhatsUp, and WS_FTP are registered trademarks of Progress Software Corporation or one of its affiliates or subsidiaries in the U.S. and/or other countries.

Analytics360, AppServer, BusinessEdge, Chef Automate, Chef Compliance, Chef Desktop, Chef Workstation, Corticon Rules, Data Access, DataDirect Autonomous REST Connector, DataDirect Spy, DevCraft, Fiddler, Fiddler Classic, Fiddler Everywhere, Fiddler Jam, FiddlerCap, FiddlerCore, FiddlerScript, Hybrid Data Pipeline, iMail, InstaRelinker, JustAssembly, JustDecompile, JustMock, KendoReact, OpenAccess, PASOE, Pro2, ProDataSet, Progress Results, Progress Software, ProVision, PSE Pro, Push Jobs, SafeSpaceVR, Sitefinity Cloud, Sitefinity CMS, Sitefinity Digital Experience Cloud, Sitefinity Feather, Sitefinity Thunder, SmartBrowser, SmartComponent, SmartDataBrowser, SmartDataObjects, SmartDataView, SmartDialog, SmartFolder, SmartFrame, SmartObjects, SmartPanel, SmartQuery, SmartViewer, SmartWindow, Supermarket, SupportLink, Unite UX, and WebClient are trademarks or service marks of Progress Software Corporation and/or its subsidiaries or affiliates in the U.S. and other countries. Java is a registered trademark of Oracle and/or its affiliates. Any other marks contained herein may be trademarks of their respective owners.

Please refer to the NOTICE.txt or Release Notes – Third-Party Acknowledgements file applicable to a particular Progress product/hosted service offering release for any related required third-party acknowledgements.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

Table of Contents

1 Introduction **4**

1.1 Document Purpose 4

1.2 Intended Audience 4

2 Template **5**

3 Architecture **6**

4 Configure the LoadMaster **7**

4.1 Enable Subnet Originating Requests Globally 7

5 Virtual Services **8**

5.1 Create the PASOE HTTP Virtual Service 8

5.1.1 PASOE HTTP Source IP Virtual Service Recommended API Settings (optional) 9

5.1.2 PASOE HTTP JSESSIONID Cookie Virtual Service Recommended API Settings (optional) 10

5.2 Create the PASOE HTTPS Offloaded Virtual Service 10

5.2.1 PASOE HTTPS Offloaded Source IP Virtual Service Recommended API Settings (optional) 11

5.2.2 PASOE HTTPS Offloaded JSESSIONID Cookie Virtual Service Recommended API Settings (optional) 12

5.3 Create the PASOE HTTPS ReEncrypt Virtual Service 13

5.3.1 PASOE HTTPS ReEncrypt Source IP Virtual Service Recommended API Settings (optional) 14

5.3.2 PASOE HTTPS ReEncrypt JSESSIONID Cookie Virtual Service Recommended API Settings (optional) 14

Last Updated Date **16**

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

1 Introduction

Progress Application Server for OpenEdge (PASOE), built upon the industry standard Apache Tomcat web server, delivers an efficient, highly scalable, and secure application server. This innovative application server allows organizations to modernize experiences and limit security vulnerabilities.

The LoadMaster delivers an exceptional, cost effective, and easy to use solution which, by employing intelligent server health checking, optimized performance, security and automatic failover can support an always-on application experience for PASOE.

1.1 Document Purpose

This document provides the recommended LoadMaster settings used when providing high availability, optimization and security for PASOE. The Kemp Support team is available to provide solutions for scenarios not explicitly defined. The Kemp Support site can be found at: https://support.kemptechnologies.com.

1.2 Intended Audience

This document is intended to be read by anyone who is interested in configuring the LoadMaster to optimize Progress Application Server for OpenEdge (PASOE).

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

2 Template

Kemp has developed a template containing our recommended settings for this workload. You can install this template to help create Virtual Services (VSs) because it automatically populates the settings. You can use the template to easily create the required VSs with the recommended settings. For some workloads, additional manual steps may be required such as assigning a certificate or applying port following. These steps are covered in the document, if needed.

You can remove templates after use and this will not affect deployed services. If needed, you can make changes to any of the VS settings after using the template.

Download released templates from the following page: LoadMaster Templates.

For more information and steps on how to import and use templates, refer to the Virtual Services and Templates, Feature Description on the Kemp Documentation page.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

3 Architecture

PASOE deployments consist of 2 or more servers running the PASOE and a back-end database server (set up with High Availability recommended).



© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

4 Configure the LoadMaster

Refer to the sections below for details on some recommended global settings.

4.1 Enable Subnet Originating Requests Globally

It is best practice to enable the **Subnet Originating Requests** option globally.

In a one-armed setup (where the Virtual Service and Real Servers are on the same network/subnet) **Subnet Originating Requests** is usually not needed. However, enabling **Subnet Originating Requests** should not affect the routing in a one-armed setup.

In a two-armed setup where the Virtual Service is on network/subnet A, for example, and the Real Servers are on network B, **Subnet Originating Requests** should be enabled on LoadMasters with firmware version 7.1-16 and above.



When **Subnet Originating Requests** is enabled, the Real Server sees traffic originating from 10.20.20.21 (LoadMaster eth1 address) and responds correctly in most scenarios.

With **Subnet Originating Requests** disabled, the Real Server sees traffic originating from 10.0.0.15 (LoadMaster Virtual Service address on **eth0**) and responds to **eth0** which could cause asymmetric routing.

When **Subnet Originating Requests** is enabled globally, it is automatically enabled on all Virtual Services. If the **Subnet Originating Requests** option is disabled globally, you can choose whether to enable **Subnet Originating Requests** on a per-Virtual Service basis.

To enable **Subnet Originating Requests** globally, follow the steps below:

1. In the main menu of the LoadMaster User Interface (UI), go to **System Configuration > Miscellaneous Options > Network Options**.
2. Select the **Subnet Originating Requests** check box.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

5 Virtual Services

This step-by-step setup of Virtual Services (VSs) leverages the Kemp application template for Progress Application Server for OpenEdge (PASOE).

> Progress Application Server for OpenEdge (PASOE) can be published with different configuration options dependent on the customer requirements. In many cases if anonymous access or basic authentication is used for PASOE, using Source IP Persistence is supported. However, if Forms Based Authentication is leveraged for PASOE, Active Cookie Persistence is recommended.

> The PASOE template is using HTTP/HTTPS health checking along with the default PASOE default TCP port numbers. If enabled on the PASOE environment, OpenEdge Ping can be leveraged to provide more advanced health checking. This advanced health checking will be determined on how OpenEdge Ping is configured within PASOE environment.

The table in each section outlines the settings configured by the application template. You can use this information to manually configure Virtual Services or use the Kemp LoadMaster Application Programming Interface (API) and automation tools.

> This document assumes an SSL/TLS certificate has already been installed on the LoadMaster. For more information on adding SSL/TLS Certificates reference the SSL Accelerated Services, Feature Description.

5.1 Create the PASOE HTTP Virtual Service

The following are the steps involved and the recommended settings to configure the PASOE HTTP Virtual Service.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

1. In the main menu of the LoadMaster User Interface (UI), go to **Virtual Services > Add New**.



2. Type a valid **Virtual Address**.
3. Select the **PASOE-HTTP-Source_IP** or **PASOE-HTTP-JSESSIONID_Cookie** template in the **Use Template** drop-down list depending on what persistence method is required. (Refer to the note in the **Virtual Services** section for recommendations about the persistence method.)
4. Click **Add this Virtual Service**.
5. Expand the **Real Servers** section.
6. Click **Add New**.
7. Type the **Real Server Address**.
8. Click **Add This Real Server**.
9. Repeat these steps to add more Real Servers as needed.

5.1.1 PASOE HTTP Source IP Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. You can use these settings with scripts and automation tools.

API Parameter	API Value
port	8810
prot	tcp
VStype	http
SubnetOriginating	1
Forcel7	1
Schedule	lc
Persist	src

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

PersistTimeOut	360
CheckType	http
CheckUseGet	1
CheckPort	8810

5.1.2 PASOE HTTP JSESSIONID Cookie Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. You can use these settings with scripts and automation tools.

API Parameter	API Value
port	8810
prot	tcp
VStype	http
SubnetOriginating	1
Forcel7	1
Schedule	lc
Persist	server-cookie
PersistTimeOut	360
Cookie	JSESSIONID
CheckType	http
CheckUseGet	1
CheckPort	8810

5.2 Create the PASOE HTTPS Offloaded Virtual Service

The following are the steps involved and the recommended settings to configure the PASOE HTTPS Offloaded Virtual Service.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

1. In the main menu of the LoadMaster User Interface (UI), go to **Virtual Services > Add New**.



2. Type a valid **Virtual Address**.
3. Select the **PASOE-HTTPS-Offloaded-Source_IP** or **PASOE-HTTP-Offloaded-JSESSIONID_Cookie** template in the **Use Template** drop-down list depending on what persistence method is required. (Refer to the note in the **Virtual Services** section for recommendations about the persistence method.)
4. Click **Add this Virtual Service**.
5. Expand the **SSL Properties** section.
6. Select the certificate to use from **Available Certificates** and click the arrow (>) to move it to **Assigned Certificates**.
7. Expand the **Real Servers** section.
8. Click **Add New**.
9. Type the **Real Server Address**.
10. Click **Add This Real Server**.
11. Repeat these steps to add more Real Servers as needed.

5.2.1 PASOE HTTPS Offloaded Source IP Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. You can use these settings with scripts and automation tools.

API Parameter	API Value
port	8811
prot	tcp
VStype	http

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

SubnetOriginating	1
Forcel7	1
Schedule	lc
Persist	src
PersistTimeOut	360
SSLAcceleration	1
TLSType	1
CipherSet	BestPractices
CheckType	http
CheckUseGet	1
CheckPort	8810

5.2.2 PASOE HTTPS Offloaded JSESSIONID Cookie Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. You can use these settings with scripts and automation tools.

API Parameter	API Value
port	8811
prot	tcp
VStype	http
SubnetOriginating	1
Forcel7	1
Schedule	lc
Persist	server-cookie
PersistTimeOut	360
Cookie	JSESSIONID
SSLAcceleration	1

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

TLSType	1
CipherSet	BestPractices
CheckType	http
CheckUseGet	1
CheckPort	8810

5.3 Create the PASOE HTTPS ReEncrypt Virtual Service

The following are the steps involved and the recommended settings to configure the PASOE HTTPS ReEncrypt Virtual Service.

1. In the main menu of the LoadMaster User Interface (UI), go to **Virtual Services > Add New**.



2. Type a valid **Virtual Address**.
3. Select the **PASOE-HTTPS-ReEncrypt-Source_IP** or **PASOE-HTTP- ReEncrypt -JSESSIONID_Cookie** template in the **Use Template** drop-down list depending on what persistence method is required. (Refer to the note in the **Virtual Services** section for recommendations about the persistence method.)
4. Click **Add this Virtual Service**.
5. Expand the **SSL Properties** section.
6. Select the certificate to use from **Available Certificates** and click the arrow (>) to move it to **Assigned Certificates**.
7. Expand the **Real Servers** section.
8. Click **Add New**.
9. Type the **Real Server Address**.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

10. Click **Add This Real Server**.
11. Repeat these steps to add more Real Servers as needed.

5.3.1 PASOE HTTPS ReEncrypt Source IP Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. You can use these settings with scripts and automation tools.

API Parameter	API Value
port	8811
prot	tcp
VStype	http
SubnetOriginating	1
Forcel7	1
Schedule	lc
Persist	src
PersistTimeOut	360
SSLAcceleration	1
SSLReencrypt	1
TLSType	1
CipherSet	BestPractices
CheckType	http
CheckUseGet	1
CheckPort	8811

5.3.2 PASOE HTTPS ReEncrypt JSESSIONID Cookie Virtual Service Recommended API Settings (optional)

This table outlines the API parameters and values set using the Kemp application template. You can use these settings with scripts and automation tools.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

API Parameter	API Value
port	8811
prot	tcp
VStype	http
SubnetOriginating	1
Forcel7	1
Schedule	lc
Persist	server-cookie
PersistTimeOut	360
Cookie	JSESSIONID
SSLAcceleration	1
SSLReencrypt	1
TLSType	1
CipherSet	BestPractices
CheckType	http
CheckUseGet	1
CheckPort	8811

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.

Last Updated Date

This document was last updated on 27 July 2023.

© 2022 Progress Software Corporation and/or one of its subsidiaries or affiliates. All rights reserved.