Progress®
Kemp® LoadMaster®

Deployment Guide MS Exchange 2016

Generated on: 10 March 2025

Copyright

Visit the following page online to see Progress Software Corporation's current Product Documentation Copyright Notice/Trademark Legend: Product Documentation Copyright Notice & Trademarks | Progress

Table of Contents

Chapter 1: Introduction 5

About This Manual 6

Prerequisites 6

Chapter 2: Exchange 2016 Overview 7

Understanding Server Load Balancing 8

Enable Subnet Originating Requests Globally 9

100-Continue Handling 9

Additional L7 Header 10

Chapter 3: Virtual Service Templates 11

Chapter 4: Configuring Virtual Services for Exchange 2016 13

HTTPS Offloaded Virtual Service or Reencrypted without ESP Virtual Service 14

Add SSL/TLS Certificate 14

HTTPS Offloaded and Reencrypted with ESP 16

Add SSL/TLS Certificate 17

Configure ESP 19

HTTPS Pass-through Virtual Service 20

IMAP and IMAPS Virtual Service 21

IMAPS Offloaded and IMAP with STARTTLS Virtual Service 21

POP and POPS Virtual Service 22

POPS Offloaded and POP with STARTTLS Virtual Service 23

SMTP and SMTPS Virtual Service 24

SMTPS Offloaded and SMTP with STARTTLS Virtual Service 25

SMTP with ESP Virtual Service 26
Office Online Server Virtual Service 27

Chapter 5: Exchange 2016 Virtual Service Recommended Settings (Optional) 29

Exchange 2016 HTTP Virtual Service Recommended Settings (Optional) 30
Exchange 2016 HTTPS Pass-through Virtual Service Recommended Settings (Optional) 55
Exchange 2016 IMAP Virtual Service Recommended Settings (Optional) 58
Exchange 2016 POP Virtual Service Recommended Settings (Optional) 63
Exchange 2016 SMTP Virtual Service Recommended Settings (Optional) 68
Exchange 2016 Office Online Server Virtual Service Recommended Settings (Optional) 75

Chapter 6: References 78

1

Introduction

Introduction

The LoadMaster combines versatility with ease-of-use to speed deployment of the complete portfolio of advanced messaging applications and protocols used by Microsoft Exchange 2016 (Exchange 2016), including Outlook on the Web, MAPI/HTTP, Outlook Anywhere (OA), Exchange ActiveSync (EAS), Simple Mail Transfer Protocol (SMTP), Post Office Protocol version 3 (POP3), Internet Message Access Protocol version 4 (IMAP4) and Office Online Server (OOS). With built-in SSL acceleration and/or overlay, the LoadMaster offloads a key source of CPU drain to improve the capacity of the Exchange 2016 infrastructure. Layer 7 health checking at the LoadMaster ensures that if one of the client access components becomes inaccessible, the load balancer will take that component offline for that server, while automatically re-routing and reconnecting users to other functioning servers.

The entire LoadMaster product family, including the Virtual LoadMaster (VLM) supports Exchange 2016, and includes a comprehensive first year warranty and technical support agreement.

Related Links

- About This Manual
- Prerequisites

About This Manual

About This Manual

This manual addresses how to deploy and configure a LoadMaster appliance with Exchange 2016 using Progress Kemp application templates.

The LoadMaster family of products has various models to support networks of different throughput requirements. Information in this manual applies to all LoadMaster models.

Prerequisites

Prerequisites

This guide assumes the reader is a network administrator or familiar with networking and general computer terminology. It is further assumed that the Exchange 2016 environment is set up and the LoadMaster is installed.

LoadMaster documentation is available at https://docs.progress.com.

At a minimum, you should have:

- Installed the Microsoft Servers, Active Directories, and followed other Microsoft requirements.
- Installed the LoadMaster on the same network as the servers.
- Established access to the LoadMaster Web User Interface (WUI).

2

Exchange 2016 Overview

Exchange 2016 Overview

Microsoft Exchange Server is a mail server, calendaring software, and contact manager. It is a server program that runs on Windows Server and is part of the Microsoft Servers line of products. The improvements made in Exchange 2016 have made it easier to load balance Exchange-related traffic.

Exchange 2016 includes the following solutions for switchover and failover redundancy:

- **High availability:** Exchange 2016 uses Database Availability Groups (DAGs) to keep multiple copies of your mailboxes on different servers synchronized. That way, if a mailbox database fails on one server, users can connect to a synchronized copy of the database on another server.
- **Site resilience:** You can deploy two Active Directory sites in separate geographic locations, keep the mailbox data synchronized between the two, and have one of the sites take on the entire load if the other fails.
- **Online mailbox moves:** During an online mailbox move, email accounts are still accessible. Users are locked out for a brief period at the end of the process, when the final synchronization occurs. Online mailbox moves can be performed across forests or in the same forest.
- **Shadow redundancy:** Shadow redundancy protects the availability and recoverability of messages while they are in transit. With shadow redundancy, the deletion of a message from the transport databases is delayed until the transport server verifies that all the next hops for that message have completed. If any of the next hops fail before reporting successful delivery, the message is resubmitted for delivery to the hop that did not complete.

Related Links

- Understanding Server Load Balancing

- Enable Subnet Originating Requests Globally
- 100-Continue Handling
- Additional L7 Header

Understanding Server Load Balancing

Understanding Server Load Balancing

Understanding Server Load Balancing



Server load balancing is a way to manage which servers receive traffic. Server load balancing provides failover redundancy to ensure users continue to receive service in case of failure. It also enables your deployment to handle more traffic than one server can process while offering a single host name for clients.

Server load balancing serves two primary purposes. It reduces the impact of server failures within an exchange organization. In addition, server load balancing ensures that the load on the CAS and transport services are optimally distributed.

As OWA is rendered on the same server that is hosting the user's mailbox database; if a client hits a different CAS, there is no performance degradation because the session rendering for that user is already up and running.

Forms-based authentication is improved. The authentication cookie is provided to the user after logon and it is encrypted using the CAS's SSL certificate. This allows a logged in user to resume their session on a different CAS without having to re-authenticate (if servers share the same SSL certificate).

Enable Subnet Originating Requests Globally

Enable Subnet Originating Requests Globally

It is best practice to enable the **Subnet Originating Requests** option globally.

In a one-armed setup (where the Virtual Service and Real Servers are on the same network/subnet) **Subnet Originating Requests** is usually not needed. However, enabling **Subnet Originating Requests** should not affect the routing in a one-armed setup.

In a two-armed setup where the Virtual Service is on network/subnet A, for example, and the Real Servers are on network B, **Subnet Originating Requests** should be enabled on LoadMasters with firmware version 7.1-16 and above.



When **Subnet Originating Requests** is enabled, the Real Server sees traffic originating from 10.20.20.21 (LoadMaster eth1 address) and responds correctly in most scenarios.

With **Subnet Originating Requests** disabled, the Real Server sees traffic originating from 10.0.0.15 (LoadMaster Virtual Service address on **eth0**) and responds to **eth0** which could cause asymmetric routing.

When **Subnet Originating Requests** is enabled globally, it is automatically enabled on all Virtual Services. If the **Subnet Originating Requests** option is disabled globally, you can choose whether to enable **Subnet Originating Requests** on a per-Virtual Service basis.

To enable **Subnet Originating Requests** globally, follow the steps below:

1. In the main menu of the LoadMaster User Interface (UI), go to **System Configuration > Miscellaneous Options > Network Options**.
2. Select the **Subnet Originating Requests** check box.

100-Continue Handling

100-Continue Handling

To avoid issues with Exchange Web Services, especially in hybrid configuration, configure 100-continue handling to comply with RFC-7231 instead of the standard setting of RFC-2616.

To resolve this issue, apply the following setting on the LoadMaster.

100-Continue handling = RFC-7231 Complaint

1. To select **RFC-7231 Compliant** globally, follow the steps below:
    1. In the main menu of the LoadMaster WUI, go to **System Configuration > Miscellaneous Options > L7 Configuration**.



    1. Select **RFC-7231 Complaint** under **100-Continue Handling**.

Additional L7 Header

Additional L7 Header

When using the built-in Mail client on Mac, you may experience connectivity issues. This happens due to how the Mail client on Mac handles Persistent-Auth headers from the Exchange server. This behavior is not present on Outlook for Mac clients or any Windows Office clients.

To resolve this issue, apply the following settings on the LoadMaster.

Additional L7 Header = None

To select **None** for **Additional L7 Header** globally, follow the steps below:

1. In the main menu of the LoadMaster WUI, go to **System Configuration > Miscellaneous Options > L7 Configuration**.



2. Select **None** under **Additional L7 Header**.

3

Virtual Service Templates

Virtual Service Templates

Progress Kemp has developed templates containing our recommended settings for Exchange 2016. These templates can be installed on the LoadMaster and can be used when creating each of the Virtual Services. Using a template automatically populates the settings in the Virtual Services. This is quicker and easier than manually configuring each Virtual Service. If needed, you can make changes to any of the Virtual Service settings after using the templates.

Download released templates from the following page: LoadMaster Templates.

For more information and steps on how to import and use templates, refer to the **Virtual Services and Templates, Feature Description**.

This guide outlines the steps for setting up Virtual Services using Progress Kemp Application Templates. The Exchange 2016 templates currently available are grouped in three downloadable files as follows:

- **Exchange2016Core**
  - This file contains templates for non-SSL offloaded HTTPS, SSL offloaded HTTPS, and SMTP Virtual Services.
  - This is the primary set of services required to balance Exchange 2016.
- **Exchange2016ESP**
  - This set contains individual templates for a HTTPS service with SSL offloading and an SMTP service, both with ESP enabled.
  - These services are only necessary if you want to use ESP functionality.
- **Exchange2016Additional**

- This set contains templates for IMAP, POP, and SMTP services, including variants for STARTTLS and SSL secured services.

4

Configuring Virtual Services for Exchange 2016

Configuring Virtual Services for Exchange 2016

Follow the instructions below to set up an Exchange Virtual Services using application templates. To configure the Virtual Services using the Application Programming Interface (API), refer to the **RESTful API** on the Documentation page.

The Exchange 2016 Virtual Service Recommended API Settings (Optional) section outlines the recommended settings and values. You can use the API parameters and values when using the LoadMaster API and automation tools.

Note: When using the Web Application Firewall (WAF) in a Microsoft Exchange environment, ensure to enable WAF at the SubVS level to avoid issues with ActiveSync because standard WAF is unable to interpret the protocols used by ActiveSync.

Related Links

- HTTPS Offloaded Virtual Service or Reencrypted without ESP Virtual Service
- HTTPS Offloaded and Reencrypted with ESP
- HTTPS Pass-through Virtual Service
- IMAP and IMAPS Virtual Service
- IMAPS Offloaded and IMAP with STARTTLS Virtual Service
- POP and POPS Virtual Service

- POPS Offloaded and POP with STARTTLS Virtual Service
- SMTP and SMTPS Virtual Service
- SMTPS Offloaded and SMTP with STARTTLS Virtual Service
- SMTP with ESP Virtual Service
- Office Online Server Virtual Service

HTTPS Offloaded Virtual Service or Reencrypted without ESP Virtual Service

HTTPS Offloaded Virtual Service or Reencrypted without ESP Virtual Service

The steps are the same when using Exchange HTTPS Offloaded and Exchange HTTPS Reencrypted with ESP application templates. To add the Virtual Services for Exchange HTTPS Offloaded or Exchange HTTPS Reencrypted, using the template, follow the steps below:

1. Click **Virtual Services**.

2. Click **Add New**.

3. Enter a **Virtual Address**.

4. Select the **Exchange 2016 HTTPS Offloaded** or the **Exchange 2016 HTTPS ReEncrypted** template from the **Use Template** drop-down list depending on your preference.

5. Click **Add This Virtual Service**.

Related Links

- Add SSL/TLS Certificate

Add SSL/TLS Certificate

Add SSL/TLS Certificate

This guide assumes an SSL/TLS certificate is imported into the LoadMaster. For more information and steps for SSL/TLS configuration, refer to the **SSL Accelerated Services Feature Description** on the Documentation page.

1. Click **View/Modify Services** in the left-hand navigation.



2. Click **Modify** for the **Exchange 2016 HTTPS Offloaded** Virtual Service on port 443 (or **Exchange 2016 HTTPS Reencrypted** if that was selected during the creation)
3. Expand **SSL Properties (Acceleration Enabled)**.



4. Select the certificate to use in the **Available Certificates** and click the “arrow” > to move it to **Assigned Certificates**.
5. Click **Set Certificate**.

Note: The **Reencrypt** check box is selected when using the **Exchange 2016 HTTPS Reencrypted with ESP** template.

Add the Real Servers

1. Click **View/Modify Services** in the left-hand navigation.



2. Click **Modify** for the **Exchange 2016 HTTPS Offloaded** Virtual Service on port 443 (or the **Exchange 2016 HTTPS Reencrypted** if that was selected during the creation).
3. Expand the **SubVSs** section.
4. Click **Modify** for **Exchange 2016 HTTPS Offloaded - ActiveSync** (or the **Exchange 2016 HTTPS Reencrypted - ActiveSync** if that was selected during the creation).
5. Expand the **Real Servers** section.
6. Click **Add New**.



7. For the **Real Server Address**, enter the IP Address for one of the Exchange Servers.
8. Select the **Add to all SubVSs** check box.
9. Click **Add This Real Server**.
10. Add additional Real Servers using the **Add to all SubVSs** check box.

Note: The **Authentication Proxy** SubVS should not have a Real Server unless Kerberos Constrained Delegation (KCD) is in use.

HTTPS Offloaded and Reencrypted with ESP

HTTPS Offloaded and Reencrypted with ESP

The steps are the same when using Exchange HTTPS Offloaded and Exchange HTTPS Reencrypted with ESP application template. To add the Virtual Services for Exchange HTTPS Offloaded or Exchange HTTPS Reencrypted with ESP using the template, follow the steps below:

1. Click **Virtual Services**.
2. Click **Add New**.
3. Enter a **Virtual Address**.
4. Select the **Exchange 2016 HTTPS Offloaded with ESP** or the **Exchange 2016 HTTPS ReEncrypted with ESP** template from the **Use Template** drop-down list depending on your preference.
5. Click **Add This Virtual Service**.

Related Links

- Add SSL/TLS Certificate
- Configure ESP

Add SSL/TLS Certificate

Add SSL/TLS Certificate

This guide assumes an SSL/TLS certificate is imported into the LoadMaster. For more information and steps for SSL/TLS configuration, reference the **SSL Accelerated Services Feature Guide** on the Documentation page.

1. Click the **View/Modify Services** in the left-hand navigation.



2. Click **Modify** for the **Exchange 2016 HTTPS Offloaded with ESP** Virtual Service on port 443 (or **Exchange 2016 HTTPS Reencrypted with ESP** if that was selected during the creation)
3. Expand **SSL Properties (Acceleration Enabled)**.



4. Select the certificate to use in the **Available Certificates** and click the “arrow” > to move it to **Assigned Certificates**.
5. Click **Set Certificate**.

Note: The **Reencrypt** check box is selected when using the **Exchange 2016 HTTPS Reencrypted with ESP** template.

Add the Real Servers

1. Click **View/Modify Services** in the left-hand navigation.



2. Click **Modify** for the **Exchange 2016 HTTPS Offloaded with ESP** Virtual Service on port 443 (or the **Exchange 2016 HTTPS Reencrypted with ESP** if that was selected during the creation).
3. Expand the **SubVSs** section.
4. Click **Modify** for **Exchange 2016 HTTPS Offloaded with ESP - Authentication Proxy** (or the **Exchange 2016 HTTPS Reencrypted with ESP - Authentication Proxy** if that was selected during the creation).
5. Expand the **Real Servers** section.

6. Click **Add New**.



7. For the **Real Server Address**, enter the IP Address for one of the Exchange Servers.
8. Select the **Add to all SubVSs** check box.
9. Click **Add This Real Server**.
10. Add additional Real Servers using the **Add to all SubVSs** check box.

Configure ESP

Configure ESP

This guide assumes an SSO Domain is configured on the LoadMaster. For more information and steps for setting up an SSO Domain, refer to the **Edge Security Pack (ESP) Feature Guide** on the Documentation page.

1. Click **View/Modify Services** in the left-hand navigation.



2. Click **Modify** for the **Exchange 2016 HTTPS Offloaded with ESP** Virtual Service on port 443 (or the **Exchange 2016 HTTPS Reencrypted with ESP** if that was selected during the creation).
3. Expand the **SubVSs** section.
4. For each SubVS the following fields must be configured. Click the **set** button next to each field entered.

SubVS Name	Pre-Authorization Excluded Directories	Allowed Virtual Hosts	Logoff String	User Password Form
Authentication Proxy	n/a	Required	n/a	n/a
ActiveSync	n/a	Required	n/a	n/a
API	n/a	n/a	n/a	n/a
Autodiscover	n/a	Required	n/a	n/a
ECP	n/a	Required	n/a	n/a
EWS	n/a	Required	n/a	n/a
MAPI	n/a	Required	n/a	n/a
OAB	n/a	Required	n/a	n/a
OWA	/owa/<guid@smtpdomain>*[1]	Required	/owa/ logoff.owa	https://<Exchange URL> /owa/auth/ expiredpassword.aspx?url=/owa/auth.owa
PowerShell	n/a	Required	n/a	n/a
RPC	n/a	Required	n/a	n/a

Note: [1]GUID is unique to each Exchange deployment. To find the correct GUID, run the following command on the Exchange Server: **Get-Mailbox -Arbitration | where {$_.PersistedCapabilities -like "OrganizationCapabilityClientExtensions"} | fl exchangeGUID, primarysmtpaddress**The **Logoff String** must be set to **/owa/logoff.owa** in the OWA SubVS. In a customized environment, if the OWA logoff string has been changed, the modified logoff string must be entered in the **Logoff String** text box.The SSO Greeting Message field accepts HTML code, so the users can insert their own image if desired. The grave accent character (` ) is not supported. If this character is entered in the SSO Greeting Message, the character will not display in the output, for example, **a`b`c** becomes **abc**.

HTTPS Pass-through Virtual Service

HTTPS Pass-through Virtual Service

To add the Virtual Services for Exchange HTTPS Pass-through using the template, follow the steps below:

1. Click **Virtual Services**.
2. Click **Add New**.
3. Enter a **Virtual Address**.
4. Select the **Exchange 2016 HTTPS pass-through** template from the **Use Template** drop-down list depending on your preference.
5. Click **Add This Virtual Service**.

6. Expand the **Real Servers** section.
7. Click **Add New**.
8. For the **Real Server Address**, enter the IP Address for one of the Exchange Servers.
9. Click **Add this Real Server**.
10. Add any additional Real Servers as required.

IMAP and IMAPS Virtual Service

IMAP and IMAPS Virtual Service

The steps are the same when using Exchange IMAP and Exchange IMAPS application templates. To add the Virtual Services for Exchange IMAP and Exchange IMAPS using the template, follow the steps below:

1. Click **Virtual Services**.
2. Click **Add New**.
3. Enter a **Virtual Address**.
4. Select the **Exchange 2016 IMAP** or the **Exchange 2016 IMAPS** template from the **Use Template** drop-down list depending on your preference.
5. Click **Add This Virtual Service**.
6. Expand the **Real Servers** section.
7. Click **Add New**.
8. For **Real Server Address**, enter the **IP Address** for one of the Exchange Servers.
9. Click **Add this Real Server**.
10. Add any additional Real Servers as required.

IMAPS Offloaded and IMAP with STARTTLS Virtual Service

IMAPS Offloaded and IMAP with STARTTLS Virtual Service

The steps are the same when using Exchange IMAPS Offloaded and Exchange IMAP with STARTTLS application templates. To add the Virtual Services for Exchange IMAPS Offloaded and Exchange IMAP with STARTTLS using the template, follow the steps below:

1. Click **Virtual Services**.
2. Click **Add New**.
3. Enter a **Virtual Address**.
4. Select the **Exchange 2016 IMAP** or the **Exchange 2016 IMAPS** template from the **Use Template** drop-down list depending on your preference.

5. Click **Add This Virtual Service**.
6. Expand **SSL Properties (Acceleration Enabled)**.



7. Select the certificate to use in the **Available Certificates** and click the “arrow” > to move it to **Assigned Certificates**.
8. Click **Set Certificate**.
9. Expand the **Real Servers** section.
10. Click **Add New**.
11. For **Real Server Address**, enter the IP Address for one of the Exchange Servers.

Note: Ensure port 143 is entered in the **Port** field.

12. Click **Add this Real Server**.
13. Add any additional Real Servers as required.

POP and POPS Virtual Service

POP and POPS Virtual Service

The steps are the same when using Exchange POP and Exchange POPS application templates. To add the Virtual Services for Exchange POP and Exchange POPS using the template, follow the steps below:

1. Click **Virtual Services**.
2. Click **Add New**.

3. Enter a **Virtual Address**.
4. Select the **Exchange 2016 POP** or the **Exchange 2016 POPS** template from the **Use Template** drop-down list depending on your preference.
5. Click **Add This Virtual Service**.
6. Expand the **Real Servers** section.
7. Click **Add New**.
8. For the **Real Server Address**, enter the IP Address for one of the Exchange Servers.
9. Click **Add this Real Server**.
10. Add any additional Real Servers as required.

POPS Offloaded and POP with STARTTLS Virtual Service

POPS Offloaded and POP with STARTTLS Virtual Service

The steps are the same when using Exchange IMAPS Offloaded and Exchange IMAP with STARTTLS application templates. To add the Virtual Services for Exchange IMAPS Offloaded and Exchange IMAP with STARTTLS using the template, follow the steps below:

1. Click **Virtual Services**.
2. Click **Add New**.
3. Enter a **Virtual Address**.
4. Select the **Exchange 2016 IMAP** or the **Exchange 2016 IMAPS** template from the **Use Template** drop-down list depending on your preference.
5. Click **Add This Virtual Service**.
6. Expand **SSL Properties (Acceleration Enabled)**.



7. Select the certificate to use in the **Available Certificates** and click the “arrow” > to move it to **Assigned Certificates**.
8. Click **Set Certificate**.
9. Expand the **Real Servers** section.
10. Click **Add New**.
11. For the **Real Server Address**, enter the IP Address for one of the Exchange Servers.

Note: Ensure port 110 is entered in the **Port** field.

12. Click **Add this Real Server**.
13. Add any additional Real Servers as required.

SMTP and SMTPS Virtual Service

SMTP and SMTPS Virtual Service

The steps are the same when using Exchange SMTP and Exchange SMTPS application templates. To add the Virtual Services for Exchange SMTP and Exchange SMTPS using the template, follow the steps below:

1. Click **Virtual Services**.
2. Click **Add New**.
3. Enter a **Virtual Address**.
4. Select the **Exchange 2016 SMTP** or the **Exchange 2016 SMTPS** template from the **Use Template** drop-down list depending on your preference.

5. Click **Add This Virtual Service**.
6. Expand the **Real Servers** section.
7. Click **Add New**.
8. For the **Real Server Address**, enter the IP Address for one of the Exchange Servers.
9. Click **Add this Real Server**.
10. Add any additional Real Servers as required.

SMTPS Offloaded and SMTP with STARTTLS Virtual Service

SMTPS Offloaded and SMTP with STARTTLS Virtual Service

The steps are the same when using Exchange SMTPS Offloaded and Exchange SMTP with STARTTLS application templates. To add the Virtual Services for Exchange SMTPS Offloaded and Exchange SMTP with STARTTLS using the template, follow the steps below:

1. Click the **Add New button**.
2. Enter a **Virtual Address**.
3. Select the **Exchange 2016 SMTP** or the **Exchange 2016 SMTPS** template from the **Use Template** drop-down list depending on your preference.
4. Click **Add This Virtual Service**.
5. Expand **SSL Properties (Acceleration Enabled)**.



6. Select the certificate to use in the **Available Certificates** and click the “arrow” > to move it to **Assigned Certificates**.
7. Click **Set Certificate**.
8. Expand the **Real Servers** section.
9. Click **Add New**.
10. For the **Real Server Address**, enter the IP Address for one of the Exchange Servers.

Note: Ensure port 25 is entered in the **Port** field.

11. Click **Add this Real Server**.
12. Add any additional Real Servers as required.

Note: SMTPS can be configured as offloaded as outlined above but cannot be set to Reencrypt.

SMTP with ESP Virtual Service

SMTP with ESP Virtual Service

To add the Virtual Services for Exchange 2016 SMTP with ESP using the template, follow the steps below:

1. Click the **Add New** button.
2. Enter a **Virtual Address**.
3. Select the **Exchange 2016 SMTP with ESP** template from the **Use Template** drop-down list depending

on your preference.

4. Click **Add This Virtual Service**.
5. Expand **ESP Options**.



6. Enter the Permitted SMTP Domain for the Organization and click **Set Permitted Domains**.
7. Expand the **Real Servers** section.
8. Click **Add New**.
9. For the Real Server Address, enter the IP Address for one of the Office Online Servers.
10. Click **Add this Real Server**.
11. Add any additional Real Servers as necessary.

Office Online Server Virtual Service

Office Online Server Virtual Service

To add the Virtual Services for Office Online Server using the template, follow the steps below:

1. Click the **Add New** button.
2. Enter a **Virtual Address**.
3. Select the **Exchange 2016 Office Online Server** template from the **Use Template** drop-down list depending on your preference.
4. Click **Add This Virtual Servic**e.
5. Expand **SSL Properties (Acceleration Enabled)**.



6. Select the certificate to use in the **Available Certificates** and click the “arrow” > to move it to **Assigned Certificates**.
7. Click **Set Certificate**.
8. **Expand the Real Servers** section.
9. Click **Add New**.
10. For the **Real Server Address**, enter the IP Address for one of the Office Online Servers.
11. Click **Add this Real Server**.
12. Add any additional Real Servers as required.

5

Exchange 2016 Virtual Service Recommended Settings (Optional)

Exchange 2016 Virtual Service Recommended Settings (Optional)

These tables outline the recommended settings using the Progress Kemp application template. You can use these settings with scripts and automation tools.

Related Links

- Exchange 2016 HTTP Virtual Service Recommended Settings (Optional)
- Exchange 2016 HTTPS Pass-through Virtual Service Recommended Settings (Optional)
- Exchange 2016 IMAP Virtual Service Recommended Settings (Optional)
- Exchange 2016 POP Virtual Service Recommended Settings (Optional)
- Exchange 2016 SMTP Virtual Service Recommended Settings (Optional)
- Exchange 2016 Office Online Server Virtual Service Recommended Settings (Optional)

Exchange 2016 HTTP Virtual Service Recommended Settings (Optional)

Exchange 2016 HTTP Virtual Service Recommended Settings (Optional)

API Parameter	API Value	WUI Field Name	WUI Field Value
HTTP Redirect			
port	80	Port	80
prot	tcp	Protocol	tcp
nickname	Exchange%20Redirect	Service Name (Optional)	Exchange Redirect
ForceL7	1	Force L4	Disabled
Errorcode	302	Error Code	302 Found
ErrorUrl	https:%5C%2F%5C%2F%25h%25s	Redirect URL	https:\/\/%h%s
CheckType	none	Real Server Check Method	None
Content Rules			
Authentication Proxy			

API Parameter	API Value	WUI Field Name	WUI Field Value
name	Authentication_Proxy	Rule Name	Authentication Proxy
matchtype	Regex	Match Type	Regular Expression
pattern	%2F%5E%5C%2Flm_auth_proxy%2A%24%2F	Match String	/^\/lm_auth_proxy*$/
Nocase	1	Ignore Case	Enabled
ActiveSync			
Name	ActiveSync	Rule Name	ActiveSync
matchtype	Regex	Match Type	Regular Expression
pattern	%2F%5E%5C%2Fmicrosoft-server-activesync.%2A%2F	Match String	/^\/microsoft-server-activesync.*/
Nocase	1	Ignore Case	Enabled
Autodiscover			
name	Autodiscover	Rule Name	Autodiscover
matchtype	Regex	Match Type	Regular Expression

API Parameter	API Value	WUI Field Name	WUI Field Value
pattern	%2F%5E%5C%2Fautodiscover.%2A%2F	Match String	/^\/autodiscover.*/
Nocase	1	Ignore Case	Enabled
API			
name	api	Rule Name	api
matchtype	Regex	Match Type	Regular Expression
pattern	%2F%5E%5C%2Fapi.%2A%2F	Match String	/^\/api.*/
Nocase	1	Ignore Case	Enabled
ECP			
name	ECP	Rule Name	ECP
matchtype	Regex	Match Type	Regular Expression
Pattern	%2F%5E%5C%2Fecp.%2A%2F	Match String	/^\/ecp.*/
Nocase	1	Ignore Case	Enabled
EWS			
name	EWS	Rule Name	EWS

API Parameter	API Value	WUI Field Name	WUI Field Value
matchtype	Regex	Match Type	Regular Expression
Pattern	%2F%5E%5C%2Fews.%2A%2F	Match String	/^\/ews.*/
Nocase	1	Ignore Case	Enabled
MAPI			
name	MAPI	Rule Name	MAPI
matchtype	Regex	Match Type	Regular Expression
Pattern	%2F%5E%5C%2Fmapi.%2A%2F	Match String	/^\/mapi.*/
Nocase	1	Ignore Case	Enabled
OAB			
name	OAB	Rule Name	OAB
matchtype	Regex	Match Type	Regular Expression
Pattern	%2F%5E%5C%2Foab.%2A%2F	Match String	/^\/oab.*/
Nocase	1	Ignore Case	Enabled
OWA			

API Parameter	API Value	WUI Field Name	WUI Field Value
name	OWA	Rule Name	OWA
matchtype	Regex	Match Type	Regular Expression
Patterns	%2F%5E%5C%2Fowa.%2A%2F	Match String	/^\/owa.*/
Nocase	1	Ignore Case	Enabled
PowerShell			
name	powershell	Rule Name	powershell
matchtype	Regex	Match Type	Regular Expression
Pattern	%2F%5E%5C%2Fpowershell.%2A%2F	Match String	/^\/powershell.*/
Nocase	1	Ignore Case	Enabled
RPC			
name	RPC	Rule Name	RPC
matchtype	Regex	Match Type	Regular Expression
Pattern	%2F%5E%5C%2Frpc.%2A%2F	Match String	/^\/rpc.*/
Nocase	1	Ignore Case	Enabled

API Parameter	API Value	WUI Field Name	WUI Field Value
Main Virtual Service			
port	443	Port	443
prot	tcp	Protocol	tcp
VStype	http	Service Type	http
nickname	Exchange%20HTTPS%20 Offloaded	Service Name (Optional)	HTTP-HTTP/2-HTTPS
ForceL7	1	Force L4	Disabled
Transparent	0	Transparency	Disabled
SubnetOriginating	1	Subnet Originating Requests	Enabled
SSLAcceleration	1	SSL Acceleration	Enabled
SSLReencrypt	0 or 1	Reencrypt	Disabled or Enabled
TLSType	1	Supported Protocols	TLS1.0, TLS1.1, TLS1.2, and TLS1.3 (Enabled)

API Parameter	API Value	WUI Field Name	WUI Field Value
CipherSet	BestPractices	Cipher Set	BestPractices
Tls13CipherSet	TLS_AES_256_GCM_SHA384, TLS_CHACHA20_POLY1305_SHA256, TLS_AES_128_GCM_SHA256, TLS_AES_128_CCM_8_SHA256, TLS_AES_128_CCM_SHA256	TLS1.3 Ciphersets	TLS_AES_256_GCM_SHA384, TLS_CHACHA20_POLY1305_SHA2 TLS_AES_128_GCM_SHA256, TLS_AES_128_CCM_8_SHA256, a TLS_AES_128_CCM_SHA256
PersistTls13CipherSet	None	Persistence Options	None
Schedule	lc	Scheduling Method	least connection
Idletime	1800	Idle Connection Timeout	1800
Sub Virtual Service			
Authentication Proxy			
port	443	Port	443
prot	tcp	Protocol	tcp
Nickname	Authentication%20Proxy	Service Name (Optional)	Authentication Proxy
Errorcode	503	Error Code	503 Service Unavailable

API Parameter	API Value	WUI Field Name	WUI Field Value
ErrorUrl	Endpoint%20not%20available	Redirection URL	Endpoint not available
CheckType	None	Real Server Check Method	None
EspEnabled	1	Enable ESP	Enabled
ESPLogs	7	ESP Logging	User Access, Security, and Connecti (Enabled)
InputAuthMode	2	Client Authentication Mode	Form Based
OutputAuthMode	2	Server Authentication Mode	Form Based
AllowedHosts	Mail.example.com%20autodiscover.example.com	Allowed Virtual Hosts	Mail.example.com autodiscover.example.com
AllowedDirectories	%2F%2A	Allowed Virtual Directories	/*
SingleSignOnMessage	Please%20enter%20your%20Exchange%20credentials	SSO Greeting Message	Please enter your Exchange credentials

API Parameter	API Value	WUI Field Name	WUI Field Value
ActiveSync			
port	443	Port	443
prot	tcp	Protocol	tcp
Nickname	ActiveSync	Service Name (Optional)	ActiveSync
SubnetOriginating	1	Subnet Originating Requests	Enabled
Persist	None	Persistence Options	None
Schedule	lc	Scheduling Method	least connection
Idletime	1800	Idle Connection Timeout	1800
CheckPort	443	Checked Port	443
CheckType	https	Real Server Check Method	HTTPS Protocol
CheckUrl	%2Fmicrosoft-server-activesync%2Fhealthcheck.htm	URL	/microsoft-server-activesync/healthcheck.htm

API Parameter	API Value	WUI Field Name	WUI Field Value
CheckUse1.1	0	Use HTTP/1.1	Disabled
CheckUseGet	1	HTTP Method	GET
EspEnabled	1	Enable ESP	Enabled
ESPLogs	7	ESP Logging	User Access, Security and Connecti (Enabled)
InputAuthMode	1	Client Authentication Mode	Basic Authentication
OutputAuthMode	1	Server Authentication Mode	Basic Authentication
AllowedHosts	Mail.example.com%20autodiscover.example.com	Allowed Virtual Hosts	Mail.example.com autodiscover.example.com
AllowedDirectories	%2Fmicrosoft-server-activesync%2A	Allowed Virtual Directories	/microsoft-server-activesync*
API			
port	443	Port	443
prot	tcp	Protocol	tcp
Nickname	API	Service Name	API

API Parameter	API Value	WUI Field Name	WUI Field Value
		(Optional)	
SubnetOriginating	1	Subnet Originating Requests	Enabled
Persist	None	Persistence Options	None
Schedule	lc	Scheduling Method	least connection
Idletime	1800	Idle Connection Timeout	1800
CheckPort	443	Checked Port	443
CheckType	https	Real Server Check Method	HTTPS Protocol
CheckUrl	%2Fapi%2Fhealthcheck.htm	URL	/api/healthcheck.htm
CheckUse1.1	0	Use HTTP/1.1	Disabled
CheckUseGet	1	HTTP Method	GET
EspEnabled	0	Enable ESP	Enabled

API Parameter	API Value	WUI Field Name	WUI Field Value
Autodiscover			
port	443	Port	443
prot	tcp	Protocol	tcp
Nickname	Autodiscover	Service Name (Optional)	Autodiscover
SubnetOriginating	1	Subnet Originating Requests	Enabled
Persist	None	Persistence Options	None
Schedule	lc	Scheduling Method	least connection
Idletime	1800	Idle Connection Timeout	1800
CheckPort	443	Checked Port	443
CheckType	https	Real Server Check Method	HTTPS Protocol
CheckUrl	%2Fautodiscover%2Fhealthcheck.htm	URL	/autodiscover/healthcheck.htm

API Parameter	API Value	WUI Field Name	WUI Field Value
CheckUse1.1	0	Use HTTP/1.1	Disabled
CheckUseGet	1	HTTP Method	GET
EspEnabled	1	Enable ESP	Enabled
ESPLogs	7	ESP Logging	User Access, Security and Connecti (Enabled)
InputAuthMode	0	Client Authentication Mode	Delegate to Server
OutputAuthMode	0	Server Authentication Mode	None
AllowedHosts	Mail.example.com%20autodiscover.example.com	Allowed Virtual Hosts	Mail.example.com autodiscover.example.com
AllowedDirectories	%2Fautodiscover%2A	Allowed Virtual Directories	/autodiscover*
ECP			
port	443	Port	443
prot	tcp	Protocol	tcp

API Parameter	API Value	WUI Field Name	WUI Field Value
Nickname	ECP	Service Name (Optional)	ECP
SubnetOriginating	1	Subnet Originating Requests	Enabled
Persist	None	Persistence Options	None
Schedule	lc	Scheduling Method	least connection
Idletime	1800	Idle Connection Timeout	1800
CheckPort	443	Checked Port	443
CheckType	https	Real Server Check Method	HTTPS Protocol
CheckUrl	%2Fecp%2Fhealthcheck.htm	URL	/ecp/healthcheck.htm
CheckUse1.1	0	Use HTTP/1.1	Disabled
CheckUseGet	1	HTTP Method	GET
EspEnabled	1	Enable ESP	Enabled

API Parameter	API Value	WUI Field Name	WUI Field Value
ESPLogs	7	ESP Logging	User Access, Security and Connecti (Enabled)
InputAuthMode	2	Client Authentication Mode	Form Based
OutputAuthMode	2	Server Authentication Mode	Form Based
AllowedHosts	Mail.example.com%20autodiscover.example.com	Allowed Virtual Hosts	Mail.example.com autodiscover.example.com
AllowedDirectories	%2Fecp%2A	Allowed Virtual Directories	/ecp*
SingleSignOnMessage	Please%20enter%20your%20Exchange%20credentials	SSO Greeting Message	Please enter your Exchange credentials
EWS			
port	443	Port	443
prot	tcp	Protocol	tcp
Nickname	EWS	Service Name (Optional)	EWS
SubnetOriginating	1	Subnet Originating	Enabled

API Parameter	API Value	WUI Field Name	WUI Field Value
		Requests	
Persist	None	Persistence Options	None
Schedule	lc	Scheduling Method	least connection
Idletime	1800	Idle Connection Timeout	1800
CheckPort	443	Checked Port	443
CheckType	https	Real Server Check Method	HTTPS Protocol
CheckUrl	%2Fews%2Fhealthcheck.htm	URL	/ews/healthcheck.htm
CheckUse1.1	0	Use HTTP/1.1	Disabled
CheckUseGet	1	HTTP Method	GET
EspEnabled	1	Enable ESP	Enabled
ESPLogs	7	ESP Logging	User Access, Security and Connecti (Enabled)

API Parameter	API Value	WUI Field Name	WUI Field Value
InputAuthMode	0	Client Authentication Mode	Delegate to Server
OutputAuthMode	0	Server Authentication Mode	None
AllowedHosts	Mail.example.com%20autodiscover.example.com	Allowed Virtual Hosts	Mail.example.com autodiscover.example.com
AllowedDirectories	%2Fews%2A	Allowed Virtual Directories	/ews*
MAPI			
port	443	Port	443
prot	tcp	Protocol	tcp
Nickname	MAPI	Service Name (Optional)	MAPI
SubnetOriginating	1	Subnet Originating Requests	Enabled
Persist	None	Persistence Options	None
Schedule	lc	Scheduling	least connection

API Parameter	API Value	WUI Field Name	WUI Field Value
		Method	
Idletime	1800	Idle Connection Timeout	1800
CheckPort	443	Checked Port	443
CheckType	https	Real Server Check Method	HTTPS Protocol
CheckUrl	%2Fmapi%2Fhealthcheck.htm	URL	/mapi/healthcheck.htm
CheckUse1.1	0	Use HTTP/1.1	Disabled
CheckUseGet	1	HTTP Method	GET
EspEnabled	1	Enable ESP	Enabled
ESPLogs	7	ESP Logging	User Access, Security and Connecti (Enabled)
InputAuthMode	0	Client Authentication Mode	Delegate to Server
OutputAuthMode	0	Server Authentication Mode	None

API Parameter	API Value	WUI Field Name	WUI Field Value
AllowedHosts	Mail.example.com%20autodiscover.example.com	Allowed Virtual Hosts	Mail.example.com autodiscover.example.com
AllowedDirectories	%2Fmapi%2A	Allowed Virtual Directories	/mapi*
OAB			
port	443	Port	443
prot	tcp	Protocol	tcp
Nickname	OAB	Service Name (Optional)	OAB
SubnetOriginating	1	Subnet Originating Requests	Enabled
Persist	None	Persistence Options	None
Schedule	lc	Scheduling Method	least connection
Idletime	1800	Idle Connection Timeout	1800
CheckPort	443	Checked Port	443

API Parameter	API Value	WUI Field Name	WUI Field Value
CheckType	https	Real Server Check Method	HTTPS Protocol
CheckUrl	%2Foab%2Fhealthcheck.htm	URL	/oab/healthcheck.htm
CheckUse1.1	0	Use HTTP/1.1	Disabled
CheckUseGet	1	HTTP Method	GET
EspEnabled	1	Enable ESP	Enabled
ESPLogs	7	ESP Logging	User Access, Security and Connecti (Enabled)
InputAuthMode	0	Client Authentication Mode	Delegate to Server
OutputAuthMode	0	Server Authentication Mode	None
AllowedHosts	Mail.example.com%20autodiscover.example.com	Allowed Virtual Hosts	Mail.example.com autodiscover.example.com
AllowedDirectories	%2Foab%2A	Allowed Virtual Directories	/oab*
OWA			

API Parameter	API Value	WUI Field Name	WUI Field Value
port	443	Port	443
prot	tcp	Protocol	tcp
Nickname	OWA	Service Name (Optional)	ECP
SubnetOriginating	1	Subnet Originating Requests	Enabled
Persist	None	Persistence Options	None
Schedule	lc	Scheduling Method	least connection
Idletime	1800	Idle Connection Timeout	1800
CheckPort	443	Checked Port	443
CheckType	https	Real Server Check Method	HTTPS Protocol
CheckUrl	%2Fowa%2Fhealthcheck.htm	URL	/owa/healthcheck.htm
CheckUse1.1	0	Use HTTP/1.1	Disabled

API Parameter	API Value	WUI Field Name	WUI Field Value
CheckUseGet	1	HTTP Method	GET
EspEnabled	1	Enable ESP	Enabled
ESPLogs	7	ESP Logging	User Access, Security and Connecti (Enabled)
InputAuthMode	2	Client Authentication Mode	Form Based
OutputAuthMode	2	Server Authentication Mode	Form Based
AllowedHosts	Mail.example.com%20autodiscover.example.com	Allowed Virtual Hosts	Mail.example.com autodiscover.example.com
AllowedDirectories	%2Fowa%2A	Allowed Virtual Directories	/owa*
ExcludedDirectories	%2Fowa%2Fguid%40smtpdomain%2A	Pre-Authorization Excluded Directories	/owa/guid@smtpdomain*
SingleSignOnMessage	Please%20enter%20your%20Exchange%20credentials	SSO Greeting Message	Please enter your Exchange credentials
Logoff	%2Fowa%2Flogoff.owa	Logoff String	/owa/logoff.owa

API Parameter	API Value	WUI Field Name	WUI Field Value
PowerShell			
port	443	Port	443
prot	tcp	Protocol	tcp
Nickname	PowerShell	Service Name (Optional)	PowerShell
SubnetOriginating	1	Subnet Originating Requests	Enabled
Persist	None	Persistence Options	None
Schedule	lc	Scheduling Method	least connection
Idletime	1800	Idle Connection Timeout	1800
CheckPort	443	Checked Port	443
CheckType	https	Real Server Check Method	HTTPS Protocol
CheckUrl	%2Fpowershell%2Fhealthcheck.htm	URL	/powershell/healthcheck.htm

API Parameter	API Value	WUI Field Name	WUI Field Value
CheckUse1.1	0	Use HTTP/1.1	Disabled
CheckUseGet	1	HTTP Method	GET
EspEnabled	1	Enable ESP	Enabled
ESPLogs	7	ESP Logging	User Access, Security and Connecti (Enabled)
InputAuthMode	0	Client Authentication Mode	Delegate to Server
OutputAuthMode	0	Server Authentication Mode	None
AllowedHosts	Mail.example.com%20autodiscover.example.com	Allowed Virtual Hosts	Mail.example.com autodiscover.example.com
AllowedDirectories	%2Fpowershell%2A	Allowed Virtual Directories	/powershell*
RPC			
port	443	Port	443
prot	tcp	Protocol	tcp

API Parameter	API Value	WUI Field Name	WUI Field Value
Nickname	RPC	Service Name (Optional)	PowerShell
SubnetOriginating	1	Subnet Originating Requests	Enabled
Persist	None	Persistence Options	None
Schedule	lc	Scheduling Method	least connection
Idletime	1800	Idle Connection Timeout	1800
CheckPort	443	Checked Port	443
CheckType	https	Real Server Check Method	HTTPS Protocol
CheckUrl	%2Frpc%2Fhealthcheck.htm	URL	/rpc/healthcheck.htm
CheckUse1.1	0	Use HTTP/1.1	Disabled
CheckUseGet	1	HTTP Method	GET
EspEnabled	1	Enable ESP	Enabled

API Parameter	API Value	WUI Field Name	WUI Field Value
ESPLogs	7	ESP Logging	User Access, Security and Connecti (Enabled)
InputAuthMode	0	Client Authentication Mode	Delegate to Server
OutputAuthMode	0	Server Authentication Mode	None
AllowedHosts	Mail.example.com%20autodiscover.example.com	Allowed Virtual Hosts	Mail.example.com autodiscover.example.com
AllowedDirectories	%2Frpc%2A	Allowed Virtual Directories	/rpc*

Exchange 2016 HTTPS Pass-through Virtual Service Recommended Settings (Optional)

Exchange 2016 HTTPS Pass-through Virtual Service Recommended Settings (Optional)

API Parameter	API Value	WUI Field Name	WUI Field Value
HTTPS Pass-through			
port	443	Port	443

API Parameter	API Value	WUI Field Name	WUI Field Value
prot	tcp	Protocol	tcp
VStype	http	Service Type	HTTP-HTTP/2-HTTPS
nickname	Exchange%202016%20HTTPS%20pass-through	Service Name (Optional)	Exchange 2016 HTTPS pass-through
ForceL7	1	Force L4	Disabled
Transparent	0	Transparency	Disabled
SubnetOriginating	1	Subnet Originating Requests	Enabled
Persist	none	Persistence Options	None
Schedule	lc	Scheduling Method	least connection
Idletime	1800	Idle Connection Timeout	1800
CheckType	https	Real Server Check Method	HTTPS Protocol
CheckPort	443	Checked Port	443
CheckUrl	%2Fowa%2Fhealthcheck.htm	URL	/owa/healthcheck.htm

API Parameter	API Value	WUI Field Name	WUI Field Value
CheckUse1.1	0	Use HTTP/1.1	Disabled
CheckUseGet	1	HTTP Method	GET
HTTPS Pass-through Redirect			
port	80	Port	80
prot	tcp	Protocol	tcp
VStype	http	Service Type	HTTP-HTTP/2-HTTPS
nickname	Exchange%202016%20HTTPS%20pass-through%20-%20HTTP%20Redirect	Service Name (Optional)	Exchange 2016 HTTPS pass-through - HTTP Redirect
ForceL7	1	Force L4	Disabled
Errorcode	301	Error Code	301 Moved Permanently
ErrorUrl	https:%2F%2F%25h%25s	Redirect URL	https://%h%s
CheckType	none	Real Server Check Method	None

Exchange 2016 IMAP Virtual Service Recommended Settings (Optional)

Exchange 2016 IMAP Virtual Service Recommended Settings (Optional)

API Parameter	API Value	WUI Field Name	WUI Field Value
IMAP			
port	143	Port	143
prot	tcp	Protocol	tcp
VStype	gen	Service Type	Generic
nickname	Exchange%20IMAP	Service Name (Optional)	Exchange IMAP
ForceL7	1	Force L4	Disabled
Transparent	0	Transparency	Disabled
ServerInit	Imap4	Server Initiating Protocols	IMAP4
SubnetOriginating	1	Subnet Originating Requests	Enabled
Persist	None	Persistence Options	None

API Parameter	API Value	WUI Field Name	WUI Field Value
Schedule	rr	Scheduling Method	round robin
Idletime	3600	Idle Connection Timeout	3600
CheckType	Imap4	Real Server Check Method	Mailbox (IMAP) Protocol
CheckPort	110	Checked Port	110
IMAPS			
port	993	Port	993
prot	tcp	Protocol	tcp
VStype	gen	Service Type	Generic
nickname	Exchange%20IMAPS	Service Name (Optional)	Exchange IMAPS
forceL7	1	Force L4	Disabled
Transparent	0	Transparency	Disabled
ServerInit	Imap4	Server Initiating Protocols	IMAP4
SubnetOriginating	1	Subnet Originating Requests	Enabled

API Parameter	API Value	WUI Field Name	WUI Field Value
Persist	None	Persistence Options	None
Schedule	rr	Scheduling Method	round robin
Idletime	3600	Idle Connection Timeout	3600
CheckType	tcp	Real Server Check Method	TCP Connection Only
CheckPort	993	Checked Port	993
IMAPS Offloaded			
port	993	Port	993
prot	tcp	Protocol	tcp
VStype	gen	Service Type	Generic
nickname	Exchange%20IMAPS%20Offload	Service Name (Optional)	Exchange IMAPS Offload
ForceL7	1	Force L4	Disabled
Transparent	0	Transparency	Disabled
ServerInit	Imap4	Server Initiating Protocols	IMAP4

API Parameter	API Value	WUI Field Name	WUI Field Value
SubnetOriginating	1	Subnet Originating Requests	Enabled
Persist	None	Persistence Options	None
Schedule	rr	Scheduling Method	round robin
Idletime	3600	Idle Connection Timeout	3600
SSLAcceleration	1	SSL Acceleration	Enabled
SSLReencrypt	0	Reencrypt	Disabled
TLSType	1	Supported Protocols	TLS1.0, TLS1.1, TLS1.2, and TLS1.3 (Enabled)
CipherSet	BestPractices	CipherSet	BestPractices
CheckType	Imap4	Real Server Check Method	Mailbox (IMAP) Protocol
CheckPort	143	Checked Port	143
IMAP with STARTTLS			
port	143	Port	143
prot	tcp	Protocol	tcp

API Parameter	API Value	WUI Field Name	WUI Field Value
VStype	StartTLS	Service Type	STARTTLS protocols
nickname	Exchange%20IMAP%20STARTTLS	Service Name (Optional)	Exchange IMAP STARTTLS
ForceL7	1	Force L4	Disabled
Transparent	0	Transparency	Disabled
StartTLSMode	Imap	Server Initiating Protocols	IMAP4
SubnetOriginating	1	Subnet Originating Requests	Enabled
Persist	None	Persistence Options	None
Schedule	rr	Scheduling Method	round robin
Idletime	3600	Idle Connection Timeout	3600
SSLAcceleration	1	SSL Acceleration	Enabled
TLSType	1	Supported Protocols	TLS1.0, TLS1.1, TLS1.2, and TLS1.3 (Enabled)
CipherSet	BestPractices	CipherSet	BestPractices
CheckType	Imap	Real Server Check	Mailbox (IMAP) Protocol

API Parameter	API Value	WUI Field Name	WUI Field Value
		Method	
CheckPort	143	Checked Port	143

Exchange 2016 POP Virtual Service Recommended Settings (Optional)

Exchange 2016 POP Virtual Service Recommended Settings (Optional)

API Parameter	API Value	WUI Field Name	WUI Field Value
POP			
port	110	Port	110
prot	tcp	Protocol	tcp
VStype	gen	Service Type	Generic
nickname	Exchange%20POP	Service Name (Optional)	Exchange POP
ForceL7	1	Force L4	Disabled
Transparent	0	Transparency	Disabled

API Parameter	API Value	WUI Field Name	WUI Field Value
ServerInit	Pop3	Server Initiating Protocols	POP3
SubnetOriginating	1	Subnet Originating Requests	Enabled
Persist	None	Persistence Options	None
Schedule	rr	Scheduling Method	round robin
Idletime	3600	Idle Connection Timeout	3600
CheckType	Pop3	Real Server Check Method	Mailbox (POP3) Protocol
CheckPort	110	Checked Port	110
POPS			
port	995	Port	995
prot	tcp	Protocol	tcp
VStype	gen	Service Type	Generic
nickname	Exchange%20POPS	Service Name (Optional)	Exchange POPS
ForceL7	1	Force L4	Disabled

API Parameter	API Value	WUI Field Name	WUI Field Value
Transparent	0	Transparency	Disabled
ServerInit	Pop3	Server Initiating Protocols	POP3
SubnetOriginating	1	Subnet Originating Requests	Enabled
Persist	None	Persistence Options	None
Schedule	rr	Scheduling Method	round robin
Idletime	3600	Idle Connection Timeout	3600
CheckType	tcp	Real Server Check Method	TCP Connection Only
CheckPort	993	Checked Port	993
POPS Offloaded			
port	995	Port	995
prot	tcp	Protocol	tcp
VStype	gen	Service Type	Generic
nickname	Exchange%20POPS%20Offload	Service Name (Optional)	Exchange POPS Offload

API Parameter	API Value	WUI Field Name	WUI Field Value
ForceL7	1	Force L4	Disabled
Transparent	0	Transparency	Disabled
ServerInit	Pop3	Server Initiating Protocols	POP3
SubnetOriginating	1	Subnet Originating Requests	Enabled
Persist	None	Persistence Options	None
Schedule	rr	Scheduling Method	round robin
Idletime	3600	Idle Connection Timeout	3600
SSLAcceleration	1	SSL Acceleration	Enabled
SSLReencrypt	0	Reencrypt	Disabled
TLSType	1	Supported Protocols	TLS1.0, TLS1.1, TLS1.2, and TLS1.3 (Enabled)
CipherSet	BestPractice	CipherSet	BestPractices
CheckType	Pop3	Real Server Check Method	Mailbox (POP3) Protocol
CheckPort	110	Checked Port	110

API Parameter	API Value	WUI Field Name	WUI Field Value
POP with STARTTLS			
port	110	Port	110
prot	tcp	Protocol	tcp
VStype	StartTLS	Service Type	STARTTLS protocols
nickname	Exchange%20IMAP%20STARTTLS	Service Name (Optional)	Exchange IMAP STARTTLS
ForceL7	1	Force L4	Disabled
Transparent	0	Transparency	Disabled
StartTLSMode	Pop3	Server Initiating Protocols	POP3
SubnetOriginating	1	Subnet Originating Requests	Enabled
Persist	None	Persistence Options	None
Schedule	rr	Scheduling Method	round robin
Idletime	3600	Idle Connection Timeout	3600
SSLAcceleration	1	SSL Acceleration	Enabled

API Parameter	API Value	WUI Field Name	WUI Field Value
TLSType	1	Supported Protocols	TLS1.0, TLS1.1, TLS1.2, and TLS1.3 (Enabled)
CipherSet	BestPractices	CipherSet	BestPractices
CheckType	pop	Real Server Check Method	Mailbox (POP3) Protocol
CheckPort	110	Checked Port	110

Exchange 2016 SMTP Virtual Service Recommended Settings (Optional)

Exchange 2016 SMTP Virtual Service Recommended Settings (Optional)

API Parameter	API Value	WUI Field Name	WUI Field Value
SMTP			
port	25	Port	25
prot	tcp	Protocol	tcp
VStype	gen	Service Type	Generic
nickname	Exchange%20STMP	Service Name (Optional)	Exchange STMP

API Parameter	API Value	WUI Field Name	WUI Field Value
ForceL7	1	Force L4	Disabled
Transparent	0	Transparency	Disabled
ServerInit	smtp	Server Initiating Protocols	SMTP
SubnetOriginating	1	Subnet Originating Requests	Enabled
Persist	src	Persistence Options	Source IP Address
PersistTimeout	3600	Timeout	1 Hour
Schedule	rr	Scheduling Method	round robin
Idletime	120	Idle Connection Timeout	120
CheckType	smtp	Real Server Check Method	Mailbox (SMTP) Protocol
CheckPort	25	Checked Port	25
SMTPS			
port	587	Port	587
prot	tcp	Protocol	tcp

API Parameter	API Value	WUI Field Name	WUI Field Value
VStype	gen	Service Type	Generic
nickname	Exchange%20SMTPS	Service Name (Optional)	Exchange STMPS
ForceL7	1	Force L4	Disabled
Transparent	0	Transparency	Disabled
ServerInit	smtp	Server Initiating Protocols	SMTP
SubnetOriginating	1	Subnet Originating Requests	Enabled
Persist	src	Persistence Options	Source IP Address
PersistTimeout	3600	Timeout	1 Hour
Schedule	rr	Scheduling Method	round robin
Idletime	120	Idle Connection Timeout	120
CheckType	tcp	Real Server Check Method	tcp
CheckPort	587	Checked Port	587
SMTPS Offloaded			

API Parameter	API Value	WUI Field Name	WUI Field Value
port	587	Port	587
prot	tcp	Protocol	tcp
VStype	gen	Service Type	Generic
nickname	Exchange%20SMTPS%20Offload	Service Name (Optional)	Exchange STMPS Offload
ForceL7	1	Force L4	Disabled
Transparent	0	Transparency	Disabled
ServerInit	smtp	Server Initiating Protocols	SMTP
SubnetOriginating	1	Subnet Originating Requests	Enabled
Persist	src	Persistence Options	Source IP Address
PersistTimeout	3600	Timeout	1 Hour
Schedule	rr	Scheduling Method	round robin
Idletime	120	Idle Connection Timeout	120
SSLAcceleration	1	SSL Acceleration	Enabled

API Parameter	API Value	WUI Field Name	WUI Field Value
SSLReencrypt	0	Reencrypt	Disabled
TLSType	1	Supported Protocols	TLS1.0, TLS1.1, TLS1.2, and TLS1.3 (Enabled)
CipherSet	BestPractices	CipherSet	BestPractices
CheckType	smtp	Real Server Check Method	Mail (SMTP) Protocol
CheckPort	25	Checked Port	25
SMTP with STARTTLS			
port	25	Port	25
prot	tcp	Protocol	tcp
VStype	StartTLS	Service Type	STARTTLS protocols
nickname	Exchange%20SMTP%20STARTTLS	Service Name (Optional)	Exchange STMP STARTTLS
ForceL7	1	Force L4	Disabled
Transparent	0	Transparency	Disabled
StartTLSMode	smtp	Server Initiating Protocols	SMTP

API Parameter	API Value	WUI Field Name	WUI Field Value
SubnetOriginating	1	Subnet Originating Requests	Enabled
Persist	src	Persistence Options	Source IP Address
PersistTimeout	3600	Timeout	1 Hour
Schedule	rr	Scheduling Method	round robin
Idletime	120	Idle Connection Timeout	120
SSLAcceleration	1	SSL Acceleration	Enabled
TLSType	1	Supported Protocols	TLS1.0, TLS1.1, TLS1.2, and TLS1.3 (Enabled)
CipherSet	BestPractices	CipherSet	BestPractices
CheckType	smtp	Real Server Check Method	Mail (SMTP) Protocol
CheckPort	25	Checked Port	25
SMTP with ESP			
port	25	Port	25
prot	tcp	Protocol	tcp

API Parameter	API Value	WUI Field Name	WUI Field Value
VStype	gen	Service Type	Generic
nickname	Exchange%20STMP%20ESP	Service Name (Optional)	Exchange STMP ESP
ForceL7	1	Force L4	Disabled
Transparent	0	Transparency	Disabled
ServerInit	smtp	Server Initiating Protocols	SMTP
SubnetOriginating	1	Subnet Originating Requests	Enabled
Persist	src	Persistence Options	Source IP Address
PersistTimeout	3600	Timeout	1 Hour
Schedule	rr	Scheduling Method	round robin
IdleTime	120	Idle Connection Timeout	120
EnableESP	1	Enable ESP	Enabled
ESPLog	4	ESP Logging	Connection (Enabled)
Smtpallow	“Example.com”	SMTP Allowed Domains	Example.com

API Parameter	API Value	WUI Field Name	WUI Field Value
CheckType	smtp	Real Server Check Method	Mail (SMTP) Protocol
CheckPort	25	Checked Port	25

Exchange 2016 Office Online Server Virtual Service Recommended Settings (Optional)

Exchange 2016 Office Online Server Virtual Service Recommended Settings (Optional)

API Parameter	API Value	WUI Field Name	WUI Field Value
Office Online Server			
port	443	Port	443
prot	tcp	Protocol	tcp
VStype	http	Service Type	HTTP-HTTP/2-HTTPS
nickname	Exchange%20Office%20Online	Service Name (Optional)	Exchange Office Online
ForceL7	1	Force L4	Disabled
Transparent	0	Transparency	Disabled

API Parameter	API Value	WUI Field Name	WUI Field Value
SubnetOriginating	1	Subnet Originating Requests	Enabled
Persist	Super-src	Persistence Options	Super HTTP and Souce IP
PersistTimeout	1800	Timeout	30 Minutes
Schedule	lc	Scheduling Method	least connection
Idletime	1800	Idle Connection Timeout	1800
SSLAcceleration	1	SSL Acceleration	Enabled
SSLReencrypt	1	Reencrypt	Enabled
TLSType	1	Supported Protocols	TLS1.0, TLS1.1, TLS1.2, and TLS1.3 (Enabled)
CipherSet	BestPractices	CipherSet	BestPractices
CheckType	https	Real Server Check Method	HTTPS Protocol
CheckPort	443	Checked Port	443
CheckUrl	/hosting/discovery	URL	/hosting/discovery
CheckUse1.1	1	Use HTTP/1.1	Enabled

API Parameter	API Value	WUI Field Name	WUI Field Value
CheckUseGet	1	HTTP Method	GET

6

References

References

Unless otherwise specified, the documents below can be found at https://docs.progress.com

Web User Interface (WUI), Configuration Guide

Virtual Services and Templates, Feature Description

ESP, Feature Description

Microsoft Exchange 2010, Deployment Guide

Microsoft Exchange 2013, Deployment Guide

Exchange Team Blog post on Load Balancing in Exchange 2016

http://blogs.technet.com/b/exchange/archive/2015/10/08/load-balancing-in-exchange-2016.aspx