Progress®
Kemp® LoadMaster®

# Deployment Guide MS Exchange 2016

Generated on: 12 January 2026

# Copyright

**Visit the following page online to see Progress Software Corporation's current Product Documentation Copyright Notice/Trademark Legend:** Product Documentation Copyright Notice & Trademarks | Progress

# Table of Contents


**Chapter 1: Introduction . . . . . 5**

About This Manual . . . . . 5

Prerequisites . . . . . 6

**Chapter 2: Exchange 2016 Overview . . . . . 7**

Understanding Server Load Balancing . . . . . 8

Enable Subnet Originating Requests Globally . . . . . 8

100-Continue Handling . . . . . 9

Additional L7 Header . . . . . 10

**Chapter 3: Virtual Service Templates . . . . . 11**

**Chapter 4: Configuring Virtual Services for Exchange 2016 . . . . . 13**

HTTPS Offloaded Virtual Service or Reencrypted without ESP Virtual Service . . . . . 14

Add SSL/TLS Certificate . . . . . 14

HTTPS Offloaded and Reencrypted with ESP . . . . . 16

Add SSL/TLS Certificate . . . . . 16

Configure ESP . . . . . 19

HTTPS Pass-through Virtual Service . . . . . 20

IMAP and IMAPS Virtual Service . . . . . 20

IMAPS Offloaded and IMAP with STARTTLS Virtual Service . . . . . 21

POP and POPS Virtual Service . . . . . 22

POPS Offloaded and POP with STARTTLS Virtual Service . . . . . 22

SMTP and SMTPS Virtual Service . . . . . 23

SMTPS Offloaded and SMTP with STARTTLS Virtual Service . . . . . 24

SMTP with ESP Virtual Service . . . . . 25
Office Online Server Virtual Service . . . . . 26
WAF Virtual Services . . . . . 27
Exchange 2016 HTTPS Offload with WAF . . . . . 28
Exchange 2016 HTTPS Offload with ESP and WAF . . . . . 30
Exchange 2016 HTTPS re-encrypted with WAF . . . . . 33
Exchange 2016 HTTPS re-encrypted with ESP and WAF . . . . . 35

**Chapter 5: Exchange 2016 Virtual Service Recommended Settings (Optional) . . . . . 39**
Exchange 2016 HTTP Virtual Service Recommended Settings (Optional) . . . . . 40
Exchange 2016 HTTPS Pass-through Virtual Service Recommended Settings (Optional) . . . . . 64
Exchange 2016 IMAP Virtual Service Recommended Settings (Optional) . . . . . 66
Exchange 2016 POP Virtual Service Recommended Settings (Optional) . . . . . 71
Exchange 2016 SMTP Virtual Service Recommended Settings (Optional) . . . . . 76
Exchange 2016 Office Online Server Virtual Service Recommended Settings (Optional) . . . . . 82
Exchange 2016 WAF Recommended Settings (Optional) . . . . . 84
Exchange 2016 HTTPS Offload with WAF Recommended Settings (Optional) . . . . . 84
Exchange 2016 HTTPS Offload with ESP and WAF Recommended Settings (Optional) . . . 97
Exchange 2016 HTTPS re-encrypted with WAF Recommended Settings (Optional) . . . . . 115
Exchange 2016 HTTPS re-encrypted with ESP and WAF Recommended Settings (Optional) . . . . . 128
Content Rules . . . . . 145

**Chapter 6: References . . . . . 151**

# 1

# Introduction

The LoadMaster combines versatility with ease-of-use to speed deployment of the complete portfolio of advanced messaging applications and protocols used by Microsoft Exchange 2016 (Exchange 2016), including Outlook on the Web, MAPI/HTTP, Outlook Anywhere (OA), Exchange ActiveSync (EAS), Simple Mail Transfer Protocol (SMTP), Post Office Protocol version 3 (POP3), Internet Message Access Protocol version 4 (IMAP4) and Office Online Server (OOS). With built-in SSL acceleration and/or overlay, the LoadMaster offloads a key source of CPU drain to improve the capacity of the Exchange 2016 infrastructure. Layer 7 health checking at the LoadMaster ensures that if one of the client access components becomes inaccessible, the load balancer will take that component offline for that server, while automatically re-routing and reconnecting users to other functioning servers.

The entire LoadMaster product family, including the Virtual LoadMaster (VLM) supports Exchange 2016, and includes a comprehensive first year warranty and technical support agreement.

**Contents**


- About This Manual
- Prerequisites


## About This Manual

This manual addresses how to deploy and configure a LoadMaster appliance with Exchange 2016 using Progress Kemp application templates.

The LoadMaster family of products has various models to support networks of different throughput requirements. Information in this manual applies to all LoadMaster models.

# Prerequisites

This guide assumes the reader is a network administrator or familiar with networking and general computer terminology. It is further assumed that the Exchange 2016 environment is set up and the LoadMaster is installed.

The LoadMaster documentation is available here: LoadMaster documentation page.

At a minimum, you should have:

- Installed the Microsoft Servers, Active Directories, and followed other Microsoft requirements.
- Installed the LoadMaster on the same network as the servers.
- Established access to the LoadMaster Web User Interface (WUI).

# 2

# Exchange 2016 Overview

Microsoft Exchange Server is a mail server, calendaring software, and contact manager. It is a server program that runs on Windows Server and is part of the Microsoft Servers line of products. The improvements made in Exchange 2016 have made it easier to load balance Exchange-related traffic.

Exchange 2016 includes the following solutions for switchover and failover redundancy:


- **High availability:** Exchange 2016 uses Database Availability Groups (DAGs) to keep multiple copies of your mailboxes on different servers synchronized. That way, if a mailbox database fails on one server, users can connect to a synchronized copy of the database on another server.
- **Site resilience:** You can deploy two Active Directory sites in separate geographic locations, keep the mailbox data synchronized between the two, and have one of the sites take on the entire load if the other fails.
- **Online mailbox moves:** During an online mailbox move, email accounts are still accessible. Users are locked out for a brief period at the end of the process, when the final synchronization occurs. Online mailbox moves can be performed across forests or in the same forest.
- **Shadow redundancy:** Shadow redundancy protects the availability and recoverability of messages while they are in transit. With shadow redundancy, the deletion of a message from the transport databases is delayed until the transport server verifies that all the next hops for that message have completed. If any of the next hops fail before reporting successful delivery, the message is resubmitted for delivery to the hop that did not complete.

**Contents**


- Understanding Server Load Balancing
- Enable Subnet Originating Requests Globally
- 100-Continue Handling

- Additional L7 Header

# Understanding Server Load Balancing



Server load balancing is a way to manage which servers receive traffic. Server load balancing provides failover redundancy to ensure users continue to receive service in case of failure. It also enables your deployment to handle more traffic than one server can process while offering a single host name for clients.

Server load balancing serves two primary purposes. It reduces the impact of server failures within an exchange organization. In addition, server load balancing ensures that the load on the CAS and transport services are optimally distributed.

As OWA is rendered on the same server that is hosting the user's mailbox database; if a client hits a different CAS, there is no performance degradation because the session rendering for that user is already up and running.

Forms-based authentication is improved. The authentication cookie is provided to the user after logon and it is encrypted using the CAS's SSL certificate. This allows a logged in user to resume their session on a different CAS without having to re-authenticate (if servers share the same SSL certificate).

# Enable Subnet Originating Requests Globally

It is best practice to enable the **Subnet Originating Requests** option globally.

In a one-armed setup (where the Virtual Service and Real Servers are on the same network/subnet) **Subnet**

**Originating Requests** is usually not needed. However, enabling **Subnet Originating Requests** should not affect the routing in a one-armed setup.

In a two-armed setup where the Virtual Service is on network/subnet A, for example, and the Real Servers are on network B, **Subnet Originating Requests** should be enabled on LoadMasters with firmware version 7.1-16 and above.




When **Subnet Originating Requests** is enabled, the Real Server sees traffic originating from 10.20.20.21 (LoadMaster eth1 address) and responds correctly in most scenarios.

With **Subnet Originating Requests** disabled, the Real Server sees traffic originating from 10.0.0.15 (LoadMaster Virtual Service address on **eth0**) and responds to **eth0** which could cause asymmetric routing.

When **Subnet Originating Requests** is enabled globally, it is automatically enabled on all Virtual Services. If the **Subnet Originating Requests** option is disabled globally, you can choose whether to enable **Subnet Originating Requests** on a per-Virtual Service basis.

To enable **Subnet Originating Requests** globally, follow the steps below:

1. In the main menu of the LoadMaster User Interface (UI), go to **System Configuration > Miscellaneous Options > Network Options**.
2. Select the **Subnet Originating Requests** check box.

# 100-Continue Handling

To avoid issues with Exchange Web Services, especially in hybrid configuration, configure 100-continue handling to comply with RFC-7231 instead of the standard setting of RFC-2616.

To resolve this issue, apply the following setting on the LoadMaster.

100-Continue handling = RFC-7231 Complaint

1. To select **RFC-7231 Compliant** globally, follow the steps below:
   1. In the main menu of the LoadMaster WUI, go to **System Configuration > Miscellaneous Options > L7 Configuration**.

   2. Select **RFC-7231 Complaint** under **100-Continue Handling**.

# Additional L7 Header

When using the built-in Mail client on Mac, you may experience connectivity issues. This happens due to how the Mail client on Mac handles Persistent-Auth headers from the Exchange server. This behavior is not present on Outlook for Mac clients or any Windows Office clients.

To resolve this issue, apply the following settings on the LoadMaster.

Additional L7 Header = None

To select **None** for **Additional L7 Header** globally, follow the steps below:

1. In the main menu of the LoadMaster WUI, go to **System Configuration > Miscellaneous Options > L7 Configuration**.




2. Select **None** under **Additional L7 Header**.

# 3

# Virtual Service Templates

Progress Kemp has developed templates containing our recommended settings for Exchange 2016. These templates can be installed on the LoadMaster and can be used when creating each of the Virtual Services. Using a template automatically populates the settings in the Virtual Services. This is quicker and easier than manually configuring each Virtual Service. If needed, you can make changes to any of the Virtual Service settings after using the templates.

Download released templates from the following page: LoadMaster Templates.

For more information and steps on how to import and use templates, refer to the **Virtual Services and Templates, Feature Description**.

This guide outlines the steps for setting up Virtual Services using Progress Kemp Application Templates. The Exchange 2016 templates currently available are grouped in three downloadable files as follows:

- **Exchange2016Core**
  - This file contains templates for non-SSL offloaded HTTPS, SSL offloaded HTTPS, and SMTP Virtual Services.
  - This is the primary set of services required to balance Exchange 2016.
- **Exchange2016ESP**
  - This set contains individual templates for a HTTPS service with SSL offloading and an SMTP service, both with ESP enabled.
  - These services are only necessary if you want to use ESP functionality.
- **Exchange2016Additional**
  - This set contains templates for IMAP, POP, and SMTP services, including variants for STARTTLS and SSL secured services.
- **Exchange2016WAF**

- This set contains templates for SSL offloaded HTTPS, SSL offloaded HTTPS with ESP enabled, and HTTPS re-encryption (both with and without ESP enabled) - all with WAF enabled.
- These services are only required if you want to use WAF functionality.

**Note:** The maximum number of WAF-enabled Virtual Services (or SubVSs) is the total (unused or available) RAM (in MB)/512 MB. For example: 8 GB/512 MB = 16 WAF-enabled Virtual Services. When the maximum is reached, no additional Virtual Services can be enabled with WAF.

**Note:** For further details on WAF, refer to the WAF Feature Description.

- WAF is only available with Enterprise Plus subscriptions.

# 4

# Configuring Virtual Services for Exchange 2016

Follow the instructions below to set up an Exchange Virtual Services using application templates. To configure the Virtual Services using the Application Programming Interface (API), refer to the RESTful API documentation.

The Exchange 2016 Virtual Service Recommended API Settings (Optional) section outlines the recommended settings and values. You can use the API parameters and values when using the LoadMaster API and automation tools.

**Note:** When using the Web Application Firewall (WAF) in a Microsoft Exchange environment, ensure to enable WAF at the SubVS level to avoid issues with ActiveSync because standard WAF is unable to interpret the protocols used by ActiveSync.

**Contents**


- HTTPS Offloaded Virtual Service or Reencrypted without ESP Virtual Service
- HTTPS Offloaded and Reencrypted with ESP
- HTTPS Pass-through Virtual Service
- IMAP and IMAPS Virtual Service
- IMAPS Offloaded and IMAP with STARTTLS Virtual Service
- POP and POPS Virtual Service
- POPS Offloaded and POP with STARTTLS Virtual Service
- SMTP and SMTPS Virtual Service

- SMTPS Offloaded and SMTP with STARTTLS Virtual Service
- SMTP with ESP Virtual Service
- Office Online Server Virtual Service
- WAF Virtual Services

# HTTPS Offloaded Virtual Service or Reencrypted without ESP Virtual Service

The steps are the same when using Exchange HTTPS Offloaded and Exchange HTTPS Reencrypted with ESP application templates. To add the Virtual Services for Exchange HTTPS Offloaded or Exchange HTTPS Reencrypted, using the template, follow the steps below:

1. Click **Virtual Services**.

2. Click **Add New**.

3. Enter a **Virtual Address**.

4. Select the **Exchange 2016 HTTPS Offloaded** or the **Exchange 2016 HTTPS ReEncrypted** template from the **Use Template** drop-down list depending on your preference.

5. Click **Add This Virtual Service**.


**Contents**


- Add SSL/TLS Certificate



## Add SSL/TLS Certificate

This guide assumes an SSL/TLS certificate is imported into the LoadMaster. For more information and steps for SSL/TLS configuration, refer to the SSL Accelerated Services Feature Description.

1. Click **View/Modify Services** in the left-hand navigation.




2. Click **Modify** for the **Exchange 2016 HTTPS Offloaded** Virtual Service on port 443 (or **Exchange 2016 HTTPS Reencrypted** if that was selected during the creation)
3. Expand **SSL Properties (Acceleration Enabled)**.




4. Select the certificate to use in the **Available Certificates** and click the “arrow” > to move it to **Assigned Certificates**.
5. Click **Set Certificate**.


---

**Note:** The **Reencrypt** check box is selected when using the **Exchange 2016 HTTPS Reencrypted with ESP** template.

---


### Add the Real Servers

1. Click **View/Modify Services** in the left-hand navigation.




2. Click **Modify** for the **Exchange 2016 HTTPS Offloaded** Virtual Service on port 443 (or the **Exchange 2016 HTTPS Reencrypted** if that was selected during the creation).
3. Expand the **SubVSs** section.
4. Click **Modify** for **Exchange 2016 HTTPS Offloaded - ActiveSync** (or the **Exchange 2016 HTTPS Reencrypted - ActiveSync** if that was selected during the creation).
5. Expand the **Real Servers** section.

6. Click **Add New**.




7. For the **Real Server Address**, enter the IP Address for one of the Exchange Servers.
8. Select the **Add to all SubVSs** check box.
9. Click **Add This Real Server**.
10. Add additional Real Servers using the **Add to all SubVSs** check box.

---

**Note:** The **Authentication Proxy** SubVS should not have a Real Server unless Kerberos Constrained Delegation (KCD) is in use.

---

# HTTPS Offloaded and Reencrypted with ESP

The steps are the same when using Exchange HTTPS Offloaded and Exchange HTTPS Reencrypted with ESP application template. To add the Virtual Services for Exchange HTTPS Offloaded or Exchange HTTPS Reencrypted with ESP using the template, follow the steps below:

1. Click **Virtual Services**.
2. Click **Add New**.
3. Enter a **Virtual Address**.
4. Select the **Exchange 2016 HTTPS Offloaded with ESP** or the **Exchange 2016 HTTPS ReEncrypted with ESP** template from the **Use Template** drop-down list depending on your preference.
5. Click **Add This Virtual Service**.

**Contents**



- Add SSL/TLS Certificate
- Configure ESP


## Add SSL/TLS Certificate


This guide assumes an SSL/TLS certificate is imported into the LoadMaster. For more information and steps

for SSL/TLS configuration, refer to the SSL Accelerated Services Feature Description.

1. Click the **View/Modify Services** in the left-hand navigation.




2. Click **Modify** for the **Exchange 2016 HTTPS Offloaded with ESP** Virtual Service on port 443 (or **Exchange 2016 HTTPS Reencrypted with ESP** if that was selected during the creation)
3. Expand **SSL Properties (Acceleration Enabled)**.




4. Select the certificate to use in the **Available Certificates** and click the “arrow” > to move it to **Assigned Certificates**.
5. Click **Set Certificate**.


---

**Note:** The **Reencrypt** check box is selected when using the **Exchange 2016 HTTPS Reencrypted with ESP** template.

---

**Add the Real Servers**

1. Click **View/Modify Services** in the left-hand navigation.





2. Click **Modify** for the **Exchange 2016 HTTPS Offloaded with ESP** Virtual Service on port 443 (or the **Exchange 2016 HTTPS Reencrypted with ESP** if that was selected during the creation).
3. Expand the **SubVSs** section.
4. Click **Modify** for **Exchange 2016 HTTPS Offloaded with ESP - Authentication Proxy** (or the **Exchange 2016 HTTPS Reencrypted with ESP - Authentication Proxy** if that was selected during the creation).
5. Expand the **Real Servers** section.
6. Click **Add New**.

---

**Note:** In the ESP-enabled Virtual Services, there should be no Real Servers in the Authentication Proxy SubVS, unless you are using Kerberos server-side authentication. For further details on Kerberos Constrained Delegation (KCD), refer to the Kerberos Constrained Delegation Feature Description.

---




7. For the **Real Server Address**, enter the IP Address for one of the Exchange Servers.
8. Select the **Add to all SubVSs** check box.

---

**Note:** Ensure to delete the Real Server from the Authentication Proxy SubVS if you are not using Kerberos server-side authentication.


---

9. Click **Add This Real Server**.
10. Add additional Real Servers using the **Add to all SubVSs** check box.

# Configure ESP

This guide assumes an SSO Domain is configured on the LoadMaster. For more information and steps for setting up an SSO Domain, refer to the Edge Security Pack (ESP) Feature Description.

1. Click **View/Modify Services** in the left-hand navigation.




2. Click **Modify** for the **Exchange 2016 HTTPS Offloaded with ESP** Virtual Service on port 443 (or the **Exchange 2016 HTTPS Reencrypted with ESP** if that was selected during the creation).
3. Expand the **SubVSs** section.
4. For each SubVS the following fields must be configured. Click the **set** button next to each field entered.

| SubVS Name | Pre-Authorization Excluded Directories | Allowed Virtual Hosts | Logoff String | User Password Form |
|---|---|---|---|---|
| Authentication Proxy | n/a | Required | n/a | n/a |
| ActiveSync | n/a | Required | n/a | n/a |
| API | n/a | n/a | n/a | n/a |
| Autodiscover | n/a | Required | n/a | n/a |
| ECP | n/a | Required | n/a | n/a |
| EWS | n/a | Required | n/a | n/a |
| MAPI | n/a | Required | n/a | n/a |
| OAB | n/a | Required | n/a | n/a |
| OWA | /owa/<guid@smtpdomain>*[1] | Required | /owa/logoff.owa | https://<Exchange URL> /owa/auth/expiredpassword.aspx?url=/owa/auth.owa |
| PowerShell | n/a | Required | n/a | n/a |
| RPC | n/a | Required | n/a | n/a |

**Note:** [1]GUID is unique to each Exchange deployment. To find the correct GUID, run the following command on the Exchange Server: **Get-Mailbox -Arbitration | where {$_.PersistedCapabilities -like "OrganizationCapabilityClientExtensions"} | fl exchangeGUID, primarysmtpaddress**The **Logoff String**

must be set to **/owa/logoff.owa** in the OWA SubVS. In a customized environment, if the OWA logoff string has been changed, the modified logoff string must be entered in the **Logoff String** text box.The SSO Greeting Message field accepts HTML code, so the users can insert their own image if desired. The grave accent character ( ` ) is not supported. If this character is entered in the SSO Greeting Message, the character will not display in the output, for example, **a`b`c** becomes **abc**.

# HTTPS Pass-through Virtual Service

To add the Virtual Services for Exchange HTTPS Pass-through using the template, follow the steps below:

1. Click **Virtual Services**.
2. Click **Add New**.
3. Enter a **Virtual Address**.
4. Select the **Exchange 2016 HTTPS pass-through** template from the **Use Template** drop-down list depending on your preference.
5. Click **Add This Virtual Service**.
6. Expand the **Real Servers** section.
7. Click **Add New**.
8. For the **Real Server Address**, enter the IP Address for one of the Exchange Servers.
9. Click **Add this Real Server**.
10. Add any additional Real Servers as required.

# IMAP and IMAPS Virtual Service

The steps are the same when using Exchange IMAP and Exchange IMAPS application templates. To add the Virtual Services for Exchange IMAP and Exchange IMAPS using the template, follow the steps below:


1. Click **Virtual Services**.
2. Click **Add New**.
3. Enter a **Virtual Address**.
4. Select the **Exchange 2016 IMAP** or the **Exchange 2016 IMAPS** template from the **Use Template** drop-down list depending on your preference.
5. Click **Add This Virtual Service**.
6. Expand the **Real Servers** section.
7. Click **Add New**.
8. For **Real Server Address**, enter the **IP Address** for one of the Exchange Servers.
9. Click **Add this Real Server**.
10. Add any additional Real Servers as required.

# IMAPS Offloaded and IMAP with STARTTLS Virtual Service

The steps are the same when using Exchange IMAPS Offloaded and Exchange IMAP with STARTTLS application templates. To add the Virtual Services for Exchange IMAPS Offloaded and Exchange IMAP with STARTTLS using the template, follow the steps below:

1. Click **Virtual Services**.
2. Click **Add New**.
3. Enter a **Virtual Address**.
4. Select the **Exchange 2016 IMAP** or the **Exchange 2016 IMAPS** template from the **Use Template** drop-down list depending on your preference.
5. Click **Add This Virtual Service**.
6. Expand **SSL Properties (Acceleration Enabled)**.

**Note:** SSL acceleration only does offloading (and not re-encrypting) for this Virtual Service.




7. Select the certificate to use in the **Available Certificates** and click the “arrow” > to move it to **Assigned Certificates**.
8. Click **Set Certificate**.

9. Expand the **Real Servers** section.
10. Click **Add New**.
11. For **Real Server Address**, enter the IP Address for one of the Exchange Servers.

    **Note:** Ensure port 143 is entered in the **Port** field.

12. Click **Add this Real Server**.
13. Add any additional Real Servers as required.

# POP and POPS Virtual Service

The steps are the same when using Exchange POP and Exchange POPS application templates. To add the Virtual Services for Exchange POP and Exchange POPS using the template, follow the steps below:


1. Click **Virtual Services**.
2. Click **Add New**.
3. Enter a **Virtual Address**.
4. Select the **Exchange 2016 POP** or the **Exchange 2016 POPS** template from the **Use Template** drop-down list depending on your preference.
5. Click **Add This Virtual Service**.
6. Expand the **Real Servers** section.
7. Click **Add New**.
8. For the **Real Server Address**, enter the IP Address for one of the Exchange Servers.
9. Click **Add this Real Server**.
10. Add any additional Real Servers as required.

# POPS Offloaded and POP with STARTTLS Virtual Service

The steps are the same when using Exchange IMAPS Offloaded and Exchange IMAP with STARTTLS application templates. To add the Virtual Services for Exchange IMAPS Offloaded and Exchange IMAP with STARTTLS using the template, follow the steps below:

1. Click **Virtual Services**.
2. Click **Add New**.
3. Enter a **Virtual Address**.
4. Select the **Exchange 2016 IMAP** or the **Exchange 2016 IMAPS** template from the **Use Template** drop-down list depending on your preference.
5. Click **Add This Virtual Service**.
6. Expand **SSL Properties (Acceleration Enabled)**.

    **Note:** SSL acceleration only does offloading (and not re-encrypting) for this Virtual Service.




7. Select the certificate to use in the **Available Certificates** and click the “arrow” > to move it to **Assigned Certificates**.
8. Click **Set Certificate**.
9. Expand the **Real Servers** section.
10. Click **Add New**.
11. For the **Real Server Address**, enter the IP Address for one of the Exchange Servers.

---

**Note:** Ensure port 110 is entered in the **Port** field.

---

12. Click **Add this Real Server**.
13. Add any additional Real Servers as required.

# SMTP and SMTPS Virtual Service

The steps are the same when using Exchange SMTP and Exchange SMTPS application templates. To add the Virtual Services for Exchange SMTP and Exchange SMTPS using the template, follow the steps below:

1. Click **Virtual Services**.
2. Click **Add New**.
3. Enter a **Virtual Address**.
4. Select the **Exchange 2016 SMTP** or the **Exchange 2016 SMTPS** template from the **Use Template** drop-down list depending on your preference.


5. Click **Add This Virtual Service**.
6. Expand the **Real Servers** section.
7. Click **Add New**.
8. For the **Real Server Address**, enter the IP Address for one of the Exchange Servers.
9. Click **Add this Real Server**.
10. Add any additional Real Servers as required.

# SMTPS Offloaded and SMTP with STARTTLS Virtual Service

The steps are the same when using Exchange SMTPS Offloaded and Exchange SMTP with STARTTLS application templates. To add the Virtual Services for Exchange SMTPS Offloaded and Exchange SMTP with STARTTLS using the template, follow the steps below:

1. Click the **Add New button**.
2. Enter a **Virtual Address**.
3. Select the **Exchange 2016 SMTP** or the **Exchange 2016 SMTPS** template from the **Use Template** drop-down list depending on your preference.
4. Click **Add This Virtual Service**.
5. Expand **SSL Properties (Acceleration Enabled)**.

**Note:** SSL acceleration only does offloading (and not re-encrypting) for this Virtual Service.




6. Select the certificate to use in the **Available Certificates** and click the “arrow” > to move it to **Assigned Certificates**.
7. Click **Set Certificate**.
8. Expand the **Real Servers** section.
9. Click **Add New**.
10. For the **Real Server Address**, enter the IP Address for one of the Exchange Servers.

**Note:** Ensure port 25 is entered in the **Port** field.

11. Click **Add this Real Server**.
12. Add any additional Real Servers as required.

**Note:** SMTPS can be configured as offloaded as outlined above but cannot be set to Reencrypt.

# SMTP with ESP Virtual Service

To add the Virtual Services for Exchange 2016 SMTP with ESP using the template, follow the steps below:

1. Click the **Add New** button.
2. Enter a **Virtual Address**.
3. Select the **Exchange 2016 SMTP with ESP** template from the **Use Template** drop-down list depending

on your preference.

4. Click **Add This Virtual Service**.
5. Expand **ESP Options**.




6. Enter the Permitted SMTP Domain for the Organization and click **Set Permitted Domains**.


**Note:** If this text box is empty, no domains are allowed and all mail is stopped.

7. Expand the **Real Servers** section.
8. Click **Add New**.
9. For the Real Server Address, enter the IP Address for one of the Office Online Servers.
10. Click **Add this Real Server**.
11. Add any additional Real Servers as necessary.

# Office Online Server Virtual Service

To add the Virtual Services for Office Online Server using the template, follow the steps below:

1. Click the **Add New** button.
2. Enter a **Virtual Address**.
3. Select the **Exchange 2016 Office Online Server** template from the **Use Template** drop-down list depending on your preference.
4. Click **Add This Virtual Servic**e.
5. Expand **SSL Properties (Acceleration Enabled)**.




6. Select the certificate to use in the **Available Certificates** and click the “arrow” > to move it to **Assigned Certificates**.
7. Click **Set Certificate**.
8. **Expand the Real Servers** section.
9. Click **Add New**.
10. For the **Real Server Address**, enter the IP Address for one of the Office Online Servers.
11. Click **Add this Real Server**.
12. Add any additional Real Servers as required.

# WAF Virtual Services

Follow the instructions below to set up Exchange WAF Virtual Services using application templates.

To fully configure WAF (including false positive tuning), we recommend engaging with our Professional Services team. For further details, refer to the following links:

- WAF False Positive Analysis (FPA) Service
- WAF Rule Writing Service

For further information on WAF in general, refer to the WAF Feature Description.

**Contents**


- Exchange 2016 HTTPS Offload with WAF

- Exchange 2016 HTTPS Offload with ESP and WAF
- Exchange 2016 HTTPS re-encrypted with WAF
- Exchange 2016 HTTPS re-encrypted with ESP and WAF


# Exchange 2016 HTTPS Offload with WAF

Follow the instructions below to set up the parent **Exchange 2016 HTTPS Offload with WAF** Virtual Service:

1. Click **Virtual Services**.
2. Click **Add New**.
3. Enter a **Virtual Address**.
4. Select the **Exchange 2016 HTTPS Offload with WAF** template from the **Use Template** drop-down list.
5. Click **Add this Virtual Service**.


**Contents**


- Add SSL/TLS Certificate


## Add SSL/TLS Certificate

This guide assumes an SSL/TLS certificate is imported into the LoadMaster. For more information and steps for SSL/TLS configuration, refer to the SSL Accelerated Services Feature Description.

1. Click **View/Modify Services** (under **Virtual Services**) in the left-hand navigation.
2. Click **Modify** for the **Exchange 2016 HTTPS Offload with WAF** Virtual Service on port 443 (or **Exchange 2016 HTTPS Reencrypted with WAF** if that was selected during creation).
3. Expand **SSL Properties (Acceleration Enabled)**.




4. Select the certificate to use in the **Available Certificates** and click the “arrow” (>) to move it to **Assigned Certificates**.
5. Click **Set Certificates**.


---

**Note:** The **Reencrypt** check box is selected when using the **Exchange 2016 HTTPS Reencrypted with WAF** template.

---

### Add the Real Servers

1. Click **View/Modify Services** in the left-hand navigation.
2. Click **Modify** for the **Exchange 2016 HTTPS Offload with WAF** Virtual Service on port 443 (or the **Exchange 2016 HTTPS Reencrypted with WAF** if that was selected during the creation).
3. Expand the **SubVSs** section.
4. Click **Modify** for **Exchange 2016 HTTPS Offload with ESP - ActiveSync** (or **Exchange 2016 HTTPS Reencrypted with ESP - ActiveSync** if the reencrypted template was selected during the creation).
5. Expand the **Real Servers** section.
6. Click **Add New**.




7. For the **Real Server Address**, enter the IP address of one of the Exchange Servers.
8. Select the **Add to all SubVSs** check box.
9. Click **Add This Real Server**.
10. Add additional Real Servers using the **Add to all SubVSs** check box.

# Exchange 2016 HTTPS Offload with ESP and WAF

Follow the instructions below to set up the parent **Exchange 2016 HTTPS Offloaded with ESP and WAF** Virtual Service:

1. Click **Virtual Services**.
2. Click **Add New**.
3. Enter a **Virtual Address**.
4. Select the **Exchange 2016 HTTPS Offload with ESP and WAF** template from the **Use Template** drop-down list.
5. Click **Add this Virtual Service**.


**Contents**


- Add SSL/TLS Certificate
- Configure ESP


## Add SSL/TLS Certificate

This guide assumes an SSL/TLS certificate is imported into the LoadMaster. For more information and steps for SSL/TLS configuration, reference the SSL Accelerated Services Feature Description.

1. Click **View/Modify Services** (under **Virtual Services**) in the left-hand navigation.
2. Click **Modify** for the **Exchange 2016 HTTPS Offload with ESP and WAF** Virtual Service on port 443 (or **Exchange 2016 HTTPS Reencrypted with ESP and WAF** if that was selected during the creation)
3. Expand **SSL Properties (Acceleration Enabled)**.




4. Select the certificate to use in the **Available Certificates** and click the “arrow” > to move it to **Assigned Certificates**.
5. Click **Set Certificate**.

---

**Note:** The **Reencrypt** check box is selected when using the **Exchange 2016 HTTPS Reencrypted with ESP and WAF** template.

---


### Add the Real Servers

1. Click **View/Modify Services** in the left-hand navigation.
2. Click **Modify** for the **Exchange 2016 HTTPS Offloade with ESP and WAF** Virtual Service on port 443 (or the **Exchange 2016 HTTPS Reencrypted with ESP and WAF** if that was selected during the creation).
3. Expand the **SubVSs** section.
4. Click **Modify** for **Exchange 2016 HTTPS Offload with ESP and WAF - Authentication Proxy** (or the **Exchange 2016 HTTPS Reencrypted with ESP and WAF - Authentication Proxy** if that template was selected during creation).
5. Expand the **Real Servers** section.
6. Click **Add New**.

---

**Note:** In the ESP-enabled Virtual Services, there should be no Real Servers in the Authentication Proxy SubVS, unless you are using Kerberos server-side authentication. For further details on Kerberos Constrained Delegation (KCD), refer to the Kerberos Constrained Delegation Feature Description.

---




7. For the **Real Server Address**, enter the IP Address for one of the Exchange Servers.
8. Select the **Add to all SubVSs** check box.

   **Note:** Ensure to delete the Real Server from the Authentication Proxy SubVS if you are not using Kerberos server-side authentication.

9. Click **Add This Real Server**.
10. Add additional Real Servers using the **Add to all SubVSs** check box.

## Configure ESP

This guide assumes an SSO Domain is configured on the LoadMaster. For more information and steps for setting up an SSO Domain, refer to the Edge Security Pack (ESP) Feature Description.

1. Click **View/Modify Services** (under **Virtual Services**) in the left-hand navigation.
2. Click **Modify** for the **Exchange 2016 HTTPS Offload with ESP and WAF** Virtual Service on port 443 (or the **Exchange 2016 HTTPS Reencrypted with ESP and WAF** if that was selected during creation).
3. Expand the **SubVSs** section.
4. For each SubVS the following fields must be configured. Click the **set** button next to each field entered.

| SubVS Name | Pre-Authorization Excluded Directories | Logoff String | User Password Form |
|---|---|---|---|
| Authentication Proxy | /api /autodiscover/ autodiscover.svc /autodiscover/ autodiscover.json /autodiscover/ autodiscover.svc/wssecurity /ews/exchange.asmx/ wssecurity /ews/ exchange.asmx /ews/ mrsproxy.svc | n/a | n/a |
| ActiveSync | n/a | n/a | n/a |

| SubVS Name | Pre-Authorization Excluded Directories | Logoff String | User Password Form |
|---|---|---|---|
| API | n/a | n/a | n/a |
| Autodiscover | n/a | n/a | n/a |
| ECP | n/a | n/a | n/a |
| EWS | n/a | n/a | n/a |
| MAPI | n/a | n/a | n/a |
| OAB | n/a | n/a | n/a |
| OWA | /owa/<guid@smtpdomain>*[1] | /owa/logoff.owa | |
| PowerShell | n/a | n/a | n/a |
| RPC | n/a | n/a | n/a |

**Note:** [1]GUID is unique to each Exchange deployment. To find the correct GUID, run the following command on the Exchange Server: **Get-Mailbox -Arbitration | where {$_.PersistedCapabilities -like "OrganizationCapabilityClientExtensions"} | fl exchangeGUID, primarysmtpaddress**.

The **Logoff String** must be set to **/owa/logoff.owa** in the OWA SubVS. In a customized environment, if the OWA logoff string has been changed, the modified logoff string must be entered in the **Logoff String** text box.The SSO Greeting Message field accepts HTML code, so the users can insert their own image if desired. The grave accent character ( ` ) is not supported. If this character is entered in the SSO Greeting Message, the character will not display in the output, for example, **a`b`c** becomes **abc**.

# Exchange 2016 HTTPS re-encrypted with WAF

Follow the instructions below to set up the parent **Exchange 2016 HTTPS re-encrypted with WAF** Virtual Service:

1. Click **Virtual Services**.
2. Click **Add New**.
3. Enter a **Virtual Address**.
4. Select the **Exchange 2016 HTTPS re-encrypted with WAF** template from the **Use Template** drop-down list.
5. Click **Add this Virtual Service**.


**Contents**


- Add SSL/TLS Certificate

## Add SSL/TLS Certificate

This guide assumes an SSL/TLS certificate is imported into the LoadMaster. For more information and steps for SSL/TLS configuration, refer to the SSL Accelerated Services Feature Description.

1. Click **View/Modify Services** (under **Virtual Services**) in the left-hand navigation.
2. Click **Modify** for the **Exchange 2016 HTTPS Offload with WAF** Virtual Service on port 443 (or **Exchange 2016 HTTPS Reencrypted with WAF** if that was selected during creation).
3. Expand **SSL Properties (Acceleration Enabled)**.




4. Select the certificate to use in the **Available Certificates** and click the “arrow” (>) to move it to **Assigned Certificates**.
5. Click **Set Certificates**.

---


**Note:** The **Reencrypt** check box is selected when using the **Exchange 2016 HTTPS Reencrypted with WAF** template.

---

### Add the Real Servers

1. Click **View/Modify Services** in the left-hand navigation.
2. Click **Modify** for the **Exchange 2016 HTTPS Offload with WAF** Virtual Service on port 443 (or the **Exchange 2016 HTTPS Reencrypted with WAF** if that was selected during the creation).
3. Expand the **SubVSs** section.

4. Click **Modify** for **Exchange 2016 HTTPS Offload with ESP - ActiveSync** (or **Exchange 2016 HTTPS Reencrypted with ESP - ActiveSync** if the reencrypted template was selected during the creation).
5. Expand the **Real Servers** section.
6. Click **Add New**.




7. For the **Real Server Address**, enter the IP address of one of the Exchange Servers.
8. Select the **Add to all SubVSs** check box.
9. Click **Add This Real Server**.
10. Add additional Real Servers using the **Add to all SubVSs** check box.

# Exchange 2016 HTTPS re-encrypted with ESP and WAF

Follow the instructions below to set up the parent **Exchange 2016 HTTPS re-encrypted with ESP and WAF** Virtual Service:

1. Click **Virtual Services**.
2. Click **Add New**.
3. Enter a **Virtual Address**.
4. Select the **Exchange 2016 HTTPS re-encrypted with ESP and WAF** template from the **Use Template** drop-down list.
5. Click **Add this Virtual Service**.

**Contents**



- Add SSL/TLS Certificate
- Configure ESP


## Add SSL/TLS Certificate

This guide assumes an SSL/TLS certificate is imported into the LoadMaster. For more information and steps for SSL/TLS configuration, reference the SSL Accelerated Services Feature Description.

1. Click **View/Modify Services** (under **Virtual Services**) in the left-hand navigation.

2. Click **Modify** for the **Exchange 2016 HTTPS Offload with ESP and WAF** Virtual Service on port 443 (or **Exchange 2016 HTTPS Reencrypted with ESP and WAF** if that was selected during the creation)
3. Expand **SSL Properties (Acceleration Enabled)**.




4. Select the certificate to use in the **Available Certificates** and click the “arrow” > to move it to **Assigned Certificates**.
5. Click **Set Certificate**.

---


**Note:** The **Reencrypt** check box is selected when using the **Exchange 2016 HTTPS Reencrypted with ESP and WAF** template.

---

### Add the Real Servers

1. Click **View/Modify Services** in the left-hand navigation.
2. Click **Modify** for the **Exchange 2016 HTTPS Offloade with ESP and WAF** Virtual Service on port 443 (or the **Exchange 2016 HTTPS Reencrypted with ESP and WAF** if that was selected during the creation).
3. Expand the **SubVSs** section.
4. Click **Modify** for **Exchange 2016 HTTPS Offload with ESP and WAF - Authentication Proxy** (or the **Exchange 2016 HTTPS Reencrypted with ESP and WAF - Authentication Proxy** if that template was selected during creation).
5. Expand the **Real Servers** section.
6. Click **Add New**.

**Note:** In the ESP-enabled Virtual Services, there should be no Real Servers in the Authentication Proxy SubVS, unless you are using Kerberos server-side authentication. For further details on Kerberos Constrained Delegation (KCD), refer to the Kerberos Constrained Delegation Feature Description.




7. For the **Real Server Address**, enter the IP Address for one of the Exchange Servers.
8. Select the **Add to all SubVSs** check box.

**Note:** Ensure to delete the Real Server from the Authentication Proxy SubVS if you are not using Kerberos server-side authentication.

9. Click **Add This Real Server**.
10. Add additional Real Servers using the **Add to all SubVSs** check box.

## Configure ESP

This guide assumes an SSO Domain is configured on the LoadMaster. For more information and steps for setting up an SSO Domain, refer to the Edge Security Pack (ESP) Feature Description.

1. Click **View/Modify Services** (under **Virtual Services**) in the left-hand navigation.
2. Click **Modify** for the **Exchange 2016 HTTPS Offload with ESP and WAF** Virtual Service on port 443 (or the **Exchange 2016 HTTPS Reencrypted with ESP and WAF** if that was selected during creation).
3. Expand the **SubVSs** section.
4. For each SubVS the following fields must be configured. Click the **set** button next to each field entered.

| SubVS Name | Pre-Authorization Excluded Directories | Logoff String | User Password Form |
|---|---|---|---|
| Authentication Proxy | /api /autodiscover/ autodiscover.svc /autodiscover/ autodiscover.json /autodiscover/ autodiscover.svc/wssecurity /ews/exchange.asmx/ | n/a | n/a |

| SubVS Name | Pre-Authorization Excluded Directories | Logoff String | User Password Form |
|---|---|---|---|
| | wssecurity /ews/ exchange.asmx /ews/ mrsproxy.svc | | |
| ActiveSync | n/a | n/a | n/a |
| API | n/a | n/a | n/a |
| Autodiscover | n/a | n/a | n/a |
| ECP | n/a | n/a | n/a |
| EWS | n/a | n/a | n/a |
| MAPI | n/a | n/a | n/a |
| OAB | n/a | n/a | n/a |
| OWA | /owa/<guid@smtpdomain>* [1] | /owa/logoff.owa | |
| PowerShell | n/a | n/a | n/a |
| RPC | n/a | n/a | n/a |

**Note:** [1]GUID is unique to each Exchange deployment. To find the correct GUID, run the following command on the Exchange Server: **Get-Mailbox -Arbitration | where {$_.PersistedCapabilities -like "OrganizationCapabilityClientExtensions"} | fl exchangeGUID, primarysmtpaddress**.

The **Logoff String** must be set to **/owa/logoff.owa** in the OWA SubVS. In a customized environment, if the OWA logoff string has been changed, the modified logoff string must be entered in the **Logoff String** text box.The SSO Greeting Message field accepts HTML code, so the users can insert their own image if desired. The grave accent character ( ` ) is not supported. If this character is entered in the SSO Greeting Message, the character will not display in the output, for example, **a`b`c** becomes **abc**.

# 5

# Exchange 2016 Virtual Service Recommended Settings (Optional)

These tables outline the recommended settings using the Progress Kemp application template. You can use these settings with scripts and automation tools.

**Contents**


- Exchange 2016 HTTP Virtual Service Recommended Settings (Optional)
- Exchange 2016 HTTPS Pass-through Virtual Service Recommended Settings (Optional)
- Exchange 2016 IMAP Virtual Service Recommended Settings (Optional)
- Exchange 2016 POP Virtual Service Recommended Settings (Optional)
- Exchange 2016 SMTP Virtual Service Recommended Settings (Optional)
- Exchange 2016 Office Online Server Virtual Service Recommended Settings (Optional)
- Exchange 2016 WAF Recommended Settings (Optional)

# Exchange 2016 HTTP Virtual Service Recommended Settings (Optional)

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| **HTTP Redirect** | | | | |
| port | 80 | Port | 80 | All |
| prot | tcp | Protocol | tcp | All |
| nickname | Exchange%20Redirect | Service Name (Optional) | Exchange Redirect | All |
| ForceL7 | 1 | Force L4 | Disabled | All |
| Errorcode | 302 | Error Code | 302 Found | All |
| ErrorUrl | https:%5C%2F%5C%2F%25h%25s | Redirect URL | https:\/\/%h%s | All |
| CheckType | none | Real Server Check Method | None | |
| **Content Rules** | | | | |
| Authentication Proxy | | | | |
| name | Authentication_Proxy | Rule Name | Authentication Proxy | ESP Enabled |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| matchtype | Regex | Match Type | Regular Expression | ESP Enabled |
| pattern | %2F%5E%5C%2Flm_auth_proxy%2A%24%2F | Match String | /^\/lm_auth_proxy*$/ | ESP Enabled |
| Nocase | 1 | Ignore Case | Enabled | ESP Enabled |
| **ActiveSync** | | | | |
| Name | ActiveSync | Rule Name | ActiveSync | All |
| matchtype | Regex | Match Type | Regular Expression | All |
| pattern | %2F%5E%5C%2Fmicrosoft-server-activesync.%2A%2F | Match String | /^\/microsoft-server-activesync.*/ | All |
| Nocase | 1 | Ignore Case | Enabled | All |
| **Autodiscover** | | | | |
| name | Autodiscover | Rule Name | Autodiscover | All |
| matchtype | Regex | Match Type | Regular Expression | All |
| pattern | %2F%5E%5C%2Fautodiscover.%2A%2F | Match String | /^\/autodiscover.*/ | All |
| Nocase | 1 | Ignore Case | Enabled | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| **API** | | | | |
| name | api | Rule Name | api | All |
| matchtype | Regex | Match Type | Regular Expression | All |
| pattern | %2F%5E%5C%2Fapi.%2A%2F | Match String | /^\/api.*/ | All |
| Nocase | 1 | Ignore Case | Enabled | All |
| **ECP** | | | | |
| name | ECP | Rule Name | ECP | All |
| matchtype | Regex | Match Type | Regular Expression | All |
| Pattern | %2F%5E%5C%2Fecp.%2A%2F | Match String | /^\/ecp.*/ | All |
| Nocase | 1 | Ignore Case | Enabled | All |
| **EWS** | | | | |
| name | EWS | Rule Name | EWS | All |
| matchtype | Regex | Match Type | Regular Expression | All |
| Pattern | %2F%5E%5C%2Fews.%2A%2F | Match String | /^\/ews.*/ | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| Nocase | 1 | Ignore Case | Enabled | All |
| **MAPI** | | | | |
| name | MAPI | Rule Name | MAPI | All |
| matchtype | Regex | Match Type | Regular Expression | All |
| Pattern | %2F%5E%5C%2Fmapi.%2A%2F | Match String | /^\/mapi.*/ | All |
| Nocase | 1 | Ignore Case | Enabled | All |
| **OAB** | | | | |
| name | OAB | Rule Name | OAB | All |
| matchtype | Regex | Match Type | Regular Expression | All |
| Pattern | %2F%5E%5C%2Foab.%2A%2F | Match String | /^\/oab.*/ | All |
| Nocase | 1 | Ignore Case | Enabled | All |
| **OWA** | | | | |
| name | OWA | Rule Name | OWA | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| matchtype | Regex | Match Type | Regular Expression | All |
| Patterns | %2F%5E%5C%2Fowa.%2A%2F | Match String | /^\/owa.*/ | All |
| Nocase | 1 | Ignore Case | Enabled | All |
| **PowerShell** | | | | |
| name | powershell | Rule Name | powershell | All |
| matchtype | Regex | Match Type | Regular Expression | All |
| Pattern | %2F%5E%5C%2Fpowershell.%2A%2F | Match String | /^\/powershell.*/ | All |
| Nocase | 1 | Ignore Case | Enabled | All |
| **RPC** | | | | |
| name | RPC | Rule Name | RPC | All |
| matchtype | Regex | Match Type | Regular Expression | All |
| Pattern | %2F%5E%5C%2Frpc.%2A%2F | Match String | /^\/rpc.*/ | All |
| Nocase | 1 | Ignore Case | Enabled | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| **Main Virtual Service** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| VStype | http | Service Type | http | All |
| nickname | Exchange%20HTTPS%20 Offloaded | Service Name (Optional) | HTTP-HTTP/ 2-HTTPS | Create Unique Name |
| ForceL7 | 1 | Force L4 | Disabled | All |
| Transparent | 0 | Transparency | Disabled | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| SSLAcceleration | 1 | SSL Acceleration | Enabled | All |
| SSLReencrypt | 0 or 1 | Reencrypt | Disabled or Enabled | 0 for Offload<br>1 for Reencrypt |
| TLSType | 1 | Supported Protocols | TLS1.0, TLS1.1, TLS1.2, and TLS1.3 (Enabled) | All |
| CipherSet | BestPractices | Cipher Set | BestPractices | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| Tls13CipherSet | TLS_AES_256_GCM_SHA384, TLS_CHACHA20_POLY1305_SHA256, TLS_AES_128_GCM_SHA256, TLS_AES_128_CCM_8_SHA256, TLS_AES_128_CCM_SHA256 | TLS1.3 Ciphersets | TLS_AES_256_GCM_SHA384, TLS_CHACHA20_POLY1305_SHA256, TLS_AES_128_GCM_SHA256, TLS_AES_128_CCM_8_SHA256, and TLS_AES_128_CCM_SHA256 | All |
| PersistTls13CipherSet | None | Persistence Options | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 1800 | Idle Connection Timeout | 1800 | All |
| **Sub Virtual Service** | | | | |
| **Authentication Proxy** | | | | |
| port | 443 | Port | 443 | ESP Enabled |
| prot | tcp | Protocol | tcp | ESP Enabled |
| Nickname | Authentication%20Proxy | Service Name (Optional) | Authentication Proxy | ESP Enabled |
| Errorcode | 503 | Error Code | 503 Service Unavailable | ESP Enabled |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| ErrorUrl | Endpoint%20not%20available | Redirection URL | Endpoint not available | ESP Enabled |
| CheckType | None | Real Server Check Method | None | ESP Enabled |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security, and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 2 | Client Authentication Mode | Form Based | ESP Enabled |
| OutputAuthMode | 2 | Server Authentication Mode | Form Based | ESP Enabled |
| AllowedHosts | Mail.example.com%20autodiscover.example.com | Allowed Virtual Hosts | Mail.example.com autodiscover.example.com | ESP Enabled |
| AllowedDirectories | %2F%2A | Allowed Virtual Directories | /* | ESP Enabled |
| SingleSignOnMessage | Please%20enter%20your%20Exchange%20credentials | SSO Greeting Message | Please enter your Exchange credentials | ESP Enabled |
| **ActiveSync** | | | | |
| port | 443 | Port | 443 | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| prot | tcp | Protocol | tcp | All |
| Nickname | ActiveSync | Service Name (Optional) | ActiveSync | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | None | Persistence Options | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 1800 | Idle Connection Timeout | 1800 | All |
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Fmicrosoft-server-activesync%2Fhealthcheck.htm | URL | /microsoft-server-activesync/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 1 | Client Authentication Mode | Basic Authentication | ESP Enabled |
| OutputAuthMode | 1 | Server Authentication Mode | Basic Authentication | ESP Enabled |
| AllowedHosts | Mail.example.com%20autodiscover.example.com | Allowed Virtual Hosts | Mail.example.com autodiscover.example.com | ESP Enabled |
| AllowedDirectories | %2Fmicrosoft-server-activesync%2A | Allowed Virtual Directories | /microsoft-server-activesync* | ESP Enabled |
| **API** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | API | Service Name (Optional) | API | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | None | Persistence Options | None | All |
| Schedule | lc | Scheduling Method | least connection | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| Idletime | 1800 | Idle Connection Timeout | 1800 | All |
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Fapi%2Fhealthcheck.htm | URL | /api/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 0 | Enable ESP | Enabled | All |
| **Autodiscover** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | Autodiscover | Service Name (Optional) | Autodiscover | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | None | Persistence Options | None | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 1800 | Idle Connection Timeout | 1800 | All |
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Fautodiscover%2Fhealthcheck.htm | URL | /autodiscover/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 0 | Client Authentication Mode | Delegate to Server | ESP Enabled |
| OutputAuthMode | 0 | Server Authentication Mode | None | ESP Enabled |
| AllowedHosts | Mail.example.com%20autodiscover.exampl | Allowed Virtual Hosts | Mail.example.com autodiscover.example | ESP Enabled |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| | e.com | | .com | |
| AllowedDirectories | %2Fautodiscover%2A | Allowed Virtual Directories | /autodiscover* | ESP Enabled |
| **ECP** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | ECP | Service Name (Optional) | ECP | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | None | Persistence Options | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 1800 | Idle Connection Timeout | 1800 | All |
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Fecp%2Fhealthch | URL | /ecp/healthcheck.htm | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| | eck.htm | | | |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 2 | Client Authentication Mode | Form Based | ESP Enabled |
| OutputAuthMode | 2 | Server Authentication Mode | Form Based | ESP Enabled |
| AllowedHosts | Mail.example.com%20autodiscover.example.com | Allowed Virtual Hosts | Mail.example.com autodiscover.example.com | ESP Enabled |
| AllowedDirectories | %2Fecp%2A | Allowed Virtual Directories | /ecp* | ESP Enabled |
| SingleSignOnMessage | Please%20enter%20your%20Exchange%20credentials | SSO Greeting Message | Please enter your Exchange credentials | ESP Enabled |
| **EWS** | | | | |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | EWS | Service Name (Optional) | EWS | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | None | Persistence Options | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 1800 | Idle Connection Timeout | 1800 | All |
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Fews%2Fhealthcheck.htm | URL | /ews/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 0 | Client Authentication Mode | Delegate to Server | ESP Enabled |
| OutputAuthMode | 0 | Server Authentication Mode | None | ESP Enabled |
| AllowedHosts | Mail.example.com%20autodiscover.example.com | Allowed Virtual Hosts | Mail.example.com autodiscover.example.com | ESP Enabled |
| AllowedDirectories | %2Fews%2A | Allowed Virtual Directories | /ews* | ESP Enabled |
| **MAPI** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | MAPI | Service Name (Optional) | MAPI | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | None | Persistence Options | None | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 1800 | Idle Connection Timeout | 1800 | All |
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Fmapi%2Fhealthcheck.htm | URL | /mapi/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 0 | Client Authentication Mode | Delegate to Server | ESP Enabled |
| OutputAuthMode | 0 | Server Authentication Mode | None | ESP Enabled |
| AllowedHosts | Mail.example.com%20autodiscover.exampl | Allowed Virtual Hosts | Mail.example.com autodiscover.example | ESP Enabled |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| | e.com | | .com | |
| AllowedDirectories | %2Fmapi%2A | Allowed Virtual Directories | /mapi* | ESP Enabled |
| **OAB** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | OAB | Service Name (Optional) | OAB | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | None | Persistence Options | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 1800 | Idle Connection Timeout | 1800 | All |
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Foab%2Fhealthch | URL | /oab/healthcheck.htm | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| | eck.htm | | | |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 0 | Client Authentication Mode | Delegate to Server | ESP Enabled |
| OutputAuthMode | 0 | Server Authentication Mode | None | ESP Enabled |
| AllowedHosts | Mail.example.com%20autodiscover.example.com | Allowed Virtual Hosts | Mail.example.com autodiscover.example.com | ESP Enabled |
| AllowedDirectories | %2Foab%2A | Allowed Virtual Directories | /oab* | ESP Enabled |
| **OWA** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| Nickname | OWA | Service Name (Optional) | ECP | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | None | Persistence Options | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 1800 | Idle Connection Timeout | 1800 | All |
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Fowa%2Fhealthcheck.htm | URL | /owa/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| InputAuthMode | 2 | Client Authentication Mode | Form Based | ESP Enabled |
| OutputAuthMode | 2 | Server Authentication Mode | Form Based | ESP Enabled |
| AllowedHosts | Mail.example.com%20autodiscover.example.com | Allowed Virtual Hosts | Mail.example.com autodiscover.example.com | ESP Enabled |
| AllowedDirectories | %2Fowa%2A | Allowed Virtual Directories | /owa* | ESP Enabled |
| ExcludedDirectories | %2Fowa%2Fguid%40smtpdomain%2A | Pre-Authorization Excluded Directories | /owa/guid@smtpdomain* | ESP Enabled |
| SingleSignOnMessage | Please%20enter%20your%20Exchange%20credentials | SSO Greeting Message | Please enter your Exchange credentials | ESP Enabled |
| Logoff | %2Fowa%2Flogoff.owa | Logoff String | /owa/logoff.owa | ESP Enabled |
| **PowerShell** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | PowerShell | Service Name (Optional) | PowerShell | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | None | Persistence Options | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 1800 | Idle Connection Timeout | 1800 | All |
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Fpowershell%2Fhealthcheck.htm | URL | /powershell/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 0 | Client Authentication Mode | Delegate to Server | ESP Enabled |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| OutputAuthMode | 0 | Server Authentication Mode | None | ESP Enabled |
| AllowedHosts | Mail.example.com%20autodiscover.example.com | Allowed Virtual Hosts | Mail.example.com autodiscover.example.com | ESP Enabled |
| AllowedDirectories | %2Fpowershell%2A | Allowed Virtual Directories | /powershell* | ESP Enabled |
| **RPC** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | RPC | Service Name (Optional) | PowerShell | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | None | Persistence Options | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 1800 | Idle Connection Timeout | 1800 | All |
| CheckPort | 443 | Checked Port | 443 | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Frpc%2Fhealthcheck.htm | URL | /rpc/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 0 | Client Authentication Mode | Delegate to Server | ESP Enabled |
| OutputAuthMode | 0 | Server Authentication Mode | None | ESP Enabled |
| AllowedHosts | Mail.example.com%20autodiscover.example.com | Allowed Virtual Hosts | Mail.example.com autodiscover.example.com | ESP Enabled |
| AllowedDirectories | %2Frpc%2A | Allowed Virtual Directories | /rpc* | ESP Enabled |

# Exchange 2016 HTTPS Pass-through Virtual Service Recommended Settings (Optional)

| API Parameter | API Value | WUI Field Name | WUI Field Value |
|---|---|---|---|
| **HTTPS Pass-through** | | | |
| port | 443 | Port | 443 |
| prot | tcp | Protocol | tcp |
| VStype | http | Service Type | HTTP-HTTP/2-HTTPS |
| nickname | Exchange%202016%20HTTPS%20pass-through | Service Name (Optional) | Exchange 2016 HTTPS pass-through |
| ForceL7 | 1 | Force L4 | Disabled |
| Transparent | 0 | Transparency | Disabled |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled |
| Persist | none | Persistence Options | None |
| Schedule | lc | Scheduling Method | least connection |
| Idletime | 1800 | Idle Connection Timeout | 1800 |
| CheckType | https | Real Server Check Method | HTTPS Protocol |

| API Parameter | API Value | WUI Field Name | WUI Field Value |
|---|---|---|---|
| CheckPort | 443 | Checked Port | 443 |
| CheckUrl | %2Fowa%2Fhealthcheck.htm | URL | /owa/healthcheck.htm |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled |
| CheckUseGet | 1 | HTTP Method | GET |
| **HTTPS Pass-through Redirect** | | | |
| port | 80 | Port | 80 |
| prot | tcp | Protocol | tcp |
| VStype | http | Service Type | HTTP-HTTP/2-HTTPS |
| nickname | Exchange%202016%20HTTPS%20pass-through%20-%20HTTP%20Redirect | Service Name (Optional) | Exchange 2016 HTTPS pass-through - HTTP Redirect |
| ForceL7 | 1 | Force L4 | Disabled |
| Errorcode | 301 | Error Code | 301 Moved Permanently |
| ErrorUrl | https:%2F%2F%25h%25s | Redirect URL | https://%h%s |
| CheckType | none | Real Server Check Method | None |

# Exchange 2016 IMAP Virtual Service Recommended Settings (Optional)

| API Parameter | API Value | WUI Field Name | WUI Field Value |
|---|---|---|---|
| **IMAP** | | | |
| port | 143 | Port | 143 |
| prot | tcp | Protocol | tcp |
| VStype | gen | Service Type | Generic |
| nickname | Exchange%20IMAP | Service Name (Optional) | Exchange IMAP |
| ForceL7 | 1 | Force L4 | Disabled |
| Transparent | 0 | Transparency | Disabled |
| ServerInit | Imap4 | Server Initiating Protocols | IMAP4 |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled |
| Persist | None | Persistence Options | None |
| Schedule | rr | Scheduling Method | round robin |
| Idletime | 3600 | Idle Connection Timeout | 3600 |

| API Parameter | API Value | WUI Field Name | WUI Field Value |
|---|---|---|---|
| CheckType | Imap4 | Real Server Check Method | Mailbox (IMAP) Protocol |
| CheckPort | 110 | Checked Port | 110 |
| **IMAPS** | | | |
| port | 993 | Port | 993 |
| prot | tcp | Protocol | tcp |
| VStype | gen | Service Type | Generic |
| nickname | Exchange%20IMAPS | Service Name (Optional) | Exchange IMAPS |
| forceL7 | 1 | Force L4 | Disabled |
| Transparent | 0 | Transparency | Disabled |
| ServerInit | Imap4 | Server Initiating Protocols | IMAP4 |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled |
| Persist | None | Persistence Options | None |
| Schedule | rr | Scheduling Method | round robin |
| Idletime | 3600 | Idle Connection Timeout | 3600 |

| API Parameter | API Value | WUI Field Name | WUI Field Value |
|---|---|---|---|
| CheckType | tcp | Real Server Check Method | TCP Connection Only |
| CheckPort | 993 | Checked Port | 993 |
| **IMAPS Offloaded** | | | |
| port | 993 | Port | 993 |
| prot | tcp | Protocol | tcp |
| VStype | gen | Service Type | Generic |
| nickname | Exchange%20IMAPS%20Offload | Service Name (Optional) | Exchange IMAPS Offload |
| ForceL7 | 1 | Force L4 | Disabled |
| Transparent | 0 | Transparency | Disabled |
| ServerInit | Imap4 | Server Initiating Protocols | IMAP4 |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled |
| Persist | None | Persistence Options | None |
| Schedule | rr | Scheduling Method | round robin |

| API Parameter | API Value | WUI Field Name | WUI Field Value |
|---|---|---|---|
| Idletime | 3600 | Idle Connection Timeout | 3600 |
| SSLAcceleration | 1 | SSL Acceleration | Enabled |
| SSLReencrypt | 0 | Reencrypt | Disabled |
| TLSType | 1 | Supported Protocols | TLS1.0, TLS1.1, TLS1.2, and TLS1.3 (Enabled) |
| CipherSet | BestPractices | CipherSet | BestPractices |
| CheckType | Imap4 | Real Server Check Method | Mailbox (IMAP) Protocol |
| CheckPort | 143 | Checked Port | 143 |
| **IMAP with STARTTLS** | | | |
| port | 143 | Port | 143 |
| prot | tcp | Protocol | tcp |
| VStype | StartTLS | Service Type | STARTTLS protocols |
| nickname | Exchange%20IMAP%20STARTTLS | Service Name (Optional) | Exchange IMAP STARTTLS |
| ForceL7 | 1 | Force L4 | Disabled |

| API Parameter | API Value | WUI Field Name | WUI Field Value |
|---|---|---|---|
| Transparent | 0 | Transparency | Disabled |
| StartTLSMode | Imap | Server Initiating Protocols | IMAP4 |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled |
| Persist | None | Persistence Options | None |
| Schedule | rr | Scheduling Method | round robin |
| Idletime | 3600 | Idle Connection Timeout | 3600 |
| SSLAcceleration | 1 | SSL Acceleration | Enabled |
| TLSType | 1 | Supported Protocols | TLS1.0, TLS1.1, TLS1.2, and TLS1.3 (Enabled) |
| CipherSet | BestPractices | CipherSet | BestPractices |
| CheckType | Imap | Real Server Check Method | Mailbox (IMAP) Protocol |
| CheckPort | 143 | Checked Port | 143 |

# Exchange 2016 POP Virtual Service Recommended Settings (Optional)

| API Parameter | API Value | WUI Field Name | WUI Field Value |
|---|---|---|---|
| **POP** | | | |
| port | 110 | Port | 110 |
| prot | tcp | Protocol | tcp |
| VStype | gen | Service Type | Generic |
| nickname | Exchange%20POP | Service Name (Optional) | Exchange POP |
| ForceL7 | 1 | Force L4 | Disabled |
| Transparent | 0 | Transparency | Disabled |
| ServerInit | Pop3 | Server Initiating Protocols | POP3 |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled |
| Persist | None | Persistence Options | None |
| Schedule | rr | Scheduling Method | round robin |
| Idletime | 3600 | Idle Connection Timeout | 3600 |

| API Parameter | API Value | WUI Field Name | WUI Field Value |
|---|---|---|---|
| CheckType | Pop3 | Real Server Check Method | Mailbox (POP3) Protocol |
| CheckPort | 110 | Checked Port | 110 |
| **POPS** | | | |
| port | 995 | Port | 995 |
| prot | tcp | Protocol | tcp |
| VStype | gen | Service Type | Generic |
| nickname | Exchange%20POPS | Service Name (Optional) | Exchange POPS |
| ForceL7 | 1 | Force L4 | Disabled |
| Transparent | 0 | Transparency | Disabled |
| ServerInit | Pop3 | Server Initiating Protocols | POP3 |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled |
| Persist | None | Persistence Options | None |
| Schedule | rr | Scheduling Method | round robin |
| Idletime | 3600 | Idle Connection Timeout | 3600 |

| API Parameter | API Value | WUI Field Name | WUI Field Value |
|---|---|---|---|
| CheckType | tcp | Real Server Check Method | TCP Connection Only |
| CheckPort | 993 | Checked Port | 993 |
| **POPS Offloaded** | | | |
| port | 995 | Port | 995 |
| prot | tcp | Protocol | tcp |
| VStype | gen | Service Type | Generic |
| nickname | Exchange%20POPS%20Offload | Service Name (Optional) | Exchange POPS Offload |
| ForceL7 | 1 | Force L4 | Disabled |
| Transparent | 0 | Transparency | Disabled |
| ServerInit | Pop3 | Server Initiating Protocols | POP3 |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled |
| Persist | None | Persistence Options | None |
| Schedule | rr | Scheduling Method | round robin |

| API Parameter | API Value | WUI Field Name | WUI Field Value |
|---|---|---|---|
| Idletime | 3600 | Idle Connection Timeout | 3600 |
| SSLAcceleration | 1 | SSL Acceleration | Enabled |
| SSLReencrypt | 0 | Reencrypt | Disabled |
| TLSType | 1 | Supported Protocols | TLS1.0, TLS1.1, TLS1.2, and TLS1.3 (Enabled) |
| CipherSet | BestPractice | CipherSet | BestPractices |
| CheckType | Pop3 | Real Server Check Method | Mailbox (POP3) Protocol |
| CheckPort | 110 | Checked Port | 110 |
| **POP with STARTTLS** | | | |
| port | 110 | Port | 110 |
| prot | tcp | Protocol | tcp |
| VStype | StartTLS | Service Type | STARTTLS protocols |
| nickname | Exchange%20IMAP%20STARTTLS | Service Name (Optional) | Exchange IMAP STARTTLS |
| ForceL7 | 1 | Force L4 | Disabled |

| API Parameter | API Value | WUI Field Name | WUI Field Value |
|---|---|---|---|
| Transparent | 0 | Transparency | Disabled |
| StartTLSMode | Pop3 | Server Initiating Protocols | POP3 |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled |
| Persist | None | Persistence Options | None |
| Schedule | rr | Scheduling Method | round robin |
| Idletime | 3600 | Idle Connection Timeout | 3600 |
| SSLAcceleration | 1 | SSL Acceleration | Enabled |
| TLSType | 1 | Supported Protocols | TLS1.0, TLS1.1, TLS1.2, and TLS1.3 (Enabled) |
| CipherSet | BestPractices | CipherSet | BestPractices |
| CheckType | pop | Real Server Check Method | Mailbox (POP3) Protocol |
| CheckPort | 110 | Checked Port | 110 |

# Exchange 2016 SMTP Virtual Service Recommended Settings (Optional)

| API Parameter | API Value | WUI Field Name | WUI Field Value |
|---|---|---|---|
| **SMTP** | | | |
| port | 25 | Port | 25 |
| prot | tcp | Protocol | tcp |
| VStype | gen | Service Type | Generic |
| nickname | Exchange%20STMP | Service Name (Optional) | Exchange STMP |
| ForceL7 | 1 | Force L4 | Disabled |
| Transparent | 0 | Transparency | Disabled |
| ServerInit | smtp | Server Initiating Protocols | SMTP |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled |
| Persist | src | Persistence Options | Source IP Address |
| PersistTimeout | 3600 | Timeout | 1 Hour |
| Schedule | rr | Scheduling Method | round robin |

| API Parameter | API Value | WUI Field Name | WUI Field Value |
|---|---|---|---|
| Idletime | 120 | Idle Connection Timeout | 120 |
| CheckType | smtp | Real Server Check Method | Mailbox (SMTP) Protocol |
| CheckPort | 25 | Checked Port | 25 |
| **SMTPS** | | | |
| port | 587 | Port | 587 |
| prot | tcp | Protocol | tcp |
| VStype | gen | Service Type | Generic |
| nickname | Exchange%20SMTPS | Service Name (Optional) | Exchange STMPS |
| ForceL7 | 1 | Force L4 | Disabled |
| Transparent | 0 | Transparency | Disabled |
| ServerInit | smtp | Server Initiating Protocols | SMTP |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled |
| Persist | src | Persistence Options | Source IP Address |
| PersistTimeout | 3600 | Timeout | 1 Hour |

| API Parameter | API Value | WUI Field Name | WUI Field Value |
|---|---|---|---|
| Schedule | rr | Scheduling Method | round robin |
| Idletime | 120 | Idle Connection Timeout | 120 |
| CheckType | tcp | Real Server Check Method | tcp |
| CheckPort | 587 | Checked Port | 587 |
| **SMTPS Offloaded** | | | |
| port | 587 | Port | 587 |
| prot | tcp | Protocol | tcp |
| VStype | gen | Service Type | Generic |
| nickname | Exchange%20SMTPS%20Offload | Service Name (Optional) | Exchange STMPS Offload |
| ForceL7 | 1 | Force L4 | Disabled |
| Transparent | 0 | Transparency | Disabled |
| ServerInit | smtp | Server Initiating Protocols | SMTP |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled |

| API Parameter | API Value | WUI Field Name | WUI Field Value |
|---|---|---|---|
| Persist | src | Persistence Options | Source IP Address |
| PersistTimeout | 3600 | Timeout | 1 Hour |
| Schedule | rr | Scheduling Method | round robin |
| Idletime | 120 | Idle Connection Timeout | 120 |
| SSLAcceleration | 1 | SSL Acceleration | Enabled |
| SSLReencrypt | 0 | Reencrypt | Disabled |
| TLSType | 1 | Supported Protocols | TLS1.0, TLS1.1, TLS1.2, and TLS1.3 (Enabled) |
| CipherSet | BestPractices | CipherSet | BestPractices |
| CheckType | smtp | Real Server Check Method | Mail (SMTP) Protocol |
| CheckPort | 25 | Checked Port | 25 |
| **SMTP with STARTTLS** | | | |
| port | 25 | Port | 25 |
| prot | tcp | Protocol | tcp |
| VStype | StartTLS | Service Type | STARTTLS protocols |

| API Parameter | API Value | WUI Field Name | WUI Field Value |
|---|---|---|---|
| nickname | Exchange%20SMTP%20STARTTLS | Service Name (Optional) | Exchange STMP STARTTLS |
| ForceL7 | 1 | Force L4 | Disabled |
| Transparent | 0 | Transparency | Disabled |
| StartTLSMode | smtp | Server Initiating Protocols | SMTP |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled |
| Persist | src | Persistence Options | Source IP Address |
| PersistTimeout | 3600 | Timeout | 1 Hour |
| Schedule | rr | Scheduling Method | round robin |
| Idletime | 120 | Idle Connection Timeout | 120 |
| SSLAcceleration | 1 | SSL Acceleration | Enabled |
| TLSType | 1 | Supported Protocols | TLS1.0, TLS1.1, TLS1.2, and TLS1.3 (Enabled) |
| CipherSet | BestPractices | CipherSet | BestPractices |
| CheckType | smtp | Real Server Check Method | Mail (SMTP) Protocol |

| API Parameter | API Value | WUI Field Name | WUI Field Value |
|---|---|---|---|
| CheckPort | 25 | Checked Port | 25 |
| **SMTP with ESP** | | | |
| port | 25 | Port | 25 |
| prot | tcp | Protocol | tcp |
| VStype | gen | Service Type | Generic |
| nickname | Exchange%20STMP%20ESP | Service Name (Optional) | Exchange STMP ESP |
| ForceL7 | 1 | Force L4 | Disabled |
| Transparent | 0 | Transparency | Disabled |
| ServerInit | smtp | Server Initiating Protocols | SMTP |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled |
| Persist | src | Persistence Options | Source IP Address |
| PersistTimeout | 3600 | Timeout | 1 Hour |
| Schedule | rr | Scheduling Method | round robin |

| API Parameter | API Value | WUI Field Name | WUI Field Value |
|---|---|---|---|
| IdleTime | 120 | Idle Connection Timeout | 120 |
| EnableESP | 1 | Enable ESP | Enabled |
| ESPLog | 4 | ESP Logging | Connection (Enabled) |
| Smtpallow | “Example.com” | SMTP Allowed Domains | Example.com |
| CheckType | smtp | Real Server Check Method | Mail (SMTP) Protocol |
| CheckPort | 25 | Checked Port | 25 |

# Exchange 2016 Office Online Server Virtual Service Recommended Settings (Optional)

| API Parameter | API Value | WUI Field Name | WUI Field Value |
|---|---|---|---|
| **Office Online Server** | | | |
| port | 443 | Port | 443 |
| prot | tcp | Protocol | tcp |
| VStype | http | Service Type | HTTP-HTTP/2-HTTPS |
| nickname | Exchange%20Office%20Online | Service Name (Optional) | Exchange Office Online |

| API Parameter | API Value | WUI Field Name | WUI Field Value |
|---|---|---|---|
| ForceL7 | 1 | Force L4 | Disabled |
| Transparent | 0 | Transparency | Disabled |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled |
| Persist | Super-src | Persistence Options | Super HTTP and Souce IP |
| PersistTimeout | 1800 | Timeout | 30 Minutes |
| Schedule | lc | Scheduling Method | least connection |
| Idletime | 1800 | Idle Connection Timeout | 1800 |
| SSLAcceleration | 1 | SSL Acceleration | Enabled |
| SSLReencrypt | 1 | Reencrypt | Enabled |
| TLSType | 1 | Supported Protocols | TLS1.0, TLS1.1, TLS1.2, and TLS1.3 (Enabled) |
| CipherSet | BestPractices | CipherSet | BestPractices |
| CheckType | https | Real Server Check Method | HTTPS Protocol |
| CheckPort | 443 | Checked Port | 443 |

| API Parameter | API Value | WUI Field Name | WUI Field Value |
|---|---|---|---|
| CheckUrl | /hosting/discovery | URL | /hosting/discovery |
| CheckUse1.1 | 1 | Use HTTP/1.1 | Enabled |
| CheckUseGet | 1 | HTTP Method | GET |

# Exchange 2016 WAF Recommended Settings (Optional)

These tables in the following sections outline the recommended settings using the WAF application templates. You can use these settings with scripts and automation tools.

**Contents**


- Exchange 2016 HTTPS Offload with WAF Recommended Settings (Optional)
- Exchange 2016 HTTPS Offload with ESP and WAF Recommended Settings (Optional)
- Exchange 2016 HTTPS re-encrypted with WAF Recommended Settings (Optional)
- Exchange 2016 HTTPS re-encrypted with ESP and WAF Recommended Settings (Optional)
- Content Rules


## Exchange 2016 HTTPS Offload with WAF Recommended Settings (Optional)

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| **HTTP Redirect** | | | | |
| port | 80 | Port | 80 | All |
| prot | tcp | Protocol | tcp | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| nickname | Exchange%202016%20HTTPS%20Offloaded%20with%20WAF%20HTTP%20Redirect | Service Name | Exchange 2016 HTTPS Offloaded with WAF - HTTP Redirect | All |
| Errorcode | 302 | Error Code | 302 Found | All |
| ErrorUrl | https:%2F%2F%25h%25s | Redirect URL | https://%h%s | All |
| CheckType | http | Real Server Check Method | HTTP Protocol | All |
| **Main Virtual Service** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| VStype | http | Service Type | HTTP-HTTP/2-HTTPS | All |
| nickname | Exchange%202016%20HTTPS%20Offload%20with%20WAF | Service Name | Exchange 2016 HTTPS Offload with WAF | Create Unique Name |
| SSLAcceleration | 1 | SSL Acceleration | Enabled | All |
| SSLReencrypt | 0 | Reencrypt | Disabled | 0 for Offload<br>1 for Reencrypt |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| TLSType | 7 | Supported Protocols | TLS1.2 and TLS1.3 (Enabled) | All |
| CipherSet | BestPractices | Cipher Set | BestPractices | All |
| Tls13CipherSet | TLS_AES_256_GCM_SHA384%20TLS_CHACHA20_POLY1305_SHA256%20TLS_AES_128_GCM_SHA256 | TLS1.3 Ciphersets | TLS_AES_256_GCM_SHA384, TLS_CHACHA20_POLY1305_SHA256, and TLS_AES_128_GCM_SHA256 enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 1800 | Idle Connection Timeout | 1800 | All |
| **SubVSs** | | | | |
| **ActiveSync** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | ActiveSync | SubVS Name | ActiveSync | All |
| SubnetOriginating | 1 | Subnet Originating | Enabled | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| | | Requests | | |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 80 | Checked Port | 80 | All |
| CheckType | http | Real Server Check Method | HTTP Protocol | All |
| CheckUrl | %2Fmicrosoft-server-activesync%2Fhealthcheck.htm | URL | /microsoft-server-activesync/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 0 | Enable ESP | Disabled | All |
| **API** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| Nickname | API | SubVS Name | API | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 80 | Checked Port | 80 | All |
| CheckType | http | Real Server Check Method | HTTP Protocol | All |
| CheckUrl | %2Fapi%2Fhealthcheck.htm | URL | /api/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 0 | Enable ESP | Disabled | All |
| **Autodiscover** | | | | |
| port | 443 | Port | 443 | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| prot | tcp | Protocol | tcp | All |
| Nickname | Autodiscover | SubVS Name | Autodiscover | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 80 | Checked Port | 80 | All |
| CheckType | http | Real Server Check Method | HTTP Protocol | All |
| CheckUrl | %2Fautodiscover%2Fhealthcheck.htm | URL | /autodiscover/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 0 | Enable ESP | Disabled | All |
| **ECP** | | | | |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | ECP | SubVS Name | ECP | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| Interceptmode | 2 | OWASP Core Rule Set WAF | Enabled | WAF Enabled |
| CheckPort | 80 | Checked Port | 80 | All |
| CheckType | http | Real Server Check Method | HTTP Protocol | All |
| CheckUrl | %2Fecp%2Fhealthcheck.htm | URL | /ecp/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| EspEnabled | 0 | Enable ESP | Disabled | All |
| **EWS** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | EWS | SubVS Name | EWS | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 80 | Checked Port | 80 | All |
| CheckType | http | Real Server Check Method | HTTP Protocol | All |
| CheckUrl | %2Fews%2Fhealthcheck.htm | URL | /ews/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 0 | Enable ESP | Disabled | All |
| **MAPI** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | MAPI | SubVS Name | MAPI | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 80 | Checked Port | 80 | All |
| CheckType | http | Real Server Check Method | HTTP Protocol | All |
| CheckUrl | %2Fmapi%2Fhealthcheck.htm | URL | /mapi/healthcheck.htm | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 0 | Enable ESP | Disabled | All |
| **OAB** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | OAB | SubVS Name | OAB | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 80 | Checked Port | 80 | All |
| CheckType | http | Real Server Check Method | HTTP Protocol | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| CheckUrl | %2Foab%2Fhealthcheck.htm | URL | /oab/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 0 | Enable ESP | Disabled | All |
| **OWA** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | OWA | SubVS Name | OWA | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| Interceptmode | 2 | OWASP Core Rule Set WAF | Enabled | |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| CheckPort | 80 | Checked Port | 80 | All |
| CheckType | http | Real Server Check Method | HTTP Protocol | All |
| CheckUrl | %2Fowa%2Fhealthcheck.htm | URL | /owa/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 0 | Enable ESP | Disabled | All |
| **PowerShell** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | PowerShell | SubVS Name | PowerShell | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 80 | Checked Port | 80 | All |
| CheckType | http | Real Server Check Method | HTTP Protocol | All |
| CheckUrl | %2Fpowershell%2Fhealthcheck.htm | URL | /powershell/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 0 | Enable ESP | Disabled | All |
| **RPC** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | RPC | SubVS Name | RPC | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 80 | Checked Port | 80 | All |
| CheckType | http | Real Server Check Method | HTTP Protocol | All |
| CheckUrl | %2Frpc%2Fhealthcheck.htm | URL | /rpc/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 0 | Enable ESP | Disabled | All |

# Exchange 2016 HTTPS Offload with ESP and WAF Recommended Settings (Optional)

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| **HTTP Redirect** | | | | |
| port | 80 | Port | 80 | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| prot | tcp | Protocol | tcp | All |
| nickname | Exchange%202016%20HTTPS%20Offloaded%20with%20ESP%20and%20WAF%20HTTP%20Redirect | Service Name | Exchange 2016 HTTPSOffloaded with ESP and WAF - HTTP Redirect | All |
| Errorcode | 302 | Error Code | 302 Found | All |
| ErrorUrl | https:%2F%2F%25h%25s | Redirect URL | https://%h%s | All |
| CheckType | http | Real Server Check Method | HTTP Protocol | All |
| **Main Virtual Service** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| VStype | http | Service Type | HTTP-HTTP/ 2-HTTPS | All |
| nickname | Exchange%202016%20HTTPS%20Offload%20with%20ESP%20and%20WAF | Service Name | Exchange 2016 HTTPS Offload with ESP and WAF | Create Unique Name |
| Transparent | 1 | Transparency | Enabled | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| SSLAcceleration | 1 | SSL Acceleration | Enabled | All |
| SSLReencrypt | 0 | Reencrypt | Disabled | 0 for Offload<br>1 for Reencrypt |
| TLSType | 7 | Supported Protocols | TLS1.2 and TLS1.3 (Enabled) | All |
| CipherSet | BestPractices | Cipher Set | BestPractices | All |
| Tls13CipherSet | TLS_AES_256_GCM_SHA384%20TLS_CHACHA20_POLY1305_SHA256%20TLS_AES_128_GCM_SHA256 | TLS1.3 Ciphersets | TLS_AES_256_GCM_SHA384, TLS_CHACHA20_POLY1305_SHA256, and TLS_AES_128_GCM_SHA256 enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 1800 | Idle Connection Timeout | 1800 | All |
| **SubVSs** | | | | |
| **Authentication Proxy** | | | | |
| port | 443 | Port | 443 | ESP Enabled |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| prot | tcp | Protocol | tcp | ESP Enabled |
| Nickname | Authentication%20Proxy | SubVS Name | Authentication Proxy | ESP Enabled |
| Errorcode | 503 | Error Code | 503 Service Unavailable | ESP Enabled |
| ErrorUrl | Endpoint%20not%20available | Error Message | Endpoint not available | ESP Enabled |
| CheckType | http | Real Server Check Method | HTTP Protocol | ESP Enabled |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security, and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 2 | Client Authentication Mode | Form Based | ESP Enabled |
| OutputAuthMode | 2 | Server Authentication Mode | Form Based | ESP Enabled |
| AllowedDirectories | %2F%2A | Allowed Virtual Directories | /* | ESP Enabled |
| SingleSignOnMessage | Please%20enter%20your%20Exchange%20credentials | SSO Greeting Message | Please enter your Exchange credentials | ESP Enabled |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| **ActiveSync** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | ActiveSync | SubVS Name | ActiveSync | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 80 | Checked Port | 80 | All |
| CheckType | http | Real Server Check Method | HTTP Protocol | All |
| CheckUrl | %2Fmicrosoft-server-activesync%2Fhealthcheck.htm | URL | /microsoft-server-activesync/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 1 | Client Authentication Mode | Basic Authentication | ESP Enabled |
| AllowedDirectories | %2Fmicrosoft-server-activesync%2A | Allowed Virtual Directories | /microsoft-server-activesync* | ESP Enabled |
| **API** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | API | SubVS Name | API | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 80 | Checked Port | 80 | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| CheckType | http | Real Server Check Method | HTTP Protocol | All |
| CheckUrl | %2Fapi%2Fhealthcheck.htm | URL | /api/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 0 | Enable ESP | Disabled | All |
| **Autodiscover** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | Autodiscover | SubVS Name | Autodiscover | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| CheckPort | 80 | Checked Port | 80 | All |
| CheckType | http | Real Server Check Method | HTTP Protocol | All |
| CheckUrl | %2Fautodiscover%2Fhealthcheck.htm | URL | /autodiscover/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 0 | Client Authentication Mode | Delegate to Server | ESP Enabled |
| AllowedDirectories | %2Fautodiscover%2A | Allowed Virtual Directories | /autodiscover* | ESP Enabled |
| **ECP** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| Nickname | ECP | SubVS Name | ECP | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| Interceptmode | 2 | OWASP Core Rule Set WAF | Enabled | WAF Enabled |
| CheckPort | 80 | Checked Port | 80 | All |
| CheckType | http | Real Server Check Method | HTTP Protocol | All |
| CheckUrl | %2Fecp%2Fhealthcheck.htm | URL | /ecp/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, | ESP Enabled |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| | | | Security and Connection (Enabled) | |
| InputAuthMode | 2 | Client Authentication Mode | Form Based | ESP Enabled |
| AllowedDirectories | %2Fecp%2A | Allowed Virtual Directories | /ecp* | ESP Enabled |
| SingleSignOnMessage | Please%20enter%20your%20Exchange%20credentials | SSO Greeting Message | Please enter your Exchange credentials | ESP Enabled |
| **EWS** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | EWS | SubVS Name | EWS | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| CheckPort | 80 | Checked Port | 80 | All |
| CheckType | http | Real Server Check Method | HTTP Protocol | All |
| CheckUrl | %2Fews%2Fhealthcheck.htm | URL | /ews/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 0 | Client Authentication Mode | Delegate to Server | ESP Enabled |
| AllowedDirectories | %2Fews%2A | Allowed Virtual Directories | /ews* | ESP Enabled |
| **MAPI** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| Nickname | MAPI | SubVS Name | MAPI | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 80 | Checked Port | 80 | All |
| CheckType | http | Real Server Check Method | HTTP Protocol | All |
| CheckUrl | %2Fmapi%2Fhealthcheck.htm | URL | /mapi/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| InputAuthMode | 0 | Client Authentication Mode | Delegate to Server | ESP Enabled |
| AllowedDirectories | %2Fmapi%2A | Allowed Virtual Directories | /mapi* | ESP Enabled |
| **OAB** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | OAB | SubVS Name | OAB | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 80 | Checked Port | 80 | All |
| CheckType | http | Real Server Check Method | HTTP Protocol | All |
| CheckUrl | %2Foab%2Fhealthch | URL | /oab/healthcheck.htm | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| | eck.htm | | | |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 0 | Client Authentication Mode | Delegate to Server | ESP Enabled |
| AllowedDirectories | %2Foab%2A | Allowed Virtual Directories | /oab* | ESP Enabled |
| **OWA** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | OWA | SubVS Name | OWA | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| Interceptmode | 2 | OWASP Core Rule Set WAF | Enabled | WAF Enabled |
| CheckPort | 80 | Checked Port | 80 | All |
| CheckType | http | Real Server Check Method | HTTP Protocol | All |
| CheckUrl | %2Fowa%2Fhealthcheck.htm | URL | /owa/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 2 | Client Authentication Mode | Form Based | ESP Enabled |
| AllowedDirectories | %2Fowa%2A | Allowed Virtual Directories | /owa* | ESP Enabled |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| ExcludedDirectories | %2Fowa%2Fguid%40smtpdomain%2A | Pre-Authorization Excluded Directories | /owa/guid@smtpdomain* | ESP Enabled |
| SingleSignOnMessage | Please%20enter%20your%20Exchange%20credentials | SSO Greeting Message | Please enter your Exchange credentials | ESP Enabled |
| Logoff | %2Fowa%2Flogoff.owa | Logoff String | /owa/logoff.owa | ESP Enabled |
| **PowerShell** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | PowerShell | SubVS Name | PowerShell | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 80 | Checked Port | 80 | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| CheckType | http | Real Server Check Method | HTTP Protocol | All |
| CheckUrl | %2Fpowershell%2Fhealthcheck.htm | URL | /powershell/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 0 | Client Authentication Mode | Delegate to Server | ESP Enabled |
| AllowedDirectories | %2Fpowershell%2A | Allowed Virtual Directories | /powershell* | ESP Enabled |
| **RPC** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | RPC | SubVS Name | RPC | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 80 | Checked Port | 80 | All |
| CheckType | http | Real Server Check Method | HTTP Protocol | All |
| CheckUrl | %2Frpc%2Fhealthcheck.htm | URL | /rpc/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 0 | Client Authentication Mode | Delegate to Server | ESP Enabled |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| AllowedDirectories | %2Frpc%2A | Allowed Virtual Directories | /rpc* | ESP Enabled |

# Exchange 2016 HTTPS re-encrypted with WAF Recommended Settings (Optional)

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| **HTTP Redirect** | | | | |
| port | 80 | Port | 80 | All |
| prot | tcp | Protocol | tcp | All |
| nickname | Exchange%202016%20HTTPS%20re-encrypted%20with%20WAF%20HTTP%20Redirect | Service Name | Exchange 2016 HTTPS re-encrypted with WAF - HTTP Redirect | All |
| Errorcode | 302 | Error Code | 302 Found | All |
| ErrorUrl | https:%2F%2F%25h%25s | Redirect URL | https://%h%s | All |
| CheckType | http | Real Server Check Method | HTTP Protocol | All |
| **Main Virtual Service** | | | | |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| VStype | http | Service Type | HTTP-HTTP/<br>2-HTTPS | All |
| nickname | Exchange%202016%<br>20HTTPS%20re-<br>encrypted%20with%2<br>0WAF | Service Name | Exchange 2016<br>HTTPS re-encrypted<br>with WAF | Create Unique Name |
| Transparent | 0 | Transparency | Disabled | All |
| SSLAcceleration | 1 | SSL Acceleration | Enabled | All |
| SSLReencrypt | 1 | Reencrypt | Enabled | 0 for Offload<br>1 for Reencrypt |
| TLSType | 7 | Supported Protocols | TLS1.2 and TLS1.3<br>(Enabled) | All |
| CipherSet | BestPractices | Cipher Set | BestPractices | All |
| Tls13CipherSet | TLS_AES_256_GCM<br>_SHA384%20TLS_C<br>HACHA20_POLY130<br>5_SHA256%20TLS_<br>AES_128_GCM_SH<br>A256 | TLS1.3 Ciphersets | TLS_AES_256_GCM<br>_SHA384,<br>TLS_CHACHA20_P<br>OLY1305_SHA 256,<br>and<br>TLS_AES_128_GCM<br>_SHA256 enabled | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 1800 | Idle Connection Timeout | 1800 | All |
| **SubVSs** | | | | |
| **ActiveSync** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | ActiveSync | SubVS Name | ActiveSync | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 443 | Checked Port | 443 | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Fmicrosoft-server-activesync%2Fhealthcheck.htm | URL | /microsoft-server-activesync/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 0 | Enable ESP | Disabled | All |
| **API** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | API | SubVS Name | API | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Fapi%2Fhealthcheck.htm | URL | /api/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 0 | Enable ESP | Disabled | All |
| **Autodiscover** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | Autodiscover | SubVS Name | Autodiscover | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Fautodiscover%2Fhealthcheck.htm | URL | /autodiscover/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 0 | Enable ESP | Disabled | All |
| **ECP** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | ECP | SubVS Name | ECP | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| Interceptmode | 2 | OWASP Core Rule Set WAF | Enabled | |
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Fecp%2Fhealthcheck.htm | URL | /ecp/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 0 | Enable ESP | Disabled | All |
| **EWS** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | EWS | SubVS Name | EWS | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Fews%2Fhealthcheck.htm | URL | /ews/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 0 | Enable ESP | Disabled | All |
| **MAPI** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| Nickname | MAPI | SubVS Name | MAPI | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Fmapi%2Fhealthcheck.htm | URL | /mapi/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 0 | Enable ESP | Disabled | All |
| **OAB** | | | | |
| port | 443 | Port | 443 | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| prot | tcp | Protocol | tcp | All |
| Nickname | OAB | SubVS Name | OAB | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Foab%2Fhealthcheck.htm | URL | /oab/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 0 | Enable ESP | Disabled | All |
| **OWA** | | | | |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | OWA | SubVS Name | OWA | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| Interceptmode | 2 | OWASP Core Rule Set WAF | Enabled | WAF Enabled |
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Fowa%2Fhealthcheck.htm | URL | /owa/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| EspEnabled | 0 | Enable ESP | Disabled | All |
| **PowerShell** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | PowerShell | SubVS Name | PowerShell | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Fpowershell%2Fhealthcheck.htm | URL | /powershell/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 0 | Enable ESP | Disabled | All |
| **RPC** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | RPC | SubVS Name | RPC | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Frpc%2Fhealthcheck.htm | URL | /rpc/healthcheck.htm | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 0 | Enable ESP | Disabled | All |

# Exchange 2016 HTTPS re-encrypted with ESP and WAF Recommended Settings (Optional)

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| **HTTP Redirect** | | | | |
| port | 80 | Port | 80 | All |
| prot | tcp | Protocol | tcp | All |
| nickname | Exchange%202016%20HTTPS%20re-encrpted%20with%20ESP%20and%20WAF%20HTTP%20Redirect | Service Name | Exchange 2016 HTTPS<br>re-encrypted with ESP<br>and WAF - HTTP Redirect | All |
| Errorcode | 302 | Error Code | 302 Found | All |
| ErrorUrl | https:%2F%2F%25h%25s | Redirect URL | https://%h%s | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| CheckType | http | Real Server Check Method | HTTP Protocol | All |
| **Main Virtual Service** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| VStype | http | Service Type | HTTP-HTTP/ 2-HTTPS | All |
| nickname | Exchange%202016%20HTTPS%20re-encrypted%20with%20ESP%20and%20WAF | Service Name | Exchange 2016 HTTPS re-encrypted with ESP and WAF | Create Unique Name |
| Transparent | 0 | Transparency | Disabled | All |
| SSLAcceleration | 1 | SSL Acceleration | Enabled | All |
| SSLReencrypt | 1 | Reencrypt | Enabled | 0 for Offload<br>1 for Reencrypt |
| TLSType | 7 | Supported Protocols | TLS1.2 and TLS1.3 (Enabled) | All |
| CipherSet | BestPractices | Cipher Set | BestPractices | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| Tls13CipherSet | TLS_AES_256_GCM_SHA384%20TLS_CHACHA20_POLY1305_SHA256%20TLS_AES_128_GCM_SHA256 | TLS1.3 Ciphersets | TLS_AES_256_GCM_SHA384, TLS_CHACHA20_POLY1305_SHA256, and TLS_AES_128_GCM_SHA256 enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 1800 | Idle Connection Timeout | 1800 | All |
| **SubVSs** | | | | |
| **Authentication Proxy** | | | | |
| port | 443 | Port | 443 | ESP Enabled |
| prot | tcp | Protocol | tcp | ESP Enabled |
| Nickname | Authentication%20Proxy | SubVS Name | Authentication Proxy | ESP Enabled |
| Errorcode | 503 | Error Code | 503 Service Unavailable | ESP Enabled |
| ErrorUrl | Endpoint%20not%20available | Error Message | Endpoint not available | ESP Enabled |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| CheckType | https | Real Server Check Method | HTTPS Protocol | ESP Enabled |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security, and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 2 | Client Authentication Mode | Form Based | ESP Enabled |
| AllowedDirectories | %2F%2A | Allowed Virtual Directories | /* | ESP Enabled |
| SingleSignOnMessage | Please%20enter%20your%20Exchange%20credentials | SSO Greeting Message | Please enter your Exchange credentials | ESP Enabled |
| **ActiveSync** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | ActiveSync | SubVS Name | ActiveSync | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Fmicrosoft-server-activesync%2Fhealthcheck.htm | URL | /microsoft-server-activesync/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 1 | Client Authentication Mode | Basic Authentication | ESP Enabled |
| AllowedDirectories | %2Fmicrosoft-server-activesync%2A | Allowed Virtual Directories | /microsoft-server-activesync* | ESP Enabled |
| **API** | | | | |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | API | SubVS Name | API | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Fapi%2Fhealthcheck.htm | URL | /api/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 0 | Enable ESP | Disabled | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| **Autodiscover** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | Autodiscover | SubVS Name | Autodiscover | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Fautodiscover%2Fhealthcheck.htm | URL | /autodiscover/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 0 | Client Authentication Mode | Delegate to Server | ESP Enabled |
| AllowedDirectories | %2Fautodiscover%2A | Allowed Virtual Directories | /autodiscover* | ESP Enabled |
| **ECP** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | ECP | SubVS Name | ECP | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| Interceptmode | 2 | OWASP Core Rule Set WAF | Enabled | WAF enabled |
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Fecp%2Fhealthcheck.htm | URL | /ecp/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 2 | Client Authentication Mode | Form Based | ESP Enabled |
| AllowedDirectories | %2Fecp%2A | Allowed Virtual Directories | /ecp* | ESP Enabled |
| SingleSignOnMessage | Please%20enter%20your%20Exchange%20credentials | SSO Greeting Message | Please enter your Exchange credentials | ESP Enabled |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| **EWS** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | EWS | SubVS Name | EWS | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Fews%2Fhealthcheck.htm | URL | /ews/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 0 | Client Authentication Mode | Delegate to Server | ESP Enabled |
| AllowedDirectories | %2Fews%2A | Allowed Virtual Directories | /ews* | ESP Enabled |
| **MAPI** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | MAPI | SubVS Name | MAPI | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Fmapi%2Fhealthcheck.htm | URL | /mapi/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 0 | Client Authentication Mode | Delegate to Server | ESP Enabled |
| AllowedDirectories | %2Fmapi%2A | Allowed Virtual Directories | /mapi* | ESP Enabled |
| **OAB** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| Nickname | OAB | SubVS Name | OAB | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Foab%2Fhealthcheck.htm | URL | /oab/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| InputAuthMode | 0 | Client Authentication Mode | Delegate to Server | ESP Enabled |
| AllowedDirectories | %2Foab%2A | Allowed Virtual Directories | /oab* | ESP Enabled |
| **OWA** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | OWA | SubVS Name | OWA | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| Interceptmode | 2 | OWASP Core Rule Set WAF | Enabled | WAF Enabled |
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| CheckUrl | %2Fowa%2Fhealthcheck.htm | URL | /owa/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 2 | Client Authentication Mode | Form Based | ESP Enabled |
| AllowedDirectories | %2Fowa%2A | Allowed Virtual Directories | /owa* | ESP Enabled |
| ExcludedDirectories | %2Fowa%2Fguid%40smtpdomain%2A | Pre-Authorization Excluded Directories | /owa/guid@smtpdomain* | ESP Enabled |
| SingleSignOnMessage | Please%20enter%20your%20Exchange%20credentials | SSO Greeting Message | Please enter your Exchange credentials | ESP Enabled |
| Logoff | %2Fowa%2Flogoff.owa | Logoff String | /owa/logoff.owa | ESP Enabled |
| **PowerShell** | | | | |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | PowerShell | SubVS Name | PowerShell | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 443 | Checked Port | 443 | All |
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Fpowershell%2Fhealthcheck.htm | URL | /powershell/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 0 | Client Authentication Mode | Delegate to Server | ESP Enabled |
| AllowedDirectories | %2Fpowershell%2A | Allowed Virtual Directories | /powershell* | ESP Enabled |
| **RPC** | | | | |
| port | 443 | Port | 443 | All |
| prot | tcp | Protocol | tcp | All |
| Nickname | RPC | SubVS Name | RPC | All |
| SubnetOriginating | 1 | Subnet Originating Requests | Enabled | All |
| Persist | none | Persistence Mode | None | All |
| Schedule | lc | Scheduling Method | least connection | All |
| Idletime | 0 | Idle Connection Timeout | Empty | All |
| CheckPort | 443 | Checked Port | 443 | All |

| API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|
| CheckType | https | Real Server Check Method | HTTPS Protocol | All |
| CheckUrl | %2Frpc%2Fhealthcheck.htm | URL | /rpc/healthcheck.htm | All |
| CheckUse1.1 | 0 | Use HTTP/1.1 | Disabled | All |
| CheckUseGet | 1 | HTTP Method | GET | All |
| EspEnabled | 1 | Enable ESP | Enabled | ESP Enabled |
| ESPLogs | 7 | ESP Logging | User Access, Security and Connection (Enabled) | ESP Enabled |
| InputAuthMode | 0 | Client Authentication Mode | Delegate to Server | ESP Enabled |
| AllowedDirectories | %2Frpc%2A | Allowed Virtual Directories | /rpc* | ESP Enabled |

# Content Rules

| SubVSs | API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|---|
| **Authentication Proxy** | | | | | |
| | name | Authentication_Proxy | Rule Name | Authentication Proxy | ESP Enabled |
| | matchtype | Regex | Match Type | RegEx | ESP Enabled |

| SubVSs | API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|---|
| | pattern | %2F%5E%5C%2Flm_auth_proxy%2A%24%2F | Match String | /^\/lm_auth_proxy*$/ | ESP Enabled |
| | Nocase | 1 | Ignore Case | Enabled | ESP Enabled |
| **ActiveSync** | | | | | |
| | name | ActiveSync | Rule Name | ActiveSync | ESP Enabled |
| | matchtype | Regex | Match Type | RegEx | ESP Enabled |
| | pattern | %2F%5E%5C%2Fmicrosoft-server-activesync.%2A%2F | Match String | /^\/microsoft-server-activesync.*/ | ESP Enabled |
| | Nocase | 1 | Ignore Case | Enabled | ESP Enabled |
| **API** | | | | | |
| API (Content rule) | | | | | |
| | name | API | Rule Name | API | All |
| | matchtype | Regex | Match Type | RegEx | All |
| | pattern | %2F%5E%5C%2Fapi.%2A%2F | Match String | /^\/api.*/ | All |
| | Nocase | 1 | Ignore Case | Enabled | All |
| Autodiscover wssecurity (Content rule) | | | | | |
| | name | Autodiscover_wssecurity | Rule Name | Autodiscoverwssecurity | All |
| | matchtype | Regex | Match Type | RegEx | All |
| | pattern | %2F%5E%5C%2Fautodiscover%5C%2Fautodiscover%5C.svc%2Fwssecurity%24%2F | Match String | /^\/autodiscover\/autodiscover\.svc/wssecurity$/ | All |
| | Nocase | 1 | Ignore Case | Enabled | All |

| SubVSs | API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|---|
| Autodiscover svc (Content rule) | | | | | |
| | name | Autodiscover_svc | Rule Name | Autodiscover svc | All |
| | matchtype | Regex | Match Type | RegEx | All |
| | pattern | %2F%5E%5C%2Fautodiscover%5C%2Fautodiscover%5C.svc%24%2F | Match String | ^\/autodiscover\/autodiscover\.svc$/ | All |
| | Nocase | 1 | Ignore Case | Enabled | All |
| Autodiscover json (Content rule) | | | | | |
| | name | Autodiscover_json | Rule Name | Autodiscover json | All |
| | matchtype | Regex | Match Type | RegEx | All |
| | pattern | %2F%5E%5C%2Fautodiscover%5C%2Fautodiscover%5C.json%24%2F | Match String | ^\/autodiscover\/autodiscover\.json$/ | All |
| | Nocase | 1 | Ignore Case | Enabled | All |
| EWS wssecurity (Content rule) | | | | | |
| | name | EWS_wssecurity | Rule Name | EWS wssecurity | All |
| | matchtype | Regex | Match Type | RegEx | All |
| | pattern | %2F%5E%5C%2Fews%5C%2Fexchnage%5Casmx%5C%2Fwssecurity%24%2F | Match String | /^\/ews\/exchange\.asmx\/wssecurity$/ | All |
| | Nocase | 1 | Ignore Case | Enabled | All |
| EWS exchange (Content rule) | | | | | |
| | name | EWS_exchange | Rule Name | EWS exchange | All |
| | matchtype | Regex | Match Type | RegEx | All |

| SubVSs | API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|---|
| | pattern | %2F%5E%5C%2Fews%5C%2Fexchnage%5C.asmx%24%2F | Match String | /^\/ews\/exchange\.asmx$/ | All |
| | Nocase | 1 | Ignore Case | Enabled | All |
| EWS mrsproxy svc (Content rule) | | | | | |
| | name | EWS_mrsproxy_svc | Rule Name | EWS mrsproxy svc | All |
| | matchtype | Regex | Match Type | RegEx | All |
| | pattern | %2F%5E%5C%2Fews%5C%2Fexchnage%5C.svc%24%2F | Match String | /^\/ews\/mrsproxy\.svc$/ | All |
| | Nocase | 1 | Ignore Case | Enabled | All |
| **Autodiscover** | | | | | |
| | name | Autodiscover | Rule Name | Autodiscover | ESP Enabled |
| | matchtype | Regex | Match Type | RegEx | ESP Enabled |
| | pattern | %2F%5E%5C%2Fautodiscover.%2A%2F | Match String | /^\/autodiscover.*/ | ESP Enabled |
| | Nocase | 1 | Ignore Case | Enabled | ESP Enabled |
| **ECP** | | | | | |
| | name | ECP | Rule Name | ECP | ESP Enabled |
| | matchtype | Regex | Match Type | RegEx | ESP Enabled |
| | pattern | %2F%5E%5C%2Fecp.%2A%2F | Match String | /^\/ecp.*/ | ESP Enabled |
| | Nocase | 1 | Ignore Case | Enabled | ESP Enabled |
| **EWS** | | | | | |
| | name | EWS | Rule Name | EWS | ESP Enabled |
| | matchtype | Regex | Match Type | RegEx | ESP Enabled |
| | pattern | %2F%5E%5C%2Fews.%2A%2F | Match String | /^\/ews.*/ | ESP Enabled |

| SubVSs | API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|---|
| | Nocase | 1 | Ignore Case | Enabled | ESP Enabled |
| **MAPI** | | | | | |
| | name | MAPI | Rule Name | MAPI | ESP Enabled |
| | matchtype | Regex | Match Type | RegEx | ESP Enabled |
| | pattern | %2F%5E%5C%2Fmapi.%2A%2F | Match String | /^\/mapi.*/ | ESP Enabled |
| | Nocase | 1 | Ignore Case | Enabled | ESP Enabled |
| **OAB** | | | | | |
| | name | OAB | Rule Name | OAB | ESP Enabled |
| | matchtype | Regex | Match Type | RegEx | ESP Enabled |
| | pattern | %2F%5E%5C%2Foab.%2A%2F | Match String | /^\/oab.*/ | ESP Enabled |
| | Nocase | 1 | Ignore Case | Enabled | ESP Enabled |
| **OWA** | | | | | |
| OWA (Content Rule) | | | | | |
| | name | OWA | Rule Name | OWA | ESP Enabled |
| | matchtype | Regex | Match Type | RegEx | ESP Enabled |
| | pattern | %2F%5E%5C%2Fowa.%2A%2F | Match String | /^\/owa.*/ | ESP Enabled |
| | Nocase | 1 | Ignore Case | Enabled | ESP Enabled |
| Root (Content Rule) | | | | | |
| | name | Root | Rule Name | Root | ESP Enabled |
| | matchtype | Regex | Match Type | RegEx | ESP Enabled |
| | pattern | %2F%5E%5C%2F%24%2F | Match String | /^\/$/ | ESP Enabled |
| | Nocase | 1 | Ignore Case | Enabled | ESP Enabled |
| **PowerShell** | | | | | |
| | name | PowerShell | Rule Name | PowerShell | ESP Enabled |
| | matchtype | Regex | Match Type | RegEx | ESP Enabled |

| SubVSs | API Parameter | API Value | WUI Field Name | WUI Field Value | Use with Template |
|---|---|---|---|---|---|
| | pattern | %2F%5E%5C%2Fpowershell.%2A%2F | Match String | /^\/powershell.*/ | ESP Enabled |
| | Nocase | 1 | Ignore Case | Enabled | ESP Enabled |
| **RPC** | | | | | |
| | name | RPC | Rule Name | RPC | ESP Enabled |
| | matchtype | Regex | Match Type | RegEx | ESP Enabled |
| | pattern | %2F%5E%5C%2Frpc.%2A%2F | Match String | /^\/rpc.*/ | ESP Enabled |
| | Nocase | 1 | Ignore Case | Enabled | ESP Enabled |

**Note:** The **Authentication Proxy** SubVS is only applicable for the **Exchange HTTPS Offload with ESP and WAF** and **Exchange HTTPS re-encrypted with ESP and WAF** Virtual Services.

# 6

# References

Other useful documents are as follows:

Web User Interface (WUI) Configuration Guide

Virtual Services and Templates Feature Description

Edge Security Pack (ESP) Feature Description

Microsoft Exchange 2010 Deployment Guide

Microsoft Exchange 2013 Deployment Guide

Exchange Team Blog post on Load Balancing in Exchange 2016