Progress®



Configure Database Multi-tenancy with OpenEdge Management

OpenEdge®

Table of Contents

Preface....9

Overview of Multi-tenancy in OpenEdge Management....11

About working with multi-tenancy in the Database Administration Console....12
Common terminology....14

About Configuring Database Connections....17

About database connection types....17
Review the remote configuration requirements....18
Unglue OpenEdge Management from OpenEdge....18
About establishing a database connection....19
Set up the connection....19
About providing database connection user credentials....22
User credentials considerations....22
Database connection credentials for a regular tenant or super-tenant....23
Security administrators....23

About Managing Multi-tenant Databases....25

Enable a database for multi-tenancy....25
Multi-tenant database management....26
View database connection details....26
Review database features....27
Review the database security summary....27
Review sequences details....28
Load a data definition file....29
Load database contents....29
Dump database contents....35
Tune multi-tenant database performance....40
About viewing multi-tenant database areas, domains, schemas, tenants, and groups....41
View areas....41
View domains....42
View schema....42
View tenants....42
View tenant users....42
View tenant domains....42
View and filter tenant partitions....43

About Working with Tenants....45

Create a new tenant for a multi-tenant database....46
Allocate tenant partitions....46
Specify an alternate buffer pool....46
Use a tenant configuration program....47
Create a new tenant or tenant program....47
Edit a tenant....49
Add a tenant domain....50
Add a user to a tenant....51
Generate a tenant program from an existing tenant....53
Delete a tenant....53
Delete a tenant domain....54
Delete a tenant user....55
Enable a table for multi-tenancy....55
Select one or more tables to enable for multi-tenancy....55
Enable or disable access to tenant data....57
Determine if tenant data access is enabled....57
Enable or disable access....58
Deallocate tenant tables....58
Deallocating a tenant table from the tenant....58
Deallocating a tenant table from a group....59

About Updating Tenant Schema....61

Upload schema for a multi-tenant database....61
Select and load the data definition file....62
Preview the contents of an uploaded data definition file....62
Configure an area working set....64
Edit storage area assignments for regular tenants....64
Commit changes to a multi-tenant database....65
Monitor data definition file updates to the database....66

About Managing Users and Domains in a Multi-tenant Database....67

Manage users in a multi-tenant database....67
Add a user to a multi-tenant database....68
Modify a user in a multi-tenant database....69
Delete a user from a multi-tenant database....69
Manage domains in a multi-tenant database....70
View and filter database domains....70
Add a domain to a multi-tenant database....71
Modify a domain in a multi-tenant database....71
Delete a domain from a multi-tenant database....72
Manage authentication systems....72
Add an authentication system....72
Delete an authentication system....73

Manage multi-tenant database table security for users....73
Review user data security permissions....75
Configure database security options....75
Configure database security administrators....76
Set up a database connection login....77
Review user access in the Data Administration Console....77
Database landing page options....78
Tenant landing page options....79
Edit Tenant landing page options....80

About Working with Tenant Templates....83

Use tenant templates....83
Allocation considerations when creating a tenant template....84
Create a tenant template....84
Choose general tenant template settings....84
Choose partition-related template settings....85
Filter partitions from a tenant template....86
View a list of available tenant templates....86
Create a tenant from a tenant template....87
Edit a tenant template....87

About Working with Sequences....89

Work with sequences and sequence values....89
Types of sequences....89
Sequence functionality and user credentials....90
Create a multi-tenant sequence and load a data definition file with sequences....90
Export current sequence values....91
View a list of sequences....91
Edit sequence values 92
Edit the values for all sequences for a tenant....92
Edit the values for all tenants of a sequence....93
Restore sequence current values....93
Export sequences for a tenant....93
Export sequences for one or more tenants in the database....94
Export sequence current values for a selected tenant....94

About Working with Tenant Groups....97

Use tenant groups....97
Guidelines for using groups....98
Create a group or group program....98
Edit a group....99
Add a tenant to a group....100
View a list of tenant groups....101

View group details....102
Search for available groups....102
Remove a tenant from a group....102
Remove a tenant from a group using the tenant....103
Remove a tenant from a group using the group....103

Index....105

Copyright

© 2021 Progress Software Corporation and/or its subsidiaries or affiliates. All rights reserved.

These materials and all Progress® software products are copyrighted and all rights are reserved by Progress Software Corporation. The information in these materials is subject to change without notice, and Progress Software Corporation assumes no responsibility for any errors that may appear therein. The references in these materials to specific platforms supported are subject to change.

DataDirect Cloud, DataDirect Connect, DataDirect Connect64, DataDirect XML Converters, DataDirect XQuery, DataRPM, Defrag This, Deliver More Than Expected, DevReach (and design), Icenium, Inspec, Ipswitch, iMacros, Kendo UI, Kinvey, MessageWay, MOVEit, NativeChat, NativeScript, OpenEdge, Powered by Chef, Powered by Progress, Progress, Progress Software Developers Network, SequeLink, Sitefinity (and Design), Sitefinity, Sitefinity (and design), SpeedScript, Stylus Studio, Stylized Design (Arrow/3D Box logo), Styleized Design (C Chef logo), Stylized Design of Samurai, TeamPulse, Telerik, Telerik (and design), Test Studio, WebSpeed, WhatsConfigured, WhatsConnected, WhatsUp, and WS_FTP are registered trademarks of Progress Software Corporation or one of its affiliates or subsidiaries in the U.S. and/or other countries.

Analytics360, AppServer, BusinessEdge, Chef Automate, Chef Compliance, Chef Desktop, Chef Habitat, Chef WorkStation, Corticon.js, Corticon Rules, Data Access, DataDirect Autonomous REST Connector, DataDirect Spy, DevCraft, Fiddler, Fiddler Everywhere, FiddlerCap, FiddlerCore, FiddlerScript, Hybrid Data Pipeline, iMail, JustAssembly, JustDecompile, JustMock, KendoReact, NativeScript Sidekick, OpenAccess, PASOE, Pro2, ProDataSet, Progress Results, Progress Software, ProVision, PSE Pro, Push Jobs, SafeSpaceVR, Sitefinity Cloud, Sitefinity CMS, Sitefinity Digital Experience Cloud, Sitefinity Feather, Sitefinity Insight, Sitefinity Thunder, SmartBrowser, SmartComponent, SmartDataBrowser, SmartDataObjects, SmartDataView, SmartDialog, SmartFolder, SmartFrame, SmartObjects, SmartPanel, SmartQuery, SmartViewer, SmartWindow, Supermarket, SupportLink, Unite UX, and WebClient are trademarks or service marks of Progress Software Corporation and/or its subsidiaries or affiliates in the U.S. and other countries. Java is a registered trademark of Oracle and/or its affiliates. Any other marks contained herein may be trademarks of their respective owners.

July 2021

Product version: Progress OpenEdge 12.4

Preface

Purpose

This book describes how you can use the Database Administration Console in OpenEdge Management to configure and manage OpenEdge databases that are enabled for multi-tenancy. Not only can you manage tenants and multi-tenant data from the management console, you can do so in a newly designed user interface that incorporates efficient and easy-to-use navigational improvements.

Audience

This book is intended for OpenEdge Management users as well as OpenEdge Management database and system administrators.

For the latest documentation updates go to https://docs.progress.com.

Organization

Overview of Multi-tenancy in OpenEdge Management on page 11

Describes how to work with multi-tenancy. The topic also describes the management console navigational enhancements and defines some commonly used terms related to multi-tenancy.

About Configuring Database Connections on page 17

Describes database connection types, how to establish a connection to a database, and how to filter database connections. The topic also provides information about providing required user credentials when working with multi-tenancy enabled databases.

About Managing Multi-tenant Databases on page 25

Describes how to enable a database for multi-tenancy and how to manage the database's areas, domains, groups, schemas, and tenants.

About Working with Tenants on page 45

Describes how to work with tenants, such as creating, editing, or deleting a tenant; enabling a table for multi-tenancy; or enabling or disabling access to tenant data.

About Updating Tenant Schema on page 61

Describes how to upload and commit schema changes to a database enabled for multi-tenancy; how to configure an area working set; and how to edit storage area assignments for regular tenants.

About Managing Users and Domains in a Multi-tenant Database on page 67

Describes how to manage users and domains, manage multi-tenant database table security for users, and how to configure database security administrators.

About Working with Tenant Templates on page 83

Describes how to create, use, and edit tenant templates; view a list of tenant templates; and create a tenant from a template.

About Working with Sequences on page 89

Describes how to work with sequences, edit sequence values, and export sequences for a tenant.

About Working with Tenant Groups on page 97

Describes how to create, use, and edit tenant groups or group programs; remove a tenant from a group; and search for and view available groups.

Documentation conventions

See Documentation Conventions for an explanation of the terminology, format, and typographical conventions used throughout the OpenEdge content library.

1

Overview of Multi-tenancy in OpenEdge Management

OpenEdge Management now include multi-tenancy configuration functionality, which allows you to manage and work with databases enabled for multi-tenancy. From the management console, you can access the Database Administration Console and perform a variety of different tasks, such as adding a local or remote database connection definition; creating new tenants and viewing their areas, domains, and partitions; uploading and previewing schema updates; making storage area and allocation or deallocation decisions; filtering views; and creating and working with tenant templates and tenant groups.

You can also enable local and remote databases for multi-tenancy, convert tables to multi-tenancy, and establish and manage user and table security settings. Support for viewing, exporting, and editing values for sequences is also available. You can commit configuration changes you make and then view the progress of each transaction in a viewlet in the **Dashboard** page.

For details, see the following topics:

- About working with multi-tenancy in the Database Administration Console
- Common terminology

About working with multi-tenancy in the Database Administration Console

OpenEdge Management has been enhanced to introduce support for OpenEdge database multi-tenancy. Through the Database Administration Console, which is incorporated into the management console, you can manage tenants and multi-tenant data from the management console. You can do so in a newly designed user interface that incorporates efficient and easy-to-use navigational improvements.

From the Database Administration Console, you can perform multi-tenancy configuration by:

- **Converting a non-multi-tenant database to one configured for multi-tenancy**—You can quickly enable multi-tenancy for a database.
- **Establishing connections to multi-tenant databases**—You can set up local and remote connections to managed databases or scripted databases. These databases appear automatically in the list of database resources in the management console.

  You can also set up unmanaged local or remote database connections. Depending on the type of connection you define, you can also edit, copy, or delete it.
- **Creating new database tenants, deleting tenants, or generating a tenant creation program**—You can create two types of tenants: a regular tenant or a super-tenant. You can also delete a tenant.

  Alternatively, you can generate a tenant program based on preferred settings for either an existing tenant or a new tenant. You can use the resultant generated program in the future to create a tenant quickly, without needing to resupply the settings saved in the program. You can also create a tenant from an existing tenant.
- **Enabling a table for multi-tenancy**—You can enable one or more tables for multi-tenancy and then allocate the table's partitions.
- **Creating a tenant template**—You can create, view, and edit a template that includes tenant-specific details, such as default storage areas and per-object tenant mapping, so you can reuse the template to create another tenant.
- **Creating a tenant group**—You can create, view, and edit a tenant group and add one or more tenants to it. A *group* is a partition for a table and partitions for any of the LOB fields and indexes in the table. Each tenant in the group has shared access to the partition and its data.

  You can also generate a group creation program based on preferred settings, and use the program in the future to create a group quickly or that you can use to transfer a group from one database to another database.
- **Working with existing tenants and multi-tenant database objects**—You can work easily with existing tenants to accomplish various tasks related to multi-tenancy configuration, such as:
  - Viewing an alphabetical list of all tenants in the currently selected database.
  - Accessing utilities by selecting a tenant.
  - Viewing a tenant's layout, including the database object schema, tenant object areas, and object properties. Color coding in the partition layout allows you to see easily each object's allocation state.

    You can also view tenant partition details and choose how the data is displayed: within area panels or by columns in a grid format. The grid format allows you to choose the information you want to see (partition name, area, allocation state, or object type) and sort the information in ascending or descending alphabetical order.

- Deciding when storage space is to be allocated for a tenant's data: immediately, delayed (for now), or not at all. You can also deallocate a table for a tenant or a group, freeing up storage space.
- Specifying storage area assignments for a tenant's tables (which apply to their indexes and LOB fields). If you choose not to allocate storage space immediately when you create a tenant, you can reorganize the layout of the multi-tenant database objects, such as moving a table from one area to another area.
- Filtering the tenant list so you can focus on specific tenants. For example, you can set up the list so that you see only regular tenants or tenants categorized by allocation rule.
- Adding one or more tenant domains by choosing from a predefined domain list.
- Adding one or more users to a tenant.
- Searching for a particular tenant.
- Selecting which of a tenant's areas you want to see when you look at the tenant's area layout. By choosing the areas you want to see, known as the *area working set*, you can focus only on areas of current interest to you.
- Filtering the partition view by allocation state for a tenant or a tenant template.
- Enabling or disabling access to a regular tenant's data.

Note: The OpenEdge Management console displays an error when you update a multi-tenant database object that already has an exclusive lock from another multi-tenant data source.

- **Loading and previewing a data definition file**—You can upload a data definition file (`.df`) and preview its contents (tables, LOB fields, indexes, and sequences) before you commit the changes.
- **Load database contents**—You can load table and group contents into an active database. The database must have table definitions before you can load table or group contents. The console uses the `.d` files to load table contents from a directory you specify or to load group contents from the subdirectory for groups you specify.

  Note: You must have administrator privileges to load table and group contents.

- **Dump database contents**—You can dump table or group data in a text format from the console. The console creates a text file that contains the dump data of each table or group you specify. This file has a `.d` extension and is stored in the work directory you specify. You can dump data either from a shared table, a multi-tenant table, or both. You can also dump data from a group of tenants sharing a table. You can use these `.d` files to load data into a database. The console creates a separate contents file for each table or group you dump.

  Note: You must have administrator privileges to dump table and group contents.

- **Committing and monitoring database updates**—You can commit updates to the database, either from an uploaded data definition file or as a result of other changes you make.

  As changes are being saved to the database, the **Dashboard** page opens to allow you to monitor the updates' progress. The page presents a task viewlet that shows the activity as the updates are being applied.

- **Filtering database connections by AdminServer**—You can view all database connections for all AdminServers, or you can choose which AdminServer's connections you want to view.

- **Managing domains**—You can create and modify a domain for each tenant.
- **Managing authentication systems**—You can view, create, or delete authentication systems.
- **Establishing and managing user and table security settings**—While you can create and work with users for a particular tenant, you can also create, edit, and delete users at the database level. You can define and review table and field security for the database users, and you can review a summary that provides details about the database's security.

  You can also configure one or more security administrators who have control over authentication and authorization.
- **Managing sequence definitions and values**—You can manage sequences and sequence values by:
  - Viewing a list of all sequences in a database. This includes both the sequences enabled for multi-tenancy and those not enabled.
  - Viewing and editing the current values for multi-tenant-enabled sequences for a specific tenant.
  - Viewing and editing the current values for all tenants of a sequence.
  - Exporting sequence current values for one tenant, multiple tenants, or all tenants in a multi-tenant database.
- **Improve database performance**—The performance of a multi-tenant database may be improved by using multi-tenant governors: Login Governor (`-nGovernor`) and Lock Governor (`-LGovernor`). These governors limit the amount of each individual tenant's allocation of shared database resources, so that one tenant does not fully control these resources at the expense of all of the other tenants. These governors apply to the default and regular tenants in a multi-tenant database. They do not apply to super-tenants.

Note: Full access to a tenant's sequences functionality requires a database connection for a user associated with either a super-tenant or that specific tenant.

Common terminology

As you manage multiple tenants and multi-tenant database objects in OpenEdge Management, there are several terms with which you will become familiar. These terms are described in the following topics.

Tenant

There are three types of tenants: *default*, *regular*, and *super tenant*.

The default tenant in a multi-tenant database is a user who does not establish tenancy as part of authentication to the database. Because the user has not established tenancy, the default tenant can access only shared table data within the database or the default partition of a multi-tenant table. There is only one default tenant per multi-tenant database.

A regular tenant can access its own data, data for any other tenants in the same tenant group, or data in shared tables. (A shared table is one whose data is available to all tenants in the database.)

A super-tenant does not have its own data but can access all shared tables and all multi-tenant data in the database.

Area

An *area* is a physical layout on disk and represents physical storage. An area can contain multiple partitions.

Partition

A *partition* is a logical organizing of data by tenant and by object (table, index, or LOB field) within an area. A partition is contained inside a single area.

For shared tables there is one partition per table, index, and LOB field. For multi-tenant tables there is one partition for each table, index, and LOB field per tenant.

Tenants in a group share the partitions for the table and each associated LOB field and index.

Group

A group is a partition for a table, along with partitions for the table's LOB fields and indexes, that can be shared by tenants. All tenants in a group have access to the same data in the table. When you create a group, you create an independent partition that multiple tenants view.

Default area

When you convert an existing shared table to one enabled for multi-tenancy, you can decide whether to save the existing table data, known as the default area. If you are creating a new multi-tenant table, you can also decide whether to create (keep) the area for the default tenant.

Allocation

Creating a new tenant in an existing multi-tenant database results in the establishment of a new tenant partition for each existing multi-tenant table defined in the database. You can assign a specific storage area for each table, its indexes, and its LOB fields, or you can use the previously defined default locations.

You can also specify if or when partitions for a table should be allocated. The allocation decision you make for a table also applies to the table's indexes and LOB fields.

You can deallocate a multi-tenant table from a tenant or a group. Deallocation can be helpful in freeing up storage space so that it is available for reuse.

2

About Configuring Database Connections

The Database Administration Console provides you with the flexibility to work with a database on a machine that is local to or remote from where you have installed OpenEdge Management. To perform tasks in the Database Administration Console, you must specify a connection to the database.

For details, see the following topics:

- About database connection types
- About establishing a database connection
- About providing database connection user credentials

About database connection types

The machine on which OpenEdge Management is installed is known as the *local host*. The remote host where the database resides is known as the *remote AdminServer*.

All database versions, whether on the local host or a remote AdminServer, must be supported in the current release of OpenEdge Management. For details, see the *OpenEdge Platform and Product Availability Guide* on the Progress Information Hub at https://docs.progress.com.

You can configure the following database connections:

- A managed connection, which refers to a database that is either of the following:
  - **Managed database**—A database that is being managed by OpenEdge Management. The database can reside on the local host or on a remote AdminServer. For a managed database, the connection is made through shared memory.

  - **Scripted database**—A database that you start with a script outside of the OpenEdge Management environment. The database can reside on the local host or on a remote AdminServer.

- An unmanaged database connection, which refers to a database that:
  - Is not being managed by OpenEdge Management.
  - You are using only to perform database administration tasks related to multi-tenancy.

You can work with a database on a remote AdminServer by doing the following:

1. Review the remote configuration requirements on page 18
2. Unglue OpenEdge Management from OpenEdge on page 18

Review the remote configuration requirements

Remote configuration requires that you have:

- **On the local host**—One OpenEdge installation that includes OpenEdge Management
- **On the remote host**—An installation of one OpenEdge product

  On the remote host with the OpenEdge installation, OpenEdge Management cannot be enabled. If OpenEdge Management is enabled, you must disable it in the OpenEdge product by running a script known as *unglue*.

  For more information, see Unglue OpenEdge Management from OpenEdge on page 18. If OpenEdge Management is already disabled on the remote AdminServer, you can begin setting up remote configuration; see the Setting up a remote AdminServer topic in *Introduction to OpenEdge Management*.

Unglue OpenEdge Management from OpenEdge

If the host machine you plan to use as the remote AdminServer has OpenEdge Management installed as part of OpenEdge, you must disable (unglue) it before you can set up remote configuration.

To unglue OpenEdge Management from OpenEdge on the remote AdminServer:

1. Shut down the AdminServer.
2. To unglue on a Windows machine, select **Start** > **Programs (or All Programs)** > **Progress** > **OpenEdge** > **Proenv** . The **Proenv** window opens.

   To unglue on a UNIX machine, log in as root in a terminal window and then run **Proenv**. If you do not know the root password for your system, consult with your system administrator.

3. At the prompt or from the `bin` directory of the OpenEdge installation, type **unglue**, as shown here for a Windows install:

   ```
   install-dir\unglue
   ```

4. Type `y` at the prompt asking you if you want to continue, and then press **ENTER**.

About establishing a database connection

OpenEdge Management allows you to work with multi-tenant databases and their schema from the Database Administration Console running in a web browser. From the console, you can establish database connections, create tenants, edit tenant configuration, upload and preview schema updates, create tenant templates, create tenant groups, filter views, and commit updates and monitor their progress.

Once you install and configure OpenEdge Management, you are ready to start managing multi-tenant databases and their objects. You begin by establishing a database connection. By default, connections for databases defined in OpenEdge Management use the blank user ID.

However, you can set up the connection to provide user credentials (user name and password). The availability of certain features and functionality is dependent upon the permissions that exist for the user whose name and password establish the connection as well as on the type of tenant the user belongs to.

For more information, see About providing database connection user credentials on page 22.

Set up the connection

To work with a database's multi-tenant objects, you must set up a connection to the database and the database's server must be running. The connection can be:

- To a local or remote managed database resource
- To a local or remote scripted database
- To a local or remote database using an unmanaged connection

Establish a connection to a local or remote managed database resource

If the database is a resource already being managed by OpenEdge Management, you can start the database through the management console by doing the following:

1. Log in to OpenEdge Management.
2. Click **Resources** > **Go to Resources** in the management console menu.

   All resources managed by your console appear in the grid frame of **Resources**page.
3. Filter or search for, and select the database you want to start.
4. You can start the database by doing either of the following:

   - Click **Start brokers** in the **Resources** page.
   - Click **Start** in the **Resource Summary** section of the **Resources** page.
   - Select the database to access the database details page and click **Start Database**.

   Once the database is running, you can select it as a database connection.

For a local or remote managed database in the database connections list, you can also:

- View details about a database connection on the database home page. For more information, see About Managing Multi-tenant Databases on page 25.

- Copy a database connection. When you copy a connection, you are not copying the actual database resource; you are copying only the connection details. The connection copy does not represent a database resource being managed by OpenEdge Management.
- Delete a database connection.

Establish a connection to a local or remote scripted database

If the database is not being managed from within OpenEdge Management, you can start the database on the machine where it is located (either the local host or a remote host) using the command line. You can then use the Database Administration Console to work with that database once you define a connection to it.

When you define a scripted database on a remote AdminServer, be sure to use `localhost` as the database's host. This allows the ABL commands to execute on the remote AdminServer and connect to the database by using shared memory.

When you use `localhost`, the database is included in both the **Resources** list in OpenEdge Management and the Database Administration Console's **Connections** list. If you do not use `localhost`, the database is still listed as a resource but does not appear in the **Connections** list.

If you do not define the host as `localhost` for the scripted database on the remote AdminServer, you must add the database connection manually and specify the host and port required for the connection. In this case, the connection to the database is performed using the `-H` (host name) and `-S` (service name or port) parameters, and the database appears in the **Connections** list but not the **Resources** list in the management console.

To establish a connection to a scripted database:

1. On the machine where the scripted database resides (either the local host or a remote host), start **Proenv** (by choosing **Start** > **Programs (or All Programs)** > **Progress** > **OpenEdge** > **Proenv**).
2. Type the following command to start the database:

```
proserve { db-name | -servergroup [ server-group-name ] [ parameters ] }
```

3. Exit **Proenv**.
4. To add the database to the list of database resources, perform the following steps on the machine where OpenEdge Management is installed.
5. Select **Resources** > **New** > **Scripted Database** in the management console.

   The **Create Scripted Database Monitor** page appears.
6. Complete the page:
   a) Provide the following information:
      - **Name**—Name of the database.
      - **Description**—A description of the database (optional).
   b) Type the host name.
   c) Provide an IP Address (optional).
   d) Select the TCP/IP version (**IPv4** or **IPv6**).
   e) Type the complete path to the database.

f) To enable the scripted database after creation, select the **Enabled** option.

g) Click **Save**.

The **Database** details page appears

7. Click **Control**.
8. Choose one:

- If you are connecting to a scripted database on the local host:
  1. Copy the command line from the **Command line to start Monitoring Agent**.
  2. Start **Proenv**, and paste the command line details at the prompt.
  3. Exit **Proenv**.
- If you are connecting to a scripted database on a remote host:
  1. On the local host, note the command line from the **Command line to start Monitoring Agent**.
  2. Start **Proenv** on the remote machine.
  3. Type the command line details at the prompt.
  4. Exit **Proenv**.

9. From the management console on the local host, return to the **Database** details page. The database and the database agent are now running.

For a local or remote scripted database in the database connections list, you can also:

- View details about a scripted database connection on the database home page. For more information, see About Managing Multi-tenant Databases on page 25.
- Copy a scripted database connection.

Establish a connection to an unmanaged local or remote database connection

An unmanaged database connection refers to a database that is not being managed by OpenEdge Management and that you are using only to perform database administration tasks related to multi-tenancy.

You can start an unmanaged database connection (located on the local host or a remote host) by using the command line. You can then use the multi-tenancy configuration tool to work with that database once you define a connection to it.

1. On the machine where the scripted database resides (either the local host or a remote host), start **Proenv** (**Start** > **Programs (or All Programs)** > **Progress** > **OpenEdge** > **Proenv**.
2. Type the following command to start the database:

```
proserve { db-name | -servergroup [ server-group-name ] [ parameters ] }
```

3. From the management console menu on the machine where OpenEdge Management is installed, choose **Database Administration** > **New** > **Database Connection**.

   The **Edit Database Connection** page appears.

4. Provide the following information:
   - **Connection name**—Enter the name of the database connection. This is a mandatory field.
   - **Category**—Enter the category of the database connection. You can enter a category name, such as `tenant`, `tp`, or `oem`, to distinguish between the connections.
   - **Database name**—Enter the full path to the database. This is a mandatory field.
   - **Host**—Enter the host (local or remote) location of the database connection.
   - **Service name or port**—Enter the host name port.
   - **AdminServer**—Select an AdminServer from the list. This is a mandatory field.
   - Select the **Make database connection visible only to me** option to control the visibility of the connection. As an administrator, you can use this option to control which connections you want to share with other administrators or operators.
5. Click **Save**.

For a local or remote unmanaged database connection in the database connections list, you can also:

- View details about an unmanaged database connection on the database home page. For more information, see About Managing Multi-tenant Databases on page 25.
- Copy an unmanaged database connection.
- Delete an unmanaged database connection.

About providing database connection user credentials

Each database connection is based on a set of user credentials. The availability of certain database and multi-tenancy features and functionality is dependent upon the permissions that exist for the user whose credentials establish the connection, as well as upon the type of tenant the user belongs to. For example, certain users can read data and write to the database, but not delete data; and a super-tenant can view and edit sequence values for all tenants, whereas a regular tenant user can do so only for the tenant the user belongs to.

Access to certain multi-tenancy configuration features might be restricted, disabled, or hidden based on the credentials (user ID and password) provided for the database connection.

User credentials considerations

By default, a connection for a database defined in OpenEdge Management uses a blank user ID, in which no user name or password is required. However, if you are a database administrator working with multi-tenant databases, you must consider how to manage tenants effectively and the role that user credentials play in the tenants' successful management.

OpenEdge Management permits only one set of user credentials (user ID and password) per database connection; it does not, however, require the credentials. Any user with a login to OpenEdge Management can see any database connection defined in it. Passwords are encrypted and stored internally and are not visible in the user interface.

Because of this default structure, you may need to establish or change database connection credentials. You may also need to establish multiple database connections for the same database to allow performance of specific tasks as different users.

Database connection credentials for a regular tenant or super-tenant

In order to access tenant data, you must set up the database connection to use the credentials for either a user for a regular tenant or for a super-tenant. Because super-tenant's can access all users' data, establishing a database connection as a super-tenant will allow you to perform operations such as dumping and loading of data and editing sequences for any tenant. If you establish a connection with the credentials of a user for a regular tenant, you can perform operations for only that tenant.

Regardless of how you set up the connection, the operations you can perform are defined by the user data security permissions defined for the database in a series of **Can-*** actions. (For more information, see Manage multi-tenant database table security for users on page 73.) You can use wildcards to allow the performance of certain operations that any user would normally be permitted to do. Likewise, you can restrict which users can perform specific tasks. For example, by default any user can create a tenant. You can prevent this by setting up the **Can-Create** action to permit only a select user to do so.

Security administrators

Keep in mind that a database may have one or more security administrators in place. A security administrator has the authority to create and delete database users, which includes tenant users. If your database has security administrators configured and you must be able to manage users from within OpenEdge Management, be sure that the database credentials you use to establish the database connection have security administrator rights.

3

About Managing Multi-tenant Databases

You can establish a connection to a database that is enabled for multi-tenancy. You can also connect to a database that is not enabled for multi-tenancy, and then enable multi-tenancy for the database from the Database Administration Console.

For details, see the following topics:

- Enable a database for multi-tenancy
- Multi-tenant database management
- About viewing multi-tenant database areas, domains, schemas, tenants, and groups

Enable a database for multi-tenancy

You can enable a database for multi-tenancy from the Database Administration Console.

To enable a database for multi-tenancy:

1. On the management console menu, select **Database Administration** > **Go to Database Administration**.

   The **Database Administration** page appears.
2. Filter or search for, and select the database connection.

   The database connection home page appears.
3. In the **Database Features** section, verify the **Multi-tenancy** status.

   (Note that you can click the **Sort** arrow to display the features in ascending or descending order.)

If the status is a check mark in a green circle and the word **Enable** does not appear in the **Action** column, the database is already enabled for multi-tenancy.

4. Click **Enable**.

   The **Enable Multi-tenancy** page appears.

5. Click **Enable Multi-tenancy**.

   A message appears confirming that the database is now multi-tenant.

6. Click **OK**.

   The database home page appears, and the multi-tenancy status for the database reflects that the database is now enabled.

Multi-tenant database management

Once you establish a connection to a database enabled for multi-tenancy, you can:

- Use the database connection home page to manage and view various details about multi-tenancy users, domains, authentication systems, and security for the database.

  To access the database home page:

  - Select **Database Administration** > **Go to Database Administration** in the management console menu.
  - On the **Database Administration** page, filter or search for, and select the required database connection.

    The database connection home page appears.

  .

- View and work with the areas, domains, schemas (tables, LOB fields, indexes, and sequences), tenants, and groups that belong to the database.

View database connection details

From the database home page, you can see various database details that assist you in managing multi-tenancy. The multi-tenancy-related actions you can perform from the home page are dependent upon the type of database connection you define. For a managed database, a scripted database, or an unmanaged database connection, you can:

- Manage and edit a database connection.
- Review database connection features; for example, you can see if the database is enabled for multi-tenancy or has support for 64-bit sequences.
- Manage, edit, and review database security settings for users, and create one or more security administrators.
- View a security summary, which includes details about various characteristics of the database, such as whether establishing user credentials with a blank user id is allowed; how many database users exist; how many tenants are defined in the database; and additional statistics. Once you review the summary information, you can edit certain database options, modify user or domain properties, or create a tenant.

  Note that if the database whose summary you are viewing is not enabled for multi-tenancy, the summary does not include any of the details that relate specifically to multi-tenancy.

- Perform data administration by editing sequences and their current values, exporting sequences, or previewing or loading a data definition file.

For an unmanaged database, you can also delete the database connection from the database home page.

Review database features

From the database home page, you can review a database feature status list. The status for each feature that is enabled appears as a check mark in a green circle.

If you are reviewing features for a database that is not enabled for multi-tenancy, you can enable multi-tenancy for the database from the **Database Features** section. For more information, see Enable a database for multi-tenancy on page 25.

To review database features:

1. On the management console menu, select **Database Administration** > **Go to Database Administration**.

   The **Database Administration** page appears.

2. Filter or search for, and select the required database connection.

   The database connection home page appears.

3. Scroll through the entries in the **Database Features** section to see the status of one or more database features, such as Multi-tenancy, Encryption, and OpenEdge Replication.

   You can click the **Sort** arrow below the **Feature Name** column heading to sort the features in ascending or descending order.

   A status appears for a feature as long as the feature is enabled, with the exception of multi-tenancy. The status for multi-tenancy appears whether or not the database is enabled as multi-tenant. If multi-tenancy is not enabled, the Database Features panel provides that detail. You can then enable multi-tenancy for the database directly from that panel. For more information, see Enable a database for multi-tenancy on page 25.

Review the database security summary

From the database home page, you can review security information and work with different multi-tenancy components.

Note that if the database whose summary you are viewing is not enabled for multi-tenancy, you do not see any of the details that relate specifically to multi-tenancy. You can enable the database for multi-tenancy by clicking **Enable** in the **Action** column in the **Database Features** section, also on the database home page. For more information, see Enable a database for multi-tenancy on page 25.

To review the database security summary:

1. On the management console menu, select **Database Administration** > **Go to Database Administration**.

   The **Database Administration** page appears.

2. Filter or search for, and select the required database connection.

   The database connection home page appears.

3. Review the following information about the database provided in the **Security Summary** section:

   - **Blank user id access**—Whether users are allowed to connect using the blank user id.

- **Security administrator**—Whether there is a security administrator defined for the database. You create a security administrator by clicking **Edit security administrator**. For more information, see Configure database security administrators on page 76.
- **Users**—The number of users in the database.
- **Domains**—The total number of domains (active and disabled) in the database.
- **Disabled domains**—The number of disabled (inactive) domains in the database.
- **Tenants**—The total number of tenants in the database. This number includes the default tenant, super-tenants, and named regular tenants.
- **Super-tenants**—The number of super-tenants in the database.
- **Named regular tenants**—The number of named regular tenants in the database. This number excludes the super-tenants and the default tenant.

Work with the database from the security summary

In addition to reviewing the details in the database security summary, you can also manage database functionality from the summary.

You can select:

- **Edit security options** to define security options for your database.
- **Edit security administrator** to add users and user domains as security administrators.
- **Edit users** to view the **Edit Database Users** page, where you can review, add, or delete users.
- **Edit domains** to view the **Edit Database Domains** page, where you can review, add, or delete domains.
- **Create tenant** to view the **New Tenant** page, where you can create a tenant for the database.
- **Edit authentication systems** to open the **Edit Database Authentication Systems** page, where you can view, create, or delete authentication systems.
- **Edit data security** to access the user data security page and set or remove user permissions for the data.
- **Review user data security** to review the data security permissions for a particular user.

Review sequences details

From the **Data Administration** panel in the database home page, you can view and edit sequences and export sequence values.

To review sequence details:

1. On the management console menu, select **Database Administration** > **Go to Database Administration**.

   The **Database Administration** page appears.

2. Filter or search for, and select the required database connection.

   The database connection home page appears.

3. In the **Data Administration** section:

   - Click **Edit sequences**. The **Edit Database Sequences** properties page appears, with a list of the sequence names and entries for current values for both multi-tenant- enabled and non-multi-tenant-enabled sequences.

     For information about editing sequences, see Edit sequence values on page 92.

- Click **Export sequences**. The **Export Sequence current Values** page appears.

  For information about exporting sequences, see Export sequences for a tenant on page 93.

Load a data definition file

From the **Data Administration** section in the database home page, you can load a data definition file that you can then preview or load.

To load a data definition file:

1. On the management console menu, select **Database Administration** > **Go to Database Administration**.

   The **Database Administration** page appears.
2. Filter or search for, and select the required database connection.

   The database connection home page appears.
3. In the **Data Administration** section, click **Load data definitions (.df file)**.

For information about loading, previewing, and committing a data definition file, see Upload schema for a multi-tenant database on page 61.

Load database contents

The Database Administration console of OpenEdge Management enables you to load table and group contents into an active database. The database must have table definitions before you can load table or group contents. The console uses the `.d` files to load table contents from a directory you specify or to load group contents from the sub-directory for groups you specify. By default, the `.d` files used for loading table contents is stored in the work directory `C:\OpenEdge\WRK` and the `.d` files used for loading group contents is stored in the groups sub-directory of the work directory.

Note: You must have administrator privileges to load table and group contents.

Load table contents to a database

The Database Administration console uses the `.d` files to load table contents from the sub-directory for tables you specify.

To load table contents:

1. In the management console menu, do one of the following:

   - Select **Database Administration** > **Load** > **Table Contents (.d files)**.
   - Select **Database Administration** > **Go to Database Administration**. The **Database Administration** page appears.

     Filter or search for, and select the required database connection. The database connection home page appears.

     In the **Data Administration** section, click **Load table contents (.d file)**.

The **Load Table Contents** page for the selected database connection appears.

2. In the **Database connection** field, enter a database connection name that contains the database into which you want to load the table contents.

   By default, the last used database connection name appears in the **Database connection** field.

   You can select another database connection by entering a database name in the **Database connection** field.

   Note: If you type the name of the database connection, follow the format used by OpenEdge Management to define a connection: *AdminServer-name.database-name*. A database server must be running for you to connect to the database.

   You can also click the **Search** icon to choose a database for which you are creating the tenant from the **Connection Selection** dialog.

   The **Connection Selection** dialog displays the connections details in a grid. You can perform the following:

   - Filter the connections in the grid by **Connection name**, **AdminServer**, or **Category**.
   - Select the column heading and click the drop-down to choose the order (ascending or descending alphabetically) for the connections to appear in the grid.

   Note: When you select a database connection name, the **Database connection** field displays the selected database connection name. Most of the other fields get auto-populated with the default values, based on the selected database connection name.

   ---

3. In the **Load root directory** field, specify a file path of the contents (`.d`) file. By default, this field displays the work directory `C:\OpenEdge\WRK`.
4. Select **Include LOB** to enable importing of large database objects, such as images. By default, this check box is selected.
5. In the **LOB sub-directory** field, specify a sub-directory name that contains the large database objects that you want to load. By default, this field displays `lobs` and this sub-directory is contained in the default work directory `C:\OpenEdge\WRK`.
6. In the **Acceptable error percentage** field, specify an acceptable error percentage. The default value is `0`.
7. In the **Group sub-directory** field, specify a sub-directory name which contains group contents in `.d` files. By default, this field displays `groups` and this sub-directory is contained in the default work directory `C:\OpenEdge\WRK`.
8. Select the **Skip secured tables** check box, if you do not want to load secured tables.
9. Select the **Do not load group tables** check box, if you do not want to load the group tables.
10. Select the **Skip missing directories** check box, to skip validating the missing sub-directories mentioned under the root directory when loading table contents.
11. Select one of the following options for **Tables**:

Option	Description
All [1]	Load contents to all shared and multi-tenant tables. By default, this option is selected.

[1] Databases that are not enabled for multi-tenancy do not have shared or multi-tenant tables.

Option	Description
All shared tables	Load contents to all shared tables only. **Note:** This option is available only for multi-tenant database connections.
All multi-tenant tables	Load contents to all multi-tenant tables only. **Note:** This option is available only for multi-tenant database connections.
Selected	Load content either to one or many, shared or multi-tenant tables. This option appears both for multi-tenant and non-multi-tenant database connections. Selecting this option displays the **Selected Tables** section.

If you choose the **Selected** option for **Tables**, the **Selected Tables** section appears.

In the **Selected Tables** section, do the following:

a) In the **Table name** field, enter a table name. You can specify a keyword, use the wildcard operator *, or a combination of both.

b) In the **Database area** field, specify a database area name which contains the tables you want to view. When you type a keyword in this field, the console lists database areas matching your keyword. You can select a database area name. For example, if you type **Cu**, the console lists the database areas **Cust_Data** and **Cust_Index**.

c) Select one of the following options (available only for multi-tenant databases):

- **Show shared and multi-tenant**—To view tables that are both shared and multi-tenant. By default, this option is selected.
- **Show shared**—To view only shared tables.
- **Show multi-tenant**—To view only multi-tenant tables.

d) Select the **Show hidden** check box to view any hidden tables from the database.

e) Click **Apply Filter**. Based on your search criteria, the **Selected Tables** section lists the table names and displays the following columns:

Column name	Description
Schema	Displays whether the schema associated with the database table is public or user-defined. The default value is **PUB** which indicates that the default public schema is assigned to the OpenEdge database.
Table name	Displays the name of tables in an ascending alphabetical order.
Area	Displays the area in the database in which the table resides.

Column name	Description
Multi-Tenant	Displays true for multi-tenant tables and false for shared tables.
Description	Displays details associated with the table name. This column is optional. To view this column, click any of the column's drop-down and select **Columns** > **Description** check box.

12. Select **Tenants** based on whether you access the database as a regular or a super user.

Note: In the case of multi-tenant database connections, you must provide either regular or super user credentials to dump or load tenant data. Refer to Manage users in a multi-tenant database on page 67. If you do not provide any credentials for database authentication, you can dump or load only default database tables.

- For regular tenant user credentials, **Tenants** displays a preselected radio button for the regular tenant and you can only load contents to the tables within that specific regular tenant.
- For super-tenant user credentials, **Tenants** displays two options for you to select and load contents to the tables included within these tenants.

  You can choose **All** to select all the regular tenants or **Selected** to filter one or more tenants. Upon choosing **Selected**, the console displays the **Selected Tenants** section.

  You can enter either a keyword, the wildcard operator `*`, or a combination of the two in the **Tenant name** field. Click **Apply filter** to view the **Tenant name** and the **Description** in the respective columns. Use the check boxes to select or clear any of the tenant entries.

  Optionally, you can click the columns drop-down to select options such as **Type**, **Id**, **External Id**, and **Data Enabled** to display the respective tenant properties. Similarly, you can clear the check box to remove any of the columns from the **Selected Tenants** view.

  Note: The option for displaying tenants is not available for non-multi-tenant databases.

13. Click **Load**.

    A confirmation dialog appears for table data load displaying the number of shared and multi-tenant tables that will be loaded.

14. Do one of the following:

- Click **Commit** to load the contents of the selected tables. You can view status of such a task in the **Database Administration Tasks** page by selecting **Database Administration** > **View** > **Database Tasks**.
- Click **Commit & Monitor** to load the contents of the selected tables, and view the task page. This page lists the details of the load activity performed.
- Click **Cancel** to exit the dumping process.

When this operation is successful, the contents from the `.d` file in the load directory that you specify (in this case, the work directory `C:\OpenEdge\WRK`) are imported into the database tables.

Load group contents to a database

The Database Administration console uses the `.d` files to load group contents from the sub-directory for groups you specify.

To load group contents:

1. In the management console menu, do one of the following:

   - Select **Database Administration** > **Load** > **Group Contents (.d files)**.
   - Select **Database Administration** > **Go to Database Administration**. The **Database Administration** page appears.

     Filter or search for, and select the required database connection. The database connection home page appears.

     In the **Data Administration** section, click **Load group contents (.d file)**.

   The **Load Group Contents** page for the selected database connection appears.

2. In the **Database connection** field, enter a database connection name that contains the database into which you want to load the table contents. By default, the last used database connection name appears in the **Database connection** field.

   You can select another database connection by entering a database name in the **Database connection** field.

   Note: If you type the name of the database connection, follow the format used by OpenEdge Management to define a connection: *`AdminServer-name.database-name`*. A database server must be running for you to connect to the database.

   You can also click the **Search** icon to choose a database for which you are creating the tenant from the **Connection Selection** dialog.

   The **Connection Selection** dialog displays the connections details in a grid. You can perform the following:

   - Filter the connections in the grid by **Connection name**, **AdminServer**, or **Category**.
   - Select the column heading and click the drop-down to choose the order (ascending or descending alphabetically) for the connections to appear in the grid.

   Note: When you select a database connection name, the **Database connection** field displays the selected database connection name. Most of the other fields get auto-populated with the default values, based on the selected database connection name.

   ---

3. In the **Load root directory** field, specify a file path of the groups sub-directory which contains the contents (`.d`) file. By default, this field displays the work directory `C:\OpenEdge\WRK`.
4. Select **Include LOB** to enable importing of large database objects, such as images. By default, this check box is selected.
5. In the **LOB sub-directory** field, specify a sub-directory name that contains the large database objects that you want to load. By default, this field displays `lobs` and this sub-directory is contained in the default work directory `C:\OpenEdge\WRK`.
6. In the **Acceptable error percentage** field, specify an acceptable error percentage. The default value is `0`.

7. In the **Group sub-directory** field, specify a sub-directory name which contains group contents in `.d` files. By default, this field displays `groups` and this sub-directory is contained in the default work directory `C:\OpenEdge\WRK`.
8. Select the **Skip secured tables** check box, if you do not want to load secured tables.
9. Select the **Skip missing directories** check box, to skip validating the missing sub-directories mentioned under the root directory when loading table contents.
10. Select one of the following options for **Groups**:

Option	Description
All [2]	Load contents to all groups. By default, this option is selected.
Selected	Load content either to one or many groups. Selecting this option displays the **Selected Groups** section.

In the **Selected Groups** section, do the following:

a) In the **Group name** field, enter a group name. You can specify a keyword, use the wildcard operator *, or a combination of both.

b) Click **Apply Filter**. Based on your search criteria, the **Selected Groups** section lists the group names and displays the following columns:

Column name	Description
Group name	Displays the name of groups in an ascending alphabetical order.
Schema	Displays whether the schema associated with the database table is public or user-defined. The default value is **PUB** which indicates that the default public schema is assigned to the OpenEdge database.
Table	Displays the table in the database with which the group is associated.
Is allocated	Displays true if space is allocated for objects in the group.
Description	Displays details associated with the group name. This column is optional. To view this column, click any of the column's drop-down and select **Columns** > **Description** check box.

11. Click **Load**. A confirmation dialog appears for table data load displaying the number of groups that will be loaded.
12. Do one of the following:

- Click **Commit** to load contents of the selected groups. You can view status of such a task in the **Database Administration Tasks** page by selecting **Database Administration** > **View** > **Database Tasks**.
- Click **Commit & Monitor** to load contents of the selected groups, and view the task page. This page lists the details of the load activity performed.
- Click **Cancel** to exit the dumping process.

[2] Databases that are not enabled for multi-tenancy do not have groups.

When this operation is successful, the contents from the `.d` file in the `groups` sub-directory of the load directory you specify, (in this case, the work directory `C:\OpenEdge\WRK`) are imported into the database groups.

Dump database contents

The Database Administration console of OpenEdge Management allows you to dump table or group data in a text format. The console creates a text file that contains the dump data of each table or group you specify. This file has a `.d` extension and is stored in the work directory you specify. The default work directory is `C:\OpenEdge\WRK`. You can dump data either from a shared table, a multi-tenant table, or both. You can also dump data from a group of tenants sharing a table. You can use the `.d` files to load data into a database. The console creates a separate contents file for each table or group you dump.

Note: You must have administrator privileges to dump table and group contents.

Dump table contents from a database

The Database Administration console allows you to dump table contents in a text format.

To dump table contents:

1. In the management console menu, do one of the following:

   - Select **Database Administration** > **Dump** > **Table Contents (.d files)**.
   - Select **Database Administration** > **Go to Database Administration**. The **Database Administration** page appears.

     Filter or search for, and select the required database connection. The database connection home page appears.

     In the **Data Administration** section, click **Dump table contents (.d file)**.

   The **Dump Table Contents** page for the selected database connection appears.

2. In the **Database connection** field, enter a database connection name that contains the database into which you want to load the table contents. By default, the last used database connection name appears in the **Database connection** field.

   You can select another database connection by entering a database name in the **Database connection** field.

   Note: If you type the name of the database connection, follow the format used by OpenEdge Management to define a connection: *`AdminServer-name.database-name`*. A database server must be running for you to connect to the database.

   You can also click the **Search** icon to choose a database for which you are creating the tenant from the **Connection Selection** dialog.

   The **Connection Selection** dialog displays the connections details in a grid. You can perform the following:

   - Filter the connections in the grid by **Connection name**, **AdminServer**, or **Category**.
   - Select the column heading and click the drop-down to choose the order (ascending or descending alphabetically) for the connections to appear in the grid.

Note: When you select a database connection name, the **Database connection** field displays the selected database connection name. Most of the other fields get auto-populated with the default values, based on the selected database connection name.

3. In the **Dump root directory** field, specify a file path for the directory in which you want to store the contents (`.d`) file. By default, this field displays the work directory `C:\OpenEdge\WRK`.
4. Select **Include LOB** to enable exporting of large database objects, such as images. By default, this check box is selected.
5. In the **LOB sub-directory** field, specify a sub-directory name in which you want to store the large database objects. By default, this field displays `lobs` and this sub-directory is contained in the default work directory `C:\OpenEdge\WRK`.
6. In the **Code page** field, specify a value for code page. By default, this field displays `ISO8859-1`. For more information on code pages, see *Internationalize ABL Applications*.
7. In the **Group sub-directory** field, specify a sub-directory name in which you want to store group contents. By default, this field displays `groups` and this sub-directory is contained in the default work directory `C:\OpenEdge\WRK`.
8. In the **Character mapping** field, specify MAP or NO-MAP for character mapping. For more information about character mapping, PROTERMCAP, and national language support, see *Internationalize ABL Applications*.
9. Select the **Overwrite existing .d files** check box, to overwrite the existing .d file.
10. Select the **Do not dump secured tables** check box, if you do not want to dump secured tables.
11. Select the **Do not dump group tables** check box, if you do no want to dump group tables.
12. Select the **Do not validate code page** check box, to skip validating the value entered in the **Code page** field.
13. Select one of the following options for **Tables**:

Option	Description
All [3]	Dump contents from all shared and multi-tenant tables. By default, this option is selected.
All shared tables	Dump contents from all shared tables only. **Note:** This option is available only for multi-tenant database connections.
All multi-tenant tables	Dump contents from all multi-tenant tables only. **Note:** This option is available only for multi-tenant database connections.
Selected	Dump content either from one or many, shared or multi-tenant tables. This option appears both for multi-tenant and non-multi-tenant database connections. Selecting this option displays the **Selected Tables** section.

In the **Selected Tables** section, do the following:

[3] Databases that are not enabled for multi-tenancy do not have shared or multi-tenant tables.

a) In the **Table name** field, enter a table name. You can specify a keyword, use the wildcard operator *, or a combination of both.

b) In the **Database area** field, specify a database area name which contains the tables you want to view. When you type a keyword in this field, the console lists database areas matching your keyword. You can select a database area name. For example, if you type **Cu**, the console lists the database areas **Cust_Data** and **Cust_Index**.

c) Select one of the following options:

- **Show shared and multi-tenant**—To view tables that are both shared and multi-tenant. By default, this option is selected.
- **Show shared**—To view only shared tables.
- **Show multi-tenant**—To view only multi-tenant tables.

d) Select the **Show hidden** check box to view any hidden tables from the database.

e) Click **Apply Filter**. Based on your search criteria, the **Selected Tables** section lists the table names and displays the following columns:

Column name	Description
Schema	Displays whether the schema associated with the database table is public or user-defined. The default value is **PUB** which indicates that the default public schema is assigned to the OpenEdge database.
Table name	Displays the name of tables in an ascending alphabetical order.
Area	Displays the area in the database in which the table resides.
Multi-Tenant	Displays true for multi-tenant tables and false for shared tables.
Description	Displays details associated with the table name. This column is optional. To view this column, click any of the column's drop-down and select **Columns** > **Description** check box.

14. Select **Tenants** based on whether you access the database as a regular or a super user.

Note: In the case of multi-tenant database connections, you must provide either regular or super user credentials to dump or load tenant data. Refer to Manage users in a multi-tenant database on page 67. If you do not provide any credentials for database authentication, you can only dump or load default database tables.

- For regular tenant user credentials, **Tenants** displays a preselected radio button for the regular tenant and you can only dump contents from the table within that specific regular tenant.
- For super-tenant user credentials, **Tenants** displays two options for you to select and dump contents from the tables included within these tenants.
  - Choose **All** to select all regular tenants.

- Choose **Selected** to filter one or more tenants. Upon choosing Selected, the console displays the Selected Tenants section. You can enter either a keyword, the wildcard operator `*`, or a combination of the two in the **Tenant name** field. Click **Apply filter** to view the **Tenant name** and the **Description** in the respective columns. Use the check boxes to select or clear any of the tenant entries.

  Optionally, you can click the columns drop-down to select options such **Type**, **Id**, **External Id**, and **Data Enabled** to display the respective tenant properties. Similarly, you can clear the check box to remove any of the columns from the **Selected Tenants** view.

Note: The option for displaying tenants is not available for non-multi-tenant databases.

15. Click **Dump**. A confirmation dialog appears for table data dump displaying the number of shared and multi-tenant tables that will be dumped.
16. Do one of the following:

- Click **Commit** to dump contents of the selected tables. You can view status of such a task in the **Database Administration Tasks** page by selecting **Database Administration** > **View** > **Database Tasks**.
- Click **Commit & Monitor** to dump contents of the selected tables, and view the task page. This page lists the details of the dump activity performed.
- Click **Cancel** to exit the dumping process.

When this operation is successful, a contents (`.d`) file is created for each table in the dump directory you specify (in this case, the work directory `C:\OpenEdge\WRK`).

Dump group contents from a database

When you dump group contents using the Database Administration console, the `.d` file is created in a sub-directory of the work directory you specify. The default work directory is `C:\OpenEdge\WRK`.

To dump group contents:

1. In the management console menu, do one of the following:

   - Select **Database Administration** > **Dump** > **Group Contents (.d files)**.
   - Select **Database Administration** > **Go to Database Administration**. The **Database Administration** page appears.

     Filter or search for, and select the required database connection. The database connection home page appears.

     In the **Data Administration** section, click **Dump group contents (.d file)**.

   The **Dump Group Contents** page for the selected database connection appears.

2. In the **Database connection** field, enter a database connection name that contains the database into which you want to load the table contents. By default, the last used database connection name appears in the **Database connection** field.

   You can select another database connection by entering a database name in the **Database connection** field.

   Note: If you type the name of the database connection, follow the format used by OpenEdge Management to define a connection: *`AdminServer-name.database-name`*. A database server must be running for you to connect to the database.

You can also click the **Search** icon to choose a database for which you are creating the tenant from the **Connection Selection** dialog.

The **Connection Selection** dialog displays the connections details in a grid. You can perform the following:

- Filter the connections in the grid by **Connection name**, **AdminServer**, or **Category**.
- Select the column heading and click the drop-down to choose the order (ascending or descending alphabetically) for the connections to appear in the grid.

Note: When you select a database connection name, the **Database connection** field displays the selected database connection name. Most of the other fields get auto-populated with the default values, based on the selected database connection name.

---

3. In the **Dump root directory** field, specify a file path of the directory in which you want to store the contents (`.d`) file. By default, this field displays the work directory `C:\OpenEdge\WRK`.
4. Select **Include LOB** to enable exporting of large database objects, such as images. By default, this check box is selected.
5. In the **LOB sub-directory** field, specify a sub-directory name in which you want to store the large database objects. By default, this field displays `lobs` and this sub-directory is contained in the default work directory `C:\OpenEdge\WRK`.
6. In the **Code page** field, specify a value for code page. By default, this field displays `ISO8859-1`. For more information on code pages, see *Internationalize ABL Applications*.
7. In the **Group sub-directory** field, specify a sub-directory name in which you want to store group contents. By default, this field displays `groups` and this sub-directory is contained in the default work directory `C:\OpenEdge\WRK`.
8. In the **Character mapping** field, specify MAP or NO-MAP for character mapping. For more information about character mapping, PROTERMCAP, and national language support, see *Internationalize ABL Applications*.
9. Select the **Overwrite existing .d files** check box, to overwrite the existing dump (`.d`) file.
10. Select the **Do not dump secured tables** check box, if you do not want to dump secured tables.
11. Select the **Do not dump group tables** check box, if you do no want to dump group tables.
12. Select the **Do not validate code page** check box, to skip validating the value entered in the **Code page** field.
13. Select one of the following options for **Groups**:

Option	Description
All [4]	Dump contents from all groups. By default, this option is selected.
Selected	Dump content either from one or many groups. Selecting this option displays the **Selected Groups** section.

In the **Selected Groups** section, do the following:

[4] Databases that are not enabled for multi-tenancy do not have groups.

a) In the **Group name** field, enter a group name. You can specify a keyword, use the wildcard operator *, or a combination of both.

b) Click **Apply Filter**. Based on your search criteria, the **Selected Groups** section lists the group names and displays the following columns:

Column name	Description
Group name	Displays the name of groups in an ascending alphabetical order.
Schema	Displays whether the schema associated with the database group is public or user-defined. The default value is **PUB** which indicates that the default public schema is assigned to the OpenEdge database.
Table	Displays the table in the database with which the group is associated.
Is allocated	Displays true if space is allocated for objects in the group.
Description	Displays details associated with the group name. This column is optional. To view this column, click any of the column's drop-down and select **Columns** > **Description** check box.

14. Click **Dump**. A confirmation dialog appears for group data dump displaying the number of groups that will be dumped.
15. Do one of the following:

- Click **Commit** to dump contents of the selected groups. You can view the status of such a task in the **Database Administration Tasks** page by selecting **Database Administration** > **View** > **Database Tasks**.
- Click **Commit & Monitor** to dump contents of the selected groups, and view the task page. This page lists the details of the dump activity performed.
- Click **Cancel** to exit the dumping process.

When this operation is successful, a contents (`.d`) file is created for each group in the `groups` sub-directory of the dump directory you specify (in this case, the work directory `C:\OpenEdge\WRK`).

Tune multi-tenant database performance

There are two multi-tenant governors which you can use to improve the performance of multi-tenant databases. These governors limit each tenant's access to the shared database resources. These multi-tenant governors are:

- Login Governor
- Lock Governor

Note: These governors are applicable to only the default tenant and regular tenant; these governors do not apply to a super-tenant. Also, these governors do not apply to non multi-tenant databases.

The Login Governor (Tenant Max User Governor) specifies the maximum number of users that may login for each tenant. The Lock Governor (Tenant Lock Table Governor(%)) specifies the percentage of the lock table that any tenant can occupy. The database startup parameter for Tenant Max User Governor Login Governor is `-nGovernor` and for Tenant Lock Table Governor(%) is `-LGovernor.`

When a tenant attempts to acquire more locks than the governor allows, an error message is displayed as: Attempt to exceed tenant lock governor for tenant <tenantID>. Increase -L or -LGovernor.

When a user attempts to login to a database and the available maximum number of logins for that tenant has been exceeded, an error message is displayed as: Attempt to exceed tenant login governor limit for tenant <tenant ID>. Increase -n or -nGovernor.

The Database Administration console and the PROMON utility help you to monitor and change the governor values for these parameters.

To monitor and change the values of these multi-tenant governors using the Database Configuration page, see *Configure OpenEdge Components with OpenEdge Management*.

To monitor and change the values of these multi-tenant governors using the PROMON utility, see *Manage the OpenEdge Database*.

About viewing multi-tenant database areas, domains, schemas, tenants, and groups

Once you successfully set up a connection to a multi-tenant database, you can view its contents, specifically its areas, domains, schemas, tenants, and groups.

To view the multi-tenant database contents:

1. Ensure that the database server is running and that you have set up the database connection. (For more information, see Set up the connection on page 19.)
2. On the management console menu, select **Database Administration** > **Go to Database Administration**.

   The **Database Administration** page appears.
3. Filter or search for, and select the required database connection. The database connection home page appears.

   The database connection home page appears.

You can view domains, tenants, groups, areas, and schemas in the **Storage Management** section.

You can now click any of the selections to choose the details you want to view, as described in the following sections.

View areas

Select **View areas** to view all the areas configured for the database. The **Database Areas** page appears.

To see details about an area and its extents, select the area in the list. The **Database Area Extents** page appears.

The upper part of the pane provides information about the area. The lower part provides information about extents in a grid. The grid displays the extent number, the file name, the size, and used size of the extent, and whether the extent is fixed (true) or variable (false). You can sort each column to view the information in ascending or descending order. Click the column name and then on the drop-down arrow.

View domains

In the **Security Summary** section, select **Edit domains** to view the domains available for the database. The **Edit Database Domains** page appears.

To see a domain's details, select the domain in the list.

View schema

Select **View schemas** to view the schema for the database. The **Database Schema** page appears.

View tenants

Select **View tenants** to view the **Tenant List** page.

From the **Tenants** list, you can select a particular tenant and view its details.

To see tenant details, find a tenant, or filter tenants in the view from the **Tenant name** list, do one of the following:

- To see details about a tenant, select the tenant. The tenant home page appears.
- (For a super-tenant, no **Tenant data access** link is shown.)
- Click **Edit tenant** in the **Manage Tenant** section. The tenant's **General** details appears in the Edit Tenant page.

  From this page, you can view the tenant's users, domains, and partitions, as described in View tenant users on page 42, View tenant domains on page 42, and View and filter tenant partitions on page 43.

  You can also view a tenant's groups; for more information, see Use tenant groups on page 97.

View tenant users

You can view the list of a tenant's users; you can also add users to the tenant.

To see a list of users in the `_user` table for a tenant, select **Users** in the Edit Tenant page. To sort the information in the grid, click a column name and then click the drop-down arrow.

You can filter the list of users by entering a user name in the **User name** field, and then clicking the **Search** icon. You can expand the filter option to search for users using a User ID or Domain name.

You can also move forward or backward a page, or specify a particular page, in the list of users by using the **Page** feature at the bottom of the list.

For information about adding a user to a tenant, see Add a user to a tenant on page 51.

For information about setting up multi-tenant table security for users, see Manage multi-tenant database table security for users on page 73.

View tenant domains

You can view a list of a tenant's domains; you can also add a domain and establish domain security.

To see a list of domains that exist for a selected tenant, select **Domains** in the Edit Tenant page. From the list, select a particular domain. To sort the information in the grid, click a column name and then click the drop-down arrow.

You can filter the list of domains by entering the domain name in the **Domain name** field.

You can also move forward or backward a page, or specify a particular page, in the list of domains by using the **Page** feature at the bottom of the list.

For information about adding a domain for a tenant, see Add a tenant domain on page 50. For details about adding a domain to the database, see Manage domains in a multi-tenant database on page 70.

View and filter tenant partitions

From the tenant's general details, you can view more specific information about the tenant. You can also filter the details you see and use the predefined color-coding to provide a quick view of how partitions are allocated.

View partitions

To view details about a tenant's partitions, choose a tenant from the **Tenant name** list, and click **Edit tenant** in the **Manage Tenant** section of the Tenant home page. From the tenant details, click **Partitions**; the partition details appear by default in one or more area panels. The predefined pink color coding indicates that the allocation state for the partitions is **Not allocated**.

(For details about what different predefined colors represent, see Interpret the color legend on page 44.)

To switch from the area panels layout to a grid view, click the view grid icon on the top right corner. The partitions details appear.

From the grid view, you can sort by ascending or descending alphabetical order in each of the following columns: **Partition Name**, **Area**, **Allocation State**, object **Type**, or **Buffer Pool**. You can also choose to hide any of the columns you do not want to view, or move the order of the columns. (If you cannot see the entire grid, adjust the width of the columns in the grid. You can also adjust the width of the other columns in the management console.)

To change the order of items in any column, select the column name and click the drop-down arrow that appears. From the menu, select the sort order as well as which columns to include in the grid, as shown in the following figure.

To see details (in either layout) about the database schema from the **Partitions** view, expand the schema items as necessary; or select one of the partitions in the grid. The properties for the database object appear in the **Properties** pane.

The **Properties** pane allows you to focus on details for one particular object by identifying the object's name, type, the area where the object resides, buffer pool (primary or alternate), and the allocation state. (For more information about allocation state, see Allocate tenant partitions on page 46.)

Filter partitions for a tenant

You can filter the view of partitions by allocation state from a tenant.

You can also filter the view of partitions by allocation state from a tenant template. For more information, see Filter partitions from a tenant template on page 86.

To filter partitions by allocation state from a tenant:

1. From the tenant menu bar, click **Filter Partitions**. The filtering options appear.

All filtering options are selected by default. Click any option to toggle between selected and cleared.

2. Click **Apply filter** to implement the filtering.

Interpret the color legend

So that you can quickly identify partitions by allocation state, each state corresponds to a particular color.

To access the legend in the management console:

1. From the tenants list, select a tenant.
2. Click **Edit tenant** in the **Manage Tenant** section of the Tenant home page.
3. Choose **Partitions**.
4. From the tenant menu bar, choose **Tools** > **Legends**.

4

About Working with Tenants

Using OpenEdge Management, you can create a new tenant for a database enabled for multi-tenancy. You can also manage the tenant's users and domains and delete a tenant.

For details, see the following topics:

- Create a new tenant for a multi-tenant database
- Edit a tenant
- Add a tenant domain
- Add a user to a tenant
- Generate a tenant program from an existing tenant
- Delete a tenant
- Delete a tenant domain
- Delete a tenant user
- Enable a table for multi-tenancy
- Enable or disable access to tenant data
- Deallocate tenant tables

Create a new tenant for a multi-tenant database

Using the multi-tenancy configuration tool, you can create a new tenant for a database enabled for multi-tenancy. As you are creating the tenant, you can specify a schema storage area location for each type of multi-tenant database object (table, index, or LOB field). You can also determine if access to the tenant's data should be enabled or disabled.

Once you finish specifying all the tenant's settings, you can either:

- Create the tenant immediately.
- Generate a tenant configuration ABL program that you can use to create a tenant.

You can also create a new tenant from an existing tenant or from a tenant template. A tenant template defines common general and partition settings, making it easier for you to create the new tenant. For more information about working with tenant templates, see Use tenant templates on page 83.

Details related to creating the tenant and generating a tenant program are provided in the following sections.

Allocate tenant partitions

Creating a new tenant in an existing multi-tenant database results in the establishment of a new tenant partition for each existing multi-tenant object defined in the database. You can assign a specific storage area for each table, index, or LOB field, or you can use the previously defined default locations.

You can also specify if or when partitions should be allocated, as long as the following criteria exist:

- The tenant is a regular tenant. You cannot specify the area assignment or allocation setting for partitions for a default tenant or a super-tenant.
- The allocation rule for the tenant is either **Set new objects not to allocate space** or **Set new objects to delay space allocation**. If the rule is set to **Set new objects to allocate space on tenant creation**, partitions are created and allocated at the same time as the tenant is created. You will be unable to change the area assignment for a specific partition when you add a new database object.

  You might choose not to allocate space at all when creating a tenant. This can save space if the tenant is not going to be using all of the multi-tenant tables. For example, when a tenant will be using only a subset of the multi-tenant tables, you can delay space allocation for the unused tables. Similarly, you might not be finished making modifications to an object when you create a tenant and prefer not to allocate space now.

  For a shared object, you cannot choose **not** to allocate the object, so its allocation state is immediate. If default allocation is set to immediate, that setting is always applied on new tables (along with the table's indexes and the LOB fields). If the tenant's default allocation is set to delayed or none, then the table's allocation setting applies.

  When you set the allocation state for a table, the same state applies to its indexes and LOB fields.

Specify an alternate buffer pool

As you create a tenant, you can choose between using the primary buffer pool or the alternate buffer pool.

Note: Access to the alternate buffer pool feature requires an Enterprise database license. The feature is unavailable with a Workgroup or Personal database license.

The alternate buffer pool is a set of buffers in shared memory that are logically separate from the primary buffer pool. The alternate buffer pool gives the database administrator the ability to modify buffer pool behavior by designating objects or areas to consume buffers from the alternate buffer pool, rather than from the primary buffer pool.

Management of the buffers in the alternate buffer pool is independent of the primary buffer pool. Assigning specific database areas or objects to occupy buffers from the alternate buffer pool might improve your buffer hit rate, thereby reducing the need to read and write buffers to and from disk and possibly improving performance.

For each table, index, and LOB field, you can specify whether to use the primary or the alternate buffer pool.

Use a tenant configuration program

Using OpenEdge Management, you can create a tenant for a multi-tenant database. If you prefer, you can, as an alternative, set up the tenant's properties, generate a tenant creation ABL program based on those properties, and save the program so you can run it when you want. Generating the program alone does not create the tenant; you create the tenant when you run the generated program.

Similarly, if you have an existing tenant whose configuration you want to reuse, you can generate a tenant creation program from that tenant. You might also want to use the generated code as a template for writing your own tenant creation program within your own application.

Generating the program for a new or an existing tenant creates a `.p` file (procedure file) that you then use to create the tenant and all its settings, including partition assignments. If you are generating a program for an existing tenant, you can include domain and user information associated with the tenant. For a new tenant, domain and user details are not yet available in the database; therefore, no user or domain information is included in the program.

When you create and save a tenant program, you can then use that program to create a tenant with the settings you have defined. You can also modify a generated program before you run it.

Create a new tenant or tenant program

You can create a new tenant or create a tenant based on an existing tenant. You can also generate a reusable tenant ABL program for an online multi-tenant database. Before you begin, you must select a database connection, and the database server must be running, as described in Set up the connection on page 19.

You can also create a tenant from a tenant template. For more information, see Use tenant templates on page 83.

To create a new tenant or tenant program:

1. In the management console menu, choose one of the following:

   - Select **Database Administration** > **New** > **Tenant**.
   - On the management console menu, select **Database Administration** > **Go to Database Administration**. The **Database Administration** page appears.

     Filter or search for, and select the required database connection. The database connection home page appears.

     In the **Security Summary** section, click **Create tenant**.

   The **New Tenant** page appears.

2. Provide the following information:

- **Tenant name**—The name of the new tenant, which must be unique within the database. Do not use spaces or special characters such as an asterisk (*), ampersand (&), or period (.) in this field. You can include the underscore (_).
- **Description**—An optional description of the tenant.
- **External ID**—An optional ID. If you provide an external ID, you can later refer to the ID when you view the progress of transactions being committed.

3. Select the tenant type: **Regular** or **Super**. For more information about each tenant type, see Common terminology on page 14.
4. To enable access to the tenant's data, select the **Enable data access** option. If you do not select the option, data access is disabled for any user other than the super-tenant. For more information, see Enable or disable access to tenant data on page 57.
5. In the **Database connection** name, enter a database connection name to which you want to add the new tenant. By default, the last used database connection name appears in the **Database connection** field.

   Note: If you type the name of the database connection, follow the format used by OpenEdge Management to define a connection: *`AdminServer-name.database-name`*. A database server must be running for you to connect to the database.

   You can also click the **Search** icon to choose a database for which you are creating the tenant from the **Connection Selection** dialog.

   The **Connection Selection** dialog displays the connections details in a grid. You can perform the following:

   - Filter the connections in the grid by a **Connection name**, **AdminServer**, or **Category**.
   - Select the column heading and click the drop-down to choose the order (ascending or descending alphabetically) for the connections to appear in the grid.

6. If you are creating a super-tenant, go to Step 9 on page 49 .

   If you are creating a regular tenant, type the name of each of the following areas, and then continue with Step 7 on page 48 :

   - **Default data area**—The default storage location for the tenant's tables
   - **Default index area**—The default storage location for the tenant's indexes
   - **Default LOB area**—The default storage area for the tenant's LOB fields

   For each for the areas, you can either enter the storage area name in the default area field or click the **Search** icon to choose the storage area name from the **Area Selection** dialog.

   The **Area Selection** dialog displays the storage area names in a grid. You can perform the following:

   - Filter the storage area name in the grid by **Area name**, **Records per block**, or **Cluster size**.
   - Move forward or backward a page, or specify a particular page, in the list of domains by using the **Page** feature at the bottom of the list.
   - Select the column heading and click the drop-down to choose the order (ascending or descending alphabetically) for the area names to appear in the grid.

7. Choose one of the following object allocation rules for the regular tenant:

   - **Set new objects not to allocate space**—Allocate no space for the tenant's objects.
   - **Set new objects to allocate space on tenant creation**—Allocate storage space immediately.

- **Set new objects to delay space allocation**—Do not yet allocate storage space. (You can allocate space later when you are ready to do so.)

8. If you selected either **Set new objects not to allocate space** or **Set new objects to delay space allocation** in Step 7 on page 48, select one of the these options:

   - **Do not use template**—Select this option if you are creating a new tenant without using a template.
   - **Tenant**—Select this option if you are creating a tenant by using an existing tenant. You can type the tenant name in the field, or you can click the **Search** icon to open the **Tenant Selection** dialog.

     The **Tenant Selection** dialog displays the tenant details in a grid. You can filter the tenants in the grid by **Tenant name** or **External ID**.

     You can also move forward or backward the page, or specify a particular page, in the list of tenants by using the **Page** feature at the bottom of the grid.

     Note: You can select the column heading and click the drop-down to choose the order (ascending or descending alphabetically) for the tenants to appear in the grid.

   - **Template**—Select this option if you are creating a tenant by using an existing template. You can enter a template name in the field, or you can click the **Search** icon to open the Template Selection dialog. For more information about working with tenant templates, see Use tenant templates on page 83.

9. Choose one:

   - To create the tenant immediately, click **Create tenant**.

     If you are creating a regular tenant, the tenant home page appears. Click **Edit tenant** in the **Manage Tenant** section to see a set of vertical tabs consisting of the following selections in the left pane: **General, Partitions**, **Groups**, **Users**, and **Domains**.

     OpenEdge Management console submits an asynchronous task to the OpenEdge servers when you create a tenant in a database. You can view status of such a task in the **Database Administration Tasks** page by selecting **Database Administration** > **View** > **Database Tasks**.

     If you are creating a super-tenant, the tenant home page appears. Click **Edit Tenant** to see a set of vertical tabs consisting of the following selections in the left pane: **General**, **Users**, and **Domains**.

   - To create a tenant configuration script, click **Generate tenant program**. Select a location to save the `create_tenant.p` file.

Edit a tenant

You can make changes to a tenant from the database administration console. For example, you can add it to or remove it from a group, add users, or domains, and rename a tenant (when tenant is a part of a group).

If space for a tenant partition has not yet been allocated, you can alter the allocation state, change the area assignment, and select the buffer pool assignment. You can also enable or disable access to a tenant's data.

Note that:

- You cannot disable access to the tenant you belong to as a user.
- You cannot disable access for a super-tenant. A super-tenant does not have its own data.
- You can rename a regular or super-tenant.

- You can rename a tenant when it is part of a group.
- You cannot rename the default tenant.
- The allocation state you choose for a table applies also to its indexes and LOB fields.

To edit a tenant:

1. On the management console menu, select **Database Administration** > **Go to Database Administration**.

   The **Database Administration** page appears.
2. Filter or search for, and select the required database connection.

   The database connection home page appears.
3. In the **Storage Management** section, click **View tenants**.
4. Select the tenant you want to edit. The tenant details page appears.
5. Under **Manage Tenant**, click **Edit tenant**. The **Edit tenant** page appears.
6. In the **Tenant name** field, replace the existing tenant name with a new tenant name.
7. Choose the appropriate tab to make the changes you want:
   - **General**—You can enable or disable tenant data access; change the default data area, index area, or LOB area; and modify a table's allocation rule. (Note that the modification to the allocation rule affects only the unallocated partitions.)
   - **Partitions**—For each table or table object, you can modify the buffer pool assignment, choosing either **Primary** or **Alternate**. If the partitions have already been allocated, you cannot change the area or the allocation state.
   - **Groups**—You can add a group, or generate a tenant creation program. For more information, see Create a group or group program on page 98.
   - **Users**—You can add a user. For more information, see Add a user to a tenant on page 51.
   - **Domains**—You can add a domain. For more information, see Add a tenant domain on page 50.
8. Make the changes to the tenant; when you finish, click **Commit**.

   If you have renamed the tenant, the new tenant name appears on the list frame after you commit the changes.

OpenEdge Management console submits an asynchronous task to the OpenEdge servers when you edit a tenant in a database and commit the saved changes. You can view status of such a task in the **Database Administration Tasks** page by selecting **Database Administration** > **View** > **Database Tasks**.

Add a tenant domain

You can add one or more domains for a tenant by selecting from a list of predefined authentication systems that are configured for the database.

You can also add a domain to the database. For more information, see Manage domains in a multi-tenant database on page 70.

To add a domain:

1. On the management console menu, select **Database Administration** > **Go to Database Administration**.

   The **Database Administration** page appears.

2. Filter or search for, and select the required database connection.

   The database connection home page appears.

3. Under **Storage Management**, click **View tenants**.
4. Select the tenant for which you want to add a domain. The tenant details page appears.
5. Under **Manage Tenant**, click **Edit tenant**. The **Edit tenant** page appears.
6. Click **Domains**.
7. Click **New** in the tenant menu bar.
8. Provide the following information:

   - **Domain name**—Type the domain name (required). Do not use spaces or special characters such as an asterisk (*), ampersand (&), or period (.) in this field. You can include the underscore (_).
   - The domain name represents the logical name of a single authentication system (domain) that can be used to validate the authentication of a user account.
   - **Authentication system**—From the drop-down list, specify the type of authentication system. (The available types exist in the database in the _sec-authentication-system table.)
   - **Access code**—Type an access code for the domain.
   - The access code you type is then encrypted and used to validate the identity and integrity of any CLIENT-PRINCIPAL issued by the authentication system represented by this domain.
   - **Confirm access code**—Retype the access code.
   - **Description**—Provide a description (optional).
   - **Comments**—Provide comments (optional).
   - **Enabled**—Select the check box to indicate that the domain is enabled (meaning that a user can log in).
   - **Auditing context**—Provide the audit record context value.
   - **Runtime options**—Provide a comma-delimited list of runtime options for this domain.
   - **System options**—Provide the system option value.

9. Click **Commit**.

For more information about auditing and OpenEdge, see *Learn about Security and Auditing*.

Add a user to a tenant

You can add one or more users to a tenant. You can also add one or more users to the database. For more information, see Manage users in a multi-tenant database on page 67.

To add a user:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.

2. Filter or search for, and select the required database connection.

   The database connection home page appears.

3. Click **View tenants** in the **Storage Management** section.

   The **Tenant List** page appears.

4. Select the tenant for which you want to add a user.

   The tenant details page appears.

5. Click **Edit tenant** in the **Manage Tenant** section.

   The **Edit tenant** page appears.

6. Click **Users**.

7. Click **New** in the tenant menu.

8. Provide the following information for the new user:

   - **User name**—Type the user's name (required). Do not use spaces or special characters such as an asterisk (*), ampersand (&), or a period (.) in this field. You can include the underscore (_).
   - **Domain name**—Enter a domain name or click the **Search** icon to open the **Domain Selection** dialog to select a domain name (required).

     The **Domain Selection** dialog displays the details of the domains in a grid. You can search or filter the domains in the grid by **Domain name** or **Tenant name**.

     You can also move forward or backward the page, or specify a particular page, in the list of domains by using the **Page** feature at the bottom of the grid.

     Note: You can select the column heading and click the drop-down to choose the order (ascending or descending alphabetically) for the domains to appear in the grid.

   - **Password**—Type the user's password.
   - **Confirm password** —Retype the user's password.
   - **SQL Only**—Select the check box to indicate that the _user table record can be used only by a SQL connection to authenticate to the database.

     If the check box is enabled, ABL clients cannot authenticate to the database by using user ID and user name.

     If the check box is disabled, both SQL and ABL users can use the record.

   - **User number**—Provide a number to identify the user (optional). The number must be a positive integer.
   - **Description**—Provide a description (optional).
   - **Given name/Middle initial/Surname**—Provide the user's given name, middle initial, and surname (optional).
   - **Telephone**—Type the user's telephone number (optional).
   - **E-mail**—Type the user's email address (optional).

9. Click **Commit** in the tenant menu.

Generate a tenant program from an existing tenant

Generating a tenant program for an existing tenant creates a `.p` file (procedure file) that you then use to create the tenant and all its settings, including partition assignments. You can optionally include user and domain information associated with the tenant.

To generate a tenant program from an existing tenant:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.

2. Filter or search for, and select the required database connection.

   The database connection home page appears.

3. Click **View tenants** in the **Storage Management** section.

   The **Tenant List** page appears.

4. Select the tenant for which you want to generate a tenant program..

   The tenant details page appears.

5. In the **Manage Tenant** section, choose one:

   - Click **Generate tenant program**.
   - Click **Edit tenant**.

     From the tenant menu bar, select **Tools** > **Generate tenant program**

   You are prompted to save the `create_tenant.p` file. If you want to create more than one tenant program, provide a unique file name to prevent the overwriting of an existing `create_tenant.p` file.

6. Click **Save**.

Delete a tenant

You can delete a tenant, which also deletes the tenant's domains, users, and data, including partition information. Once you delete a tenant, any space that was used for that tenant's data becomes available.

You can delete a tenant and its users, domains, and data in one transaction, or you can delete each user and domain individually. You cannot delete a tenant if it is in use by the current database connection; in other words, you cannot delete a tenant for which you are a user.

Note: The default tenant cannot be deleted.

To delete a tenant:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.
2. Filter or search for, and select the required database connection.

   The database connection home page appears.
3. Click **View tenants** in the **Storage Management** section.

   The **Tenant List** page appears.
4. Select the tenant for which you want to delete.

   The tenant details page appears.
5. In the **Manage Tenant** section, click **Delete tenant** and then click **Yes** to confirm deletion.

   Caution: When you delete a tenant from the database, all domains, users, sequence current values, and data for the tenant will also be deleted. Should you want to restore the tenant in the future, you can do so only from a backup. Therefore, it is strongly recommended that you back up a tenant before you delete it.
6. Click **Commit**. You can view status of such a task in the **Database Administration Tasks** page by selecting **Database Administration** > **View** > **Database Tasks**.

Delete a tenant domain

You can delete a tenant domain from the database using the **Edit Tenant** details page. You can also delete a domain from the **Edit Database Domains** page: see Manage domains in a multi-tenant database on page 70.

To delete a tenant domain

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.
2. Filter or search for, and select the required database connection.

   The database connection home page appears.
3. Click **View tenants** in the **Storage Management** section.

   The **Tenant List** page appears.
4. Select the tenant for which you want to add a user.

   The tenant details page appears.
5. Click **Edit tenant** in the **Manage Tenant** section.

   The **Edit tenant** page appears.
6. Click **Domains**.

   The list of tenant domains appear in a grid.
7. From the list of tenant domains, select a tenant domain that you want to delete from the database.
8. Click **Delete** and then click **Yes** to confirm deletion.

Delete a tenant user

You can delete a tenant user from the database using the **Edit Tenant** details page. You can also delete a user from the **Edit Database Users** page: see Manage users in a multi-tenant database on page 67.

To delete a tenant user

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.
2. Filter or search for, and select the required database connection.

   The database connection home page appears.
3. Click **View tenants** in the **Storage Management** section.

   The **Tenant List** page appears.
4. Select the tenant for which you want to add a user.

   The tenant details page appears.
5. Click **Edit tenant** in the **Manage Tenant** section.

   The **Edit tenant** page appears displaying the tenant details.
6. Click **Users**.

   The list of tenant users appear in a grid.
7. From the list of tenant users, select a tenant user that you want to delete from the database.
8. Click **Delete** and then click **Yes** to confirm deletion.

Enable a table for multi-tenancy

From the management console, you can choose one or more tables not enabled for multi-tenancy, and enable them. You can then make decisions about partition allocation for the table or tables that have not yet been allocated. The allocation state you choose for a table applies also to the table's indexes and LOB fields. When you enable a table for multi-tenancy, you are affecting all tenants for a selected database.

Note: A table must be in a Type II area in the database to be enabled for multi-tenancy. If a table, or any of its indexes or LOB fields, is not in a Type II area, you cannot enable the table for multi-tenancy.

In such a situation, the Notes column will identify which table, index, or LOB field is not in a Type II area, so you can correct the issue and then enable the table as multi-tenant.

Select one or more tables to enable for multi-tenancy

You can easily identify tables not enabled for multi-tenancy in a database connection. The tables appear in a list, and you can select one or more of the tables that you want to enable.

To select a table for enabling as multi-tenant:

1. Select **Database Administration** > **Configure** > **Enable Multi-tenancy for Tables** in the management console menu.

   The **Enable Multi-tenancy for Tables** page appears

2. In the **Database connection** field, enter a database connection name.

   By default, the last used database connection name appears in the **Database connection** field.

   Note: If you type the name of the database connection, follow the format used by OpenEdge Management to define a connection: *AdminServer-name.database-name*. A database server must be running for you to connect to the database.

   You can also click the **Search** icon to choose a database for which you are creating the tenant from the **Connection Selection** dialog.

   The **Connection Selection** dialog displays the connections details in a grid. You can perform the following:

   - Filter the connections in the grid by **Connection name**.

     You can also select the drop down arrow beside the **Search** icon to filter the connections by **AdminServer**, or **Category**.

   - Select the column heading and click the drop-down to choose the order (ascending or descending alphabetically) for the connections to appear in the grid.

3. From the list of tables, select one or more tables, or click the **Select All** check box to select all the tables listed in the page.

4. Click **Preview** to make partition allocation decisions, by tenant, for the tables now enabled for multi-tenancy. The schema selection page appears.

5. Select a tenant in the **Tenants** list. (Note that only regular tenants are listed.)

6. Expand the **PUB** node under **Schema Selections**, and expand the table you have enabled for multi-tenancy to view its schema.

   Note that the schema shown in the area panels includes the full schema for the database, not just the schema for the newly enabled tables.

7. Select a table whose area or allocation state you are able to modify, and make the changes to the tenant partition area or the allocation state in the **Properties** pane. If space for a partition has already been allocated, you cannot make changes.

8. Click **Commit** to save the changes. The **Confirm commit enabling multi-tenancy** dialog appears.

9. Choose from the following options:

   - To commit the changes, click **Commit**.
   - To cancel the changes, click **Cancel**.
   - To force allocation of new partitions that otherwise would not be allocated, select that option. This allows you to force allocation of partitions that otherwise would not be allocated when the changes are saved. This option overrides a tenant's default allocation for new partitions, but any changes applied to individual partitions will also be allocated if you select this option.

     If you select this option, you have an additional choice to make between the following two selections:

     - **Force allocation of all partitions with an allocation state of Delayed** — Forces allocation of partitions whosedefault allocation setting is to delay.

     - **Force allocation of all partitions with an allocation state of Delayed or None** — Forces allocation of all partitions whose default allocation setting is to either delay or not allocate space at all.

For example, if a tenant has an object allocation default of no allocation **(None)** and a partition for the tenant is changed to delay allocation **(Delayed)**, this partition will be allocated if **Force allocation** is specified. If a tenant has its default allocation set to delay and a partition is changed to no allocation, the partition will be allocated only if **Force allocation** is selected.

Note that it may take some time to commit the changes to the database. The length of time may vary, depending on the complexity of the changes (the number of tables converted to multi-tenancy, for example) as well as the number of existing tenants in the database.

The dashboard appears and displays a viewlet that allows you to monitor the status of the task. For more information, see Monitor data definition file updates to the database on page 66.

Enable or disable access to tenant data

You can enable or disable access to a regular tenant. You cannot disable access to a default tenant or a super-tenant; a super-tenant does not have its own data and can access data that other tenant types might not be able to access.

From the tenant home page, you can:

- Determine if a tenant's data is accessible.
- Disable or enable access to the tenant data.

You can also create a tenant whose data access is either enabled for disabled. For more information, see Create a new tenant for a multi-tenant database on page 46.

You cannot disable access to a tenant for which you are a user.

Determine if tenant data access is enabled

From the tenant home page, you can determine at a glance if the tenant's data is accessible.

To determine if a tenant's data access is enabled:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.
2. Filter or search for, and select the required database connection.

   The database connection home page appears.
3. Click **View tenants** in the **Storage Management** section.

   The **Tenant List** page appears.
4. Select the tenant for which you want to manage tenant data access.

   The tenant details page appears.
5. Review the **Tenant data access** status in the **Manage Tenant** section, which is either **enabled** or **disabled**.

For information about changing the data access status from enabled to disabled or vice versa, see Enable or disable access on page 58.

Enable or disable access

From the tenant home page, you can enable or disable access to a tenant's data. You cannot disable a tenant for which you are a user.

To enable or disable access to a tenant's data:

1. On the management console menu, select **Database Administration**. The **Database Administration** page appears.
2. Select the database connection. You can filter or search for the required database connection. The database connection home page appears.
3. Under **Storage Management**, click **View tenants**.
4. Select a tenant for which you want to manage tenant data access. The tenant details page appears.
5. Under **Manage Tenant**, review the **Tenant data access** status, which is either **enabled** or **disabled**.
6. To change the status, click the **Tenant data access** link. Click **Yes** to confirm the decision. The **Tenant data access** status is updated to reflect the confirmation.

Deallocate tenant tables

You can deallocate a multi-tenant table from a tenant or a group. Deallocation can be helpful in freeing up storage space so that it is available for reuse.

If you are logged in as a user to a regular tenant, you can deallocate one or more tables from the tenant. If you are logged in as a user to a super-tenant, you can deallocate a table for a group or another tenant in the database.

If you attempt to deallocate a tenant table and the table is in use, deallocation waits for the table to be available.

Note: Keep in mind that when you deallocate a multi-tenancy-enabled table's partitions, all data in the table is deleted. For this reason, it is advised that you back up a tenant before you deallocate its contents.

Deallocating a tenant table from the tenant

To deallocate a tenant table from the tenant:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.
2. Filter or search for, and select the required database connection.

   The database connection home page appears.
3. Click **View tenants** in the **Storage Management** section.

   The **Tenant List** page appears.
4. Select the tenant whose table you want to deallocate.

   The tenant details page appears.
5. Under **Data Administration**, click **Deallocate tables**.

The **Deallocate Tenant Tables** page appears and provides the table details: **Table**, **Area**, **Allocation State**, **Status**, and **Comments**. You can filter the tables which appear in the grid by a table name. Enter a table name in the **Table name** field and click on the **Search** icon. The grid displays the tables that match the entered criteria.

You can also move forward or backward a page, or specify a particular page, in the list of tables by using the **Page** feature at the bottom of the list.

Note: You can select the column heading and click the drop-down to choose the order (ascending or descending alphabetically) for the tables to appear in the grid.

---

6. Select one or more individual tables to be deallocated, or click the **Select All** check box. A warning message appears.
7. To continue, click **Yes**; to cancel the deallocation, click **No**. If you click **Yes**, you see one of the following statuses, depending on the deallocation progress:
   - If the deallocation has completed, you see the following confirmation evidence: The **Allocation state** changes to **None**; the **Status** changes to **Done**; and **Task completed successfully** appears in the comments for that table.
   - If the deallocation is in progress, you see a notation that the **Background task has been submitted**.
   - If the deallocation has timed out, you see the comment **Check the logs in the task list**. Note that the progress of the task is verified at five-second intervals, up to a maximum of ten minutes.

Deallocating a tenant table from a group

To deallocate a tenant table from a group:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.
2. Filter or search for, and select the required database connection.

   The database connection home page appears.
3. Under **Storage Management**, click **View groups**.
4. Select the group whose table you want to deallocate.

   The group details page appears.
5. Under **Mange Group**, click **Edit group**. The **Edit Group** page appears.
6. Select **Tools** > **Deallocate group**.

   The table partitions are deallocated.

5

About Updating Tenant Schema

As you work with databases enabled for multi-tenancy, you may find that you need to update the database's schema, modify the area assignments for a regular tenant's data, and save the changes. Using the multi-configuration tool, you can load and preview a data definition file and then commit the updates to the database, or you can skip the preview and just commit the changes.

For details, see the following topics:

- Upload schema for a multi-tenant database
- Configure an area working set
- Edit storage area assignments for regular tenants
- Commit changes to a multi-tenant database
- Monitor data definition file updates to the database

Upload schema for a multi-tenant database

As you work with a multi-tenant database, you may find that you need to update its schema. For example, consider the situation in which you have a multi-tenant application in production, serving tenants, and you want to update the application with additional functionality. If the application update also requires you to update the database schema, you can do this while the database is online by loading the data definition (`.df`) file that contains the schema modifications.

Once you load the data definition file, you can optionally preview the file's contents before applying the changes to the database. If you prefer, you can commit the changes without reviewing the preview.

Note that for the data definition file to upload correctly, its contents must be properly formatted.

Select and load the data definition file

You can select and load a data definition file from the **Load Data Definitions (.df)** page.

1. On the management console menu, choose one of the following:
   - Select **Database Administration** > **Load** > **Data Definitions (.df file)**
   - Select **Database Administration** > **Go to Database Administration**.The **Database Administration** page appears.

     Filter or search for, and select the required database connection. The database connection home page appears.

     In the **Data Administration** section, click **Load data definitions (.df file)**.
2. Click **Browse** to locate the file you want to upload.

   The file name appears in the **Data definitions (.df file)** field.
3. Select an available database connection from the **Database connection** drop-down list. (Note that a database server must be running for you to connect to the database.)
4. Choose one:
   - Choose **Commit**. The **Confirm Commit database definitions** dialog appears. For more information about this dialog, see Commit changes to a multi-tenant database on page 65.
   - Click **Preview**. The changes are uploaded to the server and the preview appears, as described in Preview the contents of an uploaded data definition file on page 62.

Preview the contents of an uploaded data definition file

When you load a data definition file, you can preview the changes contained in the file before you commit the changes to the database. The data definition preview reveals various details about an uploaded data definition.

The preview allows you to see the updates present in the file and make modifications before you commit the updates. The predefined color coding allows you to tell the allocation state at a glance. In the following figure, the color pink indicates that the area's partitions are not allocated.

The data definition file preview includes the following information:

- **Data Definitions**—A tree view list of the contents of the data definition file, along with a notation about which objects in the file have changed, and in what way. The notation can be **ADD**, **DELETE**, or **MODIFY**, or a combination of these, and appears after the object name in the display.

  Only those multi-tenant objects that require or are affected by partition assignments appear in the tree view, since those are the only objects you can modify in the console. (However, any and all changes that are included in the data definition file are uploaded.) Consider the following typical updates, how the updates affect partition assignments, and how the updates will appear in the tree view list:
  - The addition of a table requires partition information for each tenant; therefore, the name of the new table appears in the list and is followed by **ADD**.
  - A data definition file might drop and re-add an index in order to change the fields that the index comprises. In such an instance—in which two actions relate to one object—both actions follow the object (the index name, for example) and are separated by a comma, as in **DELETE,ADD**.

- Any changes to LOB fields are listed. Changes to any other type of field do not appear in the tree view since they do not affect partitioning.
- A deleted object is shown with the notation **DELETE**.
- An object whose details change (other than **ADD** or **DELETE**) is marked by the notation **MODIFY**.
- The drop of a table, index, or LOB field is shown, since the drop causes a removal of partition information from the database. In this case, the name of the table, index, or LOB field is followed by **DELETE**.

- **Areas Assignments**—A list of current storage area assignments for each object of the selected tenant as well as each area for any area assignment referenced by a schema object. You can select multiple partitions, and simply drag them from one area and drop them on another area.
- **Properties** —Details about a schema object you select in the **Data Definitions** tree view or a partition object you select in a storage area.

  When you select a schema object, details can include:

  - **Name**—The name of the object selected in the tree view list
  - **Default area**—The area assigned
  - **Multi-tenant**—Whether the object is enabled for multi-tenancy
  - **Keep default area**—Whether to keep the data in the default tenant upon upload
  - **Tenant partition area**—The area where the tenant partition resides
  - **Allocation state**—The partition allocation status, which identifies whether space has been allocated for the partition and when it will be allocated

  For a sequence, the following details appear:

  - **Name**—The name of the sequence
  - **Multi-tenant**—Whether the sequence is enabled for multi-tenancy. (If it is, the check box is selected.)
  - **Initial value**—The current value of the sequence.
  - **Increment by**—A positive or negative integer value with which you want to change the sequence value at each increment.
  - **Sequence minimum value**—An integer value that represents the lower limit of the sequence.
  - **Upper limit**—An integer value that represents the upper limit of the sequence.
  - **Cycle at Limit**—Whether a cycling sequence has been activated (**true**) or not (**false**)

  When you select a partition object, details include:

  - **Name**—The name of the object selected in the area
  - **Type**—The type of object (table, LOB field, index)
  - **Area**—The area where the object resides
  - **Buffer Pool**—The chosen buffer pool, either primary or alternate.
  - **Allocation state**—The partition allocation status, which identifies whether space has been allocated for the partition or when it will be allocated

- **Tenants**—A list of tenants in alphabetical order. By default, the first tenant is selected. If you have viewed the tenant already, a green indicator appears in the upper-left corner of the tenant name. If you have altered the tenant through the loading of a data definition file, a red indicator appears instead in the upper-left corner of the tenant name.

Configure an area working set

You can review a tenant's area layout in the detail frame. As you work with tenants and upload and commit schema changes, you might find that you cannot see all the database areas at one time. To remedy this, you can configure an area working set, which allows you to specify which areas you want to see in the tenant area layout. This option is useful when you are working with multi-tenancy tables with an allocation status of delayed or none.

To configure an area working set:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.

2. Filter or search for, and select the required database connection.

   The database connection home page appears.

3. Click **View tenants** in the **Storage Management** section.

   The **Tenant List** page appears.

4. Select a tenant for which you want to configure an area working set.

   The tenant details page appears.

5. Click **Edit tenant** in the **Manage Tenant** section.

   The **Edit Tenant** page appears.

6. Click **Partitions** > **Configuring working areas**.

   The **Select Working Areas** dialog appears and presents a list of all of the Type II areas in the database and the number of partitions currently assigned to that area. (Areas already being shown are preselected.)

7. Click the check box for each area or click the **Select All** check box to select all the areas listed in the dialog box to appear in the area layout .
8. Click **Save** and **Close** when you finish.
9. Click **Partitions** to scroll in the area layout and see all the areas you chose to include in the working set.
10. To save the areas you added to the working set, click **Commit** in the tenant menu bar. (Note that any other pending transactions will also be committed at this time.)

Edit storage area assignments for regular tenants

Once you preview the schema changes present in an uploaded data definition file—but before you commit those changes—you can optionally modify the area assignments for a regular tenant's data provided the object allocation space is not specified to be set immediately. In this case, you cannot modify area settings.

The allocation state is indicated by both the **Allocation state** choice in the **Properties** and the predefined yellow color coding in the area panels.

The properties also indicate that the default area is being kept. The **Keep default area** option is available when you are converting from a shared table to one enabled for multi-tenancy. If you select the option when you create a multi-tenant table, the original table data is not deleted and is retained for the default tenant in the new table.

If you did not select the **Keep default area** option, a new partition will be created for the default tenant for that shared table in the area specified by the values in the data definition file.

You can edit the area assignment from the drop-down in the **Properties** pane before you commit the updates contained in the uploaded data definition file. If you want to move **Terms8** from Area 100 to Area 101, for example, you can simply drag it from one area and drop it on another area. You can also drag and drop from the **Data Definitions** tree view to one of the areas.

Commit changes to a multi-tenant database

You can upload a data definition file, preview its contents, make storage area modifications, determine when to allocate partition space, and then commit all the changes. As you do so, you can configure one or more tenants and then commit the changes all at once, rather than needing to commit the updates for each tenant individually.

To commit changes to the database:

1. From the data definition file preview page, click **Commit** in the tenant menu bar (located above the list of tenants). The **Confirm commit database definitions** dialog appears.

   The dialog shows the task name, which is the name given to the transaction you are committing. You can later use the task name to verify that the transaction has been applied once you commit the changes.

   If you want, you can modify the task name. By default, the given task name includes the name of the AdminServer and database (`nbbedaspauldi.LocalScr`), the type of transaction being committed (`load database definitions`), and the name of the uploaded data definition file (`terms8.df`).

2. Select from the following options:

   - **Add new objects online**—Allows you to make the following changes while the database is online:
     - Add new sequences.
     - Add new tables, along with any associated fields, indexes, and database triggers (which must be added within the same transaction).
     - Add new fields to an existing table. (Note that you cannot define ASSIGN triggers for new fields while the database is online.)
     - Add new inactive indexes to an existing table.
   - **Add all new multi-tenant tables as shared tables**—Informs the load process to ignore any allocation settings for multi-tenant tables. Therefore, if a data definition file contains the MULTI-TENANT or KEEP-DEFAULT-AREA setting for a table, multi-tenancy settings are ignored and all objects become shared objects.

     In addition, any modification described in the data definition file that would cause the table to become a multi-tenant table is ignored. (Once you enable multi-tenancy for a table you cannot disable it. You would then need to dump and reload the table.) Note that this does not apply to the addition of indexes and fields for existing tables. If an index or a table is being added to an existing multi-tenant table, the table or index is added as a multi-tenant schema object to that table.

     Enabling this option can be useful, for example, if you are loading data definitions to a table that is not enabled for multi-tenancy or if you want to defer storage space allocation, particularly if you have many tenants with immediate allocation selected.

- **Force allocation of new partitions that otherwise would not be allocated**—Allows you to force allocation of partitions that otherwise would not be allocated when the data definition file is loaded. This option overrides the tenant's default allocation for new partitions, but changes applied to individual partitions will also be allocated if you select this option.

  If you select this option, you have an additional choice to make between the following two selections:

  - **Force allocation of all partitions with an allocation state of Delayed**—Forces allocation of partitions for tenants that are created as part of the uploaded data definition file and whosedefault allocation setting is to delay.
  - **Force allocation of all partitions with an allocation state of Delayed or None**—Forces allocation of all partitions created as part of the uploaded data definition file. This includes those whose default allocation setting is to either delay or not allocate space at all.

  For example, if a tenant has an object allocation default of no allocation **(None)** and a new partition for the tenant is changed to delay allocation **(Delayed)**, this partition will be allocated if **Force allocation** is specified. If a tenant has its default allocation set to delay and a partition is changed to no allocation, the partition will be allocated only if the **Force allocation of all partitions** option is selected. Note that the forced allocation option also applies to new indexes and LOB fields added to existing multi-tenant tables.

- **Add new indexes in deactivated state**—Allows you to add in a deactivated state all new indexes that are described in the data definition file. This option applies to indexes on both shared and multi-tenant tables; enabling the option can save processing time if the loaded data definition file adds new indexes to tables that contain a large amount of data.
- **Commit changes even when errors are encountered during load**—Specifies that the load of definitions should continue, even if some definitions result in errors that prevent those definitions from being applied to the database. Note that selecting this option might leave the database in a corrupt state. If you have selected the **Add new objects online** option, this option is invalid and, therefore, unavailable.

3. Click **Commit** to commit the transactions. The data definitions from the data definition file are applied to the database, partition assignments are made, and allocation settings are applied.

The **Dashboard** page opens and displays a viewlet that allows you to monitor the status of the load data definition file task by either the default name or the name you assigned using the **Task name** field. For more information, see Monitor data definition file updates to the database on page 66.

Monitor data definition file updates to the database

Once you commit transactions to the database, you can view status of such a task in the **Database Administration Tasks** page by selecting **Database Administration** > **View** > **Database Tasks**.

6

About Managing Users and Domains in a Multi-tenant Database

You can work with users and domains in tenants and in the database by using the multi-tenancy configuration tool.

For details, see the following topics:

- Manage users in a multi-tenant database
- Manage domains in a multi-tenant database
- Manage authentication systems
- Manage multi-tenant database table security for users
- Configure database security options
- Configure database security administrators
- Review user access in the Data Administration Console

Manage users in a multi-tenant database

You can create and delete users, and you can make changes to several user-related fields. You can also add users to a particular tenant. For more details, see Add a user to a tenant on page 51.

You cannot modify the User ID, User name, or Domain name. You can modify the password only if you are the user/password owner.

Note: As you work with a multi-tenant database, you may find that access to some features or operations is disabled, possibly due to the user permissions defined in the database. For more information about user permissions, see Manage multi-tenant database table security for users on page 73.

Add a user to a multi-tenant database

To add a user to a multi-tenant database:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.

2. Filter or search for, and select the required database connection.

   The database connection home page appears.

3. Click **Edit users** in the **Security Summary** section.

   A list of existing database users appears in a grid in the **Edit Database Users** page. If you have a large number of users, you can move forward or backward a page, or specify a particular page, in the list of users by using the **Page** feature at the bottom of the list.

   The list provides the following details:

   - **User ID**—The ID assigned to the user.
   - **User Name**—The user name.
   - **Domain Name**—The domain to which the user belongs.
   - **SQL Only**—If this option is enabled, the `_user` table record can be used only by a SQL connection to authenticate to the database. ABL clients cannot authenticate to the database by using user ID and user name.

     If the option is disabled, both SQL and ABL users can use the record.
   - **Description**—Provide a description or notes about a particular user.

4. Click **New**.

5. Provide the following information for the new user:

   - **User name**—Type the user's name (required). Do not use spaces or special characters such as an asterisk (*), ampersand (&), or a period (.) in this field. You can include the underscore (_).
   - **Domain name**—Enter a domain name or click the **Search** icon to open the **Domain Selection** dialog to select a domain name (required).

     The **Domain Selection** dialog displays the details of the domains in a grid. You can search or filter the domains in the grid by **Domain name** or **Tenant name**.

     You can also move forward or backward the page, or specify a particular page, in the list of domains by using the **Page** feature at the bottom of the grid.

     Note: You can select the column heading and click the drop-down to choose the order (ascending or descending alphabetically) for the domains to appear in the grid.

   - **Password**—Type the user's password.
   - **Confirm password** —Retype the user's password.

- **SQL Only**—Select the check box to indicate that the _user table record can be used only by a SQL connection to authenticate to the database.

  If the check box is enabled, ABL clients cannot authenticate to the database by using user ID and user name.

  If the check box is disabled, both SQL and ABL users can use the record.

- **User number**—Provide a number to identify the user (optional). The number must be a positive integer.
- **Description**—Provide a description (optional).
- **Given name**/**Middle initial**/**Surname**—Provide the user's given name, middle initial, and surname (optional).
- **Telephone**—Type the user's telephone number (optional).
- **E-mail**—Type the user's email address (optional).

6. Click **Save**.

Modify a user in a multi-tenant database

To modify a user in a multi-tenant database:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.

2. Filter or search for, and select the required database connection.

   The database connection home page appears.

3. Click **Edit users** in the **Security Summary** section.

   A list of existing database users appears in a grid in the **Edit Database Users** page. If you have a large number of users, you can move forward or backward a page, or specify a particular page, in the list of users by using the **Page** feature at the bottom of the list.

4. Select a user and make the modifications.
5. Click **Save**.

Delete a user from a multi-tenant database

To delete a user from a multi-tenant database:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.

2. Filter or search for, and select the required database connection.

   The database connection home page appears.

3. Click **Edit users** in the **Security Summary** section.

A list of existing database users appears in a grid in the **Edit Database Users** page. If you have a large number of users, you can move forward or backward a page, or specify a particular page, in the list of users by using the **Page** feature at the bottom of the list.

4. Select the user you want to delete from the database, and click **Delete**.
5. Click **Yes** to confirm the deletion.

Manage domains in a multi-tenant database

You can work with domains in tenants and in the database by using the Database Administration Console. You can do the following:

- View and filter the existing domains
- Create a domain
- Edit a domain (including renaming a domain)
- Delete a domain (only if the domain has no users)

You can also edit existing authentication systems or create your own. You can also add domain users to a particular tenant. For more details, see Add a tenant domain on page 50.

View and filter database domains

To view and filter the database domains:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.
2. Filter or search for, and select the required database connection.

   The database connection home page appears.
3. Under **Security Summary**, click **Edit domains**. The **Edit Database Domains** page with a list of existing database domains appears.

   The database domains grid provides the following details:

   - **Domain Name**—The domain to which the tenant belongs.
   - **Authentication System**—The authentication system; for example, **Internal** or **LDAP**.
   - **Tenant Name**—The tenant that the domain belongs to.

     Note that you can select the column heading and click the drop-down to choose the order (ascending or descending alphabetically) in which the items appear. This allows you to see which tenants belong to a particular domain.
   - **Enabled**—Whether the domain is currently enabled.

   You can filter the database domains which appear in the grid by a **Domain name** or **Tenant name**. Filtering allows you to focus only on the database domains for a particular tenant.

   You can also move forward or backward the page, or specify a particular page, in the list of domains by using the **Page** feature at the bottom.

Add a domain to a multi-tenant database

To add a domain to a multi-tenant database:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.

2. Filter or search for, and select the required database connection.

   The database connection home page appears.

3. Under **Security Summary**, click **Edit domains**. The list of existing database domains appear in a grid.
4. Click **New**.
5. Enter a new domain name in the **Domain name** field.
6. Click the drop-down arrow in the **Authentication system** field; select one of the predefined options.
7. Click the tenant name's **Search** icon; select a tenant from the **Tenant Selection** dialog, and click **OK**.
8. Type a code in the **Access Code** field. Re-type the access code in the **Confirm access code** field.
9. Enter a description or comments in the fields provided (optional).
10. If you want to disable the domain, clear the **Enabled** check box.

    Note: The **Enabled** check box is selected by default.

11. Enter the audit record context value in the **Audit Context** field (optional).
12. Enter a comma-delimited list of runtime options for the domain in the **Runtime options** field (optional).
13. Enter the system option value in the **System options** field (optional).
14. Click **Commit**.

Modify a domain in a multi-tenant database

To modify a domain in a multi-tenant database:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.

2. Filter or search for, and select the required database connection.

   The database connection home page appears.

3. Under **Security Summary**, click **Edit domains**. A list of existing database domains appears.

   You can move forward or backward a page, or specify a particular page, in the list of domains by using the **Page** feature at the bottom of the list.

4. Select the domain you want to modify, and make the changes. If you want to rename a domain, replace the existing name with a new name in the **Domain name** field.
5. Click **Save**.

If you rename a domain associated with a tenant, the new domain name appears on the list frame for **Domains** after you save your changes.

Note: You cannot rename a domain associated with a default tenant.

Delete a domain from a multi-tenant database

To delete a domain from a multi-tenant database:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.
2. Filter or search for, and select the required database connection.

   The database connection home page appears.
3. Under **Security Summary**, click **Edit domains**. A list of existing database domains appears.
4. Select the domain you want to delete from the database, and click **Delete**.

   Note: You cannot delete a domain if it has users.
5. Click **Yes** to confirm the deletion.

Manage authentication systems

You can manage authentication systems using the multi-tenancy configuration tool. You can use a built-in authentication system, you can create a new authentication system, you can integrate with an ABL-based user authentication plug-in, and you can delete an authentication system as long as no existing domains reference it.

You cannot edit a built-in authentication system.

Add an authentication system

To add an authentication system:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.
2. Filter or search for, and select the required database connection.

   The database connection home page appears.
3. Click **Edit authentication systems** in the **Security Summary** section.

   The **Edit Database Authentication Systems** page appears with a list of existing authentication systems:

   You can move forward or backward a page, or specify a particular page, in the list of domains by using the **Page** feature at the bottom of the list.

4. Click **New**.
5. Type a name of the authentication system in the **Name** field.
6. Provide a description or comments (optional).
7. Type the path of the callback procedure name in the **Callback** field. The callback procedure file must be a `.p` or `.r` file.

   Note: The callback procedure file contains the user authentication function which is implemented using the ABL-based authentication plug-ins. For details about the ABL authentication plug-ins, see *OpenEdge Programming Interfaces*.

   For the built-in domain types, the **Enabled authentication** and the **Checksum** check boxes are disabled by default. For the user-defined domain types, the check boxes get enabled and selected automatically, when you start typing the callback procedure name in the **Callback** field.

   Note: The callback procedure must be a compiled version for enabling **Checksum** field.

8. Click **Save**. The new authentication system appears in the list.

Delete an authentication system

To delete an authentication system:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.

2. Filter or search for, and select the required database connection.

   The database connection home page appears.

3. Under **Security Summary**, click **Edit authentication systems**. A list of existing database authentication systems appears.
4. Select the authentication system you want to delete, and click **Delete**.

   Note: You cannot delete an authentication system if there are existing domains that reference it.

5. Click **Yes** to confirm the deletion. The authentication system is removed from the list.

Manage multi-tenant database table security for users

As you work with users in the database, you can define what types of operations the users can perform on tables and fields enabled for multi-tenancy. You can also review at a glance the security settings you have established for the users.

To define security for one or more tables and fields:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.

2. Filter or search for, and select the required database connection.

   The database connection home page appears.

3. Under **Security Summary**, click **Edit data security**. The schema appears in the list frame, and the list of tables for the database you selected appears.

4. To view or modify permissions for a table or field, select the table or field in the schema.

   A list of current user permissions for the selected table or field appears in a permission panel for each of the following options. The default for each permission is an asterisk (*), indicating that the permission is currently in place for all users.

A user granted this permission . . .	Can . . .
Can-read	Read a table or field.
Can-write	Write to a table or field.
Can-create	Create new records in a table. To create a new record, users must also have Can-write privileges.
Can-delete	Delete records from a table.
Can-dump	Dump database or table definitions and data with triggers disabled.
Can-load	Load database or table definitions and data with triggers disabled.

5. To include hidden tables and fields in the list, click the **Filter** icon. The **Show hidden tables and fields** check box appears.

6. Select the check box to see the hidden objects, or click the **Filter** icon again to close the check box.

7. If you want to add to the list of users for a particular permission, click that permission panel. The list of actions to the right of the permission panel reflects the options you have regarding that permission, in addition to providing a link for you to review user data security based on the selected permission.

   For example, if you click the **Can-create** panel, the list of actions appears.

8. Choose one:

   - Click **Add users to**<*permission*>, from the **Actions** list. The **User Selection** dialog appears. Select one or more users in the list, and click **OK**.

     - Type the name of each user you want to add. Follow these conventions:
     - Separate user names by inserting a comma (not a period) between each one.
     - Use an asterisk (*****) to allow a permission for all users. Remember to remove the asterisk if you do not want a permission to be available for all users.
     - To allow a permission for all users except one—for example user **u1**— use **!u1,***

- To allow a permission for only those users whose names begin with a letter or letters—for example **ab**—use **ab***
- To allow a permission for a user of a domain, separate the user name with the domain name:

  user@domain

- To allow a permission for all users of a domain, put a wild card in front of the domain:

  **@domain*

9. Repeat Step 8 on page 74 for each additional permission.
10. Click **Commit** to save the settings.

Review user data security permissions

You can review the permissions that exist for users with regard to data security.

To review user data security permissions:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.
2. Filter or search for, and select the required database connection.

   The database connection home page appears.
3. Under **Security Summary**, click **Review user data security**.
4. To include hidden tables and fields in the permissions details, select the option.
5. Do either of the following to select the user whose permissions you want to view:
   - Type the **User ID** in the field provided, and click **Search**.
   - Click **Find User**. From the **Select a User** dialog that appears, select the user whose permissions you want to view. Click **OK**.

   The data security permissions that exist for the user, by table, appear in the **Data Security Permissions** dialog. Each permission the user has is marked. Where the user has no permission, there is no mark present.

Configure database security options

The **Database Security Options** page enables you to maintain the security options for a database. Only a user with administrator privileges can access this page to configure the database security options.

To configure the database security options:

1. From the OpenEdge Management menu, click **Database Administration** > **Go to Database Administration**.

   The **Database Administration** page appears.
2. Filter or search for, and select the required database connection.

   The database connection home page appears.

3. In the **Security Summary** section, click **Edit security options**. The **Database Security Options** page appears.
4. You can select one or more of the following security options:

Security options	Description
Trust application domain registry	Overrides the database connection's domain registry settings and uses the application level domain registry settings. For more information about domain registry settings, see *Learn about Security and Auditing*.
Record authenticated client sessions	Records user login sessions.
Disallow blank userid connections	Blocks database connection with blank UserId.
Use runtime permissions checking	Applies CAN-WRITE and CAN-READ permissions at runtime, rather than at compile time.
Change Data Capture user identity	Specifies how a user's identity is recorded in the Change tracking table. The options are: • **None** — Does not record any user identity. • **Database** — Records the user's identity based on the database connection used by the user. • **Application** — Records the user's identity based on the application session used by the user.

When you finish, click **Commit**.

Configure database security administrators

You can establish one or more security administrators for a multi-tenant database. You can also identify domains as security administrators; in such a case, everyone in a domain is a security administrator.

To set up a database security administrator:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.
2. Filter or search for, and select the required database connection.

   The database connection home page appears.
3. Click **Edit**.

   The **Edit Database Connection** page appears.
4. In the **Database authentication** area, select the **Log in with these credentials** option.
5. Type the User ID, password, and then type the password again to confirm it.
6. Click **Save**.

7. Under **Database Administration**, select the database connection you are logged in to.
8. Under **Security Summary**, click **Edit security administrator**. The **Security Administrators** page appears.

   You can designate one or more security administrators by:

   - Typing the login ID for each user in the box provided.
   - You can enter multiple user IDs here, but you must include your own user ID. Separate the user IDs with commas, but no spaces.
   - Clicking **Add users to Security Administrators**. A list of users appears; select each user you want to designate as a security administrator. Be sure to select your own ID in the list. Click **OK** when you finish.
   - Click **Add domains to Security Administrators**. A list of domains appears; select the domains you want to designate. All users in the domains you specify will be security administrators. Click **OK** when you finish.

9. When you finish, click **Save**.

Set up a database connection login

You can set up a database connection login that allows you access to super-tenants.

To set up a login to a database connection:

1. From the list of connections, select the connection for which you want to establish a login.
2. Under **Manage Database Connection**, click **Edit database connection**.
3. Select the **Log in with these credentials option**, and provide the user ID and password. Type the same password in the **Confirm password** field.
4. Click **Save**.

Review user access in the Data Administration Console

The access to various options and links available in the database and tenant landing pages depends on the type of user's tenant used for the database connection. There are three types of users associated with a database connection:

- Default user
- Regular user
- Super user

An user can be associated with either the default tenant, regular tenant, or super-tenant. For more information on managing users in a database connection, see Manage users in a multi-tenant database on page 67.

Database landing page options

The following table lists the options available in the Database landing page for the user associated with the database connection. Note that full access to a database landing page requires a database connection for a user with the administrator privileges.

Table 1: Database landing page

Database landing page section	Default User	Regular User	Super User
Manage Database Connection	• Edit database connection	• Edit database connection	• Edit database connection
Security Summary[5]	• Edit security options • Edit security administrator • Edit users • Edit domains • Create tenant • Edit authentication systems • Edit data security • Review user data security	• Edit security options • Edit security administrator • Edit users • Edit domains • Create tenant • Edit authentication systems • Edit data security • Review user data security	• Edit security options • Edit security administrator • Edit users • Edit domains • Create tenant • Edit authentication systems • Edit data security • Review user data security
Data Administration	• Edit sequences • Export sequences • Load data definitions (.df file) • Load table contents (.d file) • Load group contents (.d file) • Dump table contents (.d file) • Dump group contents (.d file)	• Edit sequences • Export sequences • Load data definitions (.df file) • Load table contents (.d file) • Load group contents (.d file) • Dump table contents (.d file) • Dump group contents (.d file)	• Edit sequences • Export sequences • Load data definitions (.df file) • Load table contents (.d file) • Load group contents (.d file) • Dump table contents (.d file) • Dump group contents (.d file)

[5] The **Edit security options** and **Edit security administrator** links are enabled for the default user, a regular user, or a super user with the administrator privileges. For more information on configuring database security administrators, see Configure database security administrators on page 76.

Tenant landing page options

The following table lists the options available for each type of user associated with the database connection and the tenant type selected in the Tenant's landing page. Note that full access to a tenant's landing page requires a database connection for a user associated with either a super-tenant or that specific tenant.

Table 2: Tenant's landing page

Tenant Type	Tenant's landing page section	Default User	Regular User	Super User
Default Tenant	Manage Tenant	• Edit tenant • Generate tenant program	• Edit tenant • Generate tenant program	• Edit tenant • Generate tenant program
	Database Administration	• Deallocate tables • Edit sequence values • Export sequences	• Deallocate tables • Edit sequence values • Export sequences	• Deallocate tables • Edit sequence values • Export sequences
Regular Tenant	Manage Tenant	• Edit Tenant • Delete tenant • Tenant data access: enabled • Generate tenant program	• Edit Tenant • Delete tenant • Tenant data access: enabled • Generate tenant program	• Edit Tenant • Delete tenant • Tenant data access: enabled • Generate tenant program
	Data Administration	• Deallocate tables • Edit sequence values • Export sequences	• Deallocate tables • Edit sequence values • Export sequences	• Deallocate tables • Edit sequence values • Export sequences

[6] The **Delete tenant** link is not available for the default tenant, because the default tenant in a database connection cannot be deleted by either a regular or super user.
[7] A regular user can export sequences of it own, but cannot export sequences of the default tenant or other regular tenants.
[8] The **Delete tenant** link is not available for the tenant to which the logged user belongs to. For example, for a regular user, the **Delete tenant** link is not available for a regular tenant.
[9] A default user cannot export sequences of a regular tenant.

Tenant Type	Tenant's landing page section	Default User	Regular User	Super User
super-tenant	Manage Tenant	• Edit tenant • Delete tenant • Generate tenant program	• Edit tenant • Delete tenant • Generate tenant program	• Edit tenant • Delete tenant • Generate tenant program
	Data Administration	• Edit sequence values	• Edit sequence values	• Edit sequence values

Edit Tenant landing page options

The following table lists the options available for each type of user associated with the database connection, and the tenant type selected in the Edit Tenant's landing page. Note that full access to the Edit tenant's landing page requires a database connection for a user associated with either a super-tenant or that specific tenant.

Table 3: Edit Tenant's landing page

Tenant Type	Default User	Regular User	Super User
Default Tenant #dzp1557305544510/fn_default	• Tabs: General, Partitions, Users, Domains • Configure working areas • Commit • Tools	• Tabs: General, Partitions, Users, Domains • Configure working areas • Commit • Tools	• Tabs: General, Partitions, Users, Domains • Configure working areas • Commit • Tools

[10] The Edit sequence values, Deallocate tables, and Export sequences options are not available for a super user, because super-tenant does not have data of its own.

[11] As the default tenant and a super-tenant cannot be added to a group, the Groups tab is not available for the default tenant or super-tenant. Also, for a super-tenant, the the **Partitions** tab and **Configure working areas** options are not available, as a super-tenant does not have any data of its own.

Tenant Type	Default User	Regular User	Super User
Regular Tenant	• Tabs: General, Partitions, Users, Domains, Groups • Configure working areas • Commit • Tools	• Tabs: General, Partitions, Users, Domains, Groups • Configure working areas • Commit • Tools	• Tabs: General, Partitions, Users, Domains, Groups • Configure working areas • Commit • Tools
Super-tenant	• Tabs: General, Users, Domains • Commit • Tools	• Tabs: General, Users, Domains • Commit • Tools	• Tabs: General, Users, Domains • Commit • Tools

7

About Working with Tenant Templates

As you create and work with regular tenants, you might find that the initial configuration you set up for each tenant is identical. For example, you might recognize that the database connection and the default area assignments for tables, indexes, and LOB fields are the same for many newly created tenants.

To allow you to create regular tenants more efficiently, you can create one or more reusable tenant templates.

For details, see the following topics:

- Use tenant templates
- Create a tenant template
- Filter partitions from a tenant template
- View a list of available tenant templates
- Create a tenant from a tenant template
- Edit a tenant template

Use tenant templates

To allow you to create regular tenants more efficiently, you can create one or more reusable tenant templates. Once you create a tenant template, you can use it as is or later modify it if necessary. Template modifications affect any new tenants you create from the edited template. (Any tenants already created remain unchanged.)

You begin creating a template from **Database Administration** in the management console menu bar. You can work on one or more tenant templates simultaneously.

When you later want to create a regular tenant, you can select the tenant template from a list of available templates.

Allocation considerations when creating a tenant template

When you create a tenant template, you choose between the following two allocation options:

- Set new objects not to allocate space
- Set new objects to delay space allocation

Note that the option to allocate space immediately is not available, since it would disallow the creation of partition mapping for any tenant you create with the template. A template that stipulates that allocation should be immediate would establish default assignments and ignore any area assignments you try to set, as allocation would already be complete.

Create a tenant template

To make creating tenants easier, you can create a tenant template. As you define the template, you must at a minimum provide the name of the template and make an allocation rule selection.

You establish tenant template settings on the **General** tab and the **Partitions** tab. As you select the template settings, you can switch between the two tabs, and then save the template once you finish with all the settings.

Choose general tenant template settings

You create a tenant template by making choices about general and partition-related settings.

To choose general tenant template settings:

1. Select **Database Administration** > **New** > **Tenant Template** in the management console menu.

   The template creation page opens, with the **General** details in focus.

2. In the **Template name** field, enter a template name.

   Providing the template name is the only requirement on this page; however, you can also choose the database connection, identify default areas, and select an allocation rule if you want.

3. In the **Database connection** field, enter a database connection name to which you want to add the tenant template. By default, the last used database connection name appears in the **Database connection** field.

   Note: If you type the name of the database connection, follow the format used by OpenEdge Management to define a connection: *`AdminServer-name.database-name`*. A database server must be running for you to connect to the database.

   You can also click the **Search** icon to choose a database for which you are creating the tenant from the **Connection Selection** dialog.

   The **Connection Selection** dialog displays the connections details in a grid. You can perform the following:

   - Filter the connections in the grid by **Connection name**, **AdminServer**, or **Category**.

- Select the column heading and click the drop-down to choose the order (ascending or descending alphabetically) for the connections to appear in the grid.

4. Choose a selection for each of the following:

   - **Default data area**—The default area for tenant data
   - **Default index area**—The default area for index data
   - **Default LOB area**—The default area for LOB field data

   For each of the areas, you can either enter the storage area name in the default area field or click the **Search** icon to choose the storage area name from the **Area Selection** dialog.

   The **Area Selection** dialog displays the storage area names in a grid. You can perform the following:

   - Filter the storage area name in the grid by **Area name**, **Records per block**, or **Cluster size**.
   - Move forward or backward a page, or specify a particular page, in the list of domains by using the **Page** feature at the bottom of the list.
   - Select the column heading and click the drop-down to choose the order (ascending or descending alphabetically) for the area names to appear in the grid.

5. Optionally select the object allocation rule:

   - **Set new objects not to allocate space**—Allocate no space for the tenant's objects.
   - **Set new objects to delay space allocation**—Do not yet allocate storage space. (You can allocate space later when you are ready to do so.)

6. Click **Save**. Additionally, you can Choose partition-related template settings on page 85.

Choose partition-related template settings

You create a tenant template by choosing partition-related (and general) settings.

To choose partition-related template settings:

1. Click **Partitions**. The tenant template's partitions appear.

   From this page, you can:

   - Choose to view the partitions in either of two different layouts: by area panels, which is the default and is shown above, or by columns in a grid view. To switch from one layout option to the other, click the **View Grid** or **View Area** icon in the upper-right corner of the **Template Object Area Assignments** panel.
   - Filter the partitions by allocation state. Click **Filter Partitions** in the tenant menu bar, and select one or more of the filtering options. Then click **Apply**.
   - Make changes to the template object area assignments. This is helpful because when you use the template to create a tenant in the future, any partition changes that you make to individual tenant objects from this page during the template creation are preserved for the individual objects in the new tenant.

     For example, consider that you define TenantArea20 (as shown in the **General** details) as the default data area for the template, but you want one particular table named **mtCustomer** to be in TenantArea25. You can change the partition assignment for the **mtCustomer** table from the template default data area of TenantArea20 to TenantArea 25.

     Select **mtCustomer** in the list of template object area assignments. The **mtCustomer** table properties appear in the **Properties** pane:

In the Properties pane, click the **Search** icon for the **Area** field; select **TenantArea 25** in the **Area Selection dialog** and click **OK**.

When you use the template to create a tenant in the future, the tenant partition area you explicitly set for any object (such as the **mtCustomer** table in this example) in the template is preserved.

2. Click **Save** to maintain the settings. The tenant template is created.

Filter partitions from a tenant template

You can filter the view of partitions by allocation state from a tenant template. You can also filter the view of partitions by allocation state from a tenant.

To filter partitions by allocation state from a tenant template:

1. Select **Database Administration** > **Configure** > **Tenant Templates** in the management console menu.
2. Select the template in the list, and click **Edit template**. The **Edit Tenant Templates** page appears.
3. Click **Filter partitions**. The filtering options appear:

   All filtering options are selected by default. You can deselect any of the options. (To close the filtering options box without making any changes, click **Filter partitions**.)

4. Click **Apply filter** to begin filtering.

View a list of available tenant templates

You can view a list of available tenant templates and choose one to use as the basis for a new tenant you want to create. If you want to create a tenant that is almost but not exactly identical to one for which there is a template, you can select the template from the list, modify it, save it, and use the edited template as the basis for the new tenant.

To view the list of available tenant templates:

- Select **Database Administration** > **Configure** > **Tenant Templates** in the management console menu. The list of templates appears.

From the tenant template list, you can:

- **Select all the templates**—Select the **Select All** option.
- **Refresh the list of templates**—Click the **Refresh** icon.
- **Copy a template**—Select a template, and click the **Copy** icon. The **Copy tenant template** dialog appears. Type the name of the new template or accept the default name provided, and click **OK**. The copied template appears in the list once you click the **Refresh** icon.
- **Delete a template**—Select a template, and click **Delete**. The template name is immediately removed from the list.

Create a tenant from a tenant template

You can create a new regular tenant from a tenant template.

Note that you can open a template only if it is associated with a valid database connection that you can access. If the database connection is no longer valid or accessible, either restore the database connection with the same connection name as required by the template, or delete the template.

To create a tenant from a tenant template:

1. Select **Database Administration** > **Configure** > **Tenant Templates** in the management console menu. The list of templates appears.
2. Select the template you want to use, and click **Create tenant from template**. (If you do not see a recently created template in the list, click **Refresh**.) The tenant creation page opens.

   If you defined any of the following settings when you created the selected tenant template, the settings are loaded for you:

   - **Database connection**
   - **Default data area**
   - **Default index area**
   - **Default LOB area**
   - **Object allocation rule**
   - **Template** (from which to copy defaults for the tenant)

   You can use any or all of the template defaults, or you can make changes. The changes you make override any of the default settings for this tenant but do not modify the actual template.
3. Type the tenant name, which is required, and an optional description.
4. Do one of the following:
   - Click **Create tenant**. The tenant is created, and the tenant home page appears.
   - Click **Generate tenant program**. You are prompted to save the `create_tenant.p` file.

Edit a tenant template

You can edit an existing tenant template.

To edit a tenant template:

1. Select **Database Administration** > **Configure** > **Tenant Templates** in the management console menu. The list of templates appears.
2. Select the template you want to edit, and click **Edit template**. The template's **General** information appears. You can make the required changes here.
3. Click **Partitions**. You can make the required partitions-related changes here.
4. Click **Save**.

8

About Working with Sequences

From the database home page, you can work with sequences and their values.

For details, see the following topics:

- Work with sequences and sequence values
- Edit sequence values
- Export sequences for a tenant

Work with sequences and sequence values

Sequences are database objects that provide incremental values to an application. They can generate sequential values within any range of an ABL integer (–2,147,483,648 to 2,147,483,647) and with your choice of increment (positive or negative).

You can also define sequences to cycle or terminate when a specified limit is reached. A cycling sequence restarts after it reaches the specified limit, providing non-unique values for the life of the sequence. A terminating sequence stops incrementing after it reaches the specified limit, providing unique values for the life of the sequence as long as you do not explicitly reset it.

Types of sequences

A *multi-tenant sequence* is defined for a database but allows each tenant to view and update its own current value. A *shared sequence* has one value and is non-multi-tenant enabled.

Each tenant's sequence has its own current value. All other sequence settings are shared, including the minimum, maximum, increment, and rollover values. Changing the increment, therefore, affects the value for all tenants.

Sequence functionality and user credentials

Access to sequences and their values depends on the credentials of the user who has established the database connection. To be able to access and edit the current values, the user whose credentials were supplied at login must be either a super-tenant or a user of the tenant whose sequence values are being accessed. If the user is a super-tenant user, the user can access sequence current values for all tenants.

As a user of the regular tenant whose sequence values you want to work with, you can:

- View a list of sequences with details that include, for example, whether a sequence is enabled for multi-tenancy; a sequence's initial value; and a sequence's increment value.
- Edit the current values for shared sequences.
- Edit a tenant's current values for the shared sequences.
- Edit a tenant's current values for the multi-tenant sequences (provided that the user whose credentials were provided at database connection is a user of that tenant).
- Preview sequence definitions when loading a data definition file.
- Export to a file the current values for all multi-tenant.
- Export to a file the current values for shared sequences for the tenant (provided that the user whose credentials were provided at database connection is a user of that tenant).

Database connection user credentials for a super-tenant user permit the user to do all of the above as well as the following tasks:

- Edit the current values for all tenants of a multi-tenant sequence.
- Export by tenant the current values for all regular tenants to individual files. Each tenant has an individual file that contains the current sequence values for all multi-tenant sequences. For each tenant, an export file is created and holds the current sequence values for that tenant for each multi-tenant sequence.

  The super-tenant does not have its own sequence data; therefore, when you export sequence values for multi-tenant sequences, no file is generated.

When a tenant is added to the database, a current sequence value (set to the initial value) is stored for the tenant for each multi-tenant sequence. When a tenant is removed from a database, each multi-tenant sequence and its current value for that tenant is dropped from the database.

You cannot currently convert a shared sequence to a multi-tenant sequence. However, you can add multi-tenant sequences, created in the Data Dictionary tool, to a database by loading a data definition file (`.df`) that contains them.

Create a multi-tenant sequence and load a data definition file with sequences

As has been the case in previous releases of OpenEdge, you use the Data Dictionary tool to create a sequence, which you can choose to create as multi-tenant. (If you do not choose the multi-tenant option, you create a shared sequence.)

Although you cannot create sequences from the Database Administration Console, you can use the tool to view and edit them. You begin by using the Data Administration tool (**Start** > **Programs (or All Programs)** > **Progress** > **OpenEdge** > **Data Administration**) to create a data definition file that contains sequences. Using the multi-tenancy configuration tool, you can then load the data definition file that contains the sequences into the database and edit the sequence current values.

Due to the importance of establishing the required user credentials to work with multi-tenancy, many tasks that you perform related to multi-tenancy in the Data Dictionary tool or the Data Administration tool require the user ID and password of a super-tenant user.

Export current sequence values

By using the Data Administration tool (**Start** > **Programs (or All Programs)** > **Progress** > **OpenEdge** > **Data Administration**), you can export current sequence values to a file. You have the option of doing so for multi-tenant sequences, shared sequences, or all sequences. You can then import the file to the database by using Data Administration or an ABL program. For more information, see the Data Administration online help or *ABL Reference*.

By configuring multi-tenancy in the Database Administration Console, you can export all current values for all tenants at one time. For more information, see Export sequences for a tenant on page 93.

View a list of sequences

You can view a list of sequences for a database from the database's home page. If you have connected to the database as a super-tenant user, you can view a list of multi-tenant enabled sequences for all tenants, since a super-tenant has access to all tenant data. You can also edit and export the sequence current values of multi-tenant enabled tenants.

If you have connected to the database as a regular tenant user, you can view a list of sequences only for the tenant you belong to. You cannot view, edit, or export sequence current values for any other tenants.

To view a list of sequences:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.

2. Filter or search for, and select the required database connection.

   The database connection home page appears.

3. Under **Data Administration**, click **Edit sequences**. The **Edit Database Sequences** page appears.

   Note that if you have a long list of sequences, you can type a particular sequence name in the **Sequence name** field and click the **Search** icon. You can move forward or backward the page, or specify a particular page, in the list of sequences by using the **Page** feature at the bottom of the grid.

   Note: You can also sort the details by column in either ascending or descending order by clicking the column name and then the **Sort** arrow.

   The **Edit Database Sequences** page provides the following details:

   - **Sequence Name**—The name of the sequence.
   - **Multi-tenant**—Whether the sequence is enabled for multi-tenancy (**true**) or not (**false**).
   - **Initial Value**—The value at which a sequence begins to increase (or decrease).

- **Increment by**—The value by which a sequence will increment (or decrement) values from the initial value.
- **Upper Limit**—An integer value that defines the upper (or lower) limit of the sequence.
- **Cyclic at Limit**—Whether a cycling sequence has been activated (**true**) or not (**false**).

  A cycling sequence is a sequence that restarts after it reaches the specified limit, providing non-unique values for the life of the sequence. The value of a cycling sequence resets to its defined initial value when the sequence exceeds its upper limit or falls below its lower limit providing non-unique values for the life of the sequence. The terminating sequence stops increasing when it reaches its upper limit or stops decreasing when it reaches its lower limit, providing unique values as long as you do not explicitly reset it.

- **Current Value**—The current value of the sequence.

  For a newly created (not yet committed) sequence, the field is empty. For a shared sequence, the current value for the sequence is shown.

  For a multi-tenant sequence value you can change, an **Edit** link appears. For more information, see Edit sequence values on page 92.

4. From the list, you can:
   - Edit a multi-tenant sequence's current value. See Edit sequence values on page 92.
   - Restore an edited sequence's current value to its previous setting. See Restore sequence current values on page 93.

Edit sequence values

You can edit the values for all sequences for a particular tenant or for all tenants of a particular sequence.

If you have connected to the database as a super-tenant user, you can edit and you can export the sequence current values of all multi-tenant enabled tenants.

If you have connected to the database as a regular tenant user, you can view a list of sequences and edit sequence current values for only that tenant you belong to. You cannot edit sequence current values for any other tenants.

Edit the values for all sequences for a tenant

To edit the current values for all sequences for a tenant:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.
2. Filter or search for, and select the required database connection.

   The database connection home page appears.
3. Under **Storage Management**, click **View tenants**.
4. Select the tenant you want to edit. The tenant details page appears.
5. Select a tenant. The tenant home page appears.

6. Under **Data Administration**, click **Edit sequence values**. The **Edit Tenant Sequence Current Values** page appears.

   If you have a long list of multi-tenant sequences, you can type a particular sequence name in the **Sequence name** field and click the **Search** icon. You can also move forward or backward the page, or specify a particular page, in the list of sequences by using the **Page** feature at the bottom of the grid.

   Note: You can also sort the details by column in either ascending or descending order by clicking the column name and then the **Sort** arrow.

7. To modify the current value of a multi-tenant sequence, select the value for the sequence in the **Current Value** column.
8. Change the sequence value. A red mark appears in the corner of the column cell to indicate that the value has been changed.
9. Click **Commit**.

Edit the values for all tenants of a sequence

To edit the values for all tenants of a sequence:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.

2. Filter or search for, and select the required database connection.

   The database connection home page appears.

3. Under **Data Administration**, click **Edit sequences**. The **Edit Database Sequences** page appears.
4. To modify the current value of a multi-tenant sequence, double-click the field in the **Current Value** column for the sequence and then update the value.
5. Click in the **Current Value** column to set or change the sequence value for a tenant. A red mark appears in the corner of the column to indicate that the value has been changed.
6. Click **Commit** to save the changes.

Restore sequence current values

You can restore a sequence current value that you have modified.

From the **Edit Database Sequences** page, select a tenant name and click **Restore**. The previous value is restored to the **Current Value** column.

Export sequences for a tenant

A super-tenant user can export sequences for one or more tenants; a regular tenant user can export current sequence values only for the tenant the user belongs to.

You cannot export sequences if you are connected to the database with the blank user ID.

Export sequences for one or more tenants in the database

To export sequences for one or more tenants in the database:

1. Establish the database connection as a super-tenant user.
2. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.
3. Filter or search for, and select the required database connection.

   The database connection home page appears.
4. Under **Data Administration**, click **Export sequences**.

   If the database connection is a non multi-tenant database, the **Export sequence current values** page appears.

   Note: The tenant selection options do not display for non multi-tenant databases.

   If the database connection is a multi-tenant database, the **Export sequences current values** page appears.

   The following information is prefilled:

   - **AdminServer name**—The AdminServer for the connected database.
   - **Directory location**—Where the exported file will be located.
   - **File name**—The name of the exported file.

     Note that if you export only non-multi-tenant enabled sequences, all the sequence data will be located in the one file specified in this field. However, if the export includes multi-tenancy enabled sequences and the sequences have different values per tenant, a new directory is created (in the **Directory location** you specified) for each tenant. Each separate directory contains a file; the file contains the exported sequences and current values specific to that tenant.
   - **Code page**—The code page.
5. Select which type of sequence you want to export: **All**, **Shared**, or **Multi-tenant**.
6. Select one or more tenants, or select the **Select all** option for all the tenants listed.
7. Click **Export**. You can view status of such a task in the **Database Administration Tasks** page by selecting **Database Administration** > **View** > **Database Tasks**.

You cannot import the exported file to a database from the Database Administration Console; you can, however, use the Data Administration tool (**Start** > **Programs (or All Programs)** > **Progress** > **OpenEdge** > **Data Administration**), which has been enhanced to accommodate the inclusion of multi-tenancy-enabled sequences when you are exporting or importing data. For more information, see the Data Dictionary online help.

Export sequence current values for a selected tenant

To export sequence current values for a selected tenant:

1. Establish the database connection as a regular tenant user.
2. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.
3. Filter or search for, and select the required database connection.

   The database connection home page appears.
4. Under **Storage Management**, click **View tenants**.
5. Select the tenant you want to edit. The template details page appears.
6. Under **Database Administration**, click **Export sequences**. The **Export Tenant Sequence Current Values** page appears and includes the tenant name.

   The following information is prefilled:

   - **AdminServer name**—The AdminServer for the connected database.
   - **Use default location**—Indicates if you want to use the OpenEdge Work directory (the default) for the location of the exported file. This option is preselected; to choose an alternate location, clear the check box and provide a new location in the **Directory location** field.
   - **Directory location**—Where the exported file will be located.
   - **File name**—The name of the exported file.
   - **Code Page**—The code page.
7. Select which type of sequence you want to export: **All**, **Shared**, or **Multi-tenant**.
8. Click **Export**. You can view status of such a task in the **Database Administration Tasks** page by selecting **Database Administration** > **View** > **Database Tasks**.

9

About Working with Tenant Groups

A tenant group represents a single partition for a single table, along with the partitions for the table's LOB fields and indexes, that can be shared by tenants. All tenants in a group have access to the same data. When you create a group, you are creating an independent partition that multiple tenants view.

For details, see the following topics:

- Use tenant groups
- Create a group or group program
- Edit a group
- View a list of tenant groups
- View group details
- Search for available groups
- Remove a tenant from a group

Use tenant groups

You can create a tenant group, which allows the tenants in the group access to the same data. A group can contain one table and one tenant, multiple tenants, or no tenants at all. You can add only regular tenants to a group.

If you prefer, you can, as an alternative, set up the group's properties, generate a group creation program based on those properties, and save the program so you can run it when you want. Generating the program alone does not create the group; you create the group when you run the generated program.

Guidelines for using groups

Keep in mind the following considerations as you work with tenant groups:

- When you initially create a group, the group has no tenants. You can take a table from an existing tenant's schema and add it to the group.
- You cannot add a tenant to a group if the tenant's partitions are already allocated.
- Once you assign a tenant to a group, that tenant can no longer access any data in the tenant's partition for the table partition associated with the group. In other words, the tenant can have only one partition for each given table.
- A tenant can belong to more than one group but cannot belong to two groups for the same table.
- Removing a tenant from a group restores the tenant's unique partition information for that table based on the defaults that are set up in the tenant record.

Create a group or group program

You can create a group and then add one or more tenants to it.

1. Select **Database Administration** > **New** > **Group.** in the management console.

   The **New Group** page appears.

2. Provide the following information:

   - **Group name**—The name of the group, which must be unique within the database. Do not use spaces or special characters such as an asterisk (*), ampersand (&), or period (.) in this field. You can include the underscore (_).
   - **Description**—An optional description of the group.

3. In the **Database connection** name, enter a database connection name to which you want to add the new group. By default, the last used database connection name appears in the **Database connection** field.

   Note: If you type the name of the database connection, follow the format used by OpenEdge Management to define a connection: *`AdminServer-name.database-name`*. A database server must be running for you to connect to the database.

   You can also click the **Search** icon to choose a database for which you are creating the tenant from the **Connection Selection** dialog.

   The **Connection Selection** dialog displays the connections details in a grid. You can perform the following:

   - Filter the connections in the grid by a **Connection name**, **AdminServer**, or **Category**.
   - Select the column heading and click the drop-down to choose the order (ascending or descending alphabetically) for the connections to appear in the grid.

4. Choose the **Table** you want to place in the group by either typing the table name or clicking the **Search** icon to select the table from the **Table Selection** dialog.

Note: There is one table per group and one or more tenants per group.

5. Select the default data area, default index area, and default LOB area. For each of the areas, you can either type the area name or click the **Search** icon to select the area from the **Area Selection** dialog.

   The **Area Selection** dialog displays the storage area names in a grid. You can perform the following:

   - Filter the storage area name in the grid by **Area name**, **Records per block**, or **Cluster size**.
   - Move forward or backward a page, or specify a particular page, in the list of domains by using the **Page** feature at the bottom of the list.
   - Select the column heading and click the drop-down to choose the order (ascending or descending alphabetically) for the area names to appear in the grid.

6. On the **Partitions** tab, select an item in the table schema to view its properties, which include name, type, area, buffer pool assignment, and allocation state.
7. Set the area for each partition *individually* by clicking the **Search** icon and choosing an area from the list.
8. Select a buffer pool assignment of **Primary** or **Alternate**.
9. To modify theallocation state, choose from either of the options.
10. You can perform the following actions:

    - To add one or more tenants to the group and then create the group immediately:
      1. Click the **Tenants** tab.
      2. Click **Add Tenant**.
      3. From the list of tenants that appears, select one or more tenants.
      4. Click **OK**. The newly added tenants are listed as belonging to the group.
      5. Click **Save** to save the group. If the partition in the group has already been allocated for a newly added tenant, an error message appears and the group is not created.
    - To save the group without adding tenants:
      1. Click **Save**.
      2. Click **Yes** to the message confirming that the group has no tenants.

11. To create a group creation script, click **Generate group program**.
12. From the list of groups, click **Refresh**. The new group appears in the list of groups.

Edit a group

You can make changes to a group; for example, you can edit the existing group details, add tenants, add partitions, or rename a group (when the group has tenants as members).

To edit a group:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.
2. Filter or search for, and select the required database connection.

   The database connection home page appears.
3. Under **Storage Management**, click **View groups**.
4. Select the group you want to edit. The group details page appears.
5. In the **Group name** field, replace the existing group name with a new group name.
6. Modify the description of the group (optional).
7. To make partition changes, select a table in the schema on the **Partitions** tab. Then:
   - Click the **Area** drop-down arrow if you want to choose a different area.
   - Click the **Buffer pool** drop-down to change from **Primary** to **Alternate**, or vice versa.
   - To change the allocation state, select the appropriate option.
8. To add a new tenant, click **Tenants** and then click **Add Tenant**. Click **Remove** to remove an existing tenant from the group.
9. Click **Save** to save the changes.

Add a tenant to a group

You can add a tenant to a group as long as the partition in the group has not already been allocated as a partition for the same table for the tenant.

For more details about adding a tenant to a group, see Guidelines for using groups on page 98.

You can add a tenant to a group in two ways:

- From the tenant
- From the group

Add a tenant to a group from the tenant

To add a tenant to a group *from the tenant*:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.
2. Filter or search for, and select the required database connection.

   The database connection home page appears.
3. Click **View tenants** in the **Storage Management** section.

   The **Tenant List** page appears.
4. Select a tenant you want to add to a group.

   The tenant details page appears.

5. Click **Edit tenant** in the **Manage Tenant** section.

   The **Edit Tenant** page appears.
6. Click the **Groups** tab.
7. From the tenant menu bar, click **Add Group**. The **Group Selection** dialog appears.

   The **Group Selection** dialog displays the groups for the selected tenant in a grid. You can perform the following:

   - Filter the groups in the grid by Group name or Table name.
   - Move forward or backward a page, or specify a particular page, in the list of tables by using the **Page** feature at the bottom of the list.
   - Select the column heading and click the drop-down to choose the order (ascending or descending alphabetically) for the groups to appear in the grid.
8. From the list of available groups, select the group you want and click **OK**. The group name and group title appear for the tenant.
9. Click **Commit**.

Add a tenant to a group from the group

To add a tenant to a group *from the group*:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.
2. Filter or search for, and select the required database connection.

   The database connection home page appears.
3. Click **View groups** in the **Storage Management** section.

   The **Group List** page appears.
4. Select a group using which you want to add a tenant to a group. The group details page appears.
5. Click **Tenants** > **Add Tenant** at the bottom of the page.
6. Select one or more tenants, or click **Select All** check box to select all the tenants you want to add to the group.
7. Click **OK**. The names of the tenants appear.
8. Click **Save**.

   If the partition in the group has already been allocated for a selected tenant, an error message appears and the group is not created.

   If the partition has not yet been allocated, the group is created with the selected tenants.

View a list of tenant groups

You can view a list of tenant groups that exist for a multi-tenant database.

To view a list of groups:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.
2. Filter or search for, and select the required database connection.

   The database connection home page appears.
3. Under **Storage Management**, click **View groups**. A list of groups defined for the selected database appears.

View group details

You can view details about an existing group.

To view a group's details:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.
2. Filter or search for, and select the required database connection.

   The database connection home page appears.
3. Under **Storage Management**, click **View groups**. A list of groups defined for the selected database appears.
4. Select the group for which you want to view details.

Search for available groups

You can search for a particular tenant group.

To search for a group:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.
2. Filter or search for, and select the required database connection.

   The database connection home page appears.
3. Under **Storage Management**, click **View groups**. A list of groups defined for the selected database appears.
4. Type the name of the group you are searching for in the **Search groups** field. The list of groups appear.

Remove a tenant from a group

You can remove a tenant from a group. If you later change your mind, you can restore the tenant to the group.

You can remove the tenant from either the tenant itself or from the group.

Remove a tenant from a group using the tenant

To remove a tenant from a group *using the tenant*:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.
2. Filter or search for, and select the required database connection.

   The database connection home page appears.
3. Under **Storage Management**, click **View tenants**.
4. Select a tenant using which you want to remove a tenant to a group. The tenant details page appears.
5. Under **Manage Tenant**, click **Edit tenant**. The **Edit tenant** page appears.
6. Click **Groups**.
7. Select the group name, and click **Remove**.

To restore the tenant to the group, click **Restore**.

Remove a tenant from a group using the group

To remove a tenant from a group *using the group*:

1. Click **Database Administration** > **Go to Database Administration** in the OpenEdge Management console menu.

   The **Database Administration** page appears.
2. Filter or search for, and select the required database connection.

   The database connection home page appears.
3. Under **Storage Management**, click **View groups**.
4. Select the group from which you want to remove a tenant. The group details page appears.
5. Click the **Tenants** tab.
6. Select the tenant, and click **Remove**.

Index

A

Allocation *14*
Area working set *64*
Areas
    viewing *41*
Authentication systems *72*

B

Buffer pool *46*

C

Color legend *44*
Committing changes *65*
Configuration
    database connections *17*
    for remote hosts *18*
Connections
    configuring for a database *17*

D

Data Definition file
    loading *29*, *61*
    preview *62*
Database Administration Console
    features *12*
    working with *12*
Database connections
    configuring *17*
    setting up *19*
Databases
    adding domains *70*
    adding users *68*
    connection details *26*
    deleting domains *72*
    deleting users *69*
    Dumping data from groups *38*
    Dumping data from tables *35*
    dumping group contents *38*
    dumping table contents *35*
    enabling for multi-tenancy *25*
    features *27*
    filtering domains *70*
    Loading data to groups *33*
    Loading data to tables *29*
    loading group contents *33*
    loading table contents *29*
    managing multi-tenant *25*
Databases *(continued)*
    modifying domains *71*
    modifying users *69*
    security summary *27*
    table security for users *73*
    viewing domains *70*
Deallocating tenant tables *58*
Default tenant *14*
Disabling access to tenant data *57*
Domains
    adding for a tenant *50*
    adding to databases *71*
    deleting *72*
    filtering database *70*
    modifying database *71*
    viewing *42*
    viewing database *70*
Dumping database contents *35*

E

editgroup *99*
Enabling access to tenant data *57*
Enhancements
    Database Administration Console *12*
Exporting sequences *91*, *93–94*

F

Filtering
    tenant partitions *42–43*

G

Group Contents
    dumping *38*
    Loading *33*
Group program
    creating *98*
Groups
    adding tenants *100–101*
    creating *98*
    guidelines for using *98*
    removing tenants from *102–103*
    searching for *102*
    viewing details *102*
    viewing in a list *101*
    working with *97*

L

Loading a data definition file *29*, *61*
Loading database contents *29*

M

Managed database *17*
Managing multi-tenant databases *25*
Multi-tenancy
  allocation *14*
  areas *14*
  common terminology *14*
  enabling databases for *25*
  enabling tables for *55*
  groups *14*
  partitions *14*
  tenants *14*
  tuning performance *40*
Multi-tenancy tasks viewlet *66*

P

Partitions
  allocating tenant *46*
  filtering *42*
Permissions
  reviewing for users *75*
  user *73*

R

Regular tenant *14*
Remote configuration requirements *18*

S

Schema
  updating *61*
  uploading new *61*
  viewing *42*
Scripted database *17*
Security
  for database table users *73*
Security administrators *23*, *76*
Security summary *27*
Sequences
  creating multi-tenant *90*
  details *28*
  editing values *92–93*
  exporting current values *91*
  exporting for a tenant *93*
  functionality and user credentials *90*
  loading data definition file of *90*
  restoring values *93*
Sequences *(continued)*
  types *89*
  values *89*
  viewing list of *91*
  working with *89*
Storage area assignments *64*
Super-tenant *14*

T

Table Contents
  dumping *35*
  loading *29*
Tables
  deallocating *58–59*
  enabling for multi-tenancy *53*
Tenant
  creating *47*
Tenant configuration program *47*
Tenant program
  creating *47*
Tenant templates
  allocation considerations *84*
  creating *84*
  creating tenant from *87*
  editing *87*
  filtering partitions *86*
  using *83*
  viewing in a list *86*
  working with *83*
Tenants
  adding domains *50*
  adding users *51*
  creating *46*
  deleting *53*
  editing *49*
  enabling or disabling data access for *57*
  removing from groups *102–103*
  viewing *42*
  working with *45*
Terminology
  multi-tenancy *14*

U

Ungluing from OpenEdge *18*
Unmanaged database connection *17*
User credentials
  for database connection *19*
Users
  adding to a database *68*
  adding to a tenant *51*
  database table security *73*
  deleting from a database *69*
  modifying for a database *69*
  modifying in a database *69*

Users *(continued)*
reviewing permissions *75*
viewing *42*

V

Viewing
multi-tenant areas, domains, schemas, tenants, groups *41*